

FCC PART 15C TEST REPORT FOR CERTIFICATION  
On Behalf of

TP-LINK TECHNOLOGIES Co., Ltd.

150Mbps Wireless N ADSL2 + Modem Router

Model No.: TD-W8151N

FCC ID: TE7TDW8151NV3

Prepared for : TP-LINK TECHNOLOGIES Co., Ltd.  
Building 24(floors 1,3,4,5) and 28 (floors 1-4) Central Science  
and Technology Park, Shennan Rd, Nanshan, Shenzhen, China

Prepared By : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block,  
Shenzhen Science & Industrial Park,  
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F12204  
Date of Test : Aug.23~Sep.13, 2012  
Date of Report : Sep.21, 2012

## TABLE OF CONTENTS

Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>1-5</b>
1.1. Description of Standards and Results .....	1-5
<b>2. GENERAL INFORMATION.....</b>	<b>2-1</b>
2.1. Description of Device (EUT) .....	2-1
2.2. Test Information .....	2-2
2.3. Tested Supporting System Details.....	2-3
2.4. Block Diagram of Test Setup .....	2-3
2.5. Test Facility .....	2-4
2.6. Measurement Uncertainty (95% confidence levels, k=2).....	2-4
<b>3. POWER LINE CONDUCTED EMISSION TEST.....</b>	<b>3-1</b>
3.1. Test Equipments .....	3-1
3.2. Block Diagram of Test Setup .....	3-1
3.3. Power Line Conducted Emission Test Limits .....	3-1
3.4. Configuration of EUT on Test.....	3-1
3.5. Operating Condition of EUT .....	3-2
3.6. Test Procedure .....	3-2
3.7. Power Line Conducted Emission Test Results .....	3-2
<b>4. RADIATED EMISSION TEST .....</b>	<b>4-1</b>
4.1. Test Equipment.....	4-1
4.2. Block Diagram of Test Setup .....	4-1
4.3. Radiated Emission Limit .....	4-2
4.4. EUT Configuration on Test.....	4-3
4.5. Operating Condition of EUT .....	4-3
4.6. Test Procedure .....	4-3
4.7. Radiated Emission Test Results .....	4-4
<b>5. CONDUCTED SPURIOUS EMISSIONS .....</b>	<b>5-1</b>
5.1. Test Equipment.....	5-1
5.2. Limit .....	5-1
5.3. Test Procedure .....	5-1
5.4. Test result .....	5-1
<b>6. BAND EDGE COMPLIANCE TEST .....</b>	<b>6-1</b>
6.1. Test Equipment.....	6-1
6.2. Limit .....	6-1
6.3. Test Produce .....	6-1
6.4. Test Results .....	6-1
<b>7. 6dB Bandwidth Test .....</b>	<b>7-1</b>
7.1. Test Equipment.....	7-1
7.2. Limit .....	7-1
7.3. Test Procedure .....	7-1
7.4. Test Results .....	7-1
<b>8. OUTPUT POWER TEST .....</b>	<b>8-1</b>
8.1. Test Equipment.....	8-1
8.2. Limit (FCC Part 15C 15.247 b(3)) .....	8-1
8.3. Test Procedure .....	8-1
8.4. Test Results .....	8-2
<b>9. POWER SPECTRAL DENSITY TEST .....</b>	<b>9-1</b>
9.1. Test Equipment.....	9-1

FCC ID:TE7TDW8151NV3

page 1-3

9.2. Limit .....	9-1
9.3. Test Procedure .....	9-1
9.4. Test Results .....	9-2
<b>10. ANTENNA REQUIREMENT .....</b>	<b>10-1</b>
<b>10.1. STANDARD APPLICABLE .....</b>	<b>10-1</b>
<b>10.2. ANTENNA CONNECTED CONSTRUCTION .....</b>	<b>10-1</b>
<b>11. MPE ESTIMATION .....</b>	<b>11-1</b>
11.1. Limit for General Population/ Uncontrolled Exposures.....	11-1
11.2. Estimation Result.....	11-1
<b>12. DEVIATION TO TEST SPECIFICATIONS .....</b>	<b>12-1</b>
<b>13. PHOTOGRAPH OF TEST.....</b>	<b>13-1</b>
13.1. Photos of Power Line Conducted Emission Test .....	13-1
13.2. Photos of Radiated Emission Test .....	13-2
<b>14. PHOTOS OF THE EUT .....</b>	<b>14-1</b>

**TEST REPORT CERTIFICATION**

Applicant : TP-LINK TECHNOLOGIES Co., Ltd.  
 Manufacturer : TP-LINK TECHNOLOGIES Co., Ltd.  
 EUT Description : 150Mbps Wireless N ADSL2 + Modem Router  
 FCC ID : TE7TDW8151INV3  
 (A) MODEL NO. : TD-W8151N  
 (B) SERIAL NO. : N/A  
 (C) POWER SUPPLY : DC 9V From PC Input  
 (D) TEST VOLTAGE : DC 9V From PC Input AC 120V/60Hz

Tested for comply with:  
 FCC Rules and Regulations Part 15 Subpart C: 2008

Test procedure used:  
 ANSI C63.10:2009

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Aug.23~ Sep.13, 2012 Report of date: Sep.21, 2012

Prepared by :

Selina Liu / Supervisor

Reviewed by :

Sunny Lu / Assistant Manager



信華科技(深圳)有限公司  
Audix Technology (Shenzhen) Co., Ltd.

EMC 部門 報告 專用章

Stamp only for EMC Dept. Report

Signature:

Ken Lu %415

Ken Lu / Manager

Approved & Authorized Signer :

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2009	PASS
Radiated Emission	FCC Part 15: 15.209 ANSI C63.10: 2009	PASS
Band Edge Compliance	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Conducted spurious emissions	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
6dB Bandwidth	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Power Spectral Density	FCC Part 15: 15.247 ANSI C63.10: 2009	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

Product Name	: 150Mbps Wireless N ADSL2 + Modem Router
Model Number	: TD-W8151N
FCC ID	: TE7TDW8151NV3
Operation Frequency	: IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE802.11n HT20: 2412MHz—2462MHz IEEE802.11n HT40: 2422MHz—2452MHz
Channel Number	: IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7Channels
Modulation Technology	: IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
Antenna Assembly Gain	: Dipole Antenna, 5dBi Gain
Applicant	: TP-LINK TECHNOLOGIES Co., Ltd. Building 24(floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Manufacturer	: TP-LINK TECHNOLOGIES Co., Ltd. Building 24(floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Power Adapter	Manufacturer: TP-LINK TECHNOLOGIES CO., LTD. M/N: T090060-2B1 Cable: Unshielded, Undetachable, 1.5m
Date of Test	: Aug.23~Sep.13, 2012
Date of Receipt	: Aug.20, 2012
Sample Type	: Prototype production

## 2.2. Test Information

A special test software was used to control EUT work in Continuous TX mode(100% duty cycle), and select test channel, wireless mode and data rate.


Tested mode, channel, and data rate information			
Mode	data rate (Mbps)(see Note)	Channel	Frequency (MHz)
IEEE 802.11b	1	Low :CH1	2412
	1	Middle: CH6	2437
	1	High: CH11	2462
IEEE 802.11g	6	Low :CH1	2412
	6	Middle: CH6	2437
	6	High: CH11	2462
IEEE 802.11n HT20	6.5	Low :CH1	2412
	6.5	Middle: CH6	2437
	6.5	High: CH11	2462
IEEE 802.11n HT40	13.5	Low :CH1	2422
	13.5	Middle: CH4	2437
	13.5	High: CH7	2452

Note 1: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

### 2.3. Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number	Approved type
1	Personal Computer	Test PC M	DELL	Studio 540	224XK2X	<input checked="" type="checkbox"/> FCC DoC <input checked="" type="checkbox"/> BSMI ID:R33002 Power Cord: Unshielded, Detachable, 1.8m Display Card: HD3450 (DVI+VGA+HDMI)

### 2.4. Block Diagram of Test Setup



(EUT: 150Mbps Wireless N ADSL2 + Modem Router)

## 2.5. Test Facility

### Site Description

Name of Firm

: Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block, Shenzhen  
Science & Industrial Park, Nantou,  
Shenzhen, Guangdong, China

3m Anechoic Chamber

: Certificated by FCC, USA  
Registration Number: 90454  
Valid Date: Feb.22, 2015

3m & 10m Anechoic Chamber

: Certificated by FCC, USA  
Registration Number: 794232  
Valid Date: Dec.30, 2012

EMC Lab.

: Certificated by Industry Canada  
Registration Number: IC 5183A-1  
Valid Date: Jun.13, 2014

: Certificated by DAkkS, Germany  
Registration No: D-PL-12151-01-01  
Valid Date: Feb.01, 2014

Accredited by NVLAP, USA  
NVLAP Code: 200372-0  
Valid Date: Mar.31, 2013

## 2.6. Measurement Uncertainty (95% confidence levels, k=2)


Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.2 dB (150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	3.6 dB(30~200MHz, Polarize: H)
	3.8 dB(30~200MHz, Polarize: V)
	4.2 dB(200M~1GHz, Polarize: H)
	3.8 dB(200M~1GHz, Polarize: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	3.1dB (Distance: 3m Polarize: V)
	3.7 dB (Distance: 3m Polarize: H)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.57 dB
Uncertainty for Conduction Spurious emission test	2.00 dB
Uncertainty for Output power test	0.73 dB
Uncertainty for Power density test	2.00 dB
Uncertainty for Frequency range test	7x10 <sup>-8</sup>
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.038 %
Uncertainty for test site temperature and humidity	0.6°C
	3%

### 3. POWER LINE CONDUCTED EMISSION TEST

#### 3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESHS10	838693/001	Oct.31, 11	1 Year
2.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	834066/011	Oct.31, 11	1 Year
3.	L.I.S.N.#3	Kyoritsu	KNW-242C	8-1920-1	May.08, 12	1 Year
4.	Terminator	Hubersuhner	50Ω	No. 1	May.08, 12	1 Year
5.	Terminator	Hubersuhner	50Ω	No. 2	May.08, 12	1 Year
6.	RF Cable	Fujikura	3D-2W	No.1	May.08, 12	1 Year
7.	Coaxial Switch	Anritsu	MP59B	M50564	May.08, 12	1 Year
8.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100341	May.08, 12	1 Year

#### 3.2. Block Diagram of Test Setup



■ :50Ω Terminator

#### 3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(µV)	Average Level dB(µV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

#### 3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

##### 3.4.1. 150Mbps Wireless N ADSL2 + Modem Router (EUT)

Model Number : TD-W8151N

Serial Number : N/A

##### 3.4.2. Support Equipment: As Tested Supporting System Details, in Section 2.2.

### 3.5.Operating Condition of EUT

3.5.1. Setup the EUT and simulator as shown as Section 3.2.

3.5.2. Turned on the power of all equipment.

3.5.3. PC run test software to control EUT work in Tx mode.

### 3.6.Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via PC connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2009 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESHS10) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

### 3.7.Power Line Conducted Emission Test Results

**PASS.** (All emissions not reported below are too low against the prescribed limits.)




No	Freq (MHz)	LISN	Cable	Emission				
		Factor (dB)	Loss (dB)	Reading (dBuV)	Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.59700	0.16	9.95	23.10	33.21	46.00	12.79	Average
2	0.59700	0.16	9.95	35.30	45.41	56.00	10.59	QP
3	0.68700	0.16	9.95	17.80	27.91	46.00	18.09	Average
4	0.68700	0.16	9.95	31.50	41.61	56.00	14.39	QP
5	0.80600	0.16	9.95	19.30	29.41	46.00	16.59	Average
6	0.80600	0.16	9.95	31.30	41.41	56.00	14.59	QP
7	1.190	0.18	9.94	20.40	30.52	46.00	15.48	Average
8	1.190	0.18	9.94	33.10	43.22	56.00	12.78	QP
9	1.670	0.19	9.94	20.30	30.43	46.00	15.57	Average
10	1.670	0.19	9.94	34.10	44.23	56.00	11.77	QP
11	2.030	0.20	9.94	19.20	29.34	46.00	16.66	Average
12	2.030	0.20	9.94	33.20	43.34	56.00	12.66	QP

Remarks: 1. Emission Level=LISN Factor+Cable Loss (Include 10dB pulse limit)  
 +Reading.  
 2. If the average limit is met when using a quasi-peak detector.  
 the EUT shall be deemed to meet both limits and measurement  
 with average detector is unnecessary.

Data: 12

File: D:\DATA\2012 Report data\T\TP-LINK\ACS12Q1733.EM6 (29)

Date: 2012-08-23



## Trace: (Discrete)

Site no : 1#conduction Data No : 12  
 Dis./Ant. : \*\* 2012 ESH2-25 NEUTRAL  
 Limit : FCC PART 15 C  
 Env./Ins. : 22.9°C/45% Engineer : Leo\_Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power Rating : DC 9V From Adapter Input AC 120V/60Hz  
 Test Mode : Tx Mode  
 : M/N:TD-W8151N

No	Freq (MHz)	LISN	Cable	Emission				Remark
		Factor (dB)	Loss (dB)	Reading (dBuV)	Level (dBuV)	Limits (dBuV)	Margin (dB)	
1	0.53800	0.15	9.95	30.90	41.00	46.00	5.00	Average
2	0.53800	0.15	9.95	40.80	50.90	56.00	5.10	QP
3	0.59700	0.16	9.95	31.09	41.20	46.00	4.80	Average
4	0.59700	0.16	9.95	40.49	50.60	56.00	5.40	QP
5	0.68700	0.16	9.95	24.70	34.81	46.00	11.19	Average
6	0.68700	0.16	9.95	34.30	44.41	56.00	11.59	QP
7	0.80600	0.16	9.95	25.70	35.81	46.00	10.19	Average
8	0.80600	0.16	9.95	34.90	45.01	56.00	10.99	QP
9	1.280	0.18	9.94	25.40	35.52	46.00	10.48	Average
10	1.280	0.18	9.94	35.10	45.22	56.00	10.78	QP
11	1.670	0.19	9.94	26.30	36.43	46.00	9.57	Average
12	1.670	0.19	9.94	36.20	46.33	56.00	9.67	QP

Remarks: 1. Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)  
 +Reading.  
 2. If the average limit is met when using a quasi-peak detector,  
 the EUT shall be deemed to meet both limits and measurement  
 with average detector is unnecessary.

## 4. RADIATED EMISSION TEST

### 4.1. Test Equipment

#### 4.1.1. For frequency range 30MHz~1000MHz (At Anechoic Chamber)


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Nov.28,11	1 Year
2	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 12	1 Year
3	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 12	1 Year
4	Amplifier	HP	8447D	2648A04738	May.08, 12	1 Year
5	Bilog Antenna	Schaffner	CBL6111C	2598	Oct.26, 10	2.0 Year
6	RF Cable	MIYAZAKI	CFD400-NL	3# Chamber No.1	May.08, 12	1 Year
7	Coaxial Switch	Anritsu	MP59B	M74389	May.08, 12	1 Year

#### 4.1.2. For frequency range 1GHz~25GHz (At Anechoic Chamber)


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	May.08, 12	1 Year
2	Horn Antenna	EMCO	3115	9510-4580	June.05, 12	1 Year
3	Amplifier	Agilent	8449B	3008A00863	May.08, 12	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX106	77980/6	May.08, 12	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	May.08, 12	1 Year
6	Horn Antenna	EMCO	3116	00060089	May.08, 12	1.5 Year

### 4.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz



#### 4.3.Radiated Emission Limit

##### 4.3.1.15.209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Remark : (1) Emission level  $\text{dB}\mu\text{V} = 20 \log$  Emission level  $\mu\text{V}/\text{m}$

- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

#### 4.3.2.15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

#### 4.4.EUT Configuration on Test

The configurations of EUT are listed in Section 3.5.

#### 4.5.Operating Condition of EUT

Same as Conducted Emission test that is listed in Section 3.6. except the test set up replaced by Section 4.2.

#### 4.6.Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

The frequency range from 30MHz to 10<sup>th</sup> harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

#### 4.7.Radiated Emission Test Results

**PASS.**

All the emissions from 30MHz to 25 GHz were comply with 15.209 limits.


Note: For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

## Frequency: 30MHz~1GHz

Data: 1

File: E:\2012 Report Data\T\TP-LINK\ACS12Q1733.EM6 (6)

Date: 2012-08-25



Site no. : 3m Chamber Data no. : 1  
 Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power rating : DC 9V From Adapter Input AC 120V/60Hz  
 Test Mode : Tx Mode  
 : M/N:TD-W8151N


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	141.550	11.26	0.94	19.39	31.59	43.50	11.91	QP
2	250.000	12.67	1.16	28.00	41.83	46.00	4.17	QP
3	280.260	13.30	1.24	20.77	35.31	46.00	10.69	QP
4	345.250	15.18	1.41	17.34	33.93	46.00	12.07	QP
5	419.940	17.51	1.62	15.72	34.85	46.00	11.15	QP
6	750.005	22.29	2.56	11.57	36.42	46.00	9.58	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 2

File: E:\2012 Report Data\T\TP-LINK\ACS12Q1733.EM6 (6)


Date: 2012-08-25



Site no. : 3m Chamber Data no. : 2  
Dis. / Ant. : 3m 2012 CBL6111C 2598 Ant. pol. : VERTICAL  
Limit : FCC PART 15 C (3M)  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power rating : DC 9V From Adapter Input AC 120V/60Hz  
Test Mode : Tx Mode  
: M/N:TD-W8151N

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits		Margin (dB)	Remark
						Level (dBuV/m)	Margin (dB)		
1	34.850	16.01	0.51	16.08	32.60	40.00	7.40	QP	
2	49.400	8.78	0.63	22.39	31.80	40.00	8.20	QP	
3	141.550	11.26	0.94	23.43	35.63	43.50	7.87	QP	
4	250.010	12.67	1.16	26.35	40.18	46.00	5.82	QP	
5	419.940	17.51	1.62	17.08	36.21	46.00	9.79	QP	
6	749.740	22.28	2.56	11.14	35.98	46.00	10.02	QP	

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
2. The emission levels that are 20dB below the official limit are not reported.

**Frequency: 1GHz~18GHz**


Site no. : 3m Chamber Data no. : 1  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH1 2412MHz Tx Mode  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-8

Data: 2

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)



Site no. : 3m Chamber Data no. : 2  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH1 2412MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission			
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4824.000	32.89	8.53	34.60	45.89	52.71	74.00	21.29	Peak
2 4824.000	32.89	8.53	34.60	32.13	38.95	54.00	15.05	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-9

Data: 3

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08




Site no. : 3m Chamber Data no. : 3  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH1 2412MHz Tx Mode  
M/N : TD-W8151N

Data: 4

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07




Site no. : 3m Chamber Data no. : 4  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH1 2412MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4824.000	32.89	8.53	34.60	46.07	52.89	74.00	21.11	Peak
2 4824.000	32.89	8.53	34.60	30.84	37.66	54.00	16.34	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 5  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH1 2412MHz Tx Mode  
 M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1609.000	25.79	4.76	34.60	51.64	47.59	74.00	26.41	Peak
2 2329.000	27.86	5.89	34.43	45.22	44.54	74.00	29.46	Peak
3 2412.000	27.98	6.03	34.44	91.26	90.83	74.00	-16.83	Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-12

Data: 6

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 6  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH1 2412MHz Tx Mode  
 M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1609.000	25.79	4.76	34.60	50.86	46.81	74.00	27.19	Peak
2 2329.000	27.86	5.89	34.43	51.51	50.83	74.00	23.17	Peak
3 2412.000	27.98	6.03	34.44	103.26	102.83	74.00	-28.83	Peak
4 2491.000	28.10	6.15	34.45	49.80	49.60	74.00	24.40	Peak

## Remarks:

- Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-13

Data: 11

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)


Date: 2012-09-07



Site no. : 3m Chamber Data no. : 11  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH6 2437MHz Tx Mode  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-14



Site no. : 3m Chamber Data no. : 12  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH6 2437MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission			
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4874.000	32.98	8.58	34.60	46.22	53.18	74.00	20.82	Peak
2 4874.000	32.98	8.58	34.60	30.68	37.64	54.00	16.36	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-15

Data: 13

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07




Site no. : 3m Chamber Data no. : 13  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH6 2437MHz Tx Mode  
M/N : TD-W8151N

Data: 14

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 14  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH6 2437MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission			
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4874.000	32.98	8.58	34.60	45.37	52.33	74.00	21.67	Peak
2 4874.000	32.98	8.58	34.60	32.18	39.14	54.00	14.86	Average


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 15

File: E:\2012 Report\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 15  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH6 2437MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1624.000	25.86	4.78	34.59	52.32	48.37	74.00	25.63	Peak
2 2437.000	28.03	6.06	34.44	92.12	91.77	74.00	-17.77	Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-18

Data: 16

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 16  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH6 2437MHz Tx Mode  
M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1624.000	25.86	4.78	34.59	52.55	48.60	74.00	25.40	Peak
2 2356.000	27.91	5.95	34.44	51.83	51.25	74.00	22.75	Peak
3 2437.000	28.03	6.06	34.44	104.01	103.66	74.00	-29.66	Peak
4 2521.000	28.16	6.20	34.45	49.07	48.98	74.00	25.02	Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3


page 4-19



Site no. : 3m Chamber Data no. : 17  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH11 2462MHz Tx Mode  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-20



Site no. : 3m Chamber Data no. : 18  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH11 2462MHz Tx Mode  
 M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4924.000	33.08	8.62	34.60	45.38	52.48	74.00	21.52	Peak
2 4924.000	33.08	8.62	34.60	31.05	38.15	54.00	15.85	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-21




Site no. : 3m Chamber Data no. : 19  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH11 2462MHz Tx Mode  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-22

Data: 20 File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)



Site no. : 3m Chamber Data no. : 20  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH11 2462MHz Tx Mode  
M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission			
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4924.000	33.08	8.62	34.60	46.51	53.61	74.00	20.39	Peak
2 4924.000	33.08	8.62	34.60	32.23	39.33	54.00	14.67	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-23



Site no. : 3m Chamber Data no. : 25  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH11 2462MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission			
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1639.000	25.93	4.81	34.58	52.54	48.70	74.00	25.30	Peak
2 2462.000	28.05	6.12	34.44	90.25	89.98	74.00	-15.98	Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-24

Data: 26

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 26  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH11 2462MHz Tx Mode  
 M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1639.000	25.93	4.81	34.58	52.12	48.28	74.00	25.72	Peak
2 2386.000	27.96	6.01	34.44	50.29	49.82	74.00	24.18	Peak
3 2462.000	28.05	6.12	34.44	102.33	102.06	74.00	-28.06	Peak
4 2539.000	28.29	6.23	34.46	50.24	50.30	74.00	23.70	Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-25



Site no. : 3m Chamber Data no. : 31  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH11 2462MHz Tx Mode  
 M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1645.000	25.93	4.81	34.58	44.47	40.63	74.00	33.37	Peak
2 2380.000	27.93	5.98	34.44	46.43	45.90	74.00	28.10	Peak
3 2462.000	28.05	6.12	34.44	94.68	94.41	74.00	-20.41	Peak
4 2545.000	28.29	6.23	34.46	43.97	44.03	74.00	29.97	Peak


## Remarks:

- Emission Level = Antenna Factor + Cable Loss - Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.

Data: 32

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 32  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH11 2462MHz Tx Mode  
M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1645.000	25.93	4.81	34.58	44.69	40.85	74.00	33.15	Peak
2 2380.000	27.93	5.98	34.44	51.65	51.12	74.00	22.88	Peak
3 2462.000	28.05	6.12	34.44	106.03	105.76	74.00	-31.76	Peak
4 2536.000	28.23	6.23	34.45	51.42	51.43	74.00	22.57	Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3


page 4-27



Site no. : 3m Chamber Data no. : 33  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH11 2462MHz Tx  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-28



Site no. : 3m Chamber Data no. : 34  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH11 2462MHz Tx  
 M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4924.000	33.08	8.62	34.60	45.23	52.33	74.00	21.67	Peak
2 4924.000	33.08	8.62	34.60	31.02	38.12	54.00	15.88	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-29

Data: 35

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)


Date: 2012-09-08



Site no. : 3m Chamber Data no. : 35  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH11 2462MHz Tx  
M/N : TD-W8151N

Data: 36

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)



Site no. : 3m Chamber Data no. : 36  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH11 2462MHz Tx  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	4924.000	33.08	8.62	34.60	44.59	51.69	74.00	22.31 Peak
2	4924.000	33.08	8.62	34.60	30.71	37.81	54.00	16.19 Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-31

Data: 37

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)


Date: 2012-09-08



Site no. : 3m Chamber Data no. : 37  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH6 2437MHz Tx  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-32



Site no. : 3m Chamber Data no. : 38  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH6 2437MHz Tx  
 M/N : TD-W8151N


	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	4874.000	32.98	8.58	34.60	44.95	51.91	74.00	22.09 Peak
2	4874.000	32.98	8.58	34.60	30.56	37.52	54.00	16.48 Average

## Remarks:

- Emission Level = Antenna Factor + Cable Loss - Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-33



Site no. : 3m Chamber Data no. : 39  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH6 2437MHz Tx  
M/N : TD-W8151N


FCC ID:TE7TDW8151NV3

page 4-34

Data: 40

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 40  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH6 2437MHz Tx  
M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission			
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4874.000	32.98	8.58	34.60	45.28	52.24	74.00	21.76	Peak
2 4874.000	32.98	8.58	34.60	31.24	38.20	54.00	15.80	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-35



Site no. : 3m Chamber Data no. : 41  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH6 2437MHz Tx Mode  
 M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1624.000	25.86	4.78	34.59	42.85	38.90	74.00	35.10	Peak
2 2359.000	27.91	5.95	34.44	52.35	51.77	74.00	22.23	Peak
3 2437.000	28.03	6.06	34.44	107.33	106.98	74.00	-32.98	Peak
4 2515.000	28.16	6.20	34.45	50.61	50.52	74.00	23.48	Peak

## Remarks:

- Emission Level = Antenna Factor + Cable Loss - Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-36

Data: 42

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07




Site no. : 3m Chamber Data no. : 42  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH6 2437MHz Tx Mode  
 M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission			
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 1555.000	25.58	4.67	34.62	43.98	39.61	74.00	34.39	Peak
2 2356.000	27.91	5.95	34.44	46.28	45.70	74.00	28.30	Peak
3 2437.000	28.03	6.06	34.44	94.26	93.91	74.00	-19.91	Peak
4 2521.000	28.16	6.20	34.45	44.06	43.97	74.00	30.03	Peak

## Remarks:

- Emission Level = Antenna Factor + Cable Loss - Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 43  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH1 2412MHz Tx  
M/N : TD-W8151N

Data: 44

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 44  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH1 2412MHz Tx  
M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4824.000	32.89	8.53	34.60	45.66	52.48	74.00	21.52	Peak
2 4824.000	32.89	8.53	34.60	30.78	37.60	54.00	16.40	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3


page 4-39



Site no. : 3m Chamber Data no. : 45  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH1 2412MHz Tx  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-40



Site no. : 3m Chamber Data no. : 46  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH1 2412MHz Tx  
 M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4824.000	32.89	8.53	34.60	44.57	51.39	74.00	22.61	Peak
2 4824.000	32.89	8.53	34.60	30.52	37.34	54.00	16.66	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-41



Site no. : 3m Chamber Data no. : 51  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH1 2412MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission			
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
1 2412.000	27.98	6.03	34.44	97.15	96.72	74.00	-22.72 Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-42

Data: 52

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 52  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH1 2412MHz Tx Mode  
M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dB <sub>B</sub> V)	Level (dB <sub>B</sub> V/m)	Limits (dB <sub>B</sub> V/m)	Margin (dB)	Remark
1 2335.000	27.88	5.92	34.43	50.94	50.31	74.00	23.69	Peak
2 2412.000	27.98	6.03	34.44	110.32	109.89	74.00	-35.89	Peak
3 2491.000	28.10	6.15	34.45	49.88	49.68	74.00	24.32	Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-43




Site no. : 3m Chamber Data no. : 53  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH1 2412MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2329.000	27.86	5.89	34.43	51.77	51.09	74.00	22.91 Peak
2	2412.000	27.98	6.03	34.44	109.64	109.21	74.00	-35.21 Peak
3	2494.000	28.10	6.18	34.45	50.98	50.81	74.00	23.19 Peak

Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 54  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH1 2412MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 2412.000	27.98	6.03	34.44	97.08	96.65	74.00	-22.65	Peak

Remarks:


1. Emission Level = Antenna Factor + Cable Loss + Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 59  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH1 2412MHz Tx  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-46



Site no. : 3m Chamber Data no. : 60  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH1 2412MHz Tx  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission			
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4824.000	32.89	8.53	34.60	44.73	51.55	74.00	22.45	Peak
2 4824.000	32.89	8.53	34.60	30.41	37.23	54.00	16.77	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-47

Data: 61

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 61  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH1 2412MHz Tx  
M/N : TD-W8151N


FCC ID:TE7TDW8151NV3

page 4-48

Data: 62

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08




Site no. : 3m Chamber Data no. : 62  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH1 2412MHz Tx  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	4824.000	32.89	8.53	34.60	45.33	52.15	74.00	21.85 Peak
2	4824.000	32.89	8.53	34.60	31.12	37.94	54.00	16.06 Average

## Remarks:


1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 63  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH6 2437MHz Tx  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-50



Site no. : 3m Chamber Data no. : 64  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11nHT20 CH6 2437MHz Tx  
 M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4874.000	32.98	8.58	34.60	45.48	52.44	74.00	21.56	Peak
2 4874.000	32.98	8.58	34.60	31.09	38.05	54.00	15.95	Average

## Remarks:

- Emission Level = Antenna Factor + Cable Loss - Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-51

Data: 65

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 65  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH6 2437MHz Tx  
M/N : TD-W8151N


FCC ID:TE7TDW8151NV3

page 4-52

Data: 66

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 66  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH6 2437MHz Tx  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission			
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4874.000	32.98	8.58	34.60	44.68	51.64	74.00	22.36	Peak
2 4874.000	32.98	8.58	34.60	30.47	37.43	54.00	16.57	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-53

Data: 67

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08




Site no. : 3m Chamber Data no. : 67  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH6 2437MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission			
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB)	(dB <sub>UV</sub> )	(dB <sub>UV</sub> /m)	(dB <sub>UV</sub> /m)	(dB)
1	2437.000	28.03	6.06	34.44	94.03	93.68	74.00 -19.68 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 68  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH6 2437MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 2359.000	27.91	5.95	34.44	50.23	49.65	74.00	24.35	Peak
2 2437.000	28.03	6.06	34.44	107.57	107.22	74.00	-33.22	Peak
3 2521.000	28.16	6.20	34.45	51.14	51.05	74.00	22.95	Peak


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 69

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)


Date: 2012-09-08



Site no. : 3m Chamber Data no. : 69  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH11 2462MHz Tx  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-56



Site no. : 3m Chamber Data no. : 70  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11nHT20 CH11 2462MHz Tx  
 M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4924.000	33.08	8.62	34.60	44.81	51.91	74.00	22.09	Peak
2 4924.000	33.08	8.62	34.60	30.55	37.65	54.00	16.35	Average

## Remarks:

- Emission Level = Antenna Factor + Cable Loss - Amp Factor + Reading.
- The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-57

Data: 71

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)


Date: 2012-09-08



Site no. : 3m Chamber Data no. : 71  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH11 2462MHz Tx  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-58



Site no. : 3m Chamber Data no. : 72  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11nHT20 CH11 2462MHz Tx  
 M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4924.000	33.08	8.62	34.60	45.13	52.23	74.00	21.77	Peak
2 4924.000	33.08	8.62	34.60	30.98	38.08	54.00	15.92	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-59




Site no. : 3m Chamber Data no. : 73  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH11 2462MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission					
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark	
<hr/>									
1 2386.000	27.96	6.01	34.44	50.72	50.25	74.00	23.75	Peak	
2 2462.000	28.05	6.12	34.44	107.27	107.00	74.00	-33.00	Peak	
3 2545.000	28.29	6.23	34.46	49.88	49.94	74.00	24.06	Peak	
<hr/>									

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 74  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH11 2462MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission			
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)
1	2462.000	28.05	6.12	34.44	92.78	92.51	74.00 -18.51 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 83  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH7 2452MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission			
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)
1	2452.000	28.03	6.09	34.44	89.04	88.72	74.00 -14.72 Peak


Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 84

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 84  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH7 2452MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission			
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)
1	2452.000	28.03	6.09	34.44	102.95	102.63	74.00 -28.63 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-63


Data: 85

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 85  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH7 2452MHz Tx  
M/N : TD-W8151N



Site no. : 3m Chamber Data no. : 86  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH7 2452MHz Tx  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4904.000	33.04	8.61	34.60	44.73	51.78	74.00	22.22	Peak
2 4904.000	33.04	8.61	34.60	30.37	37.42	54.00	16.58	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-65

Data: 87

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)


Date: 2012-09-08



Site no. : 3m Chamber Data no. : 87  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH7 2452MHz Tx  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-66



Site no. : 3m Chamber Data no. : 88  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11nHT40 CH7 2452MHz Tx  
 M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4904.000	33.04	8.61	34.60	44.36	51.41	74.00	22.59	Peak
2 4904.000	33.04	8.61	34.60	30.19	37.24	54.00	16.76	Average

## Remarks:

1. Emission Level = Antenna Factor + Cable Loss - Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-67



Site no. : 3m Chamber Data no. : 89  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH4 2437MHz Tx  
M/N : TD-W8151N


FCC ID:TE7TDW8151NV3

page 4-68

Data: 90

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 90  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11nHT40 CH4 2437MHz Tx  
 M/N : TD-W8151N


	Freq. (MHz)	Ant. (dB/m)	Cable loss (dB)	Amp. (dB)	Emission Level (dBuV)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.98	8.58	34.60	44.78	51.74	74.00	22.26 Peak
2	4874.000	32.98	8.58	34.60	30.59	37.55	54.00	16.45 Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-69




Site no. : 3m Chamber Data no. : 91  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH4 2437MHz Tx  
M/N : TD-W8151N

Data: 92

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 92  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH4 2437MHz Tx  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	4874.000	32.98	8.58	34.60	44.69	51.65	74.00	22.35 Peak
2	4874.000	32.98	8.58	34.60	30.51	37.47	54.00	16.53 Average


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 93

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 93  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH4 2437MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission			
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)
1	2437.000	28.03	6.06	34.44	104.13	103.78	74.00 -29.78 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-72

Data: 94

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 94  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH4 2437MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission			
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB)	(dB <sub>UV</sub> )	(dB <sub>UV</sub> /m)	(dB <sub>UV</sub> /m)	(dB)
1	2437.000	28.03	6.06	34.44	90.97	90.62	74.00 -16.62 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 4-73

Data: 95

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)


Date: 2012-09-08



Site no. : 3m Chamber Data no. : 95  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH1 2422MHz Tx  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-74



Site no. : 3m Chamber Data no. : 96  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH1 2422MHz Tx  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4844.000	32.92	8.55	34.60	44.83	51.70	74.00	22.30	Peak
2 4844.000	32.92	8.55	34.60	30.75	37.62	54.00	16.38	Average

## Remarks:


1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-75

Data: 97

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)




Site no. : 3m Chamber Data no. : 97  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH1 2422MHz Tx  
M/N : TD-W8151N

FCC ID:TE7TDW8151NV3

page 4-76

Data: 98 File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)



Site no. : 3m Chamber Data no. : 98  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH1 2422MHz Tx  
M/N : TD-W8151N


Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Reading (dBuV)	Emission			
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 4844.000	32.92	8.55	34.60	44.38	51.25	74.00	22.75	Peak
2 4844.000	32.92	8.55	34.60	30.51	37.38	54.00	16.62	Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-77



Site no. : 3m Chamber Data no. : 103  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH1 2422MHz Tx Mode  
M/N : TD-W8151N


	Ant.	Cable	Amp.	Emission			
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)
1	2422.000	28.00	6.06	34.44	90.23	89.85	74.00 -15.85 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 4-78



Site no. : 3m Chamber Data no. : 104  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH1 2422MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission			
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)
1	2422.000	28.00	6.06	34.44	104.79	104.41	74.00 -30.41 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

## 5. CONDUCTED SPURIOUS EMISSIONS

### 5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	May.08,12	1 Year
2.	Attenuator	Agilent	8491B	MY39262165	May.08,12	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,12	1 Year

### 5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

### 5.3. Test Procedure



The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions detected.



### 5.4. Test result

**PASS** (The testing data was attached in the next pages.)



Test Mode: IEEE 802.11b TX


Test CH1: 2412MHz








Test CH6: 2437MHz






Test CH11: 2462MHz











Test Mode: IEEE 802.11g TX


Test CH1: 2412MHz













Test CH6: 2437MHz







Test CH11: 2462MHz









Test Mode: IEEE 802.11n HT20 TX


Test CH1: 2412MHz








Test CH6: 2437MHz






Test CH11: 2462MHz











Test Mode: IEEE 802.11n HT40 TX


Test CH1: 2422MHz













Test CH4: 2437MHz





Test CH7: 2452MHz





## 6. BAND EDGE COMPLIANCE TEST

### 6.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 12	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 12	1 Year
3.	Antenna	EMCO	3115	9510-4580	May.08, 12	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 12	1 Year

### 6.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 6.3. Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=1MHz; VBW=3MHz; Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz; VBW=10Hz; Sweep=AUTO


### 6.4. Test Results

Pass (The testing data was attached in the next pages.)

Data: 7

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 7  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH1 2412MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2334.725	27.88	5.92	34.43	51.98	51.35	54.00	2.65 Average
2	2390.000	27.96	6.01	34.44	40.74	40.27	54.00	13.73 Average
3	2397.170	27.96	6.01	34.44	47.81	47.34	54.00	6.66 Average
4	2400.000	27.96	6.01	34.44	47.86	47.39	54.00	6.61 Average
5	2411.200	27.98	6.03	34.44	100.15	99.72	54.00	-45.72 Average


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 8

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 8  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11b CH1 2412MHz Tx Mode  
 M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2333.805	27.86	5.92	34.43	58.82	58.17	74.00	15.83 Peak
2	2390.000	27.96	6.01	34.44	52.54	52.07	74.00	21.93 Peak
3	2400.000	27.96	6.01	34.44	56.74	56.27	74.00	17.73 Peak
4	2410.625	27.98	6.03	34.44	103.48	103.05	74.00	-29.05 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 6-4

Data: 9

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 9  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH1 2412MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2335.530	27.88	5.92	34.43	51.82	51.19	74.00	22.81 Peak
2	2390.000	27.96	6.01	34.44	48.03	47.56	74.00	26.44 Peak
3	2400.000	27.96	6.01	34.44	49.69	49.22	74.00	24.78 Peak
4	2410.395	27.98	6.03	34.44	91.24	90.81	74.00	-16.81 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 6-5

Data: 10

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 10  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH1 2412MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2334.495	27.86	5.92	34.43	40.73	40.08	54.00	13.92 Average
2	2390.000	27.96	6.01	34.44	36.42	35.95	54.00	18.05 Average
3	2400.000	27.96	6.01	34.44	38.24	37.77	54.00	16.23 Average
4	2411.200	27.98	6.03	34.44	88.09	87.66	54.00	-33.66 Average


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 21

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 21  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH11 2462MHz Tx Mode  
M/N : TD-W8151N


	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2460.500	28.05	6.12	34.44	102.19	101.92	74.00	-27.92 Peak
2	2483.500	28.08	6.15	34.45	51.35	51.13	74.00	22.87 Peak
3	2497.580	28.10	6.18	34.45	53.09	52.92	74.00	21.08 Peak
4	2500.000	28.10	6.18	34.45	51.31	51.14	74.00	22.86 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 22 File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 22  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH11 2462MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2459.180	28.05	6.12	34.44	98.34	98.07	54.00	-44.07 Average
2	2483.500	28.08	6.15	34.45	38.71	38.49	54.00	15.51 Average
3	2500.000	28.10	6.18	34.45	40.75	40.58	54.00	13.42 Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3


page 6-8

Data: 23

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Level (dBuV/m)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 23  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH11 2462MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2460.680	28.05	6.12	34.44	90.09	89.82	74.00	-15.82 Peak
2	2483.500	28.08	6.15	34.45	49.49	49.27	74.00	24.73 Peak
3	2496.020	28.10	6.18	34.45	49.75	49.58	74.00	24.42 Peak
4	2500.000	28.10	6.18	34.45	50.08	49.91	74.00	24.09 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 6-9

Data: 24

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 24  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11b CH11 2462MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2459.180	28.05	6.12	34.44	86.42	86.15	54.00	-32.15 Average
2	2483.500	28.08	6.15	34.45	35.87	35.65	54.00	18.35 Average
3	2500.000	28.10	6.18	34.45	36.25	36.08	54.00	17.92 Average


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 27

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 27  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH11 2462MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2460.800	28.05	6.12	34.44	106.33	106.06	74.00	-32.06 Peak
2	2483.500	28.08	6.15	34.45	65.15	64.93	74.00	9.07 Peak
3	2500.000	28.10	6.18	34.45	53.61	53.44	74.00	20.56 Peak


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 28

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 28  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH11 2462MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2459.000	28.05	6.12	34.44	95.85	95.58	54.00	-41.58 Average
2	2483.500	28.08	6.15	34.45	42.76	42.54	54.00	11.46 Average
3	2500.000	28.10	6.18	34.45	39.37	39.20	54.00	14.80 Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 6-12

Data: 29

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 29  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH11 2462MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2458.820	28.05	6.12	34.44	94.05	93.78	74.00	-19.78 Peak
2	2483.500	28.08	6.15	34.45	51.06	50.84	74.00	23.16 Peak
3	2483.720	28.08	6.15	34.45	52.69	52.47	74.00	21.53 Peak
4	2500.000	28.10	6.18	34.45	48.34	48.17	74.00	25.83 Peak


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 30

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-07



Site no. : 3m Chamber Data no. : 30  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH11 2462MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2463.800	28.05	6.12	34.45	84.31	84.03	54.00	-30.03 Average
2	2483.500	28.08	6.15	34.45	36.70	36.48	54.00	17.52 Average
3	2500.000	28.10	6.18	34.45	36.81	36.64	54.00	17.36 Average


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 47

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 47  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH1 2412MHz Tx Mode  
 M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2333.805	27.86	5.92	34.43	52.10	51.45	54.00	2.55 Average
2	2390.000	27.96	6.01	34.44	46.93	46.46	54.00	7.54 Average
3	2400.000	27.96	6.01	34.44	63.47	63.00	54.00	-9.00 Average
4	2413.845	27.98	6.03	34.44	101.46	101.03	54.00	-47.03 Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 6-15

Data: 48

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 48  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH1 2412MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2334.380	27.86	5.92	34.43	62.06	61.41	74.00	12.59 Peak
2	2390.000	27.96	6.01	34.44	63.06	62.59	74.00	11.41 Peak
3	2400.000	27.96	6.01	34.44	81.37	80.90	74.00	-6.90 Peak
4	2408.325	27.98	6.03	34.44	110.93	110.50	74.00	-36.50 Peak


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 49

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 49  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11g CH1 2412MHz Tx Mode  
 M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2328.055	27.86	5.89	34.43	52.56	51.88	74.00	22.12 Peak
2	2390.000	27.96	6.01	34.44	48.97	48.50	74.00	25.50 Peak
3	2400.000	27.96	6.01	34.44	67.10	66.63	74.00	7.37 Peak
4	2414.650	27.98	6.03	34.44	97.91	97.48	74.00	-23.48 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 6-17

Data: 50

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 50  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11g CH1 2412MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2334.725	27.88	5.92	34.43	40.46	39.83	54.00	14.17 Average
2	2390.000	27.96	6.01	34.44	37.41	36.94	54.00	17.06 Average
3	2400.000	27.96	6.01	34.44	48.22	47.75	54.00	6.25 Average
4	2413.845	27.98	6.03	34.44	88.45	88.02	54.00	-34.02 Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 6-18

Data: 55

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 55  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH1 2412MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2336.105	27.88	5.92	34.43	62.07	61.44	74.00	12.56 Peak
2	2390.000	27.96	6.01	34.44	68.27	67.80	74.00	6.20 Peak
3	2400.000	27.96	6.01	34.44	78.64	78.17	74.00	-4.17 Peak
4	2410.280	27.98	6.03	34.44	109.80	109.37	74.00	-35.37 Peak


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 56

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 56  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C AV  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11nHT20 CH1 2412MHz Tx Mode  
 M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2335.530	27.88	5.92	34.43	50.91	50.28	54.00	3.72 Average
2	2390.000	27.96	6.01	34.44	48.19	47.72	54.00	6.28 Average
3	2400.000	27.96	6.01	34.44	62.60	62.13	54.00	-8.13 Average
4	2410.395	27.98	6.03	34.44	100.19	99.76	54.00	-45.76 Average


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 57

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 57  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH1 2412MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 2334.955	27.88	5.92	34.43	40.19	39.56	54.00	14.44	Average
2 2390.000	27.96	6.01	34.44	37.88	37.41	54.00	16.59	Average
3 2400.000	27.96	6.01	34.44	47.69	47.22	54.00	6.78	Average
4 2414.880	27.98	6.03	34.44	87.14	86.71	54.00	-32.71	Average

## Remarks:


1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 6-21

Data: 58 File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 58  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH1 2412MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2336.220	27.88	5.92	34.43	52.95	52.32	74.00	21.68 Peak
2	2390.000	27.96	6.01	34.44	54.33	53.86	74.00	20.14 Peak
3	2398.780	27.96	6.01	34.44	63.76	63.29	74.00	10.71 Peak
4	2400.000	27.96	6.01	34.44	62.60	62.13	74.00	11.87 Peak
5	2413.730	27.98	6.03	34.44	97.12	96.69	74.00	-22.69 Peak

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 6-22

Data: 75

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 75  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH11 2462MHz Tx Mode  
M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 2460.200	28.05	6.12	34.44	107.02	106.75	74.00	-32.75	Peak
2 2483.500	28.08	6.15	34.45	65.41	65.19	74.00	8.81	Peak
3 2500.000	28.10	6.18	34.45	53.27	53.10	74.00	20.90	Peak


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 76

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 76  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH11 2462MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2459.420	28.05	6.12	34.44	96.54	96.27	54.00	-42.27 Average
2	2483.500	28.08	6.15	34.45	44.03	43.81	54.00	10.19 Average
3	2500.000	28.10	6.18	34.45	39.63	39.46	54.00	14.54 Average


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 77

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 77  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT20 CH11 2462MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2459.300	28.05	6.12	34.44	82.34	82.07	54.00	-28.07 Average
2	2483.500	28.08	6.15	34.45	36.74	36.52	54.00	17.48 Average
3	2500.000	28.10	6.18	34.45	36.02	35.85	54.00	18.15 Average


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 78

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 78  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11nHT20 CH11 2462MHz Tx Mode  
 M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2460.020	28.05	6.12	34.44	92.51	92.24	74.00	-18.24 Peak
2	2483.500	28.08	6.15	34.45	51.92	51.70	74.00	22.30 Peak
3	2483.780	28.08	6.15	34.45	51.61	51.39	74.00	22.61 Peak
4	2500.000	28.10	6.18	34.45	48.60	48.43	74.00	25.57 Peak


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 79

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 79  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH7 2452MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2443.955	28.03	6.09	34.44	103.63	103.31	74.00	-29.31 Peak
2	2483.500	28.08	6.15	34.45	69.27	69.05	74.00	4.95 Peak
3	2486.200	28.08	6.15	34.45	70.42	70.20	74.00	3.80 Peak
4	2500.000	28.10	6.18	34.45	57.33	57.16	74.00	16.84 Peak


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 80

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 80  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : VERTICAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH7 2452MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2446.845	28.03	6.09	34.44	95.27	94.95	54.00	-40.95 Average
2	2483.500	28.08	6.15	34.45	50.98	50.76	54.00	3.24 Average
3	2500.000	28.10	6.18	34.45	42.80	42.63	54.00	11.37 Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


FCC ID:TE7TDW8151NV3

page 6-28

Data: 81

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 81  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH7 2452MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2442.595	28.03	6.09	34.44	88.33	88.01	74.00	-14.01 Peak
2	2483.500	28.08	6.15	34.45	51.84	51.62	74.00	22.38 Peak
3	2500.000	28.10	6.18	34.45	47.88	47.71	74.00	26.29 Peak


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 82

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 82  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH7 2452MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	28.08	6.15	34.45	37.79	37.57	54.00	16.43 Average
2	2500.000	28.10	6.18	34.45	35.90	35.73	54.00	18.27 Average


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 99

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 99  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11nHT40 CH1 2422MHz Tx Mode  
 M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2386.020	27.96	6.01	34.44	70.85	70.38	74.00	3.62 Peak
2	2390.000	27.96	6.01	34.44	68.44	67.97	74.00	6.03 Peak
3	2400.000	27.96	6.01	34.44	71.83	71.36	74.00	2.64 Peak
4	2412.620	27.98	6.03	34.44	104.95	104.52	74.00	-30.52 Peak


## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 100

File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08



Site no. : 3m Chamber Data no. : 100  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH1 2422MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2390.000	27.96	6.01	34.44	50.78	50.31	54.00	3.69 Average
2	2400.000	27.96	6.01	34.44	57.83	57.36	54.00	-3.36 Average
3	2413.320	27.98	6.03	34.44	94.06	93.63	54.00	-39.63 Average

## Remarks:


1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

FCC ID:TE7TDW8151NV3

page 6-32

Data: 101 File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)

Date: 2012-09-08




Site no. : 3m Chamber Data no. : 101  
Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C AV  
Env. / Ins. : 23°C/54% Engineer : Leo-Li  
EUT : 150Mbps Wireless N ADSL2+ Modem Router  
Power supply : DC 9V From Adapter Input AC 120V/60Hz  
Test mode : IEEE802.11nHT40 CH1 2422MHz Tx Mode  
M/N : TD-W8151N

	Ant.	Cable	Amp.	Emission				
Freq.	Factor	loss	Factor	Reading	Level	Limits	Margin	Remark
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2390.000	27.96	6.01	34.44	39.22	38.75	54.00	15.25 Average
2	2400.000	27.96	6.01	34.44	44.30	43.83	54.00	10.17 Average
3	2414.300	27.98	6.03	34.44	80.85	80.42	54.00	-26.42 Average

## Remarks:

1. Emission Level= Antenna Factor + Cable Loss -Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 102 File: E:\2012 Report\T\TP-LINK\ACS12Q1733.EM6 (104)



Site no. : 3m Chamber Data no. : 102  
 Dis. / Ant. : 3m 2011 3115 4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23°C/54% Engineer : Leo-Li  
 EUT : 150Mbps Wireless N ADSL2+ Modem Router  
 Power supply : DC 9V From Adapter Input AC 120V/60Hz  
 Test mode : IEEE802.11nHT40 CH1 2422MHz Tx Mode  
 M/N : TD-W8151N

Freq. (MHz)	Ant. Factor (dB/m)	Cable loss (dB)	Amp. Factor (dB)	Emission				
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 2386.300	27.96	6.01	34.44	56.61	56.14	74.00	17.86	Peak
2 2390.000	27.96	6.01	34.44	53.67	53.20	74.00	20.80	Peak
3 2398.480	27.96	6.01	34.44	58.55	58.08	74.00	15.92	Peak
4 2400.000	27.96	6.01	34.44	56.03	55.56	74.00	18.44	Peak
5 2414.020	27.98	6.03	34.44	90.94	90.51	74.00	-16.51	Peak

## Remarks:

1. Emission Level = Antenna Factor + Cable Loss - Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

## 7. 6dB Bandwidth Test

### 7.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 12	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 12	1 Year
3.	Antenna	EMCO	3115	9510-4580	May.08, 12	1 Year
4.	HF Cable	Hubersuhner	Sucoflex104	-	May.08, 12	1 Year

### 7.2. Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

### 7.3. Test Procedure

The transmitter output was connected to a spectrum analyzer. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300 kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

### 7.4. Test Results


EUT:150Mbps Wireless N ADSL2+ Modem Router		
M/N: TD-W8151N		
Test date: 2012-09-13	Pressure: 101.2±1 kpa	Humidity: 50.8±1%
Tested by: Leo-Li	Test site: RF Site	Temperature : 24.7±1°C

Cable loss: 1 dB		Attenuator loss: 20 dB	
Test Mode	CH	6dB bandwidth (MHz)	Limit (KHz)
11b	CH1	11.244	>500
	CH6	11.243	>500
	CH11	11.231	>500
11g	CH1	16.248	>500
	CH6	16.040	>500
	CH11	16.149	>500
11n HT20	CH1	16.965	>500
	CH6	16.904	>500
	CH11	16.957	>500
11n HT40	CH1	34.078	>500
	CH4	34.027	>500
	CH7	34.882	>500
Conclusion : PASS			

Test Mode: IEEE 802.11b TX


Test CH1: 2412MHz

\* Agilent




Test CH6: 2437MHz

\* Agilent




Test CH11: 2462MHz




Test Mode: IEEE 802.11g TX


Test CH1: 2412MHz



## Test CH6: 2437MHz




## Test CH11: 2462MHz



Test Mode: IEEE 802.11n HT20 TX


Test CH1: 2412MHz

\* Agilent




Test CH6: 2437MHz

\* Agilent




Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT40 TX


Test CH1: 2422MHz



Test CH4: 2437MHz



Test CH7: 2452MHz



## 8. OUTPUT POWER TEST

### 8.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 12	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 12	1 Year
3.	Antenna	EMCO	3115	9510-4580	May.08, 12	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 12	1 Year
5.	Power Meter	Anritsu	ML2487A	6K00002472	May.08, 12	1 Year
6.	Power Sensor	Anritsu	MA2491A	033005	May.08, 12	1 Year

### 8.2. Limit (FCC Part 15C 15.247 b(3))

For systems using digital modulation in the 2400—2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm)

### 8.3. Test Procedure

- 1, Connected the EUT's antenna port to measure device by 26dB attenuator.
- 2, For IEEE 802.11b/g and IEEE802.11n HT20 mode, use a PK power meter which's bandwidth is 20MHz and above 26dB bandwidth of signal to measure out each test modes' PK output power.
- 3, For IEEE802.11n HT40 mode, because the signal's bandwidth is about 40MHz and above 20MHz bandwidth of power sensor ML2491A. So Bandwidth correction method according to ANSI C63.10 clause 6.10.2.1 part (c) was used:
  - 1) Set the RBW=3MHz and VBW =8MHz
  - 2) Turn averaging off
  - 3) Set sweep to automatic
  - 4) Set the span just large enough to capture the emission
  - 5) Use a peak detector on max hold
  - 6) Record the measured power
  - 7) Calculate Output power of EUT use the formula:

Peak output power =measured power+ 10log[(26dB bandwidth of emission)/(analyzer RBW)]

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.



## 8.4. Test Results


EUT: 150Mbps Wireless N ADSL2+ Modem Router			
M/N: TD-W8151N			
Test date: 2012-09-13	Pressure: 101.2 ±1kpa		Humidity: 54.2±1 %
Tested by: Leo-Li	Test site: RF site		Temperature: 23.9 ±1 °C
Cable loss: 1 dB		Attenuator loss: 20 dB	
Test Mode	CH (MHz)	Peak output Power (dBm)	Limit (dBm)
11b	CH1	17.64	30
	CH6	18.75	30
	CH11	17.7	30
11g	CH1	24.09	30
	CH6	23.61	30
	CH11	22.67	30
11n HT20	CH1	24.18	30
	CH6	23.41	30
	CH11	22.44	30

Test Mode	CH	Result		Limit
		Measured power(dBm)/3MHz	PK Output power (dBm)	
11n HT40	CH1	10.61	21.83	30
	CH4	12.14	23.36	30
	CH7	9.78	21.00	30


26dB Bandwidth for 11n HT40: 39.702MHz  
BW correction factor =  $10\log[(39.702/3MHz)] = 11.22$   
Conclusion: PASS



Test Mode: IEEE 802.11n HT40





## 26dB Bandwidth





## 9. POWER SPECTRAL DENSITY TEST

### 9.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	May.08, 12	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 12	1 Year
3.	Antenna	EMCO	3115	9510-4580	May.08, 12	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 12	1 Year

### 9.2. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

### 9.3. Test Procedure

1. Connected the EUT's antenna port to spectrum analyzer device by 20dB attenuator.
2. Set the test frequency as center frequency, Set RBW=100KHz, VBW=300KHz, Span large enough capture the entire frequency the max hold, Read out maximum peak power level Value
3. Scale the observed power level get from step 2 to an equivalent value in 3KHz by adjusting the measured power by a bandwidth correction factor (BWCF), where  $BWCF=10\log(3KHz/100KHz)=-15.2dB$ )

Note: The cable loss and attenuator loss were offset into measure device as an amplitude

## 9.4. Test Results


EUT:150Mbps Wireless N ADSL2+ Modem Router			
M/N: TD-W8151N			
Test date: 2012-09-13	Pressure: 101.2±1kpa	Humidity: 52.8±1%	
Tested by: Leo-Li	Test site: RF Site	Temperature : 24.2±1°C	

Cable loss: 1 dB		Attenuator loss: 20 dB		
Test Mode	CH	Power density (dBm/100KHz)	Power density (dBm/3KHz)	Limit (dBm/3KHz)
11b	CH1	2.42	-12.78	8
	CH6	3.58	-11.62	8
	CH11	2.57	-12.63	8
11g	CH1	1.96	-13.24	8
	CH6	1.37	-13.83	8
	CH11	0.49	-14.71	8
11n HT20	CH1	2.37	-12.83	8
	CH6	1.99	-13.21	8
	CH11	0.72	-14.48	8
11n HT40	CH1	-3.14	-18.34	8
	CH4	-1.61	-16.81	8
	CH7	-3.91	-19.11	8
BW correction factor = $10\log[(3/100\text{KHz})] = -15.2$				
Conclusion : PASS				

Test Mode: IEEE 802.11b TX

Test CH1: 2412MHz


Agilent



File Operation Status, A:\SCREN064.GIF file saved


Test CH6: 2437MHz

Agilent




File Operation Status, A:\SCREN065.GIF file saved

Test CH11: 2462MHz




Test Mode: IEEE 802.11g TX


Test CH1: 2412MHz



## Test CH6: 2437MHz




## Test CH11: 2462MHz



Test Mode: IEEE 802.11n HT20 TX

Test CH1: 2412MHz


Agilent



File Operation Status, A:\SCREN073.GIF file saved


Test CH6: 2437MHz

Agilent




File Operation Status, A:\SCREN072.GIF file saved

Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT40 TX


Test CH1: 2422MHz



## Test CH4: 2437MHz



## Test CH7: 2452MHz



## 10. ANTENNA REQUIREMENT

### 10.1. STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 10.2. ANTENNA CONNECTED CONSTRUCTION

The antennas used for this product are Dipole antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 5dBi.

## 11.MPE ESTIMATION

### 11.1.Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm <sup>2</sup> )	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Frequency(MHz)	Power density (mW/ cm <sup>2</sup> )	Averaging time(minutes)
2412	1	30
2437	1	30
2462	1	30

Note: F= Frequency in MHz

### 11.2. Estimation Result

EUT: 150Mbps Wireless N ADSL2+ Modem Router			
M/N: TD-W8151N			
Test date:2012-09-13	Pressure: 101.3±1 kpa	Humidity: 53.6±1 %	
Tested by: Leo-Li	Test site: RF Site	Temperature24.8±1°C	

Cable loss: 1 dB		Attenuator loss: 20 dB				Antenna Gain: 5 dBi	
Test Mode	CH	Frequency (MHz)	Peak Output Power (dBm)	Output Power (mW)	Antenna Gain (dBi)	Antenna Gain (Linear)	MPE
11b	CH1	2412	17.64	58.08	5	3.16	0.0366
	CH6	2437	18.75	74.99	5	3.16	0.0472
	CH11	2462	17.7	58.88	5	3.16	0.0371
11g	CH1	2412	24.09	256.45	5	3.16	0.1614
	CH6	2437	23.61	229.61	5	3.16	0.1445
	CH11	2462	22.67	184.93	5	3.16	0.1164
11n HT20	CH1	2412	24.18	261.82	5	3.16	0.1648
	CH6	2437	23.41	219.28	5	3.16	0.1380
	CH11	2462	22.44	175.39	5	3.16	0.1104
11n HT40	CH1	2422	21.83	152.41	5	3.16	0.0959
	CH4	2437	23.36	216.77	5	3.16	0.1364
	CH7	2452	21.00	125.89	5	3.16	0.0792



## 12. DEVIATION TO TEST SPECIFICATIONS

[ NONE]