

FCC RF EXPOSURE REPORT

FCC ID: TE7WA850REV7

Project No. : 1911C110
Equipment : 300Mbps Wi-Fi Range Extender
Brand Name : tp-link
Test Model : TL-WA850RE
Series Model : N/A
Applicant : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Manufacturer : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Date of Receipt : Nov. 25, 2019
Date of Test : Nov. 25, 2019 ~ Dec. 20, 2019
Issued Date : Feb. 25, 2020
Report Version : R00
Test Sample : Engineering Sample No.: DG2019112218
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.



Prepared by : Welly Zhou



Approved by : Ethan Ma



Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

Tel: +86-769-8318-3000

Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue	Feb. 25, 2020

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:



S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)	Note
1		N/A	Printed	N/A	2	N/A
2		N/A	Printed	N/A	1.98	N/A

Note: This EUT supports CDD, and antenna gains are not equal, so Directional gain= $10\log [(10^{G1/20}+10^{G2/20}+\dots+10^{GN/20})^2/N]$ dBi=5.

2. TEST RESULTS

For 2.4GHz:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5	3.1623	28.76	751.6229	0.47310	1	Complies

Note: The calculated distance is 20 cm.
Output power including tune up tolerance.

End of Test Report