



中国认可
国际互认
检测
TESTING
CNAS L5313



DEKRA

RF Exposure Evaluation Declaration

Product Name : 300Mbps Wi-Fi Range Extender with Power Outlet
Pass-through

Model No. : TL-WA860RE

FCC ID : TE7WA860REV4

Applicant : TP-Link Technologies Co., Ltd..

Address : Building 24 (floors 1,3,4,5) and 28 (floors1-4)
Central Science and Technology Park,Shennan Rd,
Nanshan, Shenzhen,China

Date of Receipt : Jan. 06th, 2017

Test Date : Jan. 06th, 2017~ Apr. 12th, 2017

Issued Date : Apr. 25th, 2017

Report No. : 1712029R-RF-US-P20V01

Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.

Test Report Certification

Issued Date : Apr. 25th, 2017

Report No. : 1712029R-RF-US-P20V01



Product Name : 300Mbps Wi-Fi Range Extender with Power Outlet Pass-through

Applicant : TP-Link Technologies Co., Ltd.
Address : Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park,Shennan Rd, Nanshan, Shenzhen,China

Manufacturer : TP-Link Technologies Co., Ltd..
Address : Building 24 (floors 1,3,4,5) and 28 (floors1-4) Central Science and Technology Park,Shennan Rd, Nanshan, Shenzhen,China

Model No. : TL-WA860RE
FCC ID : TE7WA860REV4
EUT Voltage : AC 120V/60Hz
Test Voltage : AC 120V/60Hz
Brand Name : TP-Link
Applicable Standard : KDB 447498D01V06

Test Result : FCC Part1.1310
Complied

Performed Location : DEKRA Testing and Certification (Suzhou) Co., Ltd.
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392

Documented By : Kathy Feng
(Adm. Specialist: Kathy Feng)

Reviewed By : Frank He
(Senior Engineer: Frank He)

Approved By : Harry Zhao
(Engineering Manager: Harry Zhao)

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	300Mbps Wi-Fi Range Extender with Power Outlet Pass-through
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

● Antenna Information

Model No.	N/A					
Antenna manufacturer	N/A					
Antenna Delivery	<input type="checkbox"/>	1*TX+1*RX	<input checked="" type="checkbox"/>	2*TX+2*RX	<input type="checkbox"/>	3*TX+3*RX
Antenna technology	<input type="checkbox"/>	SISO				
	<input checked="" type="checkbox"/>	MIMO	<input type="checkbox"/>	Basic		
			<input checked="" type="checkbox"/>	CDD		
			<input type="checkbox"/>	Sectorized		
<input type="checkbox"/>	Beam-forming					
Antenna Type	<input checked="" type="checkbox"/>	External	<input checked="" type="checkbox"/>	Dipole		
			<input type="checkbox"/>	Sectorized		
	<input type="checkbox"/>	Internal	<input type="checkbox"/>	PIFA		
			<input type="checkbox"/>	PCB		
			<input type="checkbox"/>	Ceramic Chip Antenna		
<input type="checkbox"/>	Metal plate type F antenna					
Antenna Technology	Ant Gain (dBi)			Directional Gain (dBi)		
				For Power	For PSD	
<input checked="" type="checkbox"/>	CDD	Ant 0: 2	Ant 1: 2	2	5	

- Output Power into Antenna & RF Exposure Evaluation Distance:

Standalone modes

Test Mode	Frequency Band (MHz)	Maximum Output Power to Antenna (dBm)	Directional Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Power Density Limit at R = 20 cm (mW/cm ²)
802.11b/g/n(20MHz) with CDD	2412 ~ 2462 MHz	25.39	2	0.1091	1.0
802.11n(40MHz) with CDD	2422 ~ 2452 MHz	24.94	2	0.0983	1.0

Note: The simultaneous transmission power density is 0.1091mW/cm² for 300Mbps Wi-Fi Range Extender with Power Outlet Pass-through without any other radio equipment.

————— The End —————