

FCC

RF

TEST REPORT

ISSUED BY  
Shenzhen BALUN Technology Co., Ltd.



FOR  
**Y50 FDD-LTE Smartphone**

ISSUED TO  
TP-LINK Technologies Co., Ltd.

Building 24-1F/3F/4F/5F, 28-1F/2F/3F/4F Science and Technology Park,  
Shennan Road, Nanshan District, Shenzhen City, Guangdong Province,  
P.R. China



Tested by:

Cao Shaodong  
(Engineer)

Date Apr. 14, 2017

Approved by:

Wei Yanquan  
(Chief Engineer)

Date Apr. 14, 2017



Report No.: BL-SZ1720011-603

EUT Name: Y50 FDD-LTE Smartphone

Model Name: TP803C

Brand Name: neffos

Test Standard: 47 CFR Part 15 Subpart C

FCC ID: TE7Y50V1

Test conclusion: Pass

Test Date: Mar.06, 2017 ~ Mar. 17, 2017

Date of Issue: Apr. 14, 2017

*NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.*

### Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Apr. 06, 2017</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Apr. 14, 2017</u>	<u>Remove N40 on page 34</u>

## TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION) .....	5
1.1	Identification of the Testing Laboratory .....	5
1.2	Identification of the Responsible Testing Location .....	5
1.3	Laboratory Condition .....	5
1.4	Announce .....	5
2	PRODUCT INFORMATION .....	6
2.1	Applicant Information .....	6
2.2	Manufacturer Information .....	6
2.3	Factory Information .....	6
2.4	General Description for Equipment under Test (EUT) .....	6
2.5	Ancillary Equipment .....	7
2.6	Technical Information .....	8
2.7	Additional Instructions .....	10
3	SUMMARY OF TEST RESULTS .....	11
3.1	Test Standards .....	11
3.2	Verdict .....	11
4	GENERAL TEST CONFIGURATIONS .....	12
4.1	Test Environments .....	12
4.2	Test Equipment List .....	12
4.3	Measurement Uncertainty .....	14
4.4	Description of Test Setup .....	14
4.4.1	For Antenna Port Test .....	14
4.4.2	For AC Power Supply Port Test .....	15
4.4.3	For Radiated Test (Below 30 MHz) .....	15
4.4.4	For Radiated Test (30 MHz-1 GHz) .....	16

4.4.5	For Radiated Test (Above 1 GHz).....	16
4.5	Measurement Results Explanation Example.....	17
4.5.1	For conducted test items: .....	17
4.5.2	For radiated band edges and spurious emission test:.....	17
5	TEST ITEMS.....	18
5.1	Antenna Requirements.....	18
5.1.1	Standard Applicable .....	18
5.1.2	Antenna Anti-Replacement Construction .....	19
5.1.3	Antenna Gain .....	19
5.2	Output Power .....	20
5.2.1	Test Limit.....	20
5.2.2	Test Setup .....	20
5.2.3	Test Procedure.....	20
5.2.4	Test Result .....	21
5.3	6dB Bandwidth .....	22
5.3.1	Limit.....	22
5.3.2	Test Setup .....	22
5.3.3	Test Procedure.....	22
5.3.4	Test Result .....	22
5.4	Conducted Spurious Emission .....	23
5.4.1	Limit.....	23
5.4.2	Test Setup .....	23
5.4.3	Test Procedure.....	23
5.4.4	Test Result .....	24
5.5	Band Edge (Authorized-band band-edge).....	25
5.5.1	Limit.....	25
5.5.2	Test Setup .....	25
5.5.3	Test Procedure.....	25
5.5.4	Test Result .....	26
5.6	Conducted Emission .....	27
5.6.1	Limit.....	27
5.6.2	Test Setup .....	27

5.6.3	Test Procedure .....	27
5.6.4	Test Result .....	27
5.7	Radiated Spurious Emission .....	28
5.7.1	Limit.....	28
5.7.2	Test Setup .....	28
5.7.3	Test Procedure .....	28
5.7.4	Test Result .....	31
5.8	Band Edge (Restricted-band band-edge).....	32
5.8.1	Limit.....	32
5.8.2	Test Setup .....	32
5.8.3	Test Procedure .....	32
5.8.4	Test Result .....	32
5.9	Power Spectral density (PSD).....	33
5.9.1	Limit.....	33
5.9.2	Test Setup .....	33
5.9.3	Test Procedure .....	33
5.9.4	Test Result .....	33
ANNEX A	TEST RESULT .....	34
A.1	Output Power .....	34
A.2	Bandwidth.....	35
A.3	Conducted Spurious Emissions .....	40
A.4	Band Edge (Authorized-band band-edge).....	47
A.5	Conducted Emissions.....	50
A.6	Radiated Emission .....	52
A.7	Band Edge (Restricted-band band-edge).....	66
A.8	Power Spectral Density (PSD) .....	69
ANNEX B	TEST SETUP PHOTOS .....	72
ANNEX C	EUT EXTERNAL PHOTOS .....	72
ANNEX D	EUT INTERNAL PHOTOS .....	72

# 1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

## 1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

## 1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	<p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory has been listed by US Federal Communications Commission to perform electromagnetic emission measurements. The recognition numbers of test site are 832625.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p>
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

## 1.3 Laboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

## 1.4 Announce

- (1) The test report reference to the report template version v5.8.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

Applicant	TP-LINK Technologies Co., Ltd.
Address	Building 24-1F/3F/4F/5F, 28-1F/2F/3F/4F Science and Technology Park, Shennan Road, Nanshan District, Shenzhen City, Guangdong Province, P.R. China

### 2.2 Manufacturer Information

Manufacturer	TP-LINK Technologies Co., Ltd.
Address	Building 24-1F/3F/4F/5F, 28-1F/2F/3F/4F Science and Technology Park, Shennan Road, Nanshan District, Shenzhen City, Guangdong Province, P.R. China

### 2.3 Factory Information

Factory	N/A
Address	N/A

### 2.4 General Description for Equipment under Test (EUT)

EUT Type	Y50 FDD-LTE Smartphone
Model Name Under Test	TP803C
Series Model Name	TP803C, TP803CXXYY
Description of Model name differentiation	The Circuit, PCB Layout, Electrical Parts and Outlook of TP803CXXYY are identical to TP803C.( XX= 11 or 21 or 31 ( 11 indicates Pearl White, 21 indicates Dark Gray, 31 indicates Sunny Yellow); YY indicates different national.)
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
Network and Wireless connectivity	2G Network GSM/GPRS/EDGE 850/1900 MHz 3G Network WCDMA/HSDPA/HSUPA/HSPA+ Band 2/4/5 4G Network FDD LTE Band 2/4/7 Bluetooth 3.0+EDR, Bluetooth 4.0 Low Energy (BLE), WIFI 802.11b, 802.11g and 802.11n (HT20), FM, GPS, GLONASS

## 2.5 Ancillary Equipment

Ancillary Equipment 1	Battery 1	
	Brand Name	neffos
	Model No.	NBL-46A2020
	Serial No.	N/A
	Capacitance	2020 mAh
	Rated Voltage	3.8 V
	Limit Charge Voltage	4.35 V
Ancillary Equipment 2	Charger	
	Brand Name	neffos
	Model Name	N050100-2B3
	Rated Input	100-240 V ~, 50/60 Hz, 300 mA
	Rated Output	5 V =, 1 A
Ancillary Equipment 3	USB Cable	
	Length(Approx.)	100 cm

## 2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:

Frequency Range	802.11b/g/n(20 MHz): 2.412 GHz - 2.462 GHz $f_c = 2412 \text{ MHz} + (N-1)*5 \text{ MHz}$ , where - $f_c$ = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 1 to 11.
Modulation Type	DSSS, OFDM
Product Type	Mobile and portable
Antenna System (eg., MIMO, Smart Antenna)	N/A
Categorization as Correlated or Completely Uncorrelated	N/A
Antenna Type	PIFA Antenna
Antenna Gain	-1 dBi
About the Product	Only the WIFI 802.11b, 802.11g and 802.11n (HT20) was tested in this report.

Modulation technology	Modulation Type	Transfer Rate (Mbps)
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/ 11
OFDM (802.11g)	BPSK	6 / 9
	QPSK	12 / 18
	16QAM	24 / 36
	64QAM	48 / 54
OFDM (802.11n-20 MHz)	BPSK	6.5
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.



Test Items	Mode	Data Rate	Channel
Output Power	11b/11g/11n20	1/6/6.5 Mbps	1/6/11
6dB Bandwidth	11b/11g/11n20	1/6/6.5 Mbps	1/6/11
Conducted Spurious Emission	11b/11g/11n20	1/6/6.5 Mbps	1/6/11
Conducted Emission	11b/11g/11n20	1/6/6.5 Mbps	1/6/11
Radiated Spurious Emission	11b/11g/11n20	1/6/6.5 Mbps	1/6/11
Band Edge	11b/11g/11n20	1/6/6.5 Mbps	1/6/11
Power spectral density (PSD)	11b/11g/11n20	1/6/6.5 Mbps	1/6/11

Note: The above EUT information in section 2.4 and 2.6 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

## 2.7 Additional Instructions

EUT Software Settings:


Mode	<input checked="" type="checkbox"/> Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.
------	--

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

EUT Software Settings:

Power level setup in software			
Test Software Version	QRCT 3.0.105.0		
Support Units (Software installation media)	Description	Manufacturer	Model
	Laptop	Lenovo	X220
Mode	Channel	Soft Set	
802.11 b	All	13.5	
802.11 g	All	10	
802.11 n20	All	9	

Run software:



### 3 SUMMARY OF TEST RESULTS

#### 3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-15 Edition)	Miscellaneous Wireless Communications Services
2	KDB Publication 558074 D01v03r05	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
3	ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

#### 3.2 Verdict

No.	Description	FCC PART No.	Test Result	Verdict
1	Antenna Requirement	15.203; 15.247(b)	N/A	Pass <sup>Note 1</sup>
2	Output Power	15.247(b)	ANNEX A.1	Pass
3	6dB Bandwidth	15.247(a)	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.209; 15.247(d)	ANNEX A.4	Pass
6	Conducted Emission	15.207	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209; 15.247(d)	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209; 15.247(d)	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	ANNEX A.8	Pass
10	Receiver Spurious Emissions	N/A	N/A	N/A <sup>Note 2</sup>

Note<sup>1</sup>: Please refer to section 5.1.

Note<sup>2</sup>: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

## 4 GENERAL TEST CONFIGURATIONS

### 4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	3.8 V

### 4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2016.07.13	2017.07.12
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2016.07.13	2017.07.12
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2016.09.09	2017.09.08
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2016.07.05	2017.07.04
LISN	SCHWARZBECK	NSLK 8127	8127-687	2016.07.05	2017.07.04
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2016.07.13	2017.07.12
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2016.07.13	2017.07.12
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2016.07.13	2017.07.12
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2016.07.13	2017.07.12
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2015.07.22	2017.07.21
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2015.07.22	2017.07.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2015.07.22	2017.07.21
Test Antenna-Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2015.07.22	2017.07.21
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2019.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2016.08.09	2018.08.08
Shielded Enclosure	ChangNing	CN-130701	130703	--	--
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2016.07.13	2017.07.12
Power Amplifier	OPHIR RF	5225F	1037	2017.02.17	2018.02.16
Power Amplifier	OPHIR RF	5273F	1016	2017.02.17	2018.02.16
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Feld Strength Meter	Narda	EP601	511WX51129	2017.02.23	2018.02.22

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Mouth Simulator	B&K	4227	2423931	2016.11.15	2017.11.14
Sound Calibrator	B&K	4231	2430337	2016.11.09	2017.11.08
Sound Level Meter	B&K	NL-20	00844023	2016.11.11	2017.11.10
Ear Simulator	B&K	4185	2409449	2016.11.15	2017.11.14
Ear Simulator	B&K	4195	2418189	2016.11.15	2017.11.14
Audio analyzer	B&K	UPL 16	100129	2016.11.08	2017.11.07

### 4.3 Measurement Uncertainty


The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1.4 dB
Power Spectral Density, conducted	±2.5 dB
Unwanted Emissions, conducted	±2.8 dB
All emissions, radiated	±5.4 dB
Temperature	±1°C
Humidity	±4%


### 4.4 Description of Test Setup

#### 4.4.1 For Antenna Port Test




(Diagram 1)

## 4.4.2 For AC Power Supply Port Test




(Diagram 2)

## 4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)



## 4.5 Measurement Results Explanation Example

### 4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

### 4.5.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB $\mu$ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP= Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

## 5 TEST ITEMS

### 5.1 Antenna Requirements

#### 5.1.1 Standard Applicable

FCC §15.203 & 15.247(b); RSS-247, 5.4 (6)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### 5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is An embedded-in	An embedded-in antenna design is used.

Reference Documents	Item
Photo	<div style="border: 1px solid red; padding: 2px; display: inline-block; color: red;">Antenna Point (Diversity)</div>

### 5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

## 5.2 Output Power

### 5.2.1 Test Limit

FCC § 15.247(b); RSS-247, 5.4 (4)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

### 5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.2.3 Test Procedure

#### Maximum peak conducted output power

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

#### Maximum conducted (average) output power (Reporting Only)

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
  - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
  - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.
- c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- d) Adjust the measurement in dBm by adding  $10\log(1/x)$ , where x is the duty cycle to the measurement result.

#### Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value.

Set  $VBW \geq RBW$ . Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7$  microseconds.)

#### 5.2.4 Test Result

Please refer to ANNEX A.1.

## 5.3 6dB Bandwidth

### 5.3.1 Limit

FCC §15.247(a); RSS-GEN, 6.6

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

### 5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW)  $\geq$  3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 5.3.4 Test Result

Please refer to ANNEX A.2.

## 5.4 Conducted Spurious Emission

### 5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

#### Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to  $\geq 1.5$  times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW  $\geq 3 \times$  RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

### Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW  $\geq 3 \times$  RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

#### 5.4.4 Test Result

Please refer to ANNEX A.3.



## 5.5 Band Edge (Authorized-band band-edge)

### 5.5.1 Limit

FCC §15.247(d); RSS-GEN, 8.9, RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle  $\geq 98\%$ ). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than  $\pm 2$  percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW  $\geq 3 \times$  RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission)  $\pm 0.5$  MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission  $\pm 0.5$  MHz.

Standard method(The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (OBW/RBW)]$  below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

#### 5.5.4 Test Result

Please refer to ANNEX A.4.

## 5.6 Conducted Emission

### 5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

### 5.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

### 5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

### 5.6.4 Test Result

Please refer to ANNEX A.5.

## 5.7 Radiated Spurious Emission

### 5.7.1 Limit

FCC §15.209&15.247(c); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ )	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

### 5.7.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

#### General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).

- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dBμV/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW ≥ 3 x RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz

> 1000 MHz	1 MHz
------------	-------

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

#### Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle  $\geq 98$  percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than  $\pm 2$  percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle,  $x$ , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW  $\geq 3 \times$  RBW.
- e) Detector = RMS, if  $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$ . Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
  - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
  - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
  - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is  $10 \log(1/x)$ , where  $x$  is the duty cycle.
  - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is  $20 \log(1/x)$ , where  $x$  is the duty cycle.
  - 3) If a specific emission is demonstrated to be continuous ( $\geq 98$  percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

#### Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

#### Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

#### 5.7.4 Test Result

Please refer to ANNEX A.6.

## 5.8 Band Edge (Restricted-band band-edge)

### 5.8.1 Limit

FCC §15.209&15.247(c); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

### 5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

### 5.8.4 Test Result

Please refer to ANNEX A.7.



## 5.9 Power Spectral density (PSD)

### 5.9.1 Limit

FCC §15.247(d); RSS-247, 5.2 (2)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

### 5.9.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .

Set the VBW  $\geq 3 \text{ RBW}$ .

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 5.9.4 Test Result

Please refer to ANNEX A.8.

## ANNEX A TEST RESULT

### A.1 Output Power

#### Duty Cycle

Test Mode	Duty Cycle	T (ms)	1/T(kHz)
802.11b	0.97	8.217	0.1
802.11g	0.87	1.361	0.7
802.11n-20 MHz	0.86	1.276	0.8

#### Peak Power Test Data

##### 802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	15.46	35.16	30	1000	Pass
Middle	15.11	32.43			Pass
High	15.43	34.91			Pass

##### 802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	17.55	56.89	30	1000	Pass
Middle	17.25	53.09			Pass
High	17.26	53.21			Pass

##### 802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	16.59	45.60	30	1000	Pass
Middle	16.26	42.27			Pass
High	16.35	43.15			Pass

## A.2 Bandwidth

### Test Data

#### 802.11b Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	8.1604	13.1404	$\geq 500$
Middle	8.1602	13.1404	$\geq 500$
High	8.1604	13.1983	$\geq 500$

#### 802.11g Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	15.8198	17.8871	$\geq 500$
Middle	16.5708	18.1187	$\geq 500$
High	15.5195	18.0608	$\geq 500$


#### 802.11n-20 MHz Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	16.5205	18.6975	$\geq 500$
Middle	17.2715	18.6397	$\geq 500$
High	17.8223	18.8133	$\geq 500$

Test plots

6 dB Bandwidth

802.11b LOW CHANNEL




Date: 14 MAR 2017 16:25:31

802.11b MIDDLE CHANNEL




Date: 14 MAR 2017 16:28:09

802.11b HIGH CHANNEL




Date: 14 MAR 2017 16:30:48

802.11g LOW CHANNEL




Date: 14 MAR 2017 16:36:53

802.11g MIDDLE CHANNEL




Date: 14 MAR 2017 16:39:18

802.11g HIGH CHANNEL




Date: 14 MAR 2017 16:41:39

802.11n-20 MHz LOW CHANNEL




Date: 14.MAR.2017 16:44:15

802.11 n-20 MHz MIDDLE CHANNEL



Date: 14.MAR.2017 16:46:34


802.11n-20 MHz HIGH CHANNEL



Date: 14.MAR.2017 16:48:37


99% Bandwidth

802.11b LOW CHANNEL




Date: 14 MAR 2017 16:25:40

802.11b MIDDLE CHANNEL



Date: 14 MAR 2017 16:28:18

802.11b HIGH CHANNEL



Date: 14 MAR 2017 16:30:56

802.11g LOW CHANNEL



Date: 14 MAR 2017 16:37:02

802.11g MIDDLE CHANNEL




Date: 14 MAR 2017 16:39:26

802.11g HIGH CHANNEL




Date: 14 MAR 2017 16:41:47

802.11n-20 MHz LOW CHANNEL




Date: 14.MAR.2017 16:44:23

802.11 n-20 MHz MIDDLE CHANNEL



Date: 14.MAR.2017 16:46:42

802.11n-20 MHz HIGH CHANNEL



Date: 14.MAR.2017 16:48:46

### A.3 Conducted Spurious Emissions

#### Test Data

##### 802.11b Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-41.53	4.02	-15.98	Pass
Middle	-37.16	3.32	-16.68	Pass
High	-41.11	2.97	-17.03	Pass

##### 802.11g Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-41.07	-2.58	-22.58	Pass
Middle	-41.70	-2.36	-22.36	Pass
High	-41.39	-1.63	-21.63	Pass


##### 802.11n-20 MHz Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-41.86	-2.64	-22.64	Pass
Middle	-39.92	-3.39	-23.39	Pass
High	-41.40	-2.54	-22.54	Pass




Test Plots

802.11b LOW CHANNEL CARRIER LEVEL




Date: 14 MAR 2017 16:25:52

802.11b LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




Date: 14 MAR 2017 16:26:20

802.11b LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




Date: 14 MAR 2017 16:26:30

802.11b MIDDLE CHANNEL CARRIER LEVEL




Date: 14 MAR 2017 16:28:34

802.11b MIDDLE CHANNEL, SPURIOUS  
30 MHz ~ 3 GHz




Date: 14.MAR.2017 16:29:03

802.11b MIDDLE CHANNEL, SPURIOUS  
2 GHz ~ 25 GHz




Date: 14.MAR.2017 16:29:16

802.11b HIGH CHANNEL CARRIER LEVEL




Date: 14.MAR.2017 16:31:05

802.11b HIGH CHANNEL, SPURIOUS  
30 MHz ~ 3 GHz




Date: 14.MAR.2017 16:31:38

802.11b HIGH CHANNEL, SPURIOUS  
2 GHz ~ 25 GHz




Date: 14.MAR.2017 16:31:59

### 802.11g LOW CHANNEL CARRIER LEVEL




Date: 14.MAR.2017 16:37:13

### 802.11g LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




Date: 14.MAR.2017 16:37:32

### 802.11g LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




Date: 14.MAR.2017 16:37:43

### 802.11g MIDDLE CHANNEL CARRIER LEVEL




Date: 14.MAR.2017 16:39:39

802.11g MIDDLE CHANNEL, SPURIOUS  
30 MHz ~ 3 GHz




Date: 14.MAR.2017 16:40:02

802.11g MIDDLE CHANNEL, SPURIOUS  
2 GHz ~ 25 GHz




Date: 14.MAR.2017 16:40:10

802.11g HIGH CHANNEL CARRIER LEVEL




Date: 14.MAR.2017 16:41:59

802.11g HIGH CHANNEL, SPURIOUS  
30 MHz ~ 3 GHz




Date: 14.MAR.2017 16:42:19

802.11g HIGH CHANNEL, SPURIOUS  
2 GHz ~ 25 GHz




Date: 14.MAR.2017 16:42:27

802.11n-20 MHz LOW CHANNEL CARRIER LEVEL




Date: 14.MAR.2017 16:44:35

802.11n-20 MHz LOW CHANNEL, SPURIOUS  
30 MHz ~ 3 GHz




Date: 14.MAR.2017 16:45:05

802.11n-20 MHz LOW CHANNEL, SPURIOUS  
2 GHz ~ 25 GHz




Date: 14.MAR.2017 16:45:15

802.11n-20 MHz MIDDLE CHANNEL CARRIER  
LEVEL




Date: 14.MAR.2017 16:46:54

802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS  
30 MHz ~ 3 GHz




Date: 14.MAR.2017 16:47:18

802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS  
2 GHz ~ 25 GHz




Date: 14.MAR.2017 16:47:26

802.11n-20 MHz HIGH CHANNEL CARRIER LEVEL




Date: 14.MAR.2017 16:48:56

802.11n-20 MHz HIGH CHANNEL, SPURIOUS  
30 MHz ~ 3 GHz



Date: 14.MAR.2017 16:49:14

802.11n-20 MHz HIGH CHANNEL, SPURIOUS  
2 GHz ~ 25 GHz



Date: 14.MAR.2017 16:49:24

## A.4 Band Edge (Authorized-band band-edge)

### Test Data

Note: The 99% OBW of the fundamental emission is without 2 MHz of the authorized band.

#### 802.11b Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-43.52	4.02	-15.98	Pass
High Channel	-53.27	2.97	-17.03	Pass

#### 802.11g Mode:


Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-36.28	-2.58	-22.58	Pass
High Channel	-52.65	-1.63	-21.63	Pass

#### 802.11n-20 MHz Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-38.05	-2.64	-22.64	Pass
High Channel	-52.29	-2.54	-22.54	Pass


Test Plots

802.11b LOW CHANNEL, Carrier level




Date: 14.MAR.2017 16:25:52

802.11b LOW CHANNEL, Band Edge




Date: 14.MAR.2017 16:26:53

802.11b HIGH CHANNEL, Carrier level




Date: 14.MAR.2017 16:31:05

802.11b HIGH CHANNEL, Band Edge




Date: 14.MAR.2017 16:32:30

802.11g LOW CHANNEL, Carrier level



Date: 14.MAR.2017 16:37:13


802.11g LOW CHANNEL, Band Edge



Date: 14.MAR.2017 16:38:12




802.11g HIGH CHANNEL, Carrier level




Date: 14.MAR.2017 16:41:59

802.11g HIGH CHANNEL, Band Edge




Date: 14.MAR.2017 16:42:51

802.11n-20 MHz LOW CHANNEL, Carrier level




Date: 14.MAR.2017 16:44:35

802.11n-20 MHz LOW CHANNEL, Band Edge




Date: 14.MAR.2017 16:45:39

802.11n-20 MHz HIGH CHANNEL, Carrier level



Date: 14.MAR.2017 16:48:56

802.11n-20 MHz HIGH CHANNEL, Band Edge




Date: 14.MAR.2017 16:50:17

## A.5 Conducted Emissions

Note<sup>1</sup>: The EUT is working in the Normal link mode.


Note<sup>2</sup>: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz ) shown here.

### Test Data and Plots



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.152	56.65	11.00	65.9	9.25	Peak	L Line	Pass
1*	0.152	54.80	11.00	65.9	11.10	QP	L Line	Pass
1**	0.152	42.09	11.00	55.9	13.81	AV	L Line	Pass
2	0.220	58.1	11.00	62.8	4.70	Peak	L Line	Pass
2**	0.220	46.6	11.00	52.8	6.20	AV	L Line	Pass
3	0.438	50.3	11.00	57.1	6.80	Peak	L Line	Pass
3**	0.438	33.9	11.00	47.1	13.20	AV	L Line	Pass
4	0.866	54.41	11.00	56.0	1.59	Peak	L Line	Pass
4*	0.866	48.07	11.00	56.0	7.93	QP	L Line	Pass
4**	0.866	36.75	11.00	46.0	9.25	AV	L Line	Pass
5	2.410	44.9	11.00	56.0	11.10	Peak	L Line	Pass
5**	2.410	30.3	11.00	46.0	15.70	AV	L Line	Pass
6	20.670	44.2	11.00	60.0	15.80	Peak	L Line	Pass
6**	20.670	31.2	11.00	50.0	18.80	AV	L Line	Pass

## PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.218	50.4	11.00	62.9	12.50	Peak	N Line	Pass
1**	0.218	38.7	11.00	52.9	14.20	AV	N Line	Pass
2	0.290	49.6	11.00	60.5	10.90	Peak	N Line	Pass
2**	0.290	34.4	11.00	50.5	16.10	AV	N Line	Pass
3	0.864	51.2	11.00	56.0	4.80	Peak	N Line	Pass
3**	0.864	37.2	11.00	46.0	8.80	AV	N Line	Pass
4	1.346	44.7	11.00	56.0	11.30	Peak	N Line	Pass
4**	1.346	32.3	11.00	46.0	13.70	AV	N Line	Pass
5	2.490	44.2	11.00	56.0	11.80	Peak	N Line	Pass
5**	2.490	31.3	11.00	46.0	14.70	AV	N Line	Pass
6	3.488	44.4	11.00	56.0	11.60	Peak	N Line	Pass
6**	3.488	28.6	11.00	46.0	17.40	AV	N Line	Pass

## A.6 Radiated Emission

Note<sup>1</sup>: The symbol of “--” in the table which means not application.


Note<sup>2</sup>: For the test data above 1 GHz, According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note<sup>3</sup>: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note<sup>4</sup>: The EUT is working in the Normal link mode below 1 GHz.


### Test Data and Plots

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	47.941	10.11	-14.10	30.0	19.89	Peak	360.00	300	Horizontal	Pass
2	105.399	9.08	-15.67	33.5	24.42	Peak	15.00	100	Horizontal	Pass
3	203.587	9.46	-16.13	33.5	24.04	Peak	360.00	200	Horizontal	Pass
4	319.715	12.41	-12.67	36.0	23.59	Peak	340.00	100	Horizontal	Pass
5	416.691	15.02	-10.35	36.0	20.98	Peak	360.00	300	Horizontal	Pass
6	669.070	20.39	-6.10	36.0	15.61	Peak	254.00	100	Horizontal	Pass

## 30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	42.122	9.05	-14.26	30.0	20.95	Peak	141.00	100	Vertical	Pass
2	52.789	8.86	-13.97	30.0	21.14	Peak	360.00	200	Vertical	Pass
3	106.611	9.07	-15.85	33.5	24.43	Peak	24.00	200	Vertical	Pass
4	202.859	9.09	-16.03	33.5	24.41	Peak	85.00	300	Vertical	Pass
5	415.964	14.47	-10.30	36.0	21.53	Peak	280.00	300	Vertical	Pass
6	746.166	20.43	-4.55	36.0	15.57	Peak	297.00	200	Vertical	Pass

## 802.11b LOW CHANNEL 1 GHz to 7 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1345.000	39.23	-2.53	74.0	34.77	Peak	336.30	150	Vertical	Pass
2	1810.500	44.05	-2.48	74.0	29.95	Peak	71.00	150	Vertical	Pass
3	2413.000	82.35	1.68	74.0	-8.35	Peak	33.60	150	Vertical	N/A
4	2950.500	43.97	3.58	74.0	30.03	Peak	317.60	150	Vertical	Pass
5	4027.000	43.31	8.88	74.0	30.69	Peak	360.10	150	Vertical	Pass
6	5318.000	46.08	11.36	74.0	27.92	Peak	261.50	150	Vertical	Pass

## 802.11b LOW CHANNEL 1 GHz to 7 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1297.500	38.74	-2.30	74.0	35.26	Peak	110.70	150	Horizontal	Pass
2	1561.000	38.70	-2.75	74.0	35.30	Peak	0.00	150	Horizontal	Pass
3	2179.500	42.01	0.78	74.0	31.99	Peak	60.60	150	Horizontal	Pass
4	2411.500	90.36	1.16	74.0	-16.36	Peak	31.40	150	Horizontal	N/A
5	3877.000	42.46	8.13	74.0	31.54	Peak	141.60	150	Horizontal	Pass
6	5694.000	47.22	12.11	74.0	26.78	Peak	19.90	150	Horizontal	Pass

## 802.11b MIDDLE CHANNEL 1 GHz to 7 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1234.500	39.20	-1.88	74.0	34.80	Peak	27.60	150	Vertical	Pass
2	1861.500	45.38	-1.81	74.0	28.62	Peak	78.00	150	Vertical	Pass
3	2099.000	43.44	0.03	74.0	30.56	Peak	101.10	150	Vertical	Pass
4	2436.500	85.04	0.79	74.0	-11.04	Peak	5.70	150	Vertical	N/A
5	3561.000	42.30	7.21	74.0	31.70	Peak	332.20	150	Vertical	Pass
6	4874.000	45.66	10.71	74.0	28.34	Peak	42.40	150	Vertical	Pass

## 802.11b MIDDLE CHANNEL 1 GHz to 7 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1234.500	37.70	-1.88	74.0	36.30	Peak	298.90	150	Horizontal	Pass
2	1615.500	39.13	-2.60	74.0	34.87	Peak	249.40	150	Horizontal	Pass
3	2437.500	91.45	1.24	74.0	-17.45	Peak	90.10	150	Horizontal	N/A
4	2952.500	44.13	3.94	74.0	29.87	Peak	303.50	150	Horizontal	Pass
5	4076.000	42.99	8.39	74.0	31.01	Peak	0.70	150	Horizontal	Pass
6	5473.000	46.75	11.54	74.0	27.25	Peak	50.50	150	Horizontal	Pass

## 802.11b HIGH CHANNEL 1 GHz to 7 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1292.000	40.16	-1.62	74.0	33.84	Peak	353.40	150	Horizontal	Pass
2	1798.500	43.19	-1.73	74.0	30.81	Peak	79.50	150	Horizontal	Pass
3	2172.500	42.64	1.03	74.0	31.36	Peak	101.80	150	Horizontal	Pass
4	2461.500	84.26	0.71	74.0	-10.26	Peak	39.40	150	Horizontal	N/A
5	3583.000	42.93	7.35	74.0	31.07	Peak	109.20	150	Horizontal	Pass
6	5353.000	47.18	11.68	74.0	26.82	Peak	230.10	150	Horizontal	Pass

## 802.11b HIGH CHANNEL 1 GHz to 7 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1247.000	39.91	-3.02	74.0	34.09	Peak	16.20	150	Horizontal	Pass
2	1477.500	40.56	-1.96	74.0	33.44	Peak	0.20	150	Horizontal	Pass
3	1914.000	41.27	-0.61	74.0	32.73	Peak	25.40	150	Horizontal	Pass
4	2461.500	93.62	0.71	74.0	-19.62	Peak	151.10	150	Horizontal	N/A
5	3618.000	43.32	7.79	74.0	30.68	Peak	0.70	150	Horizontal	Pass
6	4703.000	45.19	10.35	74.0	28.81	Peak	178.60	150	Horizontal	Pass

## 802.11b LOW CHANNEL 7 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	7462.000	46.07	14.87	74.0	27.93	Peak	78.70	150	Vertical	Pass
2	9081.750	48.10	17.59	74.0	25.90	Peak	284.80	150	Vertical	Pass
3	10506.250	48.53	17.21	74.0	25.47	Peak	0.00	150	Vertical	Pass
4	11642.000	49.16	17.96	74.0	24.84	Peak	0.40	150	Vertical	Pass
5	12648.500	49.64	19.27	74.0	24.36	Peak	315.50	150	Vertical	Pass
6	13602.750	50.46	20.44	74.0	23.54	Peak	284.80	150	Vertical	Pass

## 802.11b LOW CHANNEL 7 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	7431.750	45.29	14.28	74.0	28.71	Peak	335.10	150	Horizontal	Pass
2	8658.250	46.31	15.86	74.0	27.69	Peak	218.80	150	Horizontal	Pass
3	10594.250	48.34	18.53	74.0	25.66	Peak	205.60	150	Horizontal	Pass
4	12139.750	49.09	18.48	74.0	24.91	Peak	0.00	150	Horizontal	Pass
5	13250.750	49.89	20.53	74.0	24.11	Peak	42.00	150	Horizontal	Pass
6	14356.250	52.47	23.19	74.0	21.53	Peak	69.10	150	Horizontal	Pass

## 802.11b MIDDLE CHANNEL 7 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	7753.500	45.11	14.68	74.0	28.89	Peak	61.80	150	Vertical	Pass
2	8619.750	46.83	16.39	74.0	27.17	Peak	229.30	150	Vertical	Pass
3	9744.500	45.54	16.19	74.0	28.46	Peak	75.30	150	Vertical	Pass
4	10580.500	48.23	18.90	74.0	25.77	Peak	0.70	150	Vertical	Pass
5	12103.999	48.85	18.47	74.0	25.15	Peak	70.70	150	Vertical	Pass
6	13759.500	50.57	20.46	74.0	23.43	Peak	291.40	150	Vertical	Pass



## 802.11b MIDDLE CHANNEL 7 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	7448.250	45.20	14.60	74.0	28.80	Peak	342.80	150	Horizontal	Pass
2	8138.500	44.61	13.98	74.0	29.39	Peak	60.00	150	Horizontal	Pass
3	9136.750	47.16	17.78	74.0	26.84	Peak	358.80	150	Horizontal	Pass
4	10564.000	47.97	18.50	74.0	26.03	Peak	2.60	150	Horizontal	Pass
5	12150.750	49.23	18.49	74.0	24.77	Peak	4.20	150	Horizontal	Pass
6	14018.000	52.28	21.36	74.0	21.72	Peak	320.00	150	Horizontal	Pass

## 802.11b HIGH CHANNEL 7 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	7712.250	44.72	14.46	74.0	29.28	Peak	360.00	150	Horizontal	Pass
2	8545.500	46.45	16.20	74.0	27.55	Peak	33.40	150	Horizontal	Pass
3	9794.000	45.99	16.25	74.0	28.01	Peak	13.80	150	Horizontal	Pass
4	10792.250	48.23	18.98	74.0	25.77	Peak	149.40	150	Horizontal	Pass
5	12115.000	49.55	18.45	74.0	24.45	Peak	59.70	150	Horizontal	Pass
6	14015.250	51.38	21.31	74.0	22.62	Peak	23.00	150	Horizontal	Pass

## 802.11b HIGH CHANNEL 7 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	7473.000	45.60	14.77	74.0	28.40	Peak	142.70	150	Horizontal	Pass
2	8531.750	46.22	15.91	74.0	27.78	Peak	19.10	150	Horizontal	Pass
3	9659.250	45.50	15.80	74.0	28.50	Peak	14.80	150	Horizontal	Pass
4	10795.000	48.72	18.92	74.0	25.28	Peak	242.20	150	Horizontal	Pass
5	12148.000	49.63	18.49	74.0	24.37	Peak	68.40	150	Horizontal	Pass
6	13699.000	51.37	20.42	74.0	22.63	Peak	156.20	150	Horizontal	Pass

## 802.11g LOW CHANNEL 1 GHz to 7 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1594.500	43.29	-3.37	74.0	30.71	Peak	234.50	150	Vertical	Pass
2	1991.500	46.44	-0.33	74.0	27.56	Peak	15.00	150	Vertical	Pass
3	2404.500	88.64	0.85	74.0	-14.64	Peak	58.70	150	Vertical	N/A
4	2534.000	50.24	3.76	74.0	23.76	Peak	51.70	150	Vertical	Pass
5	4031.000	44.32	7.45	74.0	29.68	Peak	246.00	150	Vertical	Pass
6	6127.000	49.47	11.05	74.0	24.53	Peak	60.50	150	Vertical	Pass

## 802.11g LOW CHANNEL 1 GHz to 7 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1993.000	46.73	-0.29	74.0	27.27	Peak	101.00	150	Horizontal	Pass
2	2405.500	96.60	0.84	74.0	-22.60	Peak	359.50	150	Horizontal	N/A
3	2885.500	48.98	5.68	74.0	25.02	Peak	0.00	150	Horizontal	Pass
4	3737.000	44.34	6.81	74.0	29.66	Peak	302.20	150	Horizontal	Pass
5	4745.000	46.97	9.64	74.0	27.03	Peak	4.10	150	Horizontal	Pass
6	6124.000	48.94	10.94	74.0	25.06	Peak	253.30	150	Horizontal	Pass

## 802.11g MIDDLE CHANNEL 1 GHz to 7 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1464.000	43.53	-2.76	74.0	30.47	Peak	195.00	150	Vertical	Pass
2**	1995.000	34.79	-0.43	54.0	19.21	AV	349.10	150	Vertical	Pass
2	1995.000	56.46	-0.43	74.0	17.54	Peak	349.10	150	Vertical	Pass
3	2441.500	90.73	1.23	74.0	-16.73	Peak	252.50	150	Vertical	N/A
4	3508.000	43.65	6.28	74.0	30.35	Peak	230.20	150	Vertical	Pass
5	4667.000	47.65	9.04	74.0	26.35	Peak	143.40	150	Vertical	Pass
6	6111.000	49.11	10.65	74.0	24.89	Peak	230.20	150	Vertical	Pass

## 802.11g MIDDLE CHANNEL 1 GHz to 7 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1485.000	42.82	-2.91	74.0	31.18	Peak	72.00	150	Horizontal	Pass
2	2442.000	96.70	1.39	74.0	-22.70	Peak	304.90	150	Horizontal	N/A
3	2880.000	49.07	5.28	74.0	24.93	Peak	246.00	150	Horizontal	Pass
4	3930.000	44.11	7.14	74.0	29.89	Peak	163.30	150	Horizontal	Pass
5	5127.000	47.71	10.15	74.0	26.29	Peak	359.50	150	Horizontal	Pass
6	6236.000	49.91	10.80	74.0	24.09	Peak	0.50	150	Horizontal	Pass

## 802.11g HIGH CHANNEL 1 GHz to 7 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2025.500	48.75	-0.16	74.0	25.25	Peak	360.00	150	Vertical	Pass
2	2457.000	91.40	0.97	74.0	-17.40	Peak	257.40	150	Vertical	N/A
3	3200.000	44.50	5.71	74.0	29.50	Peak	0.00	150	Vertical	Pass
4	4425.000	44.46	8.55	74.0	29.54	Peak	337.00	150	Vertical	Pass
5	5183.000	47.57	9.93	74.0	26.43	Peak	67.00	150	Vertical	Pass
6	5944.000	50.00	10.65	74.0	24.00	Peak	67.00	150	Vertical	Pass

## 802.11g HIGH CHANNEL 1 GHz to 7 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1439.500	44.36	-3.28	74.0	29.64	Peak	244.80	150	Horizontal	Pass
2	2455.000	96.97	0.98	74.0	-22.97	Peak	357.40	150	Horizontal	N/A
3	3164.000	44.88	5.74	74.0	29.12	Peak	113.30	150	Horizontal	Pass
4	4430.000	45.62	8.57	74.0	28.38	Peak	151.50	150	Horizontal	Pass
5	5033.000	47.80	10.01	74.0	26.20	Peak	84.70	150	Horizontal	Pass
6	6852.000	49.09	11.53	74.0	24.91	Peak	132.60	150	Horizontal	Pass

## 802.11g LOW CHANNEL 7 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	9178.000	43.48	13.27	74.0	30.52	Peak	169.10	150	Vertical	Pass
2	10484.250	44.92	14.42	74.0	29.08	Peak	119.10	150	Vertical	Pass
3	11760.250	46.06	16.82	74.0	27.94	Peak	119.10	150	Vertical	Pass
4	12673.250	46.53	15.73	74.0	27.47	Peak	44.00	150	Vertical	Pass
5	14535.000	50.09	20.44	74.0	23.91	Peak	18.80	150	Vertical	Pass
6	15032.750	51.28	21.11	74.0	22.72	Peak	356.40	150	Vertical	Pass

## 802.11g LOW CHANNEL 7 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	7860.750	42.91	12.88	74.0	31.09	Peak	285.30	150	Horizontal	Pass
2	8985.500	43.42	13.36	74.0	30.58	Peak	336.40	150	Horizontal	Pass
3	10412.750	44.51	15.52	74.0	29.49	Peak	297.90	150	Horizontal	Pass
4	10913.250	45.53	14.72	74.0	28.47	Peak	0.00	150	Horizontal	Pass
5	12277.250	46.56	16.84	74.0	27.44	Peak	196.10	150	Horizontal	Pass
6	14084.000	49.15	19.45	74.0	24.85	Peak	156.50	150	Horizontal	Pass

## 802.11g MIDDLE CHANNEL 7 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	8020.250	42.81	12.64	74.0	31.19	Peak	123.00	150	Vertical	Pass
2	8861.750	43.17	12.72	74.0	30.83	Peak	286.70	150	Vertical	Pass
3	9662.000	44.45	14.85	74.0	29.55	Peak	261.90	150	Vertical	Pass
4	10159.750	44.65	15.12	74.0	29.35	Peak	9.10	150	Vertical	Pass
5	11958.250	46.39	16.50	74.0	27.61	Peak	337.10	150	Vertical	Pass
6	13737.500	47.89	17.19	74.0	26.11	Peak	198.90	150	Vertical	Pass

## 802.11g MIDDLE CHANNEL 7 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	8738.000	43.57	13.22	74.0	30.43	Peak	99.60	150	Horizontal	Pass
2	9626.250	43.68	15.33	74.0	30.32	Peak	163.00	150	Horizontal	Pass
3	10443.000	44.79	15.94	74.0	29.21	Peak	239.10	150	Horizontal	Pass
4	11719.000	46.02	17.23	74.0	27.98	Peak	163.00	150	Horizontal	Pass
5	13052.750	46.79	16.95	74.0	27.21	Peak	352.70	150	Horizontal	Pass
6	14507.500	50.53	20.21	74.0	23.47	Peak	86.70	150	Horizontal	Pass

## 802.11g HIGH CHANNEL 7 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	8754.500	43.43	13.19	74.0	30.57	Peak	0.00	150	Vertical	Pass
2	9876.500	44.07	14.62	74.0	29.93	Peak	74.90	150	Vertical	Pass
3	10998.500	45.11	15.53	74.0	28.89	Peak	203.70	150	Vertical	Pass
4	12018.750	46.30	17.29	74.0	27.70	Peak	178.10	150	Vertical	Pass
5	13622.000	48.88	17.95	74.0	25.12	Peak	3.90	150	Vertical	Pass
6	14515.750	49.91	20.62	74.0	24.09	Peak	267.10	150	Vertical	Pass

## 802.11g HIGH CHANNEL 7 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	8020.250	43.57	12.64	74.0	30.43	Peak	132.20	150	Horizontal	Pass
2	9777.500	45.32	14.13	74.0	28.68	Peak	81.20	150	Horizontal	Pass
3	10674.000	44.65	14.90	74.0	29.35	Peak	285.10	150	Horizontal	Pass
4	12002.250	46.99	17.51	74.0	27.01	Peak	55.60	150	Horizontal	Pass
5	13025.250	46.26	16.66	74.0	27.74	Peak	30.40	150	Horizontal	Pass
6	14499.250	50.65	19.77	74.0	23.35	Peak	234.40	150	Horizontal	Pass

## 802.11n-20 MHz LOW CHANNEL 1 GHz to 7 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1317.000	43.28	-3.42	74.0	30.72	Peak	99.30	150	Vertical	Pass
2**	1995.500	33.49	-0.56	54.0	20.51	AV	265.70	150	Vertical	Pass
2	1995.500	56.85	-0.56	74.0	17.15	Peak	265.70	150	Vertical	Pass
3	2404.500	87.68	0.85	74.0	-13.68	Peak	308.30	150	Vertical	N/A
4	2875.500	50.16	4.73	74.0	23.84	Peak	215.70	150	Vertical	Pass
5	3730.000	44.96	6.68	74.0	29.04	Peak	223.10	150	Vertical	Pass
6	5136.000	48.29	10.21	74.0	25.71	Peak	332.30	150	Vertical	Pass

## 802.11n-20 MHz LOW CHANNEL 1 GHz to 7 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1487.500	44.40	-2.84	74.0	29.60	Peak	199.40	150	Horizontal	Pass
2	2404.000	94.98	0.69	74.0	-20.98	Peak	0.50	150	Horizontal	N/A
3	3689.000	45.53	6.52	74.0	28.47	Peak	278.90	150	Horizontal	Pass
4	4703.000	46.64	9.18	74.0	27.36	Peak	182.20	150	Horizontal	Pass
5	5060.000	47.72	9.98	74.0	26.28	Peak	0.00	150	Horizontal	Pass
6	6050.000	49.45	10.87	74.0	24.55	Peak	162.90	150	Horizontal	Pass

## 802.11n-20 MHz MIDDLE CHANNEL 1 GHz to 7 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1464.000	43.40	-2.76	74.0	30.60	Peak	330.20	150	Vertical	Pass
2	1993.000	50.60	-0.29	74.0	23.40	Peak	264.70	150	Vertical	Pass
3	2442.500	88.38	1.29	74.0	-14.38	Peak	22.90	150	Vertical	N/A
4	3796.000	44.59	6.88	74.0	29.41	Peak	313.00	150	Vertical	Pass
5	4753.000	46.77	9.61	74.0	27.23	Peak	235.20	150	Vertical	Pass
6	6058.000	49.15	11.15	74.0	24.85	Peak	215.90	150	Vertical	Pass

## 802.11n-20 MHz MIDDLE CHANNEL 1 GHz to 7 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1417.500	43.48	-3.14	74.0	30.52	Peak	330.10	150	Horizontal	Pass
2	2441.500	96.29	1.23	74.0	-22.29	Peak	2.30	150	Horizontal	N/A
3	2937.000	49.01	3.53	74.0	24.99	Peak	116.30	150	Horizontal	Pass
4	3727.000	45.14	6.75	74.0	28.86	Peak	176.40	150	Horizontal	Pass
5	4506.000	46.04	8.61	74.0	27.96	Peak	263.20	150	Horizontal	Pass
6	5985.000	49.72	10.65	74.0	24.28	Peak	0.50	150	Horizontal	Pass

## 802.11n-20 MHz HIGH CHANNEL 1 GHz to 7 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1374.000	44.71	-2.97	74.0	29.29	Peak	57.20	150	Vertical	Pass
2**	1991.500	33.25	-0.33	54.0	20.75	AV	257.50	150	Vertical	Pass
2	1991.500	54.68	-0.33	74.0	19.32	Peak	257.50	150	Vertical	Pass
3	2454.000	88.96	0.95	74.0	-14.96	Peak	49.80	150	Vertical	N/A
4	3736.000	44.64	6.71	74.0	29.36	Peak	221.40	150	Vertical	Pass
5	4686.000	46.63	9.12	74.0	27.37	Peak	260.30	150	Vertical	Pass
6	5252.000	48.78	10.13	74.0	25.22	Peak	348.20	150	Vertical	Pass

## 802.11n-20 MHz HIGH CHANNEL 1 GHz to 7 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1441.000	43.89	-3.26	74.0	30.11	Peak	305.60	150	Horizontal	Pass
2	1995.000	45.71	-0.43	74.0	28.29	Peak	327.90	150	Horizontal	Pass
3	2420.000	55.47	1.01	74.0	18.53	Peak	82.00	150	Horizontal	N/A
4	2457.000	96.42	0.97	74.0	-22.42	Peak	357.00	150	Horizontal	N/A
5	3700.000	44.11	6.64	74.0	29.89	Peak	93.00	150	Horizontal	Pass
6	5567.000	49.09	10.61	74.0	24.91	Peak	278.00	150	Horizontal	Pass

## 802.11n-20 MHz LOW CHANNEL 7 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	8207.250	43.20	12.19	74.0	30.80	Peak	133.50	150	Vertical	Pass
2	9604.250	44.00	14.68	74.0	30.00	Peak	133.50	150	Vertical	Pass
3	10404.500	45.68	15.23	74.0	28.32	Peak	0.00	150	Vertical	Pass
4	11875.750	46.42	14.41	74.0	27.58	Peak	323.30	150	Vertical	Pass
5	12288.250	47.02	16.78	74.0	26.98	Peak	159.00	150	Vertical	Pass
6	14086.750	49.30	19.46	74.0	24.70	Peak	298.20	150	Vertical	Pass

## 802.11n-20 MHz LOW CHANNEL 7 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	8094.500	42.82	13.32	74.0	31.18	Peak	3.70	150	Horizontal	Pass
2	9112.001	44.10	13.98	74.0	29.90	Peak	226.40	150	Horizontal	Pass
3	10415.500	44.66	15.62	74.0	29.34	Peak	360.00	150	Horizontal	Pass
4	11510.000	45.67	16.66	74.0	28.33	Peak	125.20	150	Horizontal	Pass
5	12280.001	46.91	16.80	74.0	27.09	Peak	328.40	150	Horizontal	Pass
6	13622.000	48.63	17.95	74.0	25.37	Peak	201.60	150	Horizontal	Pass

## 802.11n-20 MHz MIDDLE CHANNEL 7 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	8317.250	43.05	12.74	74.0	30.95	Peak	248.40	150	Vertical	Pass
2	9750.000	44.55	13.88	74.0	29.45	Peak	0.40	150	Vertical	Pass
3	10756.500	44.58	14.69	74.0	29.42	Peak	172.30	150	Vertical	Pass
4	11512.750	46.06	16.61	74.0	27.94	Peak	0.40	150	Vertical	Pass
5	12475.250	47.15	16.31	74.0	26.85	Peak	32.30	150	Vertical	Pass
6	14320.500	49.40	19.19	74.0	24.60	Peak	274.00	150	Vertical	Pass



## 802.11n-20 MHz MIDDLE CHANNEL 7 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	8575.750	42.87	13.31	74.0	31.13	Peak	358.80	150	Horizontal	Pass
2	9639.999	44.00	15.10	74.0	30.00	Peak	332.20	150	Horizontal	Pass
3	11259.750	46.25	16.15	74.0	27.75	Peak	360.00	150	Horizontal	Pass
4	12288.250	46.62	16.78	74.0	27.38	Peak	360.00	150	Horizontal	Pass
5	13718.250	47.41	16.87	74.0	26.59	Peak	306.90	150	Horizontal	Pass
6	14515.750	51.69	20.62	74.0	22.31	Peak	360.00	150	Horizontal	Pass

## 802.11n-20 MHz HIGH CHANNEL 7 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	7965.250	42.33	11.52	74.0	31.67	Peak	163.10	150	Vertical	Pass
2	9458.500	43.80	13.26	74.0	30.20	Peak	137.90	150	Vertical	Pass
3	11213.000	45.26	15.91	74.0	28.74	Peak	3.50	150	Vertical	Pass
4	12304.750	46.49	16.58	74.0	27.51	Peak	1.00	150	Vertical	Pass
5	13498.250	47.13	16.66	74.0	26.87	Peak	10.70	150	Vertical	Pass
6	14504.750	49.78	20.07	74.0	24.22	Peak	302.40	150	Vertical	Pass

## 802.11n-20 MHz HIGH CHANNEL 7 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	8724.250	43.73	13.09	74.0	30.27	Peak	233.50	150	Horizontal	Pass
2	10423.750	44.53	15.83	74.0	29.47	Peak	246.20	150	Horizontal	Pass
3	11507.250	45.65	16.71	74.0	28.35	Peak	195.40	150	Horizontal	Pass
4	12533.000	47.36	16.88	74.0	26.64	Peak	272.10	150	Horizontal	Pass
5	13624.750	47.81	17.85	74.0	26.19	Peak	170.20	150	Horizontal	Pass
6	14510.250	50.16	20.35	74.0	23.84	Peak	323.20	150	Horizontal	Pass

Test Frequency: 18 GHz ~ 25 GHz

Note: Only noise floor was seen above 18 GHz and not reported.

## A.7 Band Edge (Restricted-band band-edge)

### Test Data

Note<sup>1</sup>: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.


Note<sup>2</sup>: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note<sup>3</sup>: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
802.11b	Low	2390	44.64	74	29.36	PEAK	Pass
		2390	N/A	54	N/A	AVERAGE	Pass
	HIGH	2483.5	45.04	74	28.96	PEAK	Pass
		2483.5	N/A	54	N/A	AVERAGE	Pass
802.11g	Low	2390	48.29	74	25.71	PEAK	Pass
		2390	N/A	54	N/A	AVERAGE	Pass
	HIGH	2483.5	52.08	74	21.92	PEAK	Pass
		2483.5	N/A	54	N/A	AVERAGE	Pass
802.11n20	Low	2390	48.47	74	25.53	PEAK	Pass
		2390	N/A	54	N/A	AVERAGE	Pass
	HIGH	2483.5	47.74	74	26.26	PEAK	Pass
		2483.5	N/A	54	N/A	AVERAGE	Pass

802.11b Mode:

LOW CHANNEL, PEAK




HIGH CHANNEL, PEAK




802.11g Mode:

LOW CHANNEL, PEAK





HIGH CHANNEL, PEAK



802.11n-20 MHz Mode:

Low CHANNEL, PEAK

HIGH CHANNEL, PEAK



## A.8 Power Spectral Density (PSD)

### Test Data

#### 802.11b Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-9.65	8
Middle	-10.17	8
High	-9.65	8

#### 802.11g Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-14.72	8
Middle	-16.51	8
High	-15.18	8

#### 802.11n-20 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-16.01	8
Middle	-16.07	8
High	-16.72	8

Test plots

802.11b LOW CHANNEL



Date: 14 MAR 2017 16:27:12

802.11b MIDDLE CHANNEL




Date: 14 MAR 2017 16:29:48

802.11b HIGH CHANNEL




Date: 14 MAR 2017 16:32:47

802.11g LOW CHANNEL




Date: 14 MAR 2017 16:38:32

802.11g MIDDLE CHANNEL




Date: 14 MAR 2017 16:40:42

802.11g HIGH CHANNEL




Date: 14 MAR 2017 16:43:06

802.11n-20 MHz LOW CHANNEL




Date: 14 MAR 2017 16:45:55

802.11 n-20 MHz MIDDLE CHANNEL



Date: 14 MAR 2017 16:47:56

802.11n-20 MHz HIGH CHANNEL



Date: 14 MAR 2017 16:49:54

## **ANNEX B TEST SETUP PHOTOS**

Please refer the document "BL-SZ1720011-AR.pdf".

## **ANNEX C EUT EXTERNAL PHOTOS**

Please refer the document "BL-SZ1720011-AW.pdf".

## **ANNEX D EUT INTERNAL PHOTOS**

Please refer the document "BL-SZ1720011-AI.pdf".

--END OF REPORT--