



MRT Technology (Taiwan) Co., Ltd
Phone: +886-3-3288388
Fax: +886-3-3288918
Web: www.mrt-cert.com

Report No.: 1911TW5401-U6
Report Version: 1.0
Issue Date: 2020-01-14

MEASUREMENT REPORT

FCC PART 22H, 24E, 27

FCC ID: TFJPIXIE-G

APPLICANT: Uniform Industrial Corp.

Application Type: Certification

Product: Mobile POS Terminal

Model No.: PIXIE-GH1WD1

Brand Name: UIC

FCC Classification: PCS Licensed Transmitter (PCB)

FCC Rule Part(s): Part2, Part22 Subpart H, Part24 Subpart E, Part27

Test Procedure(s): ANSI/TIA-603-E-2016, KDB 971168 D01v03r01

Received Date: November 5, 2019

Test Date: November 5, 2019 ~ January 13, 2020

Tested By : *Peter Syu*
(Peter Syu)

Reviewed By : *Paddy Chen*
(Paddy Chen)

Approved By : *Chenz Ker*
(Chenz Ker)



The test results only relate to the tested sample.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1911TW5401-U6	1.0	Original Report	2020-01-14	

CONTENTS

Description	Page
§2.1033 General Information	5
1. INTRODUCTION	6
1.1. Scope	6
1.2. MRT Test Location	6
2. PRODUCT INFORMATION	7
2.1. Feature of Equipment under Test.....	7
2.2. Equipment Description	8
2.3. Device Capabilities	8
2.4. Test Configuration	8
2.5. EMI Suppression Device(s)/Modifications.....	8
3. DESCRIPTION OF TEST	9
3.1. Evaluation Procedure	9
3.2. Cellular – Base Frequency Blocks	9
3.3. Cellular – Mobile Frequency Blocks.....	9
3.4. PCS – Base Frequency Blocks.....	10
3.5. PCS – Mobile Frequency Blocks	10
3.6. Occupied Bandwidth.....	11
3.7. Spurious and Harmonic Emissions at Antenna Terminal	11
3.8. Power and Radiated Spurious Emissions	12
3.9. Peak-Average Ratio	13
3.10. Frequency Stability / Temperature Variation.....	13
4. TEST EQUIPMENT CALIBRATION DATE.....	14
5. SAMPLE CALCULATIONS	15
6. MEASUREMENT UNCERTAINTY.....	16
7. TEST RESULT	17
7.1. Summary.....	17
7.2. Occupied Bandwidth.....	19
7.2.1. Test Limit	19
7.2.2. Test Procedure used.....	19
7.2.3. Test Setting	19
7.2.4. Test Setup	19
7.2.5. Test Result.....	20
7.3. Conducted Spurious Emissions	32

7.3.1. Test Limit	32
7.3.2. Test Procedure Used	32
7.3.3. Test Setting.....	32
7.3.4. Test Setup	32
7.3.5. Test Result.....	33
7.4. Band Edge at Antenna Terminal.....	87
7.4.1. Test Limit	87
7.4.2. Test Procedure Used	87
7.4.3. Test Setting.....	87
7.4.4. Test Setup	88
7.4.5. Test Result.....	89
7.5. Power and Radiated Spurious Emissions	129
7.5.1 Test Limit	129
7.5.2 Test Procedure Used	129
7.5.3 Test Setting.....	130
7.5.4 Test Setup	132
7.5.5 Test Result.....	133
7.6. Peak-Average Ratio	167
7.6.1 Test Limit	167
7.6.2 Test Procedure	167
7.6.3 Test Setup	167
7.6.4 Test Result.....	168
7.7. Frequency Stability Under Temperature & Voltage Variations	180
7.7.1 Test Limit	180
7.7.2 Test Procedure	180
7.7.3 Test Setup	180
7.7.4 Test Result.....	181

§2.1033 General Information

Applicant	Uniform Industrial Corp.			
Applicant Address	47341 Bayside Parkway, Fremont, California 94538, United States			
Manufacturer	Uniform Industrial Corp.			
Manufacturer Address	47341 Bayside Parkway, Fremont, California 94538, United States			
Test Site	MRT Technology (Taiwan) Co., Ltd			
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)			
MRT FCC Registration No.	291082			
FCC Rule Part(s)	Part 22H, Part 24E, Part27			
Model No.	PIXIE-GH1WD1			
Test Device Serial No.	N/A	<input type="checkbox"/> Production	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Engineering

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Fuxing Rd., Taoyuan, Taiwan (R.O.C)

- MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
- MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
- MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Feature of Equipment under Test

Product Name	Mobile POS Terminal
Model No.	PIXIE-GH1WD1
Brand Name	
Supports Radios Spec.	WWAN 3G: Band 2,5 4G: FDD Band 2,4,5,12 NFC 13.56MHz
4G Operation Band (s)	Band 2, 4, 5, 12
Frequency Range	Band2: 1850MHz–1910MHz Band4: 1710MHz–1755MHz Band5: 824MHz–849MHz Band12: 699MHz–716MHz
Accessories	
PIXIE Docking	MFR: UIC Model No: PIXIE
Adapter#1	MFR: BILLION ELECTRIC CO., LTD. Model No: BA048-090500MAX Input: AC 100-240V~1.5A, 50-60Hz Output: DC 9V, 5A
Adapter #2	MFR: Powertron Electronics Corp. Model No: PA150-090T1A500 Input: AC 100-240V~1.8A, 50-60Hz Output: DC 9V, 5A

2.2. Equipment Description

Antenna Type	PCB
Antenna M/N	98G9ZIPF000
Antenna Gain	Band 2: -1.01dBi, Band 4: -0.63dBi, Band 5: -9.30dBi, Band 12: -8.55dBi
Type of Modulation	QPSK, 16QAM

Note: The test report has showed the worst test mode.

2.3. Device Capabilities

This device contains the following capabilities:

LTE Band 2, 4, 5, 12

2.4. Test Configuration

The **Mobile POS Terminal** was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01v03r01. See section 3.0 of this report for a description of the radiated and antenna port conducted emissions tests.

2.5. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168) were used in the measurement of the **Mobile POS Terminal**

Deviation from measurement procedure.....**None**


3.2. Cellular – Base Frequency Blocks

§22.905



3.3. Cellular – Mobile Frequency Blocks

§22.905



3.4. PCS – Base Frequency Blocks

§24.229



3.5. PCS – Mobile Frequency Blocks

§24.229



3.6. Occupied Bandwidth

§2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The spectrum analyzers' "occupied bandwidth" measurement function was used to record the occupied bandwidth in accordance with KDB 971168.

3.7. Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(c),(g),(m)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

3.8. Power and Radiated Spurious Emissions

§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a) §27.53(c)(g)(m)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurement and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 80cm high PVC support structure is placed on top of the turntable.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to P_g [dBm] – cable loss [dB].

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10 \log_{10}(\text{Power [Watts]})$ specified in 22.917(a).

3.9. Peak-Average Ratio

§24.232(d)

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

For pulsed signals, the spectrum analyzer is set to use an internal “RF Burst” trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the “on time” of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power. For continuous signals, the trigger is set to “free run” in the CCDF measurement mode.

3.10. Frequency Stability / Temperature Variation

§2.1055 §22.355 §22.863 §22.905 §24.229 §24.235 §27.54

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016.

The frequency stability of the transmitter is measured by:

- a.) Temperature: The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5 \text{ ppm}$) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

4. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2020/3/25
Cable	Rosnol	N1C50-RG400-B 1C50-500CM	MRTTWE00013	1 year	2020/6/18
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2020/3/25

Radiated Emissions – AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2020/6/4
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2020/3/25
Acitive Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2020/4/29
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2020/4/22
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2020/4/23
Broadband Amplifier	Schwarzbeck	BBV 9721	MRTTWA00006	1 year	2020/4/24
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2020/4/24
Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2020/4/22
Cable	Rosnol	K1K50-UP0264- K1K50-4M	MRTTWE00012	1 year	2020/6/18

Conducted Test Equipment – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2020/10/2
Spectrum Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2020/7/11
USB Wideband Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2020/3/26
Wideband Radio Communication Taster	R&S	CMW 500	MRTTWA00041	1 year	2020/1/28

Test Software

Software	Version	Function
e3	9.160520a	EMI Test Software
EMI	V3	EMI Test Software

5. SAMPLE CALCULATIONS

GSM Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EGPRS Emission Designator

Emission Designator = 250KG7W

GSM BW = 250 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA / CDMA Emission Designator

Emission Designator = 1M25F9W

WCDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

LTE Emission Designator

Emission Designator = QPSK 5M00G7D / 16QAM 5M00W7D

LTE BW = 1.4/3/5/10/15/20 MHz

QPSK G = Phase Modulation /

16QAM W= in a combination of two or more of the following modes: amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission

Example: Spurious emission at 1688.10 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -65.0dBm.

The gain of the substituted antenna is 6.5dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -65.0dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 4.5 dB at 1688.1MHz. So 2 dB is added to the signal generator reading of -25dBm yielding -23dBm. The fundamental EIRP was 24.0dBm so this harmonic was 24.0dBm - (-23) = 47dBc.

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

Radiated Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): 3.92dB (Below 30M)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): 4.25dB (30M~1G)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): 4.40dB (1G~18G)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): 4.45dB (18G~40G)
Frequency Error
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 78.4\text{Hz}$
Conducted Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 0.84\text{dB}$
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 2.65 \text{ dB}$
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): 3.3%
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 0.82^\circ\text{C} / \pm 3\%$
DC Voltage
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 0.3\%$

7. TEST RESULT

7.1. Summary

Company Name: Uniform Industrial Corp.
FCC Classification: PCS Licensed Transmitter (PCB)
Mode(s): LTE Band 2, 4, 5, 12

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
Transmitter Mode(TX)					
2.1049	Occupied bandwidth	N/A	Conducted	Pass	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(c) 27.52(h)	Conducted Spurious Emissions	> 43 + 10log ₁₀ (P[Watts]) at for all out-of-band emissions (Band 2,4,5,12,13,17)		Pass	Section 7.3
2.1051 27.53(m)		> 55 + 10log ₁₀ (P[Watts]) at for all out-of-band emissions (Band 7)			
2.1051 22.917(a) 24.238(a) 27.53(c) 27.52(h)	Band Edge	> 43 + 10log ₁₀ (P[Watts]) at for all out-of-band emissions		Pass	Section 7.4
27.53(m)		27.53(m)(4)			
2.1046	Conducted Output Power	N/A	Radiated	Pass	Section 7.5
22.913(a)	Radiated Output Power	< 7 Watts max. ERP (Band 5)		Pass	Section 7.5
24.232(c) 27.50(h)		< 2 Watts max. EIRP (Band 2, 7)		Pass	
27.50(b)		< 3 Watts max. ERP (Band 12,13)		Pass	
27.50(d)		< 1 Watts max. EIRP (Band 4)		Pass	

2.1053 22.917(a) 24.238(a) 27.53(c) 27.53(h)	Radiated Spurious Emissions	> 43 + log ₁₀ (P[Watts]) for all out-of-band emissions (Band 2,4,5,12,13,17)	Radiated	Pass	Section 7.5
2.1053 27.53(m)		> 55 + 10log ₁₀ (P[Watts]) for all out-of-band emissions (Band 7)			
24.232(d) 27.50(B)	Peak-Average Ratio	<13dB		Pass	Section 7.6
2.1055 22.355	Frequency Stability	< 2.5 ppm	Conducted	Pass	Section 7.7
2.1055 24.235 27.54		Within Authorized Band			

Notes:

- 1) Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- 2) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.

7.2. Occupied Bandwidth

7.2.1. Test Limit

N/A


7.2.2. Test Procedure used

KDB 971168 D01v03r01 – Section 4.2 & ANSI/TIA-603-E-2016

7.2.3. Test Setting


1. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
2. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW. (RBW = approximately 1% of the emission bandwidth).
3. Set the detection mode to peak, and the trace mode to max hold.
4. Use the 99 % power bandwidth function of the spectrum analyzer (if available) and report the measured bandwidth.


7.2.4. Test Setup




7.2.5. Test Result


Test Mode	Channel/ Frequency (MHz)	Modulation	Bandwidth (MHz)	RB Size	RB Offset	99% Occupied Bandwidth (MHz)	-26dB Occupied Bandwidth (MHz)	Test Result
LET Band 2	CH18900 (1880MHz)	QPSK	1.4	6	0	1.0778	1.251	Pass
			3	15	0	2.6905	2.934	Pass
			5	25	0	4.4882	4.936	Pass
			10	50	0	8.9288	9.672	Pass
			15	75	0	13.4120	14.430	Pass
			20	100	0	17.8330	19.040	Pass
	CH18900 (1880MHz)	16QAM	1.4	6	0	1.0823	1.260	Pass
			3	15	0	2.6838	2.957	Pass
			5	25	0	4.4810	4.897	Pass
			10	50	0	8.9484	9.721	Pass
			15	75	0	13.4150	14.390	Pass
			20	100	0	17.8870	19.030	Pass







Test Mode	Channel/ Frequency (MHz)	Modulation	Bandwidth (MHz)	RB Size	RB Offset	99% Occupied Bandwidth (MHz)	-26dB Occupied Bandwidth (MHz)	Test Result
LET Band 4	CH20175 (1732.5MHz)	QPSK	1.4	6	0	1.0843	1.245	Pass
			3	15	0	2.6816	2.928	Pass
			5	25	0	4.4648	4.879	Pass
			10	50	0	8.9391	9.743	Pass
			15	75	0	13.3930	14.450	Pass
			20	100	0	17.8980	19.180	Pass
	CH20175 (1732.5MHz)	16QAM	1.4	6	0	1.0862	1.278	Pass
			3	15	0	2.6888	2.929	Pass
			5	25	0	4.4711	4.917	Pass
			10	50	0	8.9359	9.758	Pass
			15	75	0	13.4010	14.350	Pass
			20	100	0	17.8590	19.000	Pass







Test Mode	Channel/ Frequency (MHz)	Modulation	Bandwidth (MHz)	RB Size	RB Offset	99% Occupied Bandwidth (MHz)	-26dB Occupied Bandwidth (MHz)	Test Result
LET Band 5	CH20525 (836.5MHz)	QPSK	1.4	6	0	1.0812	1.302	Pass
			3	15	0	2.6940	2.960	Pass
			5	25	0	4.4787	4.916	Pass
			10	50	0	8.9683	9.556	Pass
	16QAM	16QAM	1.4	6	0	1.0828	1.275	Pass
			3	15	0	2.6912	2.959	Pass
			5	25	0	4.4877	4.947	Pass
			10	50	0	8.9391	9.660	Pass





Test Mode	Channel/ Frequency (MHz)	Modulation	Bandwidth (MHz)	RB Size	RB Offset	99% Occupied Bandwidth (MHz)	-26dB Occupied Bandwidth (MHz)	Test Result
LET Band 12	CH23095 (707.5MHz)	QPSK	1.4	6	0	1.0790	1.256	Pass
			3	15	0	2.6856	2.920	Pass
			5	25	0	4.4694	4.903	Pass
			10	50	0	8.9466	9.798	Pass
		16QAM	1.4	6	0	1.0820	1.256	Pass
			3	15	0	2.6870	2.918	Pass
			5	25	0	4.4696	4.852	Pass
			10	50	0	8.9572	9.680	Pass





7.3. Conducted Spurious Emissions

7.3.1. Test Limit

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log_{10}(P)$ dB for Band 2,4,5,12,13,17/ $55+10\log_{10}(P)$ dB for Band7.

7.3.2. Test Procedure Used


KDB 971168 D01v03r01 – Section 6.0 & ANSI/TIA-603-E-2016

7.3.3. Test Setting

Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz is at or below 1GHz and 1MHz is above 1GHz, If any, up to 10th harmonic.

7.3.4. Test Setup


Spectrum Analyzer




7.3.5. Test Result

Test Mode	Modulation	Channel/ Frequency (MHz)	Bandwidth (MHz)	RB Size	RB Offset	Test Result	
LTE Band 2 (Low Channel)	QPSK	CH18607 / 1850.7MHz	1.4	1	2	Pass	
		CH18615 / 1851.5MHz	3	1	7	Pass	
		CH18625 / 1852.5MHz	5	1	12	Pass	
		CH18650 / 1855MHz	10	1	25	Pass	
		CH18675 / 1857.5MHz	15	1	36	Pass	
		CH18700 / 1860MHz	20	1	49	Pass	
	16QAM	CH18607 / 1850.7MHz	1.4	1	2	Pass	
		CH18615 / 1851.5MHz	3	1	7	Pass	
		CH18625 / 1852.5MHz	5	1	12	Pass	
		CH18650 / 1855MHz	10	1	25	Pass	
		CH18675 / 1857.5MHz	15	1	36	Pass	
		CH18700 / 1860MHz	20	1	49	Pass	
LTE Band 2 (Middle Channel)	QPSK	CH18900 / 1880MHz	1.4	1	2	Pass	
			3	1	7	Pass	
			5	1	12	Pass	
			10	1	25	Pass	
			15	1	36	Pass	
			20	1	49	Pass	
	16QAM		1.4	1	2	Pass	
			3	1	7	Pass	
			5	1	12	Pass	
			10	1	25	Pass	
			15	1	36	Pass	
			20	1	49	Pass	


Test Mode	Modulation	Channel/ Frequency (MHz)	Bandwidth (MHz)	RB Size	RB Offset	Test Result
LTE Band 2 (High Channel)	QPSK	CH19193 / 1909.3MHz	1.4	1	2	Pass
		CH19185 / 1908.5MHz	3	1	7	Pass
		CH19175 / 1907.5MHz	5	1	12	Pass
		CH19150 / 1905MHz	10	1	25	Pass
		CH19125 / 1902.5MHz	15	1	36	Pass
		CH19100 / 1900MHz	20	1	49	Pass
	16QAM	CH19193 / 1909.3MHz	1.4	1	2	Pass
		CH19185 / 1908.5MHz	3	1	7	Pass
		CH19175 / 1907.5MHz	5	1	12	Pass
		CH19150 / 1905MHz	10	1	25	Pass
		CH19125 / 1902.5MHz	15	1	36	Pass
		CH19100 / 1900MHz	20	1	49	Pass







LTE Band 2 16QAM 1.4MHz CH18607 1RB#2_30MHz-1GHz	LTE Band 2 16QAM 1.4MHz CH18607 1RB#2_1GHz-20GHz
<p>Start Freq 30.000000 MHz PNO: Fast IF Gain:Low Trig: Free Run #Atten: 20 dB Avg Type: Log-Pwr Avg Hold: >100/100</p> <p>Mkr1 838.22 MHz -38.552 dBm</p> <p>Frequency: Auto Tune Center Freq: 515.000000 MHz Start Freq: 30.000000 MHz Stop Freq: 1.00000000 GHz CF Step: 97.000000 MHz Man Freq Offset: 0 Hz</p> <p>Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 2.133 ms (32001 pts)</p>	<p>Start Freq 1.0000000000 GHz PNO: Fast IF Gain:Low Trig: Free Run #Atten: 30 dB Avg Type: Log-Pwr Avg Hold: >100/100</p> <p>Mkr1 3.8488 GHz -31.877 dBm</p> <p>Frequency: Auto Tune Center Freq: 10.5000000000 GHz Start Freq: 1.0000000000 GHz Stop Freq: 20.0000000000 GHz CF Step: 1.9000000000 GHz Auto Man Freq Offset: 0 Hz</p> <p>Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 32.00 ms (32001 pts)</p>
LTE Band 2 16QAM 3MHz CH18615 1RB#7_30MHz-1GHz	LTE Band 2 16QAM 3MHz CH18615 1RB#7_1GHz-20GHz
<p>Start Freq 30.000000 MHz PNO: Fast IF Gain:Low Trig: Free Run #Atten: 20 dB Avg Type: Log-Pwr Avg Hold: >100/100</p> <p>Mkr1 764.53 MHz -39.764 dBm</p> <p>Frequency: Auto Tune Center Freq: 515.000000 MHz Start Freq: 30.000000 MHz Stop Freq: 1.00000000 GHz CF Step: 97.000000 MHz Man Freq Offset: 0 Hz</p> <p>Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 2.133 ms (32001 pts)</p>	<p>Start Freq 1.0000000000 GHz PNO: Fast IF Gain:Low Trig: Free Run #Atten: 30 dB Avg Type: Log-Pwr Avg Hold: >100/100</p> <p>Mkr1 14.8242 GHz -29.888 dBm</p> <p>Frequency: Auto Tune Center Freq: 10.5000000000 GHz Start Freq: 1.0000000000 GHz Stop Freq: 20.0000000000 GHz CF Step: 1.9000000000 GHz Auto Man Freq Offset: 0 Hz</p> <p>Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 32.00 ms (32001 pts)</p>
LTE Band 2 16QAM 5MHz CH18625 1RB#12_30MHz-1GHz	LTE Band 2 16QAM 5MHz CH18625 1RB#12_1GHz-20GHz
<p>Start Freq 30.000000 MHz PNO: Fast IF Gain:Low Trig: Free Run #Atten: 20 dB Avg Type: Log-Pwr Avg Hold: >100/100</p> <p>Mkr1 775.96 MHz -39.405 dBm</p> <p>Frequency: Auto Tune Center Freq: 515.000000 MHz Start Freq: 30.000000 MHz Stop Freq: 1.00000000 GHz CF Step: 97.000000 MHz Man Freq Offset: 0 Hz</p> <p>Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 2.133 ms (32001 pts)</p>	<p>Start Freq 1.0000000000 GHz PNO: Fast IF Gain:Low Trig: Free Run #Atten: 30 dB Avg Type: Log-Pwr Avg Hold: >100/100</p> <p>Mkr1 18.5465 GHz -28.226 dBm</p> <p>Frequency: Auto Tune Center Freq: 10.5000000000 GHz Start Freq: 1.0000000000 GHz Stop Freq: 20.0000000000 GHz CF Step: 1.9000000000 GHz Auto Man Freq Offset: 0 Hz</p> <p>Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 32.00 ms (32001 pts)</p>


LTE Band 2 16QAM 10MHz CH18650 1RB#25_30MHz-1GHz	LTE Band 2 16QAM 10MHz CH18650 1RB#25_1GHz-20GHz
<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 22 dB Ref 32.00 dBm 10 dB/div Log Frequency: Auto Tune Center Freq: 515.000000 MHz Start Freq: 30.000000 MHz Stop Freq: 1.00000000 GHz CF Step: 97.000000 MHz Man Freq Offset: 0 Hz Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 2.133 ms (32001 pts) Stop 1.0000 GHz Mkr1 802.15 MHz -39.421 dBm</p>	<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 1.0000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 15 dB Ref 35.00 dBm 10 dB/div Log Frequency: Auto Tune Center Freq: 10.5000000000 GHz Start Freq: 1.0000000000 GHz Stop Freq: 20.0000000000 GHz CF Step: 1.9000000000 GHz Man Freq Offset: 0 Hz Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 32.00 ms (32001 pts) Stop 20.0000 GHz Mkr1 15.1087 GHz -29.252 dBm</p>
LTE Band 2 16QAM 15MHz CH18675 1RB#36_30MHz-1GHz	LTE Band 2 16QAM 15MHz CH18675 1RB#36_1GHz-20GHz
<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 22 dB Ref 32.00 dBm 10 dB/div Log Frequency: Auto Tune Center Freq: 515.000000 MHz Start Freq: 30.000000 MHz Stop Freq: 1.00000000 GHz CF Step: 97.000000 MHz Man Freq Offset: 0 Hz Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 2.133 ms (32001 pts) Stop 1.0000 GHz Mkr1 970.81 MHz -39.012 dBm</p>	<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 1.0000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 15 dB Ref 35.00 dBm 10 dB/div Log Frequency: Auto Tune Center Freq: 10.5000000000 GHz Start Freq: 1.0000000000 GHz Stop Freq: 20.0000000000 GHz CF Step: 1.9000000000 GHz Man Freq Offset: 0 Hz Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 32.00 ms (32001 pts) Stop 20.0000 GHz Mkr1 14.3891 GHz -29.693 dBm</p>
LTE Band 2 16QAM 20MHz CH18700 1RB#49_30MHz-1GHz	LTE Band 2 16QAM 20MHz CH18700 1RB#49_1GHz-20GHz
<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 22 dB Ref 32.00 dBm 10 dB/div Log Frequency: Auto Tune Center Freq: 515.000000 MHz Start Freq: 30.000000 MHz Stop Freq: 1.00000000 GHz CF Step: 97.000000 MHz Man Freq Offset: 0 Hz Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 2.133 ms (32001 pts) Stop 1.0000 GHz Mkr1 797.09 MHz -38.730 dBm</p>	<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 1.0000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 15 dB Ref 35.00 dBm 10 dB/div Log Frequency: Auto Tune Center Freq: 10.5000000000 GHz Start Freq: 1.0000000000 GHz Stop Freq: 20.0000000000 GHz CF Step: 1.9000000000 GHz Man Freq Offset: 0 Hz Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 32.00 ms (32001 pts) Stop 20.0000 GHz Mkr1 19.3314 GHz -28.151 dBm</p>









LTE Band 2 16QAM 10MHz CH18900 1RB#25_30MHz-1GHz	LTE Band 2 16QAM 10MHz CH18900 1RB#25_1GHz-20GHz
<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 22 dB Ref 32.00 dBm Mkr1 761.87 MHz -39.742 dBm 10 dB/div Log 22.0 12.0 2.0 -8.0 -18.0 -28.0 -38.0 -48.0 -58.0 Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 1.0000 GHz Sweep 2.133 ms (32001 pts) M56 STATUS:</p>	<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 1.0000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 15 dB Ref 35.00 dBm Mkr1 13.7496 GHz -29.806 dBm 10 dB/div Log 25.0 15.0 5.0 -5.0 -15.0 -25.0 -35.0 -45.0 -55.0 Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20.000 GHz Sweep 32.00 ms (32001 pts) M56 STATUS:</p>
<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 22 dB Ref 32.00 dBm Mkr1 862.53 MHz -38.831 dBm 10 dB/div Log 22.0 12.0 2.0 -8.0 -18.0 -28.0 -38.0 -48.0 -58.0 Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 1.0000 GHz Sweep 2.133 ms (32001 pts) M56 STATUS:</p>	<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 1.0000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 15 dB Ref 35.00 dBm Mkr1 13.7662 GHz -29.988 dBm 10 dB/div Log 25.0 15.0 5.0 -5.0 -15.0 -25.0 -35.0 -45.0 -55.0 Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20.000 GHz Sweep 32.00 ms (32001 pts) M56 STATUS:</p>
<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 22 dB Ref 32.00 dBm Mkr1 879.05 MHz -38.828 dBm 10 dB/div Log 22.0 12.0 2.0 -8.0 -18.0 -28.0 -38.0 -48.0 -58.0 Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 1.0000 GHz Sweep 2.133 ms (32001 pts) M56 STATUS:</p>	<p>Agilent Spectrum Analyzer - Sweep SA Start Freq 1.0000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 15 dB Ref 35.00 dBm Mkr1 15.1206 GHz -29.071 dBm 10 dB/div Log 25.0 15.0 5.0 -5.0 -15.0 -25.0 -35.0 -45.0 -55.0 Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20.000 GHz Sweep 32.00 ms (32001 pts) M56 STATUS:</p>










LTE Band 2 16QAM 10MHz CH19150 1RB#25_30MHz-1GHz	LTE Band 2 16QAM 10MHz CH19150 1RB#25_1GHz-20GHz
<p>Agilent Spectrum Analyzer - Swept SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: 100/100 Ref Offset 22 dB Ref 32.00 dBm Mkr1 956.14 MHz -38.980 dBm 10 dB/div Log 22.0 12.0 2.0 -8.0 -18.0 -28.0 -38.0 -48.0 -58.0 Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 1.0000 GHz Sweep 2.133 ms (32001 pts) M56 STATUS:</p>	<p>Agilent Spectrum Analyzer - Swept SA Start Freq 1.000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: 100/100 Ref Offset 15 dB Ref 35.00 dBm Mkr1 13.6528 GHz -29.283 dBm 10 dB/div Log 25.0 15.0 5.0 -5.0 -15.0 -25.0 -35.0 -45.0 -55.0 Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20.000 GHz Sweep 32.00 ms (32001 pts) M56 STATUS:</p>
<p>Agilent Spectrum Analyzer - Swept SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: 100/100 Ref Offset 22 dB Ref 32.00 dBm Mkr1 887.09 MHz -38.592 dBm 10 dB/div Log 22.0 12.0 2.0 -8.0 -18.0 -28.0 -38.0 -48.0 -58.0 Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 1.0000 GHz Sweep 2.133 ms (32001 pts) M56 STATUS:</p>	<p>Agilent Spectrum Analyzer - Swept SA Start Freq 1.000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: 100/100 Ref Offset 15 dB Ref 35.00 dBm Mkr1 14.5624 GHz -29.673 dBm 10 dB/div Log 25.0 15.0 5.0 -5.0 -15.0 -25.0 -35.0 -45.0 -55.0 Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20.000 GHz Sweep 32.00 ms (32001 pts) M56 STATUS:</p>
<p>Agilent Spectrum Analyzer - Swept SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: 100/100 Ref Offset 22 dB Ref 32.00 dBm Mkr1 683.93 MHz -39.302 dBm 10 dB/div Log 22.0 12.0 2.0 -8.0 -18.0 -28.0 -38.0 -48.0 -58.0 Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 1.0000 GHz Sweep 2.133 ms (32001 pts) M56 STATUS:</p>	<p>Agilent Spectrum Analyzer - Swept SA Start Freq 1.000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: 100/100 Ref Offset 15 dB Ref 35.00 dBm Mkr1 18.5483 GHz -27.305 dBm 10 dB/div Log 25.0 15.0 5.0 -5.0 -15.0 -25.0 -35.0 -45.0 -55.0 Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Stop 20.000 GHz Sweep 32.00 ms (32001 pts) M56 STATUS:</p>

Test Mode	Modulation	Channel/ Frequency (MHz)	Bandwidth (MHz)	RB Size	RB Offset	Test Result	
LTE Band 4 (Low Channel)	QPSK	CH19957 / 1710.7MHz	1.4	1	2	Pass	
		CH19965 / 1711.5MHz	3	1	7	Pass	
		CH19975 / 1712.5MHz	5	1	12	Pass	
		CH20000 / 1715MHz	10	1	25	Pass	
		CH20025 / 1717.5MHz	15	1	36	Pass	
		CH20050 / 1720MHz	20	1	49	Pass	
	16QAM	CH19957 / 1710.7MHz	1.4	1	2	Pass	
		CH19965 / 1711.5MHz	3	1	7	Pass	
		CH19975 / 1712.5MHz	5	1	12	Pass	
		CH20000 / 1715MHz	10	1	25	Pass	
		CH20025 / 1717.5MHz	15	1	36	Pass	
		CH20050 / 1720MHz	20	1	49	Pass	
LTE Band 4 (Middle Channel)	QPSK	CH20175 / 1732.5MHz	1.4	1	2	Pass	
			3	1	7	Pass	
			5	1	12	Pass	
			10	1	25	Pass	
			15	1	36	Pass	
			20	1	49	Pass	
	16QAM		1.4	1	2	Pass	
			3	1	7	Pass	
			5	1	12	Pass	
			10	1	25	Pass	
			15	1	36	Pass	
			20	1	49	Pass	

Test Mode	Modulation	Channel/ Frequency (MHz)	Bandwidth (MHz)	RB Size	RB Offset	Test Result
LTE Band 4 (High Channel)	QPSK	CH20393 / 1754.3MHz	1.4	1	2	Pass
		CH20385 / 1753.5MHz	3	1	7	Pass
		CH20375 / 1752.5MHz	5	1	12	Pass
		CH20350 / 1750MHz	10	1	25	Pass
		CH20325 / 1747.5MHz	15	1	36	Pass
		CH20300 / 1745MHz	20	1	49	Pass
	16QAM	CH20393 / 1754.3MHz	1.4	1	2	Pass
		CH20385 / 1753.5MHz	3	1	7	Pass
		CH20375 / 1752.5MHz	5	1	12	Pass
		CH20350 / 1750MHz	10	1	25	Pass
		CH20325 / 1747.5MHz	15	1	36	Pass
		CH20300 / 1745MHz	20	1	49	Pass







LTE Band 4 16QAM 10MHz CH20000 1RB#25_30MHz-1GHz	LTE Band 4 16QAM 10MHz CH20000 1RB#25_1GHz-20GHz
<p>Agilent Spectrum Analyzer - Swept SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 22 dB Ref 32.00 dBm Mkr1 818.97 MHz -39.567 dBm 10 dB/div Log 22.0 12.0 2.0 -8.0 -18.0 -28.0 -38.0 -48.0 -58.0 Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 2.133 ms (32001 pts) Stop 1.0000 GHz</p>	<p>Agilent Spectrum Analyzer - Swept SA Start Freq 1.0000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 15 dB Ref 35.00 dBm Mkr1 3.7900 GHz -31.737 dBm 10 dB/div Log 25.0 15.0 5.0 -5.0 -15.0 -25.0 -35.0 -45.0 -55.0 Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 32.00 ms (32001 pts) Stop 20.000 GHz</p>
LTE Band 4 16QAM 15MHz CH20025 1RB#36_30MHz-1GHz	LTE Band 4 16QAM 15MHz CH20025 1RB#36_1GHz-20GHz
<p>Agilent Spectrum Analyzer - Swept SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: 94/100 Ref Offset 22 dB Ref 32.00 dBm Mkr1 941.86 MHz -39.676 dBm 10 dB/div Log 22.0 12.0 2.0 -8.0 -18.0 -28.0 -38.0 -48.0 -58.0 Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 2.133 ms (32001 pts) Stop 1.0000 GHz</p>	<p>Agilent Spectrum Analyzer - Swept SA Start Freq 1.0000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 15 dB Ref 35.00 dBm Mkr1 3.1713 GHz -31.701 dBm 10 dB/div Log 25.0 15.0 5.0 -5.0 -15.0 -25.0 -35.0 -45.0 -55.0 Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 32.00 ms (32001 pts) Stop 20.000 GHz</p>
LTE Band 4 16QAM 20MHz CH20050 1RB#49_30MHz-1GHz	LTE Band 4 16QAM 20MHz CH20050 1RB#49_1GHz-20GHz
<p>Agilent Spectrum Analyzer - Swept SA Start Freq 30.000000 MHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 22 dB Ref 32.00 dBm Mkr1 947.50 MHz -39.152 dBm 10 dB/div Log 22.0 12.0 2.0 -8.0 -18.0 -28.0 -38.0 -48.0 -58.0 Start 30.0 MHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 2.133 ms (32001 pts) Stop 1.0000 GHz</p>	<p>Agilent Spectrum Analyzer - Swept SA Start Freq 1.0000000000 GHz PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100 Ref Offset 16 dB Ref 35.00 dBm Mkr1 2.5954 GHz -31.632 dBm 10 dB/div Log 25.0 15.0 5.0 -5.0 -15.0 -25.0 -35.0 -45.0 -55.0 Start 1.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Sweep 32.00 ms (32001 pts) Stop 20.000 GHz</p>

