



Test Report No.: RF2011WSZ0069



# TEST REPORT

Applicant	FKA Distributing Co., LLC
Address	3000 N. Pontiac Trail, Commerce Township, Michigan, 48390, United States

Manufacturer or Supplier	Shenzhen Xsound Innovation Technologies Co., Ltd
Address	No.207-211, Building A1, Fuhai Xinxigang, Qiaotou Community, Fuhai Street, Bao'an district, Shenzhen, 518103, China
Product	Jam Live Loud
Brand Name	N/A
Model	HX-EP410A
Additional Model & Model Difference	N/A
Date of tests	Nov. 13, 2020~ Dec. 03, 2020

the tests have been carried out according to the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Tested by Evans He Project Engineer / EMC Department	Approved by David Huang Assistant Manager / EMC Department
	Date: Dec. 03, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



# TABLE OF CONTENTS

**RELEASE CONTROL RECORD ..... 4**

**1 SUMMARY OF TEST RESULTS..... 5**

2 MEASUREMENT UNCERTAINTY..... 5

3 GENERAL INFORMATION..... 6

3.1 GENERAL DESCRIPTION OF EUT ..... 6

3.2 DESCRIPTION OF TEST MODES ..... 7

    3.2.1. CONFIGURATION OF SYSTEM UNDER TEST ..... 8

    3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... 8

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS ..... 10

3.4 DESCRIPTION OF SUPPORT UNITS ..... 10

4 TEST TYPES AND RESULTS .....11

4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT.....11

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT .....11

4.2.2 TEST INSTRUMENTS ..... 12

4.2.3 TEST PROCEDURES..... 13

4.2.4 DEVIATION FROM TEST STANDARD ..... 14

4.2.5 TEST SETUP ..... 14

4.2.6 EUT OPERATING CONDITIONS ..... 15

4.2.7 TEST RESULTS ..... 16

4.3 NUMBER OF HOPPING FREQUENCY USED ..... 24

4.3.1 LIMIT OF HOPPING FREQUENCY USED..... 24

4.3.2 TEST SETUP ..... 24

4.3.3 TEST INSTRUMENTS ..... 24

4.3.4 TEST PROCEDURES..... 25

4.3.5 DEVIATION FROM TEST STANDARD ..... 25

4.3.6 TEST RESULTS ..... 25

4.4 DWELL TIME ON EACH CHANNEL..... 27

4.4.1 LIMIT OF DWELL TIME USED ..... 27

4.4.2 TEST SETUP ..... 27

4.4.3 TEST INSTRUMENTS ..... 27

4.4.4 TEST PROCEDURES..... 27

4.4.5 DEVIATION FROM TEST STANDARD ..... 28

4.4.6 TEST RESULTS ..... 28



4.5 CHANNEL BANDWIDTH ..... 31

4.5.1 LIMITS OF CHANNEL BANDWIDTH ..... 31

4.5.2 TEST SETUP ..... 31

4.5.3 TEST INSTRUMENTS ..... 31

4.5.4 TEST PROCEDURE ..... 31

4.5.5 DEVIATION FROM TEST STANDARD ..... 31

4.5.6 EUT OPERATING CONDITION ..... 31

4.5.7 TEST RESULTS ..... 32

4.6 HOPPING CHANNEL SEPARATION..... 36

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION ..... 36

4.6.2 TEST SETUP ..... 36

4.6.3 TEST INSTRUMENTS ..... 36

4.6.4 TEST PROCEDURES ..... 36

4.6.5 DEVIATION FROM TEST STANDARD ..... 36

4.6.6 TEST RESULTS ..... 37

4.7 CONDUCTED OUTPUT POWER..... 41

4.7.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT ..... 41

4.7.2 TEST SETUP ..... 41

4.7.3 TEST INSTRUMENTS ..... 41

4.7.4 TEST PROCEDURES ..... 41

4.7.5 DEVIATION FROM TEST STANDARD ..... 41

4.7.6 EUT OPERATING CONDITION ..... 41

4.7.7 TEST RESULTS ..... 42

4.8 OUT OF BAND EMISSION MEASUREMENT ..... 43

4.8.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT ..... 43

4.8.2 TEST INSTRUMENTS ..... 43

4.8.3 TEST PROCEDURE ..... 43

4.8.4 DEVIATION FROM TEST STANDARD ..... 43

4.8.5 EUT OPERATING CONDITION ..... 43

4.8.6 TEST RESULTS ..... 43

**5 PHOTOGRAPHS OF THE TEST CONFIGURATION ..... 50**

**6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING  
CHANGES TO THE EUT BY THE LAB..... 51**



Test Report No.: RF2011WSZ0069

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF2011WSZ0069	Original release	Dec. 03, 2020



# 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	N/A	Powered from battery
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output Power	PASS	Meet the requirement of limit.
15.247(d)& 15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

# 2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.70dB
Radiated emissions	9KHz ~ 30MHz	2.16dB
	30MHz ~ 1GMHz	3.74dB
	1GHz ~ 18GHz	4.66dB
	18GHz ~ 40GHz	4.67dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Jam Live Loud
<b>MODEL NO.</b>	HX-EP410A
<b>ADDITIONAL MODEL</b>	N/A
<b>FCC ID</b>	TG3-HXEP410A
<b>POWER SUPPLY</b>	Earphone: DC 3.7V from battery or DC 5V from charging case Charging case: DC 5V from USB
<b>MODULATION TECHNOLOGY</b>	FHSS
<b>MODULATION TYPE</b>	GFSK, $\pi/4$ -DQPSK, 8 DPSK
<b>OPERATING FREQUENCY</b>	2402MHz~2480MHz
<b>NUMBER OF CHANNEL</b>	79
<b>PEAK OUTPUT POWER</b>	6.138mW (Max. Measured)
<b>ANTENNA TYPE</b>	Ceramic Antenna, 0.5dBi Gain
<b>I/O PORTS</b>	Refer to user's manual
<b>CABLE SUPPLIED</b>	USB Line: Unshielded, Detachable 30cm

**NOTE:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 2011WSZ0069) for detailed product photo.
4. When the EUT charging that wireless function can't working, the charging mode was tested in the FCC Part 15B(sDOC) report.(report no.: FS2011WSZ0069)



### 3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned on X axis for radiated emission.

Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	-	√	DC 3.7V from battery

Where RE<1G: Radiated Emission below 1GHz  
PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz  
APCM: Antenna Port Conducted Measurement

**RADIATED EMISSION TEST (BELOW 1 GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

**RADIATED EMISSION TEST (ABOVE 1 GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5





**POWER LINE CONDUCTED EMISSION TEST:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	Hopping	FHSS	GFSK	DH5

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	25deg. C, 55%RH	DC 3.7V from Battery	Aaron Liang
RE≥1G	25deg. C, 55%RH	DC 3.7V from Battery	Aaron Liang
PLC	N/A	N/A	N/A
APCM	25deg. C, 60%RH	DC 3.7V from Battery	Aaron Liang



**BUREAU  
VERITAS**

Test Report No.: RF2011WSZ0069

### **3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. Section 15.247**

**KDB 558074 D01 15.247 Meas Guidance v05r02**

**ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

### **3.4 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit without any other necessary accessory or support units.



## 4 TEST TYPES AND RESULTS

### 4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



### 4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESL6	1300.5001K06 -100262-eQ	Mar. 24, 20	Mar. 24, 21
Bilog Antenna	Sunol Sciences	JB6	A110712	Jul. 21, 20	Jul. 21, 21
Active Antenna	COM-POWER	AL-130	121031	Jun. 30, 20	Jun. 30, 21
Signal Amplifier	HP	8447E	443008	Mar. 24, 20	Mar. 24, 21
Signal and Spectrum Analyzer	R&S	FSV40	101094	Mar. 19, 20	Mar. 19, 21
MXA signal analyzer	Agilent	N9020A	MY49100060	Mar. 24, 20	Mar. 24, 21
Horn Antenna	COM-POWER	AH-118	71259	Apr. 17, 20	Apr. 17, 21
Horn Antenna	COM-POWER	AH-118	71283	Jul. 21, 20	Jul. 21, 21
SHF-EHF Horn	Schwarzbeck	BBHA9170	BBHA9170147	May 10, 20	May 10, 21
SHF-EHF Horn	Schwarzbeck	BBHA9170	BBHA9170242	May 10, 20	May 10, 21
AMPLIFIER	EM Electornic Corporation	EM01G26G	60613	Mar. 24, 20	Mar. 24, 21
Pre-amplifier	Rohde&Schwarz	SCU40	100437	Oct. 17, 20	Oct. 16, 21
3m Semi-anechoic Chamber	SAEMC	9m*6m*6m	N/A	Oct. 18,18	Oct. 17, 21
Test Software	EZ-EMC	ICP-03A1	N/A	N/A	N/A

**NOTE:**

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 months (except 3m Semi-anechoic Chamber). And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 535293.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

#### **NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.




#### 4.2.4 DEVIATION FROM TEST STANDARD


No deviation.

#### 4.2.5 TEST SETUP

##### Below 30MHz test setup




##### Below 1GHz test setup



**Note:** For the actual test configuration, please refer to the attached file (Test Setup Photo).

## Above 1GHz test setup



**Note:** For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



### 4.2.7 TEST RESULTS

#### BELOW 1GHz WORST-CASE DATA:


#### GFSK

<b>CHANNEL</b>	Channel 39	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m										
No.	Frequency (MHz)	Reading (dBuV/m)	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)
1	33.2112	27.24	18.95	21.62	0.64	25.21	40.00	-14.79	100	72
2	82.3589	28.56	7.35	21.61	0.93	15.23	40.00	-24.77	200	288
3	126.3286	27.47	13.45	21.66	1.13	20.39	43.50	-23.11	100	105
4	198.5880	27.28	12.63	21.80	1.39	19.50	43.50	-24.00	200	110
5	489.0269	27.79	17.57	22.02	2.10	25.44	46.00	-20.56	100	131
6	790.6188	29.66	21.27	21.72	2.67	31.88	46.00	-14.12	100	349

#### REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value







**BUREAU  
VERITAS**


Test Report No.: RF2011WSZ0069

<b>CHANNEL</b>	Channel 39	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m										
No.	Frequency (MHz)	Reading (dBuV/m)	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)
1	36.1272	28.69	16.91	21.62	0.66	24.64	40.00	-15.36	100	290
2	80.6442	28.92	7.39	21.61	0.92	15.62	40.00	-24.38	200	276
3	146.3735	28.06	12.73	21.70	1.20	20.29	43.50	-23.21	100	83
4	329.0390	27.53	14.06	21.99	1.80	21.40	46.00	-24.60	100	25
5	607.7867	28.54	19.02	22.03	2.32	27.85	46.00	-18.15	200	118
6	975.7529	28.48	22.80	21.41	3.02	32.89	54.00	-21.11	100	140

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



Bureau Veritas (Shenzhen)  
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology  
Park, South Side of Zhoushi Road, Bao'an District,  
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800  
Email: [customerservice.sz@bureauveritas.com](mailto:customerservice.sz@bureauveritas.com)



ABOVE 1GHZ DATA

BT\_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2389.32	52.32 PK	74	-21.68	201	104	63.7	-11.38
2	2389.32	29.82 AV	54	-24.18	201	104	41.2	-11.38
3	*2402	95.11 PK			121	53	106.49	-11.38
4	*2402	72.61 AV			121	53	83.99	-11.38
5	4804	66.26 PK	74	-7.74	218	46	72.33	-6.07
6	4804	43.76 AV	54	-10.24	218	46	49.83	-6.07
7	7206	54.18 PK	74	-19.82	174	123	53.89	0.29
8	7206	31.68 AV	54	-22.32	174	123	31.39	0.29

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2389.8	52.52 PK	74	-21.48	231	170	63.9	-11.38
2	2389.8	30.02 AV	54	-23.98	231	170	41.4	-11.38
3	*2402	91.66 PK			145	279	103.04	-11.38
4	*2402	69.16 AV			145	279	80.54	-11.38
5	4804	64.2 PK	74	-9.8	232	225	70.27	-6.07
6	4804	41.7 AV	54	-12.3	232	225	47.77	-6.07
7	7206	55.04 PK	74	-18.96	138	264	54.75	0.29
8	7206	32.54 AV	54	-21.46	138	264	32.25	0.29

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441	95.64 PK			159	111	107.02	-11.38
2	*2441	73.14 AV			159	111	84.52	-11.38
3	4882	62.53 PK	74	-11.47	236	110	68.6	-6.07
4	4882	40.03 AV	54	-13.97	236	110	46.1	-6.07
5	7323	54.43 PK	74	-19.57	139	72	54.14	0.29
6	7323	31.93 AV	54	-22.07	139	72	31.64	0.29
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441	95.44 PK			184	58	106.82	-11.38
2	*2441	72.94 AV			184	58	84.32	-11.38
3	4882	60.84 PK	74	-13.16	203	206	66.91	-6.07
4	4882	38.34 AV	54	-15.66	203	206	44.41	-6.07
5	7323	56.26 PK	74	-17.74	108	355	55.97	0.29
6	7323	33.76 AV	54	-20.24	108	355	33.47	0.29

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2483.5	60.92 PK	74	-13.08	241	162	72.3	-11.38
2	2483.5	38.42 AV	54	-15.58	241	162	49.8	-11.38
3	*2480	98.45 PK			140	4	109.83	-11.38
4	*2480	75.95 AV			140	4	87.33	-11.38
5	4960	62.77 PK	74	-11.23	217	189	68.84	-6.07
6	4960	40.27 AV	54	-13.73	217	189	46.34	-6.07
7	7440	54.78 PK	74	-19.22	218	79	54.49	0.29
8	7440	32.28 AV	54	-21.72	218	79	31.99	0.29
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2483.5	58.94 PK	74	-15.06	215	14	70.32	-11.38
2	2483.5	36.44 AV	54	-17.56	215	14	47.82	-11.38
3	*2480	96.88 PK			139	182	108.26	-11.38
4	*2480	74.38 AV			139	182	85.76	-11.38
5	4960	62.33 PK	74	-11.67	134	223	68.4	-6.07
6	4960	39.83 AV	54	-14.17	134	223	45.9	-6.07
7	7440	53.98 PK	74	-20.02	117	177	53.69	0.29
8	7440	31.48 AV	54	-22.52	117	177	31.19	0.29

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



BT\_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2319.02	52.16 PK	74	-21.84	246	333	63.54	-11.38
2	2319.02	29.66 AV	54	-24.34	246	333	41.04	-11.38
3	*2402	94.55 PK			155	57	105.93	-11.38
4	*2402	72.05 AV			155	57	83.43	-11.38
5	4804	64.32 PK	74	-9.68	246	250	70.39	-6.07
6	4804	41.82 AV	54	-12.18	246	250	47.89	-6.07
7	7206	54.27 PK	74	-19.73	129	120	53.98	0.29
8	7206	31.77 AV	54	-22.23	129	120	31.48	0.29

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2376.02	51.98 PK	74	-22.02	246	208	63.36	-11.38
2	2376.02	29.48 AV	54	-24.52	246	208	40.86	-11.38
3	*2402	90.47 PK			129	92	101.85	-11.38
4	*2402	67.97 AV			129	92	79.35	-11.38
5	4804	62.19 PK	74	-11.81	242	174	68.26	-6.07
6	4804	39.69 AV	54	-14.31	242	174	45.76	-6.07
7	7206	53.84 PK	74	-20.16	157	314	53.55	0.29
8	7206	31.34 AV	54	-22.66	157	314	31.05	0.29

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441	94.4 PK			174	92	105.78	-11.38
2	*2441	71.9 AV			174	92	83.28	-11.38
3	4882	61.9 PK	74	-12.1	193	174	67.97	-6.07
4	4882	39.4 AV	54	-14.6	193	174	45.47	-6.07
5	7323	54.42 PK	74	-19.58	128	325	54.13	0.29
6	7323	31.92 AV	54	-22.08	128	325	31.63	0.29
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441	93.33 PK			139	245	104.71	-11.38
2	*2441	70.83 AV			139	245	82.21	-11.38
3	4882	60.54 PK	74	-13.46	237	108	66.61	-6.07
4	4882	38.04 AV	54	-15.96	237	108	44.11	-6.07
5	7323	54.42 PK	74	-19.58	178	128	54.13	0.29
6	7323	31.92 AV	54	-22.08	178	128	31.63	0.29

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2483.5	60.45 PK	74	-13.55	235	99	71.83	-11.38
2	2483.5	37.95 AV	54	-16.05	235	99	49.33	-11.38
3	*2480	97.49 PK			132	215	108.87	-11.38
4	*2480	74.99 AV			132	215	86.37	-11.38
5	4960	62.03 PK	74	-11.97	167	245	68.1	-6.07
6	4960	39.53 AV	54	-14.47	167	245	45.6	-6.07
7	7440	54.15 PK	74	-19.85	141	313	53.86	0.29
8	7440	31.65 AV	54	-22.35	141	313	31.36	0.29
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2483.5	57.38 PK	74	-16.62	226	278	68.76	-11.38
2	2483.5	34.88 AV	54	-19.12	226	278	46.26	-11.38
3	*2480	95.95 PK			224	183	107.33	-11.38
4	*2480	73.45 AV			224	183	84.83	-11.38
5	4960	58.94 PK	74	-15.06	117	41	65.01	-6.07
6	4960	36.44 AV	54	-17.56	117	41	42.51	-6.07
7	7440	54.59 PK	74	-19.41	180	244	54.3	0.29
8	7440	32.09 AV	54	-21.91	180	244	31.8	0.29

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.




### 4.3 NUMBER OF HOPPING FREQUENCY USED

#### 4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

#### 4.3.2 TEST SETUP



#### 4.3.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Wireless Connectivity Tester	R&S	CMW270	1201.0002K75	Dec. 28, 19	Dec. 27, 20
MXA VEXTOR SIGNAL	Agilent	n5182a	MY50140530	Mar. 24, 20	Mar. 24, 21
MXA signal analyzer	Agilent	n9020a	MY49100060	Mar. 24, 20	Mar. 24, 21
RF Control Unit	Tonscend	JS0806-2	188060112	Mar. 24, 20	Mar. 24, 21
Signal Generation	Agilent	E4421B	US40051152	Dec. 18, 19	Dec. 17, 20
DC Power Supply	Agilent	E3640A	MY40004013	Mar. 30, 20	Mar. 30, 21
Programmable Temperature & Humidity Chamber	Hongjin	HYC-TH-225 DH	DG-180746	Mar. 24, 20	Mar. 24, 21
Test System	Tonscend	JS 1120-3	N/A	N/A	N/A
Power Splitter	Weinschel	1580-1	TL177	Mar. 27, 20	Mar. 27, 21

**NOTE:**

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



#### 4.3.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.

#### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.3.6 TEST RESULTS


There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.




BUREAU VERITAS

Test Report No.: RF2011WSZ0069

GFSK



8DPSK



Bureau Veritas (Shenzhen)  
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology  
Park, South Side of Zhoushi Road, Bao'an District,  
Shenzhen Guangdong, 518108, China.


Tel: +86-755-26014629 Ext.800  
Email: [customerservice.sz@bureauveritas.com](mailto:customerservice.sz@bureauveritas.com)

## 4.4 DWELL TIME ON EACH CHANNEL

### 4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 4.4.2 TEST SETUP



### 4.4.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

### 4.4.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.



#### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.4.6 TEST RESULTS

##### GFSK


Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	3.16	32	320	0.374	119.68	400	PASS
DH3	79	31.6	3.16	16	160	1.622	259.52	400	PASS
DH5	79	31.6	3.16	11	110	2.87	315.7	400	PASS

##### 8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
3DH1	79	31.6	3.16	32	320	0.382	122.24	400	PASS
3DH3	79	31.6	3.16	16	160	1.631	260.96	400	PASS
3DH5	79	31.6	3.16	10	100	2.883	288.3	400	PASS


**NOTE:** Test plots of the transmitting time slot are shown on next page.

GFSK





### 8DPSK



Bureau Veritas (Shenzhen)  
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology Park, South Side of Zhoushi Road, Bao'an District, Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800  
Email: [customerservice.sz@bureauveritas.com](mailto:customerservice.sz@bureauveritas.com)




## 4.5 CHANNEL BANDWIDTH

### 4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

### 4.5.2 TEST SETUP



### 4.5.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

### 4.5.4 TEST PROCEDURE

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.

### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




### 4.5.7 TEST RESULTS

#### GFSK


CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.936
39	2441	0.894
78	2480	0.957

#### CH 0






CH 39



CH 78





**BUREAU  
VERITAS**

Test Report No.: RF2011WSZ0069

**8DPSK**

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.293
39	2441	1.299
78	2480	1.296

**CH 0**





BUREAU VERITAS

Test Report No.: RF2011WSZ0069

CH 39



CH 78



Bureau Veritas (Shenzhen)  
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology  
Park, South Side of Zhoushi Road, Bao'an District,  
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800  
Email: [customerservice.sz@bureauveritas.com](mailto:customerservice.sz@bureauveritas.com)




## 4.6 HOPPING CHANNEL SEPARATION

### 4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

### 4.6.2 TEST SETUP



### 4.6.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

### 4.6.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

### 4.6.5 DEVIATION FROM TEST STANDARD

No deviation.



**BUREAU  
VERITAS**

Test Report No.: RF2011WSZ0069

### 4.6.6 TEST RESULTS


#### GFSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.002	0.936	0.936	PASS
39	2441	1.002	0.894	0.894	PASS
78	2480	1.002	0.957	0.957	PASS

#### CH 0



CH 39



CH 78





8DPSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.002	1.293	0.86	PASS
39	2441	1.002	1.299	0.87	PASS
78	2480	1.002	1.296	0.86	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39



CH 78








## 4.7 CONDUCTED OUTPUT POWER

### 4.7.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

### 4.7.2 TEST SETUP



### 4.7.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

### 4.7.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A peak power meter was used to read the response of the peak power sensor. Record the peak power level.

### 4.7.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.7.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



### 4.7.7 TEST RESULTS

#### MAXIMUM PEAK OUTPUT POWER

##### GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	7.63	5.794	1000	PASS
39	2441	7.83	6.067	1000	PASS
78	2480	7.6	5.754	1000	PASS

##### 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	7.73	5.929	125	PASS
39	2441	7.88	<b>6.138</b>	125	PASS
78	2480	7.66	5.834	125	PASS

#### AVERAGE OUTPUT POWER(FOR REFERENCE)

##### GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	<b>5.21</b>	3.32
39	2441	5.12	3.251
78	2480	4.98	3.148

##### 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	3.92	2.466
39	2441	4.11	2.576
78	2480	3.75	2.371

## 4.8 OUT OF BAND EMISSION MEASUREMENT

### 4.8.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

### 4.8.2 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

### 4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

### 4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

### 4.8.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

### 4.8.6 TEST RESULTS


The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.



BUREAU VERITAS

Test Report No.: RF2011WSZ0069

GFSK



Bureau Veritas (Shenzhen)  
Consumer Products Services Co., Ltd.


Zone A, Floor 1, Building 2, Wan Ye Long Technology  
Park, South Side of Zhoushi Road, Bao'an District,  
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800  
Email: [customerservice.sz@bureauveritas.com](mailto:customerservice.sz@bureauveritas.com)







BUREAU VERITAS

Test Report No.: RF2011WSZ0069



CH 78



Bureau Veritas (Shenzhen)  
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology  
Park, South Side of Zhoushi Road, Bao'an District,  
Shenzhen Guangdong, 518108, China.


Tel: +86-755-26014629 Ext.800  
Email: [customerservice.sz@bureauveritas.com](mailto:customerservice.sz@bureauveritas.com)



BUREAU VERITAS

Test Report No.: RF2011WSZ0069

8DPSK



Bureau Veritas (Shenzhen)  
Consumer Products Services Co., Ltd.


Zone A, Floor 1, Building 2, Wan Ye Long Technology  
Park, South Side of Zhoushi Road, Bao'an District,  
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800  
Email: [customerservice.sz@bureauveritas.com](mailto:customerservice.sz@bureauveritas.com)






BUREAU VERITAS

Test Report No.: RF2011WSZ0069



CH 78



Bureau Veritas (Shenzhen)  
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology  
Park, South Side of Zhoushi Road, Bao'an District,  
Shenzhen Guangdong, 518108, China.


Tel: +86-755-26014629 Ext.800  
Email: [customerservice.sz@bureauveritas.com](mailto:customerservice.sz@bureauveritas.com)



BUREAU VERITAS

Test Report No.: RF2011WSZ0069

GFSK



Bureau Veritas (Shenzhen)  
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology  
Park, South Side of Zhoushi Road, Bao'an District,  
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800  
Email: [customerservice.sz@bureauveritas.com](mailto:customerservice.sz@bureauveritas.com)






BUREAU VERITAS

Test Report No.: RF2011WSZ0069

8DPSK



Bureau Veritas (Shenzhen)  
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology  
Park, South Side of Zhoushi Road, Bao'an District,  
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800  
Email: [customerservice.sz@bureauveritas.com](mailto:customerservice.sz@bureauveritas.com)



**BUREAU  
VERITAS**

**Test Report No.: RF2011WSZ0069**

## **5 PHOTOGRAPHS OF THE TEST CONFIGURATION**

Please refer to the attached file (Test Setup Photo).



**BUREAU  
VERITAS**

Test Report No.: RF2011WSZ0069

## **6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.

**---END---**