

Test Report - FCC Part 1.1310/ MPE
Applicant: Enernet Corporation

Approved for Release By:

Signature: Bruno Clavier

Name & Title: Bruno Clavier, General Manager

Date of Signature 12/20/2023

This test report shall not be reproduced except in full without the written and signed permission of Timco Engineering Inc. (IIA). This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.

Table of Contents

| | | |
|-------|--|---|
| 1. | APPLICANT INFORMATION..... | 3 |
| 2. | LOCATION OF TESTING | 3 |
| 2.1 | TEST LABORATORY..... | 3 |
| 2.2 | TESTING WAS PERFORMED, REVIEWED BY | 4 |
| 3. | TEST SAMPLE(S) (EUT/DUT)..... | 5 |
| 3.1 | DESCRIPTION OF THE EUT | 5 |
| 4. | TEST METHODS & APPLICABLE REGULATORY LIMITS..... | 6 |
| 4.1 | TEST METHODS/STANDARDS/GUIDANCE:..... | 6 |
| 4.1.1 | <i>FCC Limits for Maximum Permissible Exposure (MPE)</i> | 6 |
| 4.2 | EQUATIONS | 7 |
| 5. | RF EXPOSURE RESULTS | 8 |
| 6. | HISTORY OF TEST REPORT CHANGES..... | 9 |



13146 NW 86th Drive, Suite 400, Alachua, Florida 32615
(352) 472-5500 / testing@industrial-ia.com

1. Applicant Information

Applicant: Enernet Corporation
Address: 272 June Apple Road
Trace, TN 37691 United States

2. Location of Testing

2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at IIA's permanent laboratory located at 13146 NW 86th Drive, Suite 400, Alachua, Florida 32615.

FCC test firm # 578780
FCC Designation # US1070
FCC site registration is under A2LA certificate # 0955.01
ISED Canada test site registration # 2056A
EU Notified Body # 1177
For all designations see A2LA scope # 0955.01

2.2 Testing was performed, reviewed by

Dates of Testing: 10/25/2023

Signature:



Sr. EMC Engineer
EMC-003838-NE




Name & Title:

Tim Royer, EMC Engineer

Date of Signature

12/20/2023

Signature:



Name & Title:

Kristoffer Costa, EMC Technician

Date of Signature

12/20/2023

3. Test Sample(s) (EUT/DUT)

The test sample was received: 10/25/2023

3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

| Identification | |
|-------------------|------------------------------|
| FCC ID: | TGD17200 |
| Brief Description | Transceiver |
| Model(s) # | 17200 (Cable Antenna Unit B) |
| Firmware version | N/A |
| Software version | N/A |
| Serial Number | N/A |

| Technical Characteristics | |
|------------------------------|-------------------------|
| Frequency Range | 900 MHz |
| RF O/P Power (Max.) | 93.84 dBμV/m (-1.39dBm) |
| Duty Cycle | 100% |
| Antenna Type | Cable |
| Voltage Rating (AC or Batt.) | 110 VAC |

| Antenna Characteristics | | | |
|-------------------------|-----------------|-----------|--------------|
| Antenna | Frequency Range | Mode / BW | Antenna Gain |
| 1 | n/a | n/a | 0 dBi |

- Note: Information such as antenna gain, firmware/software numbers are provided by manufacturer and cannot be validated by the test lab.

4. Test methods & Applicable Regulatory Limits

4.1 Test methods/Standards/Guidance:

The following guidance FCC KDB 447498 D01 General RF Exposure Guidance v06 was used for RF exposure evaluation as per FCC Part 1.1310 and FCC Part 2.1091 and part 2.1093. Full test results are available in this report.

4.1.1 FCC Limits for Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging Time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| A Limits for Occupational/Controlled Exposure | | | | |
| 0.3-3.0 | 614 | 1.63 | *(100) | ≤6 |
| 3.0-30 | 1842/f | 4.89/f | *(900/f ²) | <6 |
| 30-300 | 61.4 | 0.163 | 1.0 | <6 |
| 300-1,500 | | | f/300 | <6 |
| 1,500-100,000 | | | 5 | <6 |
| B Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | <30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | <30 |
| 30-300 | 27.5 | 0.073 | 0.2 | <30 |
| 300-1,500 | | | f/1500 | <30 |
| 1,500-100,000 | | | 1.0 | <30 |

4.2 Equations

POWER DENSITY

$$E(V/m) = \text{SQRT} (30 * P * G) / d$$

$$Pd(W/m^2) = E^2 / 377$$

$$S = \text{EIRP} / (4 * \text{Pi} * D^2v)$$

Where:

S = Power density, in mW/cm²

EIRP = Equivalent Isotropic Radiated Power, in mW

D = Separation distance in cm

Power density is converted from units of mW/cm² to units of W/m² by multiplying by 10.

DISTANCE

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

Where:

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power, in mW

S = Power density in mW/cm²

SOURCE-BASED DUTY CYCLE (When applicable (for example, multi-slot mobile phone applications) A duty cycle factor may be applied.)

$$\text{Source-based time-average EIRP} = (DC / 100) * \text{EIRP}$$

Where:

DC = Duty Cycle in % as applicable.

EIRP = Equivalent Isotropic radiated Power, in mW

5. RF Exposure Results

MPE

| Frequency Band | Evaluation Distance (cm) | Max Power + Tolerance (dBm) | Antenna Gain (dBi) | Duty Cycle (%) | EIRP (W) | Power Density | Limit for Uncontrolled Exposure | Limit for Controlled Exposure | Distance Required to meet Uncontrolled Exposure Limit (cm) |
|-----------------|--------------------------|-----------------------------|--------------------|----------------|----------|----------------------|---------------------------------|-------------------------------|--|
| 902.875-920 MHz | 20 | -1.39 | 0.00 | 100% | 0.00 | 0 mW/cm ² | 0.61 mW/cm ² | 3.07 mW/cm ² | 20.00 |

RESULT: Pass at DISTANCE 20 cm

6. History of Test Report Changes

| Test Report # | Revision # | Description | Date of Issue |
|------------------------------|------------|---------------------|---------------|
| TR_10653-23_FCC 1.1310/ MPE_ | 1 | Initial release | 10/26/2023 |
| | 2 | Updated pages 3,5,8 | 3/19/2024 |
| | | | |



13146 NW 86th Drive, Suite 400, Alachua, Florida 32615
(352) 472-5500 / testing@industrial-ia.com

END OF TEST REPORT
