



FCC TEST REPORT (15.247)

REPORT NO.: RF940728H06

MODEL NO.: BSAP-1500

RECEIVED: July 28, 2005

TESTED: Aug. 3 to 26, 2005

ISSUED: Aug. 31, 2005

APPLICANT: Bluesocket, Inc.

ADDRESS: 10 North Avenue Burlington, MA 01803

ISSUED BY: Advance Data Technology Corporation

TEST LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien, Taiwan, R.O.C.

This test report consists of 107 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



0536

ILAC MRA



No. 2177-01



Table of Contents

- 1. CERTIFICATION 6
- 2. SUMMARY OF TEST RESULTS 7
- 3. GENERAL INFORMATION 9
 - 3.1 GENERAL DESCRIPTION OF EUT 9
 - 3.2 DESCRIPTION OF TEST MODES 11
 - 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL: 12
 - 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 14
 - 3.4 DESCRIPTION OF SUPPORT UNITS..... 15
 - 3.5 CONFIGURATION OF SYSTEM UNDER TEST 16
- 4. TEST TYPES AND RESULTS (802.11b & g, 2412~2462MHz Band) 19
 - 4.1 CONDUCTED EMISSION MEASUREMENT 19
 - 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 19
 - 4.1.2 TEST INSTRUMENTS..... 19
 - 4.1.3 TEST PROCEDURES 20
 - 4.1.4 DEVIATION FROM TEST STANDARD 20
 - 4.1.5 TEST SETUP 21
 - 4.1.6 EUT OPERATING CONDITIONS 21
 - 4.1.7 TEST RESULTS 22
 - 4.2 RADIATED EMISSION MEASUREMENT 26
 - 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 26
 - 4.2.2 TEST INSTRUMENTS..... 27
 - 4.2.3 TEST PROCEDURES 28
 - 4.2.4 DEVIATION FROM TEST STANDARD 28
 - 4.2.5 TEST SETUP 29
 - 4.2.6 EUT OPERATING CONDITIONS 29
 - 4.2.7 TEST RESULTS 30
 - 4.3 6DB BANDWIDTH MEASUREMENT 38
 - 4.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT 38
 - 4.3.2 TEST INSTRUMENTS..... 38
 - 4.3.3 TEST PROCEDURE..... 39
 - 4.3.4 DEVIATION FROM TEST STANDARD 39



4.3.5 TEST SETUP 39

4.3.6 EUT OPERATING CONDITIONS 39

4.3.7 TEST RESULTS 40

4.4 MAXIMUM PEAK OUTPUT POWER..... 46

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT 46

4.4.2 INSTRUMENTS 46

4.4.3 TEST PROCEDURES 47

4.4.4 DEVIATION FROM TEST STANDARD 47

4.4.5 TEST SETUP 47

4.4.6 EUT OPERATING CONDITIONS 47

4.4.7 TEST RESULTS 48

4.5 POWER SPECTRAL DENSITY MEASUREMENT..... 50

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT..... 50

4.5.2 TEST INSTRUMENTS..... 50

4.5.3 TEST PROCEDURE..... 51

4.5.4 DEVIATION FROM TEST STANDARD 51

4.5.5 TEST SETUP 51

4.5.6 EUT OPERATING CONDITION..... 51

4.5.7 TEST RESULTS 52

4.6 BAND EDGES MEASUREMENT..... 58

4.6.1 LIMITS OF BAND EDGES MEASUREMENT 58

4.6.2 TEST INSTRUMENTS..... 58

4.6.3 TEST PROCEDURE..... 58

4.6.4 EUT OPERATING CONDITION..... 58

4.6.5 TEST RESULTS – DSSS..... 59

4.6.6 TEST RESULTS – OFDM..... 62

4.7 ANTENNA REQUIREMENT 67

4.7.1 STANDARD APPLICABLE..... 67

4.7.2 ANTENNA CONNECTED CONSTRUCTION..... 67

5. TEST TYPES AND RESULTS (802.11a, 5725~5850MHz Band) 68

5.1 CONDUCTED EMISSION MEASUREMENT 68

5.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 68

5.1.2 TEST INSTRUMENTS..... 68

5.1.3 TEST PROCEDURES 69



5.1.4	DEVIATION FROM TEST STANDARD	69
5.1.5	TEST SETUP	70
5.1.6	EUT OPERATING CONDITIONS	70
5.1.7	TEST RESULTS	71
5.2	RADIATED EMISSION MEASUREMENT	75
5.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	75
5.2.2	TEST INSTRUMENTS.....	76
5.2.3	TEST PROCEDURES	77
5.2.4	DEVIATION FROM TEST STANDARD	77
5.2.5	TEST SETUP	78
5.2.6	EUT OPERATING CONDITIONS	78
5.2.7	TEST RESULTS	79
5.3	6DB BANDWIDTH MEASUREMENT	84
5.3.1	LIMITS OF 6DB BANDWIDTH MEASUREMENT	84
5.3.2	TEST INSTRUMENTS.....	84
5.3.3	TEST PROCEDURE.....	85
5.3.4	DEVIATION FROM TEST STANDARD	85
5.3.5	TEST SETUP	85
5.3.6	EUT OPERATING CONDITIONS	85
5.3.7	TEST RESULTS	86
5.4	MAXIMUM PEAK OUTPUT POWER.....	89
5.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	89
5.4.2	INSTRUMENTS	89
5.4.3	TEST PROCEDURES	90
5.4.4	DEVIATION FROM TEST STANDARD	90
5.4.5	TEST SETUP	90
5.4.6	EUT OPERATING CONDITIONS	90
5.4.7	TEST RESULTS	91
5.5	POWER SPECTRAL DENSITY MEASUREMENT	92
5.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT.....	92
5.5.2	TEST INSTRUMENTS.....	92
5.5.3	TEST PROCEDURE.....	93
5.5.4	DEVIATION FROM TEST STANDARD	93
5.5.5	TEST SETUP	93



- 5.5.6 EUT OPERATING CONDITION..... 93
- 5.5.7 TEST RESULTS 94
- 5.6 BAND EDGES MEASUREMENT..... 97
- 5.6.1 LIMITS OF BAND EDGES MEASUREMENT 97
- 5.6.2 TEST INSTRUMENTS..... 97
- 5.6.3 TEST PROCEDURE..... 98
- 5.6.4 DEVIATION FROM TEST STANDARD 98
- 5.6.5 EUT OPERATING CONDITION..... 98
- 5.6.6 TEST RESULTS 99
- 5.7 ANTENNA REQUIREMENT 102
- 5.7.1 STANDARD APPLICABLE..... 102
- 5.7.2 ANTENNA CONNECTED CONSTRUCTION..... 102
- 6. PHOTOGRAPHS OF THE TEST CONFIGURATION..... 103
- 7. INFORMATION ON THE TESTING LABORATORIES 107



1. CERTIFICATION

PRODUCT: Access point
BRAND NAME: Bluesocket
MODEL NO.: BSAP-1500
TEST SAMPLE: ENGINEERING SAMPLE
TESTED: Aug. 3 to 26, 2005
APPLICANT: Bluesocket, Inc.
STANDARDS: FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-2003

The above equipment (Model: BSAP-1500) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Carol Liao , **DATE:** Aug. 31, 2005
(Carol Liao)

TECHNICAL ACCEPTANCE : Hank Chung , **DATE:** Aug. 31, 2005
Responsible for RF (Hank Chung)

APPROVED BY : May Chen , **DATE:** Aug. 31, 2005
(May Chen, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

For 802.11b & g, 2412~2462MHz Band

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.247)			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -13.04dB at 0.271MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -0.20dB at 2483.50MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

For 802.11a, 5725~5850MHz Band

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.247)			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -1.04dB at 1.205MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.80dB at 11570.0MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

NOTE:

1. The EUT was operating in 2.412 ~ 2.462GHz, 5.150 ~ 5.350GHz and 5.725 ~ 5.850GHz frequencies band. This report was recorded the RF parameters including 2.412 ~ 2.462GHz and 5.725 ~ 5.850GHz. For the 5.150 ~ 5.350GHz RF parameters was recorded in another test report.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Access point
MODEL NO.	BSAP-1500
POWER SUPPLY	DC 48V from power adapter or POE (Power over Ethernet)
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b:11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps 802.11a: 54/48/36/24/18/12/9/6Mbps
FREQUENCY RANGE	802.11b & 802.11g: 2412 ~ 2462MHz 802.11a: 5.15 ~ 5.35GHz and 5.725 ~ 5.850GHz
NUMBER OF CHANNEL	802.11b & 802.11g: 11 802.11a: 13
CHANNEL SPACING	802.11b & 802.11g: 5MHz 802.11a: 20MHz for Normal mode
OUTPUT POWER	802.11b: 23.90 dBm 802.11g: 25.82 dBm 802.11a: 24.92 dBm
DATA CABLE	NA
ANTENNA TYPE	Dual Band Antenna Dipole antenna with 2.0dBi gain (for 2.4GHz) Dipole antenna with 4.0dBi gain (for 5.0GHz)
I/O PORTS	RS232 Port, POE port, DC power Port
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT operates in both the 5GHz and 2.4GHz Bands and compatibility with 802.11a and 802.11b, 802.11g technology.

2. The EUT was operated with the following power adapter or POE:

ADAPTER	
BRAND:	PHIHONG
MODEL:	PSA 18U-480C (A1)
INPUT:	AC 90~264V, 0.5A, 50~60Hz 1.8m/ shield/ without core
OUTPUT:	DC 48V, 0.38A , 1.5m/ nonshield/ with one core

POE (for test only)	
BRAND:	3Com
MODEL:	PW130
INPUT:	AC100-250V, 0.5A, 50/60Hz
OUTPUT:	DC 48V, 0.42A

3. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Operated in 2400 ~ 2483.5MHz band:

For 802.11b/g: Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

Operated in 5725 ~ 5850MHz band:

For 802.11a (5725 ~ 5850MHz band): Five channels are provided to this EUT.

Channel	Frequency
1	5745 MHz
2	5765 MHz
3	5785 MHz
4	5805 MHz
5	5825 MHz



3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
-	X	X	X	X	NA

Where PLC: Power Line Conducted Emission RE<1G RE: Radiated Emission below 1GHz
 RE≥1G: Radiated Emission above 1GHz APCM: Antenna Port Conducted Measurement

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6
802.11a	1 to 5	5	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6
802.11a	1 to 5	5	OFDM	BPSK	6

Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11a	1 to 5	1, 3, 5	OFDM	BPSK	6



Bandedge Measurement:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 11	DSSS	CCK	11
802.11g	1 to 11	1, 11	OFDM	BPSK	6
802.11a	1 to 5	1, 5	OFDM	BPSK	6

Antenna Port Conducted Measurement:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11a	1 to 5	1, 3, 5	OFDM	BPSK	6



3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an Access point. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP01L	TW-09c748- 12800-165-3171	FCC DoC

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA

NOTE: All power cords of the above support units are non shielded (1.8m).


3.5 CONFIGURATION OF SYSTEM UNDER TEST

With ADAPTER




- NOTE:** 1. Support unit 1 was kept in the control room during the test.
2. Please refer to the photos of test configuration in Item 5 also.

With POE (Conducted Emissions)



- NOTE:**
1. Support unit 1 was kept in the control room during the test.
 2. Please refer to the photos of test configuration in Item 5 also.

With POE (Radiated Emission)



NOTE: 1. Support unit 1 was kept in the control room during the test.
2. Please refer to the photos of test configuration in Item 5 also.

4. TEST TYPES AND RESULTS (802.11b & g, 2412~2462MHz Band)

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	847124/029	Dec. 07, 2005
ROHDE & SCHWARZ LISN (for EUT)	ESHS-Z5	848773/004	Nov. 08, 2005
KYORITSU LISN (for peripheral)	KNW-407	8/1395/12	Jul. 19, 2006
RF Cable (JETBAO)	RG233/U	Cable_CA_01	Jul. 19, 2006
Terminator(for KYORITSU)	50	3	Oct. 12, 2005
Software	Cond-V2e	NA	NA

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in ADT Shielded Room No. A.
3. The VCCI Con A Registration No. is C-817.
4. The measurement uncertainty is 2.53 dB, which is calculated as per the document CISPR 16-4




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table.
- b. Prepared another computer system to act as a communication partner and placed it outside of testing area.
- c. The communication partner run test program “Art V48 build16” to enable EUT under transmission/receiving condition continuously at specific channel frequency via UTP cable.




4.1.7 TEST RESULTS

Conducted Worst-Case Data

EUT	Access point	MODEL	BSAP-1500
TEST MODE	With Adapter	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.271	0.16	47.89	-	48.05	-	61.08
2	0.537	0.18	42.41	-	42.59	-	56.00	46.00	-13.41	-
3	1.076	0.20	33.25	-	33.45	-	56.00	46.00	-22.55	-
4	4.730	0.49	36.03	-	36.52	-	56.00	46.00	-19.48	-
5	6.465	0.57	37.35	-	37.92	-	60.00	50.00	-22.08	-
6	9.148	0.71	33.04	-	33.75	-	60.00	50.00	-26.25	-
7	27.160	1.48	35.64	-	37.12	-	60.00	50.00	-22.88	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






EUT	Access point	MODEL	BSAP-1500
TEST MODE	With Adapter	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.267	0.16	47.16	-	47.32	-	61.20	51.20	-13.89	-
2	0.541	0.18	42.33	-	42.51	-	56.00	46.00	-13.49	-
3	1.755	0.24	33.08	-	33.32	-	56.00	46.00	-22.68	-
4	4.727	0.47	35.10	-	35.57	-	56.00	46.00	-20.43	-
5	6.168	0.52	36.97	-	37.49	-	60.00	50.00	-22.51	-
6	24.898	1.28	33.93	-	35.21	-	60.00	50.00	-24.79	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






Conducted Worst-Case Data

EUT	Access point	MODEL	BSAP-1500
TEST MODE	With POE	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.408	0.17	37.50	-	37.67	-	57.69
2	0.478	0.17	35.40	-	35.57	-	56.37	46.37	-20.80	-
3	1.201	0.21	35.11	-	35.32	-	56.00	46.00	-20.68	-
4	2.517	0.30	28.57	-	28.87	-	56.00	46.00	-27.13	-
5	3.133	0.36	31.41	-	31.77	-	56.00	46.00	-24.23	-
6	13.480	0.92	41.86	-	42.78	-	60.00	50.00	-17.22	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






EUT	Access point	MODEL	BSAP-1500
TEST MODE	With POE	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.478	0.17	35.77	-	35.94	-	56.37
2	1.205	0.21	35.44	-	35.65	-	56.00	46.00	-20.35	-
3	2.552	0.31	30.92	-	31.23	-	56.00	46.00	-24.77	-
4	2.892	0.34	31.53	-	31.87	-	56.00	46.00	-24.13	-
5	3.637	0.41	27.58	-	27.99	-	56.00	46.00	-28.01	-
6	13.602	0.82	41.24	-	42.06	-	60.00	50.00	-17.94	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ADVANTEST Spectrum Analyzer	R3271A	85060311	July 07, 2006
HP Pre_Amplifier	8449B	3008A01922	Oct. 13, 2005
ROHDE & SCHWARZ Test Receiver	ESCS30	100287	Dec. 08, 2005
CHASE Broadband Antenna	VULB9168	138	Dec. 21, 2005
Schwarzbeck Horn_Antenna	BBHA9120	D124	Dec. 11, 2005
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 30, 2006
SCHWARZBECK Biconical Antenna	VHBA9123	459	Jun. 26, 2006
SCHWARZBECK Periodic Antenna	UPA6108	1148	Jun. 26, 2006
RF Switches (ARNITSU)	CS-201	1565157	NA
RF CABLE (Chaintek) 1GHz-20GHz	SF102	22054-2	Nov. 15. 2005
RF Cable(RICHTEC)	9913-30M	STCCAB-30M- 1GHz-021	Jul. 16, 2006
Software	ADT_Radiated_V 5.14	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
CHANCE MOST Turn Table	TT-100	0203	NA

- Note: 1. The calibration interval of the above test instruments is 12 months (36 months for Tunable Periodic Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in ADT Open Site No. C.
4. The FCC Site Registration No. is 656396.
5. The VCCI Site Registration No. is R-1626.
6. The CANADA Site Registration No. is IC 4824-3.
7. The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4.

Measurement	Value
Radiated emissions (30MHz-1GHz)	2.98 dB
Radiated emissions (1GHz ~18GHz)	2.21 dB
Radiated emissions (18GHz ~20GHz)	1.88 dB



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

Below 1GHz Worst-Case Data

EUT	Access point	MODEL	BSAP-1500
TEST MODE	With Adapter	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	250.00	22.10 QP	46.00	-23.90	1.41 H	355	8.80	13.30
2	300.00	22.50 QP	46.00	-23.50	1.00 H	2	6.20	16.30
3	375.00	22.00 QP	46.00	-24.00	2.16 H	3	4.40	17.60
4	500.00	24.70 QP	46.00	-21.30	2.10 H	204	3.80	20.90
5	792.00	36.60 QP	46.00	-9.40	2.14 H	306	10.00	26.60
6	890.99	39.90 QP	46.00	-6.10	1.08 H	275	12.10	27.80
7	924.00	34.80 QP	46.00	-11.20	1.00 H	276	6.50	28.40
8	989.99	31.70 QP	54.00	-22.30	2.10 H	51	2.80	28.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	42.90	31.00 QP	40.00	-9.00	1.01 V	226	16.80	14.20
2	500.00	32.80 QP	46.00	-13.20	1.01 V	226	11.90	20.90
3	792.00	34.00 QP	46.00	-12.00	1.33 V	1	7.40	26.60
4	858.00	35.00 QP	46.00	-11.00	1.32 V	128	7.50	27.50
5	891.00	39.90 QP	46.00	-6.10	1.19 V	108	12.10	27.80
6	924.00	38.60 QP	46.00	-7.40	1.13 V	355	10.20	28.40
7	958.00	34.20 QP	46.00	-11.80	1.70 V	276	5.30	28.90
8	990.00	34.90 QP	54.00	-19.10	1.84 V	94	6.00	28.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value



Below 1GHz Worst-Case Data

EUT	Access point	MODEL	BSAP-1500
TEST MODE	With POE	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	250.00	23.00 QP	46.00	-23.00	1.76 H	176	9.70	13.30
2	300.00	21.70 QP	46.00	-24.30	1.15 H	342	5.40	16.30
3	375.00	24.90 QP	46.00	-21.10	1.11 H	224	7.30	17.60
4	500.00	24.70 QP	46.00	-21.30	1.00 H	6	3.80	20.90
5	792.00	37.10 QP	46.00	-8.90	1.26 H	277	10.50	26.60
6	891.00	39.60 QP	46.00	-6.40	1.03 H	278	11.80	27.80
7	924.00	37.60 QP	46.00	-8.40	1.05 H	269	9.30	28.40
8	990.00	39.60 QP	54.00	-14.40	1.00 H	261	10.70	28.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	43.51	32.80 QP	40.00	-7.20	1.24 V	28	18.50	14.20
2	249.99	27.40 QP	46.00	-18.60	1.17 V	49	14.10	13.30
3	500.00	26.50 QP	46.00	-19.50	1.04 V	210	5.70	20.90
4	792.00	34.80 QP	46.00	-11.20	1.00 V	261	8.20	26.60
5	858.00	34.10 QP	46.00	-11.90	1.29 V	2	6.60	27.50
6	891.00	38.00 QP	46.00	-8.00	1.16 V	109	10.20	27.80
7	924.00	38.90 QP	46.00	-7.10	1.05 V	1	10.60	28.40
8	990.00	37.00 QP	54.00	-17.00	1.00 V	105	8.10	28.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value

**802.11b DSSS modulation**

EUT	Access point	MODEL	BSAP-1500
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Rex Hunag

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2387.00	52.40 PK	74.00	-21.60	1.23 H	294	19.60	32.80
1	2387.00	42.30 AV	54.00	-11.70	1.23 H	294	9.50	32.80
2	2390.00	49.90 PK	74.00	-24.10	1.23 H	294	16.20	33.70
2	2390.00	40.40 AV	54.00	-13.60	1.23 H	294	6.70	33.70
3	*2412.00	106.30 PK			1.23 H	294	76.50	29.80
3	*2412.00	98.60 AV			1.23 H	294	68.80	29.80
4	4824.00	40.40 PK	74.00	-33.60	1.26 H	317	5.30	35.10
4	4824.00	30.60 AV	54.00	-23.40	1.26 H	317	-4.50	35.10
5	7236.00	46.30 PK	74.00	-27.70	1.18 H	218	5.80	40.50
5	7236.00	34.80 AV	54.00	-19.20	1.18 H	218	-5.70	40.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2387.00	63.30 PK	74.00	-10.70	1.07 V	68	30.50	32.80
1	2387.00	53.10 AV	54.00	-0.90	1.07 V	68	20.30	32.80
2	2390.00	60.80 PK	74.00	-13.20	1.07 V	68	27.10	33.70
2	2390.00	51.20 AV	54.00	-2.80	1.07 V	68	17.50	33.70
3	*2412.00	117.20 PK			1.07 V	68	87.40	29.80
3	*2412.00	109.40 AV			1.07 V	68	79.60	29.80
4	4824.00	44.20 PK	74.00	-29.80	1.38 V	207	9.10	35.10
4	4824.00	32.30 AV	54.00	-21.70	1.38 V	207	-2.80	35.10
5	7236.00	45.00 PK	74.00	-29.00	1.20 V	119	4.50	40.50
5	7236.00	35.00 AV	54.00	-19.00	1.20 V	119	-5.50	40.50

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



EUT	Access point	MODEL	BSAP-1500
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Rex Hunag

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	106.20 PK			1.62 H	34	76.30	29.90
1	*2437.00	98.70 AV			1.62 H	34	68.80	29.90
2	4874.00	40.90 PK	74.00	-33.10	1.14 H	17	5.60	35.30
2	4874.00	30.60 AV	54.00	-23.40	1.14 H	17	-4.70	35.30
3	7311.00	45.60 PK	74.00	-28.40	1.51 H	279	4.90	40.70
3	7311.00	34.40 AV	54.00	-19.60	1.51 H	279	-6.30	40.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	116.60 PK			1.37 V	344	86.70	29.90
1	*2437.00	109.30 AV			1.37 V	344	79.40	29.90
2	4874.00	44.50 PK	74.00	-29.50	1.32 V	278	9.20	35.30
2	4874.00	32.20 AV	54.00	-21.80	1.32 V	278	-3.10	35.30
3	7311.00	45.30 PK	74.00	-28.70	1.32 V	278	4.60	40.70
3	7311.00	35.00 AV	54.00	-19.00	1.32 V	278	-5.70	40.70

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



EUT	Access point	MODEL	BSAP-1500
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Rex Hunag

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	104.20 PK			1.61 H	41	74.20	30.00
1	*2462.00	97.10 AV			1.61 H	41	67.10	30.00
2	2483.50	49.70 PK	74.00	-24.30	1.61 H	41	19.60	30.10
2	2483.50	40.80 AV	54.00	-13.20	1.61 H	41	10.70	30.10
3	2487.00	51.50 PK	74.00	-22.50	1.61 H	41	21.40	30.10
3	2487.00	41.30 AV	54.00	-12.70	1.61 H	41	11.20	30.10
4	4924.00	40.70 PK	74.00	-33.30	1.23 H	182	5.20	35.50
4	4924.00	30.70 AV	54.00	-23.30	1.23 H	182	-4.80	35.50
5	7386.00	46.50 PK	74.00	-27.50	1.46 H	323	5.70	40.80
5	7386.00	34.30 AV	54.00	-19.70	1.46 H	323	-6.50	40.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	115.40 PK			1.34 V	343	85.40	30.00
1	*2462.00	108.30 AV			1.34 V	343	78.30	30.00
2	2483.50	60.90 PK	74.00	-13.10	1.34 V	343	30.80	30.10
2	2483.50	52.00 AV	54.00	-2.00	1.34 V	343	21.90	30.10
3	2487.00	62.70 PK	74.00	-11.30	1.34 V	343	32.60	30.10
3	2487.00	52.50 AV	54.00	-1.50	1.34 V	343	22.40	30.10
4	4924.00	43.80 PK	74.00	-30.20	1.29 V	257	8.30	35.50
4	4924.00	32.10 AV	54.00	-21.90	1.29 V	257	-3.40	35.50
5	7386.00	47.00 PK	74.00	-27.00	1.39 V	325	6.20	40.80
5	7386.00	35.20 AV	54.00	-18.80	1.39 V	325	-5.60	40.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. " * " : Fundamental frequency



802.11g OFDM modulation

EUT	Access point	MODEL	BSAP-1500
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Rex Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	51.60 PK	74.00	-22.40	1.27 H	311	17.90	33.70
1	2390.00	40.10 AV	54.00	-13.90	1.27 H	311	6.40	33.70
2	*2412.00	99.80 PK			1.27 H	311	70.00	29.80
2	*2412.00	90.30 AV			1.27 H	311	60.50	29.80
3	4824.00	40.40 PK	74.00	-33.60	1.27 H	311	5.30	35.10
3	4824.00	30.30 AV	54.00	-23.70	1.27 H	311	-4.80	35.10
4	7236.00	45.50 PK	74.00	-28.50	1.17 H	225	5.00	40.50
4	7236.00	34.50 AV	54.00	-19.50	1.17 H	225	-6.00	40.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	63.80 PK	74.00	-10.20	1.08 V	68	30.10	33.70
1	2390.00	52.60 AV	54.00	-1.40	1.08 V	68	18.90	33.70
2	*2412.00	112.10 PK			1.08 V	68	82.30	29.80
2	*2412.00	102.80 AV			1.08 V	68	73.00	29.80
3	4824.00	43.20 PK	74.00	-30.80	1.33 V	200	8.10	35.10
3	4824.00	31.60 AV	54.00	-22.40	1.33 V	200	-3.50	35.10
4	7236.00	45.40 PK	74.00	-28.60	1.21 V	116	4.90	40.50
4	7236.00	34.80 AV	54.00	-19.20	1.21 V	116	-5.70	40.50

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



EUT	Access point	MODEL	BSAP-1500
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Rex Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	104.10 PK			1.24 H	33	74.20	29.90
1	*2437.00	95.70 AV			1.24 H	33	65.80	29.90
2	4874.00	40.50 PK	74.00	-33.50	1.18 H	345	5.20	35.30
2	4874.00	30.40 AV	54.00	-23.60	1.18 H	345	-4.90	35.30
3	7311.00	45.40 PK	74.00	-28.60	1.43 H	321	4.70	40.70
3	7311.00	34.50 AV	54.00	-19.50	1.43 H	321	-6.20	40.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	114.50 PK			1.37 V	347	84.60	29.90
1	*2437.00	106.20 AV			1.37 V	347	76.30	29.90
2	4874.00	43.10 PK	74.00	-30.90	1.35 V	229	7.80	35.30
2	4874.00	31.50 AV	54.00	-22.50	1.35 V	229	-3.80	35.30
3	7311.00	44.90 PK	74.00	-29.10	1.49 V	314	4.20	40.70
3	7311.00	34.80 AV	54.00	-19.20	1.49 V	314	-5.90	40.70

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



EUT	Access point	MODEL	BSAP-1500
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Rex Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	99.50 PK			1.26 H	298	69.50	30.00
1	*2462.00	89.50 AV			1.26 H	298	59.50	30.00
2	2483.50	54.30 PK	74.00	-19.70	1.26 H	298	24.20	30.10
2	2483.50	42.00 AV	54.00	-12.00	1.26 H	298	11.90	30.10
3	4924.00	40.60 PK	74.00	-33.40	1.25 H	320	5.10	35.50
3	4924.00	30.80 AV	54.00	-23.20	1.25 H	320	-4.70	35.50
4	7386.00	45.90 PK	74.00	-28.10	1.19 H	218	5.10	40.80
4	7386.00	34.70 AV	54.00	-19.30	1.19 H	218	-6.10	40.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.90 PK			1.07 V	57	80.90	30.00
1	*2462.00	101.30 AV			1.07 V	57	71.30	30.00
2	2483.50	65.70 PK	74.00	-8.30	1.07 V	57	35.60	30.10
2	2483.50	53.80 AV	54.00	-0.20	1.07 V	57	23.70	30.10
3	4924.00	43.40 PK	74.00	-30.60	1.36 V	196	7.90	35.50
3	4924.00	31.90 AV	54.00	-22.10	1.36 V	196	-3.60	35.50
4	7386.00	45.60 PK	74.00	-28.40	1.22 V	115	4.80	40.80
4	7386.00	34.90 AV	54.00	-19.10	1.22 V	115	-5.90	40.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS


802.11b DSSS modulation

EUT	Access point	MODEL	BSAP-1500
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 64%RH, 961hPa
TESTED BY	Rex Huang		


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	12.40	0.5	PASS
6	2437	11.95	0.5	PASS
11	2462	11.55	0.5	PASS



CH1




CH6





CH11




**802.11g OFDM modulation**

EUT	Access point	MODEL	BSAP-1500
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 64%RH, 961hPa
TESTED BY	Rex Huang		


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.40	0.5	PASS
6	2437	16.35	0.5	PASS
11	2462	16.10	0.5	PASS



CH1




CH6





CH11





4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005
Agilent SIGNAL GENERATOR	E8257C	MY43320668	Dec. 07, 2005
TEKTRONIX OSCILLOSCOPE	TDS380	B016335	Jun. 22, 2006
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b DSSS modulation

EUT	Access point	MODEL	BSAP-1500
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 64%RH, 961hPa
TESTED BY	Rex Huang		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	23.90	30	PASS
6	2437	23.41	30	PASS
11	2462	21.90	30	PASS

**802.11g OFDM modulation**

EUT	Access point	MODEL	BSAP-1500
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 64%RH, 961hPa
TESTED BY	Rex Huang		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	22.70	30	PASS
6	2437	25.82	30	PASS
11	2462	20.30	30	PASS



4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.5.7 TEST RESULTS


802.11b DSSS modulation

EUT	Access point	MODEL	BSAP-1500
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	26deg.C, 64%RH, 961hPa
TESTED BY	Rex Huang		


CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-0.58	8	PASS
6	2437	0.08	8	PASS
11	2462	-1.84	8	PASS



CH1




CH6





CH11




**802.11g OFDM modulation**

EUT	Access point	MODEL	BSAP-1500
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	26deg.C, 64%RH, 961hPa
TESTED BY	Rex Huang		


CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-7.58	8	PASS
6	2437	-3.44	8	PASS
11	2462	-9.84	8	PASS



CH1




CH6





CH11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 1MHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

NOTE:

- 1.The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set RBW spectrum analyzer to 1 MHz and set VBW spectrum analyzer to 10 Hz with suitable frequency span including 1 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW=VBW=100kHz ; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 EUT OPERATING CONDITION

Same as Item 4.3.5



4.6.5 TEST RESULTS – DSSS

The spectrum plots are attached on the following page. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

NOTE (Peak):



The band edge emission plot of DSSS technique on the following first page show 56.41dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 117.2dBuV/m, so the maximum field strength in restrict band is $117.2-56.41=60.79$ dBuV/m which is under 74 dBuV/m limit.



The band edge emission plot of DSSS technique on the following first page shows 54.51dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 115.4dBuV/m, so the maximum field strength in restrict band is $115.4-54.51=60.89$ dBuV/m which is under 74 dBuV/m limit.


NOTE (Average):

The band edge emission plot of DSSS technique on the following second page shows 58.20dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 109.4dBuV/m, so the maximum field strength in restrict band is $109.4-58.20=51.20$ dBuV/m which is under 54 dBuV/m limit.

The band edge emission plot of DSSS technique on the following second page shows 56.27dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 108.3dBuV/m, so the maximum field strength in restrict band is $108.3-56.27=52.03$ dBuV/m which is under 54 dBuV/m limit.







4.6.6 TEST RESULTS – OFDM

The spectrum plots are attached on the following page. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

NOTE (Peak) :



The band edge emission plot of OFDM technique on the following first page show 48.26dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 112.1dBuV/m, so the maximum field strength in restrict band is $112.1-48.26=63.84$ dBuV/m which is under 74 dBuV/m limit.



The band edge emission plot of OFDM technique on the following first page shows 45.20dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 110.90dBuV/m, so the maximum field strength in restrict band is $110.90-45.20=65.70$ dBuV/m which is under 74 dBuV/m limit.


NOTE (Average):

The band edge emission plot of OFDM technique on the following second page shows 50.20dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 102.80dBuV/m, so the maximum field strength in restrict band is $102.80-50.20=52.60$ dBuV/m which is under 54 BuV/m limit.

The band edge emission plot of OFDM technique on the following second page shows 47.51dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 101.30dBuV/m, so the maximum field strength in restrict band is $101.30-47.51=53.79$ dBuV/m which is under 54 dBuV/m limit.









4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Dipole Antenna with MMCX connector. The maximum Gain of the antenna is 2.0dBi.

5. TEST TYPES AND RESULTS (802.11a, 5725~5850MHz Band)

5.1 CONDUCTED EMISSION MEASUREMENT

5.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
- The lower limit shall apply at the transition frequencies.
 - The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 - All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

5.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	847124/029	Dec. 07, 2005
ROHDE & SCHWARZ LISN (for EUT)	ESHS-Z5	848773/004	Nov. 08, 2005
KYORITSU LISN (for peripheral)	KNW-407	8/1395/12	Jul. 19, 2006
RF Cable (JETBAO)	RG233/U	Cable_CA_01	Jul. 19, 2006
Terminator(for KYORITSU)	50	3	Oct. 12, 2005
Software	Cond-V2e	NA	NA

- NOTE:**
- The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 - The test was performed in ADT Shielded Room No. A.
 - The VCCI Con A Registration No. is C-817.
 - The measurement uncertainty is 2.53 dB, which is calculated as per the document CISPR 16-4




5.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs
- b. provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- c. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- d. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit – 20dB) was not recorded.

5.1.4 DEVIATION FROM TEST STANDARD

No deviation

5.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.1.6 EUT OPERATING CONDITIONS

- d. Placed the EUT on the testing table.
- e. Prepared another computer system to act as a communication partner and placed it outside of testing area.
- f. The communication partner run test program “Art V48 build16” to enable EUT under transmission/receiving condition continuously at specific channel frequency via UTP cable.




5.1.7 TEST RESULTS

Conducted Worst-Case Data

EUT	Access point	MODEL	BSAP-1500
TEST MODE	With Adapter	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.271	0.16	48.51	-	48.67	-	61.08	51.08	-12.42	-
2	0.552	0.18	42.11	-	42.29	-	56.00	46.00	-13.71	-
3	1.076	0.20	32.91	-	33.11	-	56.00	46.00	-22.89	-
4	4.105	0.46	35.24	-	35.70	-	56.00	46.00	-20.30	-
5	6.465	0.57	37.03	-	37.60	-	60.00	50.00	-22.40	-
6	9.148	0.71	33.21	-	33.92	-	60.00	50.00	-26.08	-
7	27.160	1.48	35.64	-	37.12	-	60.00	50.00	-22.88	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






EUT	Access point	MODEL	BSAP-1500
TEST MODE	With Adapter	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Tony Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.271	0.16	47.28	-	47.44	-	61.08
2	0.541	0.18	42.17	-	42.35	-	56.00	46.00	-13.65	-
3	1.232	0.21	31.09	-	31.30	-	56.00	46.00	-24.70	-
4	1.752	0.24	32.10	-	32.34	-	56.00	46.00	-23.66	-
5	6.070	0.52	35.67	-	36.19	-	60.00	50.00	-23.81	-
6	21.660	1.18	36.21	-	37.39	-	60.00	50.00	-22.61	-
7	27.156	1.24	36.08	-	37.32	-	60.00	50.00	-22.68	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






EUT	Access point	MODEL	BSAP-1500
TEST MODE	With POE	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	27deg. C, 64%RH, 961hPa	TESTED BY	Wen Yu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.341	0.16	35.26	-	35.42	-	59.17
2	1.005	0.20	34.63	-	34.83	-	56.00	46.00	-21.17	-
3	1.205	0.21	46.05	44.30	46.26	44.51	56.00	46.00	-9.74	-1.49
4	2.048	0.25	33.88	-	34.13	-	56.00	46.00	-21.87	-
5	10.047	0.75	37.01	-	37.76	-	60.00	50.00	-22.24	-
6	13.602	0.92	41.85	-	42.77	-	60.00	50.00	-17.23	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






EUT	Access point	MODEL	BSAP-1500
TEST MODE	With POE	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	27deg. C, 64%RH, 961hPa	TESTED BY	Wen Yu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.341	0.16	34.64	-	34.80	-	59.17
2	1.005	0.20	34.85	-	35.05	-	56.00	46.00	-20.95	-
3	1.205	0.21	46.33	44.75	46.54	44.96	56.00	46.00	-9.46	-1.04
4	2.529	0.30	29.92	-	30.22	-	56.00	46.00	-25.78	-
5	13.418	0.81	42.30	-	43.11	-	60.00	50.00	-16.89	-
6	16.227	0.95	37.93	-	38.88	-	60.00	50.00	-21.12	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.





5.2 RADIATED EMISSION MEASUREMENT

5.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



5.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ADVANTEST Spectrum Analyzer	R3271A	85060311	July 07, 2006
HP Pre_Amplifier	8449B	3008A01922	Oct. 13, 2005
ROHDE & SCHWARZ Test Receiver	ESCS30	100287	Dec. 08, 2005
CHASE Broadband Antenna	VULB9168	138	Dec. 21, 2005
Schwarzbeck Horn_Antenna	BBHA9120	D124	Dec. 11, 2005
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 30, 2006
SCHWARZBECK Biconical Antenna	VHBA9123	459	Jun. 26, 2006
SCHWARZBECK Periodic Antenna	UPA6108	1148	Jun. 26, 2006
RF Switches (ARNITSU)	CS-201	1565157	NA
RF CABLE (Chaintek) 1GHz-20GHz	SF102	22054-2	Nov. 15. 2005
RF Cable(RICHTEC)	9913-30M	STCCAB-30M- 1GHz-021	Jul. 16, 2006
Software	ADT_Radiated_V 5.14	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
CHANCE MOST Turn Table	TT-100	0203	NA

- Note: 1. The calibration interval of the above test instruments is 12 months (36 months for Tunable Periodic Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in ADT Open Site No. C.
4. The FCC Site Registration No. is 656396.
5. The VCCI Site Registration No. is R-1626.
6. The CANADA Site Registration No. is IC 4824-3.
7. The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4.

Measurement	Value
Radiated emissions (30MHz-1GHz)	2.98 dB
Radiated emissions (1GHz ~18GHz)	2.21 dB
Radiated emissions (18GHz ~20GHz)	1.88 dB



5.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

5.2.4 DEVIATION FROM TEST STANDARD

No deviation

5.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

5.2.7 TEST RESULTS

Below 1GHz Worst-Case Data

EUT	Access point	MODEL	BSAP-1500
TEST MODE	With Adapter	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	250.00	23.80 QP	46.00	-22.20	1.82 H	287	10.50	13.30
2	300.00	23.70 QP	46.00	-22.30	1.28 H	322	7.40	16.30
3	375.00	26.20 QP	46.00	-19.80	1.05 H	307	8.60	17.60
4	500.00	26.00 QP	46.00	-20.00	1.12 H	216	5.10	20.90
5	792.00	37.10 QP	46.00	-8.90	1.06 H	187	10.50	26.60
6	891.00	38.90 QP	46.00	-7.10	1.03 H	274	11.10	27.80
7	924.00	38.50 QP	46.00	-7.50	1.54 H	321	10.10	28.40
8	990.00	40.10 QP	54.00	-13.90	1.72 H	243	11.20	28.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	43.10	25.50 QP	40.00	-14.50	1.13 V	275	11.30	14.20
2	250.00	28.50 QP	46.00	-17.50	1.07 V	238	15.20	13.30
3	500.00	26.30 QP	46.00	-19.70	1.31 V	143	5.40	20.90
4	792.00	33.70 QP	46.00	-12.30	1.15 V	246	7.10	26.60
5	858.00	33.60 QP	46.00	-12.40	1.22 V	48	6.10	27.50
6	891.00	38.50 QP	46.00	-7.50	1.25 V	210	10.70	27.80
7	924.00	37.20 QP	46.00	-8.80	1.00 V	54	8.80	28.40
8	990.00	38.10 QP	54.00	-15.90	1.09 V	219	9.20	28.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value



Below 1GHz Worst-Case Data

EUT	Access point	MODEL	BSAP-1500
TEST MODE	With POE	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	27deg. C, 53%RH, 961hPa	TESTED BY	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	250.00	23.40 QP	46.00	-22.60	1.84 H	203	10.10	13.30
2	300.00	21.90 QP	46.00	-24.10	1.19 H	324	5.60	16.30
3	375.00	24.70 QP	46.00	-21.30	1.21 H	176	7.10	17.60
4	500.00	25.20 QP	46.00	-20.80	1.01 H	84	4.30	20.90
5	792.00	36.80 QP	46.00	-9.20	1.31 H	305	10.20	26.60
6	891.00	39.90 QP	46.00	-6.10	1.13 H	249	12.10	27.80
7	924.00	37.50 QP	46.00	-8.50	1.06 H	278	9.10	28.40
8	990.00	39.30 QP	54.00	-14.70	1.00 H	302	10.40	28.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	42.10	32.10 QP	40.00	-7.90	1.00 V	342	17.90	14.20
2	250.00	26.50 QP	46.00	-19.50	1.01 V	296	13.20	13.30
3	500.00	26.10 QP	46.00	-19.90	1.31 V	58	5.20	20.90
4	792.00	35.50 QP	46.00	-10.50	1.25 V	264	8.90	26.60
5	858.00	33.50 QP	46.00	-12.50	1.28 V	172	6.00	27.50
6	891.00	37.20 QP	46.00	-8.80	1.21 V	273	9.40	27.80
7	924.00	38.30 QP	46.00	-7.70	1.14 V	84	9.90	28.40
8	990.00	37.00 QP	54.00	-17.00	1.03 V	209	8.10	28.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value

802.11a OFDM modulation

EUT	Access point	MODEL	BSAP-1500
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 40 GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	27deg. C, 54%RH, 961hPa	TESTED BY	Rex Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5745.00	104.50 PK			1.28 H	246	68.10	36.40
1	*5745.00	96.00 AV			1.28 H	246	59.60	36.40
2	#11490.00	62.50 PK	74.00	-11.50	1.54 H	142	11.40	51.10
2	#11490.00	51.20 AV	54.00	-2.80	1.54 H	142	0.10	51.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5745.00	114.90 PK			1.25 V	278	78.50	36.40
1	*5745.00	106.70 AV			1.25 V	278	70.30	36.40
2	#11490.00	62.90 PK	74.00	-11.10	1.38 V	314	11.80	51.10
2	#11490.00	51.80 AV	54.00	-2.20	1.38 V	314	0.70	51.10

- NOTE:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value
 5. "*" : Fundamental frequency
 6. "#"The radiated frequency falling in the restricted band.
 7. The limit value is defined as per 15.247

EUT	Access point	MODEL	BSAP-1500
CHANNEL	Channel 3	FREQUENCY RANGE	1 ~ 40 GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	27deg. C, 54%RH, 961hPa	TESTED BY	Rex Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5785.00	105.10 PK			1.21 H	287	68.60	36.50
1	*5785.00	96.40 AV			1.21 H	287	59.90	36.50
2	#11570.00	62.50 PK	74.00	-11.50	1.51 H	3	11.60	50.90
2	#11570.00	51.50 AV	54.00	-2.50	1.51 H	3	0.60	50.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5785.00	115.80 PK			1.17 V	265	79.30	36.50
1	*5785.00	107.00 AV			1.17 V	265	70.50	36.50
2	#11570.00	63.10 PK	74.00	-10.90	1.42 V	343	12.20	50.90
2	#11570.00	52.20 AV	54.00	-1.80	1.42 V	343	1.30	50.90

- NOTE:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value
 5. "*" : Fundamental frequency
 6. "#"The radiated frequency falling in the restricted band.
 7. The limit value is defined as per 15.247



EUT	Access point	MODEL	BSAP-1500
CHANNEL	Channel 5	FREQUENCY RANGE	1 ~ 40 GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	27deg. C, 54%RH, 961hPa	TESTED BY	Rex Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5825.00	104.30 PK			1.26 H	274	67.70	36.60
1	*5825.00	96.00 AV			1.26 H	274	59.40	36.60
2	#11650.00	62.20 PK	74.00	-11.80	1.47 H	335	11.60	50.60
2	#11650.00	51.40 AV	54.00	-2.60	1.47 H	335	0.80	50.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5825.00	115.70 PK			1.17 V	270	79.10	36.60
1	*5825.00	107.10 AV			1.17 V	270	70.50	36.60
2	#11650.00	62.30 PK	74.00	-11.70	1.39 V	26	11.70	50.60
2	#11650.00	51.20 AV	54.00	-2.80	1.39 V	26	0.60	50.60

- NOTE:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value
 5. “*” : Fundamental frequency
 6. “#”The radiated frequency falling in the restricted band.
 7. The limit value is defined as per 15.247



5.3 6dB BANDWIDTH MEASUREMENT

5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

5.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

5.3.4 DEVIATION FROM TEST STANDARD

No deviation

5.3.5 TEST SETUP



5.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

5.3.7 TEST RESULTS


802.11a OFDM modulation

EUT	Access point	MODEL	BSAP-1500
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 64%RH, 961hPa
TESTED BY	Rex Huang		


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	5745	16.40	0.5	PASS
3	5785	16.40	0.5	PASS
5	5825	16.40	0.5	PASS



CH1




CH3





CH5





5.4 MAXIMUM PEAK OUTPUT POWER

5.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

5.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005
Agilent SIGNAL GENERATOR	E8257C	MY43320668	Dec. 07, 2005
TEKTRONIX OSCILLOSCOPE	TDS380	B016335	Jun. 22, 2006
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

5.4.4 DEVIATION FROM TEST STANDARD

No deviation

5.4.5 TEST SETUP



5.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

5.4.7 TEST RESULTS

802.11a OFDM modulation

EUT	Access point	MODEL	BSAP-1500
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 64%RH, 961hPa
TESTED BY	Rex Huang		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	5745	24.85	30	PASS
3	5785	24.92	30	PASS
5	5825	24.76	30	PASS



5.5 POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time = span/3 kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3 kHz for a full response of the mixer in the spectrum analyzer.

5.5.4 DEVIATION FROM TEST STANDARD

No deviation

5.5.5 TEST SETUP



5.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

5.5.7 TEST RESULTS


802.11a OFDM modulation

EUT	Access point	MODEL	BSAP-1500
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 64%RH, 961hPa
TESTED BY	Rex Huang		


CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	5745	-2.89	8	PASS
3	5785	-2.92	8	PASS
5	5825	-2.50	8	PASS



CH1




CH3





CH5



5.6 BAND EDGES MEASUREMENT

5.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

5.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.



5.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

5.6.4 DEVIATION FROM TEST STANDARD

No deviation

5.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6






5.6.6 TEST RESULTS

The spectrum plots are attached on the following pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(d).



802.11a OFDM modulation







5.7 ANTENNA REQUIREMENT

5.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247(a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Dipole Antenna with MMCX connector. The maximum Gain of the antenna is 4.0dBi.

6. PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST (WITH ADAPTER)



CONDUCTED EMISSION TEST (WITH POE)



RADIATED EMISSION TEST (WITH ADAPTER)



RADIATED EMISSION TEST (WITH POE)





7. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also