



RF Exposure Evaluation Declaration

FCC ID: TK4WLE1216V220

APPLICANT: Compex Systems Pte Ltd


Application Type: Certification

Product: 4x4 Wave-2 802.11BGN Mini PCIe WiFi Module


Model No.: WLE1216V2-20, WLE1216V2-20-I

Brand Name: COMPEX

FCC Classification: Digital Transmission System (DTS)

Reviewed By : 

(Jame Yuan)

Approved By : 

(Marlin Chen)



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1801RSU037-U2	Rev. 01	Initial report	03-08-2018	Valid

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name	4x4 Wave-2 802.11BGN Mini PCIe WiFi Module
Model No.	WLE1216V2-20, WLE1216V2-20-I
Brand Name	COMPEX
Wi-Fi Specification	802.11b/g/n
Frequency Range	802.11b/g/n-HT20: 2412 ~ 2462 MHz 802.11n-HT40: 2422 ~ 2452 MHz
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM
Data Rate:	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 600Mbps

1.2. Antenna Description

Antenna Type	Frequency Band (GHz)	TX Paths	Max Peak Gain (dBi)
Dipole Antenna	2.4	4	5
Panel Antenna	2.4	4	11

Note: The device didn't support beam-forming technology and Cyclic Delay Diversity (CDD) technology, and the transmit signals are uncorrected, so no add array gain to the band power and band PSD.

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	4x4 Wave-2 802.11BGN Mini PCIe WiFi Module
Test Item	RF Exposure Evaluation

Antenna Gain: Refer to clause 1.2.

Test Mode	Frequency Band (MHz)	Maximum Conducted Power (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
For Dipole Antenna				
802.11b/g/n	2412 ~ 2462	26.24	1	0.2647
For Panel Antenna				
802.11b/g/n	2412 ~ 2462	23.44	1	0.5530

CONCLUSION:

The max Power Density at R (20 cm) = 0.5530mW/cm² < 1mW/cm².

Therefore, the Min Safety Distance is 20cm.

_____ The End _____