



RF Exposure Evaluation Declaration

FCC ID: TK4WLE200NX

APPLICANT: Compex Systems Pte Ltd


Application Type: Certification


Product: WIRELESS-ABGN 2X2 NETWORK MINIPCIE
ADAPTER

Model No.: WLE200NX, WLE200NX-I

Trademark: COMPEX

FCC Classification: Digital Transmission System (DTS)
Unlicensed National Information Infrastructure (UNII)

Reviewed By : 
Manager : _____
(Robin Wu)

Approved By : 
CEO : _____
(Marlin Chen)



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1608RSU02004	Rev. 01	Initial report	09-07-2016	Valid

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name	WIRELESS-ABGN 2X2 NETWORK MINIPCIE ADAPTER
Model No.	WLE200NX, WLE200NX-I
Brand Name	COMPEX
Wi-Fi Specification	802.11a/b/g/n
Frequency Range	<p><u>2.4GHz:</u> For 802.11b/g/n-HT20: 2412 ~ 2462 MHz For 802.11n-HT40: 2422 ~ 2452 MHz</p> <p><u>5GHz:</u> For 802.11a/n-HT20: 5180~5320MHz, 5500~5700MHz, 5745~5825MHz For 802.11n-HT40: 5190~5310MHz, 5510~5670MHz, 5755~5795MHz</p>
Type of Modulation	802.11b: DSSS 802.11g/a/n: OFDM
Maximum Average Output Power	<p><u>For 2.4GHz Band:</u> 802.11b: 20.80dBm 802.11g: 20.58dBm 802.11n-HT20: 23.57dBm 802.11n-HT40: 24.78dBm</p> <p><u>For 5GHz Band:</u> 802.11a: 21.96dBm 802.11n-HT20: 22.29dBm 802.11n-HT40: 22.48dBm</p>

1.2. Antenna Description

Antenna Type	Frequency Band (GHz)	Manufacturer	Tx Paths	Max Peak Gain (dBi)	Directional Gain (dBi)	
					For Power	For PSD
Dipole Antenna	2.4	Compex Systems Pte Ltd	2	2	2	5.01
	5		2	2	2	5.01
Panel Antenna	2.4	SMARTANT Inc.	2	4.5	4.5	7.51
	5		2	7	7	10.01

Note 1: The EUT supports Cyclic Delay Diversity (CDD) technology, and CDD signals are correlated.

For CDD transmissions, directional gain is calculated as follows, $N_{ANT} = 2$, $N_{SS} = 1$.

If all antennas have the same gain, G_{ANT} , Directional gain = $G_{ANT} + \text{Array Gain}$, where Array Gain is as follows.

- For power spectral density (PSD) measurements on all devices,
Array Gain = $10 \log (N_{ANT} / N_{SS}) \text{ dB} = 3.01$;
- For power measurements on IEEE 802.11 devices,
Array Gain = 0 dB for $N_{ANT} \leq 4$;

Note 2: 802.11n mode support CDD technology, not include 802.11a/b/g.

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	WIRELESS-ABGN 2X2 NETWORK MINIPCIE ADAPTER
Test Item	RF Exposure Evaluation

Antenna Gain: Refer to clause 1.2.

Test Mode	Frequency Band (MHz)	Maximum Average Output Power (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
802.11b/g/n	2412 ~ 2462	24.78	0.1686	1
802.11a/n	5180 ~ 5825	22.48	0.1765	1

CONCLUSION:

The Max Power Density at R (20 cm) = 0.1765mW/cm² < 1mW/cm².
 So the EUT complies with the requirement.

_____ The End _____