

RF Exposure Report

Report No.: SA180914C09

Test Model: FW-7551SEC

Series Model: FW-7551SExxxxxx (where x can be 0-9, A-Z, a-z, any alphanumeric character or blank)

Received Date: Sep. 14, 2018

Test Date: Oct. 26, 2018

Issued Date: Nov. 06, 2018

Applicant: Compex Systems Pte Ltd

Address: No. 9 Harrison Road, Harrison Industrial Building #05-01, Singapore 369651

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specifically mentioned, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Tune up Power	6

Release Control Record

Issue No.	Description	Date Issued
SA180914C09	Original release.	Nov. 06, 2018

1 Certificate of Conformity

Product: Network Appliance Platform

Brand: Lanner

Test Model: FW-7551SEC

Series Model: FW-7551SExxxxxx (where x can be 0-9, A-Z, a-z, any alphanumeric character or blank)

Sample Status: Engineering sample

Applicant: Compex Systems Pte Ltd

Test Date: Oct. 26, 2018

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen , **Date:** Nov. 06, 2018
Pettie Chen / Senior Specialist

Approved by : Bruce Chen , **Date:** Nov. 06, 2018
Bruce Chen / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Tune up Power

For WLAN: (Base on WLAN module report (Model: WLE600VX, FCC ID: TK4WLE600VX))

Frequency Band (MHz)	TX Funtion	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN: 2.4GHz Band	1TX	22.26	1.60	20	0.048	1
	2TX	24.22	4.61	20	0.152	1
WLAN: 5GHz Band	1TX	21.89	1.94	20	0.048	1
	2TX	24.63	4.95	20	0.181	1

Note:

2.4GHz: Directional gain = 1.60dBi + 10log(2) = 4.61dBi

5GHz: Directional gain = 1.94dBi + 10log(2) = 4.95dBi

For WWAN: (Base on WWAN module report (Model: EM7455, FCC ID: N7NEM7455))

Function	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA Band 2	1852.4-1907.6	26.84	1.56	20	0.138	1
WCDMA Band 4	1712.4-1752.6	26.62	1.62	20	0.133	1
WCDMA Band 5	826.4-846.6	26.74	3.20	20	0.196	0.551
LTE Band 4	1710.7-1754.3	28.94	1.62	20	0.226	1
LTE Band 7	2622.5-2687.5	27.72	0.44	20	0.130	1
LTE Band 12	699.7-715.3	28.98	1.49	20	0.222	0.466
LTE Band 13	779.5-784.5	28.79	1.66	20	0.221	0.520
LTE Band 25	1850.7-1914.3	28.83	1.56	20	0.218	1
LTE Band 26	824.7-848.3	29.06	3.20	20	0.335	0.550
LTE Band 30	2307.5-2312.5	27.98	2.27	20	0.211	1
LTE Band 41	2537.5-2652.5	27.83	0.44	20	0.134	1

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

1. WLAN 2.4G+ WWAN LTE Band 4 = $0.152 / 1 + 0.226 / 1 = 0.378$
2. WLAN 5.0G+ WWAN LTE Band 4 = $0.181 / 1 + 0.226 / 1 = 0.407$
3. WLAN 2.4G+ WWAN LTE Band 25 = $0.152 / 1 + 0.218 / 1 = 0.370$
4. WLAN 5.0G+ WWAN LTE Band 25 = $0.181 / 1 + 0.218 / 1 = 0.399$
5. WLAN 2.4G+ WWAN LTE Band 26 = $0.152 / 1 + 0.335 / 0.550 = 0.761$
6. WLAN 5.0G+ WWAN LTE Band 26 = $0.181 / 1 + 0.335 / 0.550 = 0.791$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---