

Partial FCC Test Report

Report No.: RF191211C28A

FCC ID: TK4WLE600VX

Test Model: WLE600VX

Received Date: Dec. 11, 2019

Test Date: Jan. 12 ~ Feb. 07, 2020

Issued Date: Feb. 24, 2020

Applicant: Compex Systems Pte Ltd

Address: 135, Joo Seng Road, #08-01 Singapore 368363

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location (1): No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

Test Location (2): B2F., No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231,
Taiwan

FCC Registration / 788550 / TW0003

Designation Number: 427177 / TW0011



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results.....	5
2.1 Measurement Uncertainty.....	5
2.2 Modification Record	5
3 General Information	6
3.1 General Description of EUT	6
3.2 Description of Test Modes.....	7
3.2.1 Test Mode Applicability and Tested Channel Detail.....	8
3.3 Description of Support Units	10
3.3.1 Configuration of System under Test	10
3.4 General Description of Applied Standards and References	10
4 Test Types and Results	11
4.1 Radiated Emission and Bandedge Measurement	11
4.1.1 Limits of Radiated Emission and Bandedge Measurement	11
4.1.2 Test Instruments	12
4.1.3 Test Procedures.....	13
4.1.4 Deviation from Test Standard	13
4.1.5 Test Set Up	14
4.1.6 EUT Operating Conditions.....	15
4.1.7 Test Results	16
4.2 Conducted Emission Measurement.....	30
4.2.1 Limits of Conducted Emission Measurement	30
4.2.2 Test Instruments	30
4.2.3 Test Procedures.....	31
4.2.4 Deviation from Test Standard	31
4.2.5 Test Setup.....	31
4.2.6 EUT Operating Conditions.....	31
4.2.7 Test Results	32
4.3 Conducted Output Power Measurement	34
4.3.1 Limits of Conducted Output Power Measurement.....	34
4.3.2 Test Setup.....	34
4.3.3 Test Instruments	34
4.3.4 Test Procedures.....	34
4.3.5 Deviation from Test Standard	34
4.3.6 EUT Operating Conditions.....	34
4.3.7 Test Results	35
5 Pictures of Test Arrangements.....	37
Appendix – Information of the Testing Laboratories	38

Release Control Record


Issue No.	Description	Date Issued
RF191211C28A	Original Release	Feb. 24, 2020

1 Certificate of Conformity

Product: 802.11ac Dual Band Module
Brand: COMPEX
Test Model: WLE600VX
Sample Status: Engineering Sample
Applicant: Compex Systems Pte Ltd
Test Date: Jan. 12 ~ Feb. 07, 2020
Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : , **Date:** Feb. 24, 2020
Lena Wang / Specialist

Approved by : , **Date:** Feb. 24, 2020
Dylan Chiou / Senior Project Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -12.69 dB at 0.19500 MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -1.72 dB at 2389.92 MHz.
15.247(d)	Antenna Port Emission	N/A	Refer to Note
15.247(a)(2)	6 dB Bandwidth	N/A	Refer to Note
---	Occupied Bandwidth Measurement	N/A	Refer to Note
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	N/A	Refer to Note
15.203	Antenna Requirement	Pass	Antenna connector is ipex (MHF) not a standard connector.

Note:

1. This report is a partial report, certified module graded into a new host, addition of new antennas with higher antenna gain, reduced power implementation in the intentional transmit frequency bands. only test item of AC Power Conducted Emission, Radiated Emissions and Conducted power tests were performed for this report. Other testing data please refer to MRT report no.: 153RSU02901 for module (Brand: COMPEX, Model: WLE600VX).
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.79 dB
Radiated Emissions up to 1 GHz	9 kHz ~ 30 MHz	3.04 dB
	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	802.11ac Dual Band Module
Brand	COMPEX
Test Model	WLE600VX
Status of EUT	Engineering Sample
Power Supply Rating	120 Vac
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps 802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to 300.0 Mbps
Operating Frequency	2412 ~ 2462 MHz
Number of Channel	11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
Output Power	588.844 mW
Antenna Type	Refer to Note as below
Antenna Connector	Refer to Note as below
Accessory Device	Refer to Note as below
Data Cable Supplied	Refer to Note as below

Note:

- The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers.

Modulation Mode	Tx Function
802.11b	1TX
802.11g	1TX
802.11n (HT20)	2TX
802.11n (HT40)	2TX

- The EUT is authorized for use in specific End-product. Please refer to below table for further details.

Product Name	Brand	Model
Networking device	CITRIX	SD-WAN 110-WiFi

- The antenna information is listed as below.

Antenna Type	Manufacturer	Model	Antenna Connector	Antenna Gain	
				WLAN 2.4 GHz	WLAN 5 GHz
Dipole	Taoglas	FXP.830.07.0100C	i-pex(MHF)	2.6	5.0
	Ethertronics	1001932FT	i-pex(MHF)	2.5	4.4

- The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	AOEM	ADS0248T-U120200	I/P: 100-240 Vac, 50-60 Hz, 0.6 A O/P: 12.0 Vdc, 2.0 A Cable: 1.46m cable w/o core

- The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

7 channels are provided for 802.11n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To				Description
	RE \geq 1G	RE $<$ 1G	PLC	APCM	
-	√	√	√	√	-

Where **RE \geq 1G**: Radiated Emission above 1 GHz **RE $<$ 1G**: Radiated Emission below 1 GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.
NOTE: "-" means no effect.

Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11g	1 to 11	1	OFDM	BPSK	6.0

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11g	1 to 11	1	OFDM	BPSK	6.0

Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.


EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee, Harry Hsueh
RE<1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee
PLC	25 deg. C, 65 % RH	120 Vac, 60 Hz	Jisyong Wang
APCM	25 deg. C, 65 % RH	120 Vac, 60 Hz	Gavin Wu

3.3 Description of Support Units

3.3.1 Configuration of System under Test



3.4 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

All test items have been performed as a reference to the above KDB test guidance.

Test Types and Results

3.5 Radiated Emission and Bandedge Measurement

3.5.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 30 dB under any condition of modulation.

3.5.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	Aug. 26, 2019	Aug. 25, 2020
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Apr. 15, 2019	Apr. 14, 2020
BILOG Antenna SCHWARZBECK	VULB 9168	9168-616	Nov. 12, 2019	Nov. 11, 2020
HORN Antenna ETS-Lindgren	3117	00143293	Nov. 24, 2019	Nov. 23, 2020
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Nov. 24, 2019	Nov. 23, 2020
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 15, 2019	Apr. 14, 2020
Loop Antenna	EM-6879	269	Sep. 16, 2019	Sep. 15, 2020
Preamplifier Agilent	310N	187226	Jun. 18, 2019	Jun. 17, 2020
Preamplifier Agilent	83017A	MY39501357	Jun. 18, 2019	Jun. 17, 2020
Power Meter Anritsu	ML2495A	1012010	Sep. 04, 2019	Sep. 03, 2020
Power Sensor Anritsu	MA2411B	1315050	Sep. 04, 2019	Sep. 03, 2020
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(RFC-SMS-100-SMS-120+RFC-SMS-100-SMS-400)	Jun. 18, 2019	Jun. 17, 2020
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(RFC-SMS-100-SMS-24)	Jun. 18, 2019	Jun. 17, 2020
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HsinTien Chamber 1.

3.5.3 Test Procedures

For Radiated Emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.

For Radiated Emission above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz. (11g: RBW = 1 MHz, VBW = 1 kHz)
4. All modes of operation were investigated and the worst-case emissions are reported.

3.5.4 Deviation from Test Standard


No deviation.

3.5.5 Test Set Up


<Radiated Emission below 30 MHz>



<Radiated Emission 30 MHz to 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.5.6 EUT Operating Conditions

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.

3.5.7 Test Results

Above 1 GHz Data :
802.11b

EUT Test Condition		Measurement Detail	
Channel	Channel 1	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2386.16	52	47	5	54	-2	232	145	Average
2386.16	56.59	51.59	5	74	-17.41	232	145	Peak
2412	105.37	100.31	5.06			232	145	Average
2412	107.72	102.66	5.06			232	145	Peak
4824	51.77	41.48	10.29	54	-2.23	100	76	Average
4824	53.98	43.69	10.29	74	-20.02	100	76	Peak

Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2386.16	47.76	42.76	5	54	-6.24	100	225	Average
2386.16	53.48	48.48	5	74	-20.52	100	225	Peak
2412	99	93.94	5.06			100	225	Average
2412	101.76	96.7	5.06			100	225	Peak
4824	51.67	41.38	10.29	54	-2.33	112	14	Average
4824	53.83	43.54	10.29	74	-20.17	112	14	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2412 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

EUT Test Condition		Measurement Detail	
Channel	Channel 6	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2347.24	40.17	35.29	4.88	54	-13.83	162	144	Average
2347.24	49.8	44.92	4.88	74	-24.2	162	144	Peak
2437	106.62	101.51	5.11			162	144	Average
2437	108.97	103.86	5.11			162	144	Peak
2483.5	39.45	34.26	5.19	54	-14.55	162	144	Average
2483.5	49.38	44.19	5.19	74	-24.62	162	144	Peak
4874	50.18	39.97	10.21	54	-3.82	100	42	Average
4874	53.08	42.87	10.21	74	-20.92	100	42	Peak
7311	50.45	37.99	12.46	54	-3.55	272	55	Average
7311	55.8	43.34	12.46	74	-18.2	272	55	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2357.04	37.77	32.87	4.9	54	-16.23	111	226	Average
2357.04	48.08	43.18	4.9	74	-25.92	111	226	Peak
2437	99.61	94.5	5.11			111	226	Average
2437	102.41	97.3	5.11			111	226	Peak
2483.5	36.93	31.74	5.19	54	-17.07	111	226	Average
2483.5	47.22	42.03	5.19	74	-26.78	111	226	Peak
4874	49.12	38.91	10.21	54	-4.88	103	14	Average
4874	52	41.79	10.21	74	-22	103	14	Peak
7311	52.86	40.4	12.46	54	-1.14	110	11	Average
7311	57.2	44.74	12.46	74	-16.8	110	11	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2437 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

EUT Test Condition		Measurement Detail	
Channel	Channel 11	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	102.05	96.91	5.14			186	146	Average
2462	104.21	99.07	5.14			186	146	Peak
2483.5	41.68	36.49	5.19	54	-12.32	186	146	Average
2483.5	50.03	44.84	5.19	74	-23.97	186	146	Peak
4924	52.97	42.72	10.25	54	-1.03	106	84	Average
4924	54.49	44.24	10.25	74	-19.51	106	84	Peak
7386	41.59	29.03	12.56	54	-12.41	104	82	Average
7386	52.21	39.65	12.56	74	-21.79	104	82	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	95.43	90.29	5.14			129	234	Average
2462	98.13	92.99	5.14			129	234	Peak
2483.5	37.79	32.6	5.19	54	-16.21	129	234	Average
2483.5	47.75	42.56	5.19	74	-26.25	129	234	Peak
4924	47.93	37.68	10.25	54	-6.07	130	188	Average
4924	51.7	41.45	10.25	74	-22.3	130	188	Peak
7386	45.66	33.1	12.56	54	-8.34	106	12	Average
7386	52.63	40.07	12.56	74	-21.37	106	12	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2462 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

802.11g

EUT Test Condition		Measurement Detail	
Channel	Channel 1	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.92	52.28	47.78	4.5	54	-1.72	333	261	Average
2389.92	63.58	59.08	4.5	74	-10.42	333	261	Peak
2412	99.89	62.89	37	54	45.89	333	261	Average
2412	106.9	69.9	37	74	32.9	333	261	Peak
4824	40.93	30.64	10.29	54	-13.07	175	153	Average
4824	52.05	41.76	10.29	74	-21.95	175	153	Peak
*6000	54.03	41.91	12.12	69.89	-15.86	125	314	Average
*6000	57.26	45.14	12.12	76.9	-19.64	125	314	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.92	48.79	44.29	4.5	54	-5.21	338	284	Average
2389.92	59.73	55.23	4.5	74	-14.27	338	284	Peak
2412	96.12	91.57	4.55	54	42.12	338	284	Average
2412	103.41	98.86	4.55	74	29.41	338	284	Peak
4824	44.07	33.78	10.29	54	-9.93	196	151	Average
4824	55.03	44.74	10.29	74	-18.97	196	151	Peak
*6000	57.56	45.44	12.12	66.12	-8.56	106	276	Average
*6000	60.42	48.3	12.12	73.41	-12.99	106	276	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2412 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

EUT Test Condition		Measurement Detail	
Channel	Channel 6	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.66	51.42	46.42	5	54	-2.58	161	144	Average
2389.66	66.38	61.38	5	74	-7.62	161	144	Peak
2437	104.16	99.05	5.11	54	50.16	161	144	Average
2437	111.39	106.28	5.11	74	37.39	161	144	Peak
2483.52	47.34	42.15	5.19	54	-6.66	161	144	Average
2483.52	61.74	56.55	5.19	74	-12.26	161	144	Peak
4874	48.9	38.69	10.21	54	-5.1	122	76	Average
4874	54.63	44.42	10.21	74	-19.37	122	76	Peak
*5775	54.38	42.73	11.65	74.16	-19.78	126	73	Average
*5775	56.93	45.28	11.65	81.39	-24.46	126	73	Peak
*6000	47.67	35.55	12.12	74.16	-26.49	120	74	Average
*6000	49.42	37.3	12.12	81.39	-31.97	120	74	Peak
7311	48.39	35.93	12.46	54	-5.61	100	82	Average
7311	54.84	42.38	12.46	74	-19.16	100	82	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.94	44.1	39.09	5.01	54	-9.9	100	235	Average
2389.94	57.79	52.78	5.01	74	-16.21	100	235	Peak
2437	97.55	92.44	5.11	54	43.55	100	235	Average
2437	104.61	99.5	5.11	74	30.61	100	235	Peak
2483.56	42.98	37.79	5.19	54	-11.02	100	235	Average
2483.56	56.16	50.97	5.19	74	-17.84	100	235	Peak
4874	45.75	35.54	10.21	54	-8.25	143	85	Average
4874	49.42	39.21	10.21	74	-24.58	143	85	Peak
*5790	54.71	43.11	11.6	67.55	-12.84	133	226	Average
*5790	57.18	45.58	11.6	74.61	-17.43	133	226	Peak
*6000	48.24	36.12	12.12	67.55	-19.31	100	88	Average
*6000	50.94	38.82	12.12	74.61	-23.67	100	88	Peak
7311	51.89	39.43	12.46	54	-2.11	100	280	Average
7311	59.27	46.81	12.46	74	-14.73	100	280	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2437 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

EUT Test Condition		Measurement Detail	
Channel	Channel 11	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	100.19	95.05	5.14	54	46.19	160	145	Average
2462	107.36	102.22	5.14	74	33.36	160	145	Peak
2483.52	52.97	47.78	5.19	54	-1.03	160	145	Average
2483.52	64.57	59.38	5.19	74	-9.43	160	145	Peak
4924	41.11	30.86	10.25	54	-12.89	120	78	Average
4924	47.92	37.67	10.25	74	-26.08	120	78	Peak
*6000	47.91	35.79	12.12	70.19	-22.28	147	62	Average
*6000	49.03	36.91	12.12	77.36	-28.33	147	62	Peak

Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	93.76	88.62	5.14	54	39.76	100	234	Average
2462	100.74	95.6	5.14	74	26.74	100	234	Peak
2483.52	47.49	42.3	5.19	54	-6.51	100	234	Average
2483.52	59.02	53.83	5.19	74	-14.98	100	234	Peak
4924	32.77	22.52	10.25	54	-21.23	125	88	Average
4924	44.44	34.19	10.25	74	-29.56	125	88	Peak
*6000	50.62	38.5	12.12	63.76	-13.14	148	96	Average
*6000	52.48	40.36	12.12	70.74	-18.26	148	96	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2462 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

802.11n (HT20)

EUT Test Condition		Measurement Detail	
Channel	Channel 1	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	52.53	47.52	5.01	54	-1.47	121	21	Average
2390	65.37	60.36	5.01	74	-8.63	121	21	Peak
2412	101.4	96.34	5.06			126	18	Average
2412	108.68	103.62	5.06			126	18	Peak
4824	39.18	28.89	10.29	54	-14.82	136	221	Average
4824	47.52	37.23	10.29	74	-26.48	136	221	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	45.4	40.39	5.01	54	-8.6	100	305	Average
2390	60.05	55.04	5.01	74	-13.95	100	305	Peak
2412	96.51	91.45	5.06			356	305	Average
2412	103.95	98.89	5.06			356	305	Peak
4824	37.43	27.14	10.29	54	-16.57	119	105	Average
4824	46.84	36.55	10.29	74	-27.16	119	105	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2412 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

EUT Test Condition		Measurement Detail	
Channel	Channel 6	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	42.15	37.14	5.01	54	-11.85	125	27	Average
2390	53.2	48.19	5.01	74	-20.8	125	27	Peak
2437	105.85	100.74	5.11			122	18	Average
2437	113.78	108.67	5.11			122	18	Peak
2483.5	44.12	38.93	5.19	54	-9.88	125	27	Average
2483.5	56.75	51.56	5.19	74	-17.25	125	27	Peak
4874	42.04	31.83	10.21	54	-11.96	167	1	Average
4874	53.08	42.87	10.21	74	-20.92	167	1	Peak
7311	52.7	40.24	12.46	54	-1.3	100	64	Average
7311	63.58	51.12	12.46	74	-10.42	100	64	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	43.53	38.52	5.01	54	-10.47	400	270	Average
2390	57.44	52.43	5.01	74	-16.56	400	270	Peak
2437	102.95	97.84	5.11			400	264	Average
2437	110.2	105.09	5.11			400	264	Peak
2483.5	42.53	37.34	5.19	54	-11.47	400	270	Average
2483.5	55.15	49.96	5.19	74	-18.85	400	270	Peak
4874	37.6	27.39	10.21	54	-16.4	100	353	Average
4874	47.9	37.69	10.21	74	-26.1	100	353	Peak
7311	45.73	33.27	12.46	54	-8.27	226	9	Average
7311	56.93	44.47	12.46	74	-17.07	226	9	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2437 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

EUT Test Condition		Measurement Detail	
Channel	Channel 11	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	103.11	97.97	5.14			120	18	Average
2462	110.5	105.36	5.14			120	18	Peak
2483.5	50.42	45.23	5.19	54	-3.58	119	19	Average
2483.5	62.38	57.19	5.19	74	-11.62	119	19	Peak
4924	41.21	30.96	10.25	54	-12.79	230	4	Average
4924	51.56	41.31	10.25	74	-22.44	230	4	Peak
7386	42.63	30.07	12.56	54	-11.37	100	7	Average
7386	54.31	41.75	12.56	74	-19.69	100	7	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	95.86	90.72	5.14			112	319	Average
2462	103	97.86	5.14			112	319	Peak
2483.5	49.41	44.22	5.19	54	-4.59	376	264	Average
2483.5	62.18	56.99	5.19	74	-11.82	376	264	Peak
4924	37.44	27.19	10.25	54	-16.56	158	0	Average
4924	47.85	37.6	10.25	74	-26.15	158	0	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2462 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

802.11n (HT40)

EUT Test Condition		Measurement Detail	
Channel	Channel 3	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	52.93	47.92	5.01	54	-1.07	121	331	Average
2390	64.18	59.17	5.01	74	-9.82	121	331	Peak
2422	95.56	90.49	5.07			128	12	Average
2422	103.33	98.26	5.07			128	12	Peak
2483.5	39.92	34.73	5.19	54	-14.08	121	331	Average
2483.5	49.74	44.55	5.19	74	-24.26	121	331	Peak
4844	32.3	22.07	10.23	54	-21.7	167	304	Average
4844	41.87	31.64	10.23	74	-32.13	167	304	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	50.21	45.2	5.01	54	-3.79	400	268	Average
2390	60.54	55.53	5.01	74	-13.46	400	268	Peak
2422	93.5	88.43	5.07			400	262	Average
2422	101.16	96.09	5.07			400	262	Peak
2483.5	38.02	32.83	5.19	54	-15.98	400	268	Average
2483.5	48.43	43.24	5.19	74	-25.57	400	268	Peak
4844	33.69	23.46	10.23	54	-20.31	103	166	Average
4844	42.41	32.18	10.23	74	-31.59	103	166	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2422 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

EUT Test Condition		Measurement Detail	
Channel	Channel 6	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2385.32	46.3	41.32	4.98	54	-7.7	121	18	Average
2385.32	61.78	56.8	4.98	74	-12.22	121	18	Peak
2437	99.66	94.55	5.11			118	17	Average
2437	107.12	102.01	5.11			118	17	Peak
2488	46.19	40.98	5.21	54	-7.81	121	18	Average
2488	56.8	51.59	5.21	74	-17.2	121	18	Peak
4874	34.41	24.2	10.21	54	-19.59	162	101	Average
4874	45.86	35.65	10.21	74	-28.14	162	101	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	51.44	46.43	5.01	54	-2.56	355	285	Average
2390	62.84	57.83	5.01	74	-11.16	355	285	Peak
2437	94.6	89.49	5.11			358	306	Average
2437	101.87	96.76	5.11			358	306	Peak
2483.5	46.34	41.15	5.19	54	-7.66	355	285	Average
2483.5	56.57	51.38	5.19	74	-17.43	355	285	Peak
4874	35.26	25.05	10.21	54	-18.74	109	112	Average
4874	45.52	35.31	10.21	74	-28.48	109	112	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2437 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

EUT Test Condition		Measurement Detail	
Channel	Channel 9	Frequency Range	1 GHz ~ 25 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	38.03	33.02	5.01	54	-15.97	121	17	Average
2390	47.45	42.44	5.01	74	-26.55	121	17	Peak
2452	95.6	90.48	5.12			100	16	Average
2452	103.42	98.3	5.12			100	16	Peak
2483.5	52.5	47.31	5.19	54	-1.5	121	17	Average
2483.5	64.12	58.93	5.19	74	-9.88	121	17	Peak
4904	32.97	22.83	10.14	54	-21.03	177	231	Average
4904	43.31	33.17	10.14	74	-30.69	177	231	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	37.53	32.52	5.01	54	-16.47	400	274	Average
2390	47.37	42.36	5.01	74	-26.63	400	274	Peak
2452	91.97	86.85	5.12			350	265	Average
2452	99.63	94.51	5.12			350	265	Peak
2486.16	43.8	38.61	5.19	54	-10.2	400	274	Average
2486.16	57.87	52.68	5.19	74	-16.13	400	274	Peak
4904	31.36	21.22	10.14	54	-22.64	102	134	Average
4904	43.03	32.89	10.14	74	-30.97	102	134	Peak

Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value
- 2452 MHz: Fundamental frequency.
- The emission levels of other frequencies were very low against the limit.

9 kHz ~ 30 MHz Data:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

30 MHz ~ 1 GHz Worst-Case Data:

802.11g


EUT Test Condition		Measurement Detail	
Channel	Channel 1	Frequency Range	30 MHz ~ 1 GHz
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Quasi-peak (QP)
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
100.74	36.23	53.41	-17.18	43.5	-7.27	174	100	Peak
218.46	37.82	55.72	-17.9	46	-8.18	124	252	Peak
234.93	39.43	56.69	-17.26	46	-6.57	135	25	Peak
372.1	32.42	46.78	-14.36	46	-13.58	177	174	Peak
479.2	25.24	37.96	-12.72	46	-20.76	105	25	Peak
747.3	29.33	37.87	-8.54	46	-16.67	143	250	Peak
Antenna Polarity & Test Distance: Vertical at 3 m								
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
49.98	31.96	47.12	-15.16	40	-8.04	149	282	Peak
115.05	35.22	53.5	-18.28	43.5	-8.28	104	44	Peak
217.65	34.28	52.2	-17.92	46	-11.72	152	22	Peak
375.6	26.47	40.79	-14.32	46	-19.53	157	14	Peak
599.6	24.29	34.86	-10.57	46	-21.71	199	353	Peak
726.3	23.55	32.25	-8.7	46	-22.45	162	256	Peak


Remarks:

- Emission Level = Read Level + Factor
Margin value = Emission level – Limit value.
- The emission levels of other frequencies were very low against the limit.

Horizontal



Vertical



3.6 Conducted Emission Measurement

3.6.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

- Note: 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

3.6.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESR3	102412	Feb. 14, 2019	Feb. 13, 2020
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond2-01	Sep. 05, 2019	Sep. 04, 2020
LISN/AMN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Feb. 11, 2019	Feb. 10, 2020
LISN/AMN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Aug. 13, 2019	Aug. 12, 2020
Software ADT	BV ADT_Cond_ V7.3.7.4	NA	NA	NA

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-12047.

3.6.3 Test Procedures


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz – 30 MHz.

3.6.4 Deviation from Test Standard

No deviation.

3.6.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.6.6 EUT Operating Conditions

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.


3.6.7 Test Results

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Jisyong Wang	Test Date	2020/1/12

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16093	10.11	38.01	32.30	48.12	42.41	65.42	55.42	-17.30	-13.01
2	0.19500	10.12	34.64	31.01	44.76	41.13	63.82	53.82	-19.06	-12.69
3	0.26437	10.13	28.50	23.39	38.63	33.52	61.29	51.29	-22.66	-17.77
4	0.40425	10.16	22.30	20.82	32.46	30.98	57.77	47.77	-25.31	-16.79
5	1.20975	10.23	15.09	11.62	25.32	21.85	56.00	46.00	-30.68	-24.15
6	10.83975	10.44	19.23	13.72	29.67	24.16	60.00	50.00	-30.33	-25.84

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Jisyong Wang	Test Date	2020/1/12

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15346	10.16	37.74	31.47	47.90	41.63	65.81	55.81	-17.91	-14.18
2	0.19006	10.18	32.44	30.37	42.62	40.55	64.03	54.03	-21.41	-13.48
3	0.25748	10.19	28.51	25.57	38.70	35.76	61.51	51.51	-22.81	-15.75
4	0.40123	10.22	24.80	20.68	35.02	30.90	57.83	47.83	-22.81	-16.93
5	1.20300	10.29	12.71	10.19	23.00	20.48	56.00	46.00	-33.00	-25.52
6	10.52700	10.56	20.06	13.61	30.62	24.17	60.00	50.00	-29.38	-25.83

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



3.7 Conducted Output Power Measurement

3.7.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20 MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

3.7.2 Test Setup



3.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

3.7.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.7.5 Deviation from Test Standard

No deviation.

3.7.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.7.7 Test Results

Peak Power (For reference)

802.11b

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	157.036	21.96	30	Pass
6	2437	193.642	22.87	30	Pass
11	2462	92.683	19.67	30	Pass

802.11g

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	186.638	22.71	30	Pass
6	2437	363.915	25.61	30	Pass
11	2462	225.944	23.54	30	Pass

802.11n (HT20)

Channel	Frequency (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	19.92	19.10	179.473	22.54	30	Pass
6	2437	24.96	24.41	588.844	27.70	30	Pass
11	2462	21.39	21.46	277.971	24.44	30	Pass

802.11n (HT40)

Channel	Frequency (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	17.42	16.63	101.158	20.05	30	Pass
6	2437	21.24	20.67	249.459	23.97	30	Pass
9	2452	16.14	15.85	79.616	19.01	30	Pass

Average Power

802.11b

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	90.782	19.58	30	Pass
6	2437	114.025	20.57	30	Pass
11	2462	53.456	17.28	30	Pass

802.11g

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	44.875	16.52	30	Pass
6	2437	132.739	21.23	30	Pass
11	2462	58.210	17.65	30	Pass

802.11n (HT20)

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	13.82	12.98	43.954	16.43	30	Pass
6	2437	19.19	18.76	158.125	21.99	30	Pass
11	2462	15.00	15.15	64.417	18.09	30	Pass

802.11n (HT40)

Channel	Frequency (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	10.00	10.14	20.324	13.08	30	Pass
6	2437	14.00	14.37	52.481	17.20	30	Pass
9	2452	9.00	9.64	17.140	12.34	30	Pass

4 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---