

RF Exposure Report

Report No.: SA190618D07C

FCC ID: TK4WLE900VX (For WiFi)
N7NEM7455 (For LTE)

Test Model: WLE900VX (For WiFi)
EM7455 (For LTE)

Received Date: Mar. 18, 2020

Test Date: Mar. 26, 2020

Issued Date: Mar. 27, 2020

Applicant: Compex Systems Pte Ltd

Address: No 9 Harrison Road, Harrison Industrial Building, #05-01, 369651, Singapore

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

FCC Registration /
Designation Number: 198487 / TW2021



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 General Information	5
2.1 General Description of EUT	5
3 RF Exposure	9
2.1 Limits for Maximum Permissible Exposure (MPE).....	9
2.2 MPE Calculation Formula	9
2.3 Classification	9
2.4 Calculation Result of Maximum Conducted Power	10

Release Control Record

Issue No.	Description	Date Issued
SA190618D07C	Original release.	Mar. 27, 2020

1 Certificate of Conformity

Product: 802.11ac Dual Band Module (For WiFi)
Wireless Modules (For LTE)

Brand: COMPEX (For WiFi)
Sierra Wireless Inc. (For LTE)

Test Model: WLE900VX (For WiFi)
EM7455 (For LTE)

Sample Status: Engineering sample

Applicant: Compex Systems Pte Ltd

Test Date: Mar. 26, 2020

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Annie Chang , Date: Mar. 27, 2020
Annie Chang / Senior Specialist

Approved by : Rex Lai , Date: Mar. 27, 2020
Rex Lai / Associate Technical Manager

2 General Information

2.1 General Description of EUT

WiFi Module (FCC ID: TK4WLE900VX)

Product	802.11ac Dual Band Module
Brand	COMPEX
Test Model	WLE900VX
Status of EUT	Engineering sample
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode only.
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: up to 11Mbps 802.11g: up to 54Mbps 802.11a: up to 54Mbps 802.11n: up to 450Mbps 802.11ac: up to 1299.9Mbps
Operating Frequency	2412 ~ 2462MHz, 5180 ~ 5240MHz, 5745 ~ 5825MHz
Number of Channel	2412~2462MHz 11 for 802.11b, 802.11g, 802.11n (20MHz) 7 for 802.11n (40MHz) 5180~5240MHz 4 for 802.11a, 802.11n (20MHz), 802.11ac (20MHz) 2 for 802.11n (40MHz), 802.11ac (40MHz) 1 for 802.11ac (80MHz) 5745~5825MHz 5 for 802.11a, 802.11n (20MHz) 802.11ac (20MHz) 2 for 802.11n (40MHz) 802.11ac (40MHz) 1 for 802.11ac (80MHz)
Output Power	2412~2462MHz: 209.152mW 5180~5240MHz: 139.657mW 5745~5825MHz: 254.153mW
Antenna Type	Refer to note as below
Antenna Connector	Reverse SMA
Accessory Device	N/A
Data Cable Supplied	N/A

LTE Module (FCC ID: N7NEM7455)

Product	Wireless Modules	
Brand	Sierra Wireless Inc.	
Test Model	EM7455	
Status of EUT	MASS-PRODUCTION	
Power Supply Rating	3.3 Vdc (Host equipment)	
Modulation Type	WCDMA	QPSK
	LTE	QPSK, 16QAM
Frequency Range <WCDMA>	WCDMA	826.4 ~ 846.6 MHz, 1852.4 ~ 1907.6 MHz, 1712.4 ~ 1752.6 MHz
Frequency Range <LTE Band 4>	LTE Band 4 (Channel Bandwidth: 1.4 MHz)	1710.7 ~ 1754.3 MHz
	LTE Band 4 (Channel Bandwidth: 3 MHz)	1711.5 ~ 1753.5 MHz
	LTE Band 4 (Channel Bandwidth: 5 MHz)	1712.5 ~ 1752.5 MHz
	LTE Band 4 (Channel Bandwidth: 10 MHz)	1715.0 ~ 1750.0 MHz
	LTE Band 4 (Channel Bandwidth: 15 MHz)	1717.5 ~ 1747.5 MHz
	LTE Band 4 (Channel Bandwidth: 20 MHz)	1720.0 ~ 1745.0 MHz
Frequency Range <LTE Band 5>	LTE Band 5 (Channel Bandwidth: 1.4 MHz)	824.7 ~ 848.3 MHz
	LTE Band 5 (Channel Bandwidth: 3 MHz)	825.5 ~ 847.5 MHz
	LTE Band 5 (Channel Bandwidth: 5 MHz)	826.5 ~ 846.5 MHz
	LTE Band 5 (Channel Bandwidth: 10 MHz)	829 ~ 844 MHz
Frequency Range <LTE Band 7>	LTE Band 7 (Channel Bandwidth: 5 MHz)	2502.5 ~ 2567.5 MHz
	LTE Band 7 (Channel Bandwidth: 10 MHz)	2505 ~ 2565 MHz
	LTE Band 7 (Channel Bandwidth: 15 MHz)	2507.5 ~ 2562.5 MHz
	LTE Band 7 (Channel Bandwidth: 20 MHz)	2510 ~ 2560 MHz
Frequency Range <LTE Band 12>	LTE Band 12 (Channel Bandwidth: 1.4 MHz)	699.7 ~ 715.3 MHz
	LTE Band 12 (Channel Bandwidth: 3 MHz)	700.5 ~ 714.5 MHz
	LTE Band 12 (Channel Bandwidth: 5 MHz)	701.5 ~ 713.5 MHz
	LTE Band 12 (Channel Bandwidth: 10 MHz)	704.0 ~ 711.0 MHz
Frequency Range <LTE Band 13>	LTE Band 13 (Channel Bandwidth: 5 MHz)	779.5 ~ 784.5 MHz
	LTE Band 13 (Channel Bandwidth: 10 MHz)	782.0 MHz
Frequency Range <LTE Band 25>	LTE Band 25 (Channel Bandwidth: 1.4 MHz)	1850.7 ~ 1914.3 MHz
	LTE Band 25 (Channel Bandwidth: 3 MHz)	1851.5 ~ 1913.5 MHz
	LTE Band 25 (Channel Bandwidth: 5 MHz)	1852.5 ~ 1912.5 MHz
	LTE Band 25 (Channel Bandwidth: 10 MHz)	1855.0 ~ 1910.0 MHz
	LTE Band 25 (Channel Bandwidth: 15 MHz)	1857.5 ~ 1907.5 MHz
	LTE Band 25 (Channel Bandwidth: 20 MHz)	1860.0 ~ 1905.0 MHz
Frequency Range <LTE Band 26_Part 22>	LTE Band 26 (Channel Bandwidth: 1.4 MHz)	824.7 ~ 848.3 MHz
	LTE Band 26 (Channel Bandwidth: 3 MHz)	825.5 ~ 847.5 MHz
	LTE Band 26 (Channel Bandwidth: 5 MHz)	826.5 ~ 846.5 MHz
	LTE Band 26 (Channel Bandwidth: 10 MHz)	829 ~ 844 MHz
	LTE Band 26 (Channel Bandwidth: 15 MHz)	831.5 ~ 841.5 MHz

Frequency Range <LTE Band 26_Part 90S>	LTE Band 26 (Channel Bandwidth: 1.4 MHz)	814.7 ~ 823.3 MHz
	LTE Band 26 (Channel Bandwidth: 3 MHz)	815.5 ~ 822.5 MHz
	LTE Band 26 (Channel Bandwidth: 5 MHz)	816.5 ~ 821.5 MHz
	LTE Band 26 (Channel Bandwidth: 10 MHz)	819 MHz
Frequency Range <LTE Band 30>	LTE Band 30 (Channel Bandwidth: 5 MHz)	2307.5 ~ 2312.5 MHz
	LTE Band 30 (Channel Bandwidth: 10 MHz)	2310 MHz
Frequency Range <LTE Band 41>	LTE Band 41 (Channel Bandwidth: 5 MHz)	2498.5 ~ 2687.5 MHz
	LTE Band 41 (Channel Bandwidth: 10 MHz)	2501.0 ~ 2685.0 MHz
	LTE Band 41 (Channel Bandwidth: 15 MHz)	2503.5 ~ 2682.5 MHz
	LTE Band 41 (Channel Bandwidth: 20 MHz)	2506.0 ~ 2680.0 MHz
Antenna Type	LTE Band 5 & 26	Dipole Antenna with 3.2 dBi gain
	LTE Band 25	Dipole Antenna with 1.56 dBi gain
	LTE Band 4	Dipole Antenna with 1.62 dBi gain
	LTE Band 12	Dipole Antenna with 1.49 dBi gain
	LTE Band 13	Dipole Antenna with 1.66 dBi gain
	LTE Band 7 & 41	Dipole Antenna with 0.86 dBi gain
	LTE Band 30	Dipole Antenna with 2.27 dBi gain
	WCDMA_826.4 ~ 846.6 MHz	Dipole Antenna with 3.2 dBi gain
	WCDMA_1852.4 ~ 1907.6 MHz	Dipole Antenna with 1.56 dBi gain
	WCDMA_1712.4 ~ 1752.6 MHz	Dipole Antenna with 1.62 dBi gain
Accessory Device	N/A	
Data Cable Supplied	N/A	

Note:

1. The EUT provides 3 completed transmitter and 3 receiver.

Modulation Mode	TX Function
802.11a	1TX
802.11b	1TX
802.11g	1TX
802.11n (20MHz)	3TX
802.11n (40MHz)	3TX
802.11ac (20MHz)	3TX
802.11ac (40MHz)	3TX
802.11ac (80MHz)	3TX

2. This report is prepared for FCC class II permissive change.

3. 2.4GHz and 5GHz modes cannot transmit simultaneously.

4. WiFi & LTE technologies can transmit at same time.

5. The emission of the simultaneous operation has been evaluated and no non-compliance was found.

6. The antenna information is listed as below:

Description	Platform: Network Security Appliance (Brand: Check Point / Model: V-81WLR)
Antenna Model	RFDPA171300SBLB801
Antenna Type	Dipole Antenna
Maximum Gain (dBi)	2412-2462MHz: 2.22 5180-5825MHz: 4.29

The Platform is authorized for use frequency bands: 2412-2462MHz, 5180-5240MHz and 5745-5825MHz only.

7. Accessory device of Platform as follows.

Brand	Model	Rating
FSP	FSP120-AHAN3	AC I/P : 100-240V ~ 2.0A 50-60Hz DC O/P: 12.0V ===10.0A 120.0W Power cord: Non-shielded AC 3 Pin (1.8m) Non-shielded DC cable (1.45m) with one ferrite core

8. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 29cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Calculation Result of Maximum Conducted Power

WiFi Module (FCC ID: TK4WLE900VX)

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	23.20	6.99	29	0.0989	1
5180-5240	21.45	9.06	29	0.1064	1
5745~5825	24.05	9.06	29	0.1936	1

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- 2.4GHz: Directional gain = 2.22dBi + 10log(3) = 6.99dBi
5.0GHz: Directional gain = 4.29dBi + 10log(3) = 9.06dBi

LTE Module (FCC ID: N7NEM7455)

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA II: 1852.4 ~ 1907.6 MHz	22.90	1.56	29	0.0264	1.00
WCDMA V: 826.4 ~ 846.6 MHz	23.45	3.2	29	0.0438	0.55
WCDMA IV: 1712.4 ~ 1752.6 MHz	22.88	1.62	29	0.0267	1.00
LTE Band 4: 1710.7 ~ 1754.3 MHz	22.60	1.62	29	0.0250	1.00
LTE Band 5: 824.7 ~ 848.3 MHz	23.15	3.2	29	0.0408	0.55
LTE Band 7: 2502.5 ~ 2567.5 MHz	21.02	0.86	29	0.0146	1.00
LTE Band 12: 699.7 ~ 715.3 MHz	23.20	1.49	29	0.0279	0.47
LTE Band 13: 779.5 ~ 784.5 MHz	23.06	1.66	29	0.0281	0.52
LTE Band 25: 1850.7 ~ 1914.3 MHz	22.24	1.56	29	0.0227	1.00
LTE Band 26 Part 22: 824.7 ~ 848.3 MHz	22.98	3.2	29	0.0393	0.55
LTE Band 26 Part 90S: 814.7 ~ 823.3 MHz	22.97	3.2	29	0.0392	0.54
LTE Band 30: 2307.5 ~ 2312.5 MHz	21.25	2.27	29	0.0213	1.00
LTE Band 41: 2498.5 ~ 2687.5 MHz	20.91	0.86	29	0.0142	1.00

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Simultaneously transmitter condition:

$$WLAN\ 5GHz + LTE = 0.1936 + 0.0438/0.55 = 0.2732$$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---