

MPE CALCULATION

FCC ID: TK4WLM200N5-23ESD

RF Exposure Requirements:	47 CFR §1. 1307(b)
RF Radiation Exposure Limits:	47 CFR §1. 1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65
EUT Frequency Band:	5160-5825MHz
Limits for General Population/Uncontrolled Exposure in the band of:	1500 - 100,000 MHz
Power Density Limit:	1 mW / cm ²

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain


R = distance to the center of radiated antenna

Prediction distance 80cm

Mode	Distance (cm)	Conducted power (dBm)	Max. Antenna Gain (dBi)	Apprarent Gain (dBi)	Power Density (mW/ cm ²)	Limit (mW/ cm ²)
WLAN (5GHz)	80	23.04	23	26	0.99	0.99

The Above Result had shown that the Device complied with MPE requirement.

Completed By: Teody Manansala



SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: March 16, 2016