





CURTIS-STRAUS

Test Report

Report No	H0825-2
Client	InterSense, Inc
Address	36 Crosby Drive Bedford, MA 01730
Phone	781-541-7616
Items tested	IS900 Micro-Transmitter
FCC ID	TK5910EWTX
IC ID	6414A-910EWTX
FRN	0013917356
Equipment Code	DTS
Emission Designator	2M70G1D
FCC/IC Rule Parts	47 CFR 15.247, RSS 210 issue 7 and RSS GEN issue 2
Test Dates	July 19 th , 20 th , 26 th , and 29 th 2007
Results	As detailed within this report
Prepared by	 David Harris – Test Engineer
Authorized by	 Michael Buchholz – EMC Manager
Issue Date	<u>8/30/07</u>
Conditions of Issue	This Test Report is issued subject to the conditions stated in the 'Conditions of Testing' section on page 31 of this report.

Curtis-Straus LLC is accredited to ISO/IEC 17025 by A2LA for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation. See our scope of accreditation at the end of this test report. Any opinions or interpretations expressed in this report are outside the scope of our A2LA accreditation as A2LA only accredits testing.

Testing Cert. No. 1627-01

Contents

Contents	2
Summary	3
Test Methodology	3
Product Tested - Configuration Documentation	4
<i>Statement of Conformity</i>	5
Test Results	6
<i>Bandwidth</i>	6
<i>Peak Power</i>	8
<i>Band Edge Measurements</i>	10
<i>Duty Cycle Correction Calculation</i>	12
<i>Radiated Spurious Emissions</i>	14
<i>Conducted Spurious Emissions</i>	15
<i>Power Spectral Density</i>	20
<i>AC Line Conducted Emissions</i>	22
<i>Voltage Variations</i>	23
<i>Occupied Bandwidth</i>	24
Test Equipment Used	26
Conditions Of Testing	31
A2LA Accreditation	33

Form Final Report REV 7-20-07 (DW)

Summary

This test report supports an application for certification of a transmitter operating pursuant to 47 CFR 15.247 and RSS-210. The product is the IS900 Micro-Transmitter MN100-91000-EWTX. It is a transceiver that operates in the range 2405-2480MHz.

We found that the product met the above requirements without modification. The test sample was received in good condition.

Test Methodology

Radiated emission and AC Line conducted testing was performed according to the procedures specified in ANSI C63.4 (2003) and RSS-GEN. Radiated Emissions were maximized by rotating the device around three orthogonal axes as well as varying the test antenna's height and polarity. The device antenna cannot be maximized separately.

The EUT does not have an antenna gain <6dBi. Therefore there is no limit reduction. [15.247 (b) (4)]

Conducted emission at the antenna port was performed as required by rule section.

The EUT operating voltage is 3.7Vdc powered by a battery. A fresh battery was used for testing.

The environmental conditions are shown below.

Date	Temperature	Humidity
7/19/07	24.4°C	49%
7/20/07	24.8°C	41%
7/26/07	25.1°C	38%
7/29/07	25.1°C	39%

The following bandwidths were used during radiated spurious and line conducted emissions.

Frequency	RBW	VBW
0.15-30MHz	9kHz	30kHz
30-1000MHz	120kHz	1MHz
1-25GHz	1MHz	3MHz

Release Control Record

Issue No. Reason for change
1 Original Release

Date Issued
August 30, 2007

Product Tested - Configuration Documentation

EUT Configuration				
Work Order: H0825 Company: InterSense, Inc Company Address: 36 Crosby Drive Bedford, MA 01730 Contact: Bob Hommel				
EUT	MN	SN		
Transmitter 100-91000-EWTX ETX-0707254-A EUT Description: Wireless Wand and Head Tracker System EUT Max Frequency: 2.48GHz				
Support Equipment:	MN	SN		
Head Tracker	100-91003-AWHT	UHT-0707258-A		
Receiver	100-IS9MW-RX16	I9W-0707260-A		
Compaq Presario Laptop	1670	1V92CGX3P4TS		
Serial to RS232 Dongle	N/A	NA		
Dongle Supply (9Vdc)	KSAFE0900275T1M2	NA		
EUT Cables:	Qty	Shielded?	Length	Ferrites
Head Tracker Cable	1	Braid	1m	None
Receiver Cable	1	Braid	1m	None
Charger side of charger power cable	1	Braid	1.5m	None
Mains side of charger power cable	1	None	1.5m	None
Unpopulated EUT Ports:	Qty	Reason		
None				
Software / Operating Mode Description:				
EUT uses DSS in the 2.4 to 2.48GHz range. 16 channels can be selected at 5MHz spacing. No frequency hopping is implemented. EUT uses three different programs. DeviceTool allows you to change channels, FCC_Wireless puts the EUT in normal pulse mode operation. FCC_Direct.exe allows you to put the EUT in continuous Tx mode, with or without modulation.				

Statement of Conformity

The IS900 Micro-Transmitter has been tested and found to conform to the following parts of 47 CFR, RSS-GEN and RSS 210 as detailed below:

RSS-GEN	RSS 210	Part 15	Comments
5.3		15.15(b)	There are no controls accessible to the user that varies the output power.
5.2		15.19	The label is shown in the label exhibit.
7.1.5		15.21	Information to the user is shown in the instruction manual exhibit.
		15.27	No special accessories are required for compliance.
		15.31	The EUT was tested in accordance with the measurement standards in this section.
		15.33	Frequency range was investigated according to this section, unless noted in specific rule section under which the equipment operates.
		15.35	The EUT emissions were measured using the measurement detector and bandwidth specified in this section, unless noted in specific rule section under which the equipment operates.
7.1.4		15.203	The antenna for this device is hardwired to the PCB.
	2.6	15.205 15.209	The fundamental is not in a Restricted band and the spurious and harmonic emissions in the Restricted bands comply with the general emission limits of 15.209.
7.2.2		15.207	EUT meets the AC Line conducted emissions requirements of 15.207.
	Annex 8	15.247	The unit complies with the requirements of 15.247
4.6.1			Occupied Bandwidth measurements were made.

Test Results**Bandwidth****LIMIT**

The minimum 6 dB bandwidth shall be at least 500 kHz. [15.247(a) (2)]


MEASUREMENTS / RESULTS

RBW = 100kHz

VBW = 3MHz


Measured 6dB bandwidth = Channel 0 – 1.625MHz
 Channel 7 – 1.615MHz
 Channel 15 – 1.605MHz

All readings exceed the limit of 500kHz therefore the EUT passes the requirement.

PLOTS

Agilent 12:37:16 Jul 29, 2007


R T



Channel 7 6dB Bandwidth

Agilent 13:04:32 Jul 29, 2007

R T



Channel 15 6dB Bandwidth

Peak Power**LIMIT**

Conducted Output Power at the antenna port

1 Watt

[15.247(b) (3)]

MEASUREMENTS / RESULTS

RBW = 3MHz


VBW = 3MHz

Cable loss factored into Spectrum Analyzer Reading.

Measured conducted output power – Channel 0 = -6.523dBm = 0.00022W

Channel 7 = -5.764dBm = 0.00027W


Channel 15 = -5.007dBm = 0.00032W

All power readings are below the limit 1 Watt therefore the EUT passes the requirement.**PLOTS**

Channel 0 Peak Conducted Output Power Channel 0

* Agilent 13:54:23 Jul 29, 2007


R T



Channel 0 Peak Conducted Output Power Channel 7

* Agilent 13:21:56 Jul 29, 2007

R T



Channel 0 Peak Conducted Output Power Channel 15

Band Edge Measurements

LIMITS

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

[15.247(d)]


MEASUREMENTS / RESULTS

Band Edge								Curtis-Straus LLC					
Date: 20-Jul-07				Company: Intersense				Work Order: H0825					
Engineer: David Harris				EUT Desc: Wireless Head Tracker Transmitter									
Measurement Distance: 3 m													
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dBμV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	DCC Factor (dB)	Adjusted Reading (dBμV/m)	---			FCC Part 15.209		
											Limit (dBμV/m)	Margin (dB)	Result (Pass/Fail)
Hpk	2390.0	15.7	0.0	28.9	1.4	0.0	46.0				74.0	-28.0	Pass
Hav	2390.0	15.7	0.0	28.9	1.4	20.0	26.0				54.0	-28.0	Pass
Hpk	2483.5	19.5	0.0	29.1	1.4	0.0	50.0				74.0	-24.0	Pass
Hav	2483.5	19.5	0.0	29.1	1.4	20.0	30.0				54.0	-24.0	Pass
Table Result: Pass by -14.9 dB Worst Freq: 2483.5 MHz													
Test Site: "T"		Pre-Amp: none		Cable: EMIR-HIGH-14		Analyzer: Orange		Antenna: Black Horn					

RBW = 1MHz

VBW = 3MHz


PLOTS



Low Bandedge Channel 0

* Agilent 15:10:28 Jul 20, 2007

R T



C:\temp.gif file saved

High Bandedge Channel 15

Duty Cycle Correction Calculation

MEASUREMENTS / CALCULATIONS

EUT on time = 1.012mS

of transmits in 100mS = 4


Total on time = 1.012 x 4 = 4.048mS

Duty Cycle = 4.048/100 = .04048 = 4.0484%

DCCF = $20\log(4.048/100) = -27.8552\text{dB}$

Max DCCF = -20dB


PLOTS



EUT on Time of Single Pulse

Agilent 12:21:01 Jul 29, 2007

R T



Of Transmits in 100ms (worst case)

Radiated Spurious Emissions

LIMITS

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

[15.247(d)]

MEASUREMENTS / RESULTS

Harmonics (pulsed emissions)								Curtis-Straus LLC				
Date: 26-Jul-07			Company: Intersense					Work Order: H0825				
Engineer: David Harris			EUT Desc: Wireless Head Tracker Transmitter									
Frequency Range: 1-18GHz							Measurement Distance: 3 m					
Notes: Radiated Spurious Emissions Harmonics 20dB DCCF							EUT Max Freq: 2.4GHz					
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dBμV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dBμV/m)	---			FCC Part 15.209		
										Limit (dBμV/m)	Margin (dB)	Result (Pass/Fail)
Channel 0			---	---	---	---				---	---	---
Vpk	4810.0	61.6	39.5	33.0	1.8	56.9				74.0	-17.1	Pass
Vav	4810.0	41.6	39.5	33.0	1.8	36.9				54.0	-17.1	Pass
Channel 7			---	---	---	---				---	---	---
Vpk	4880.0	61.2	39.4	33.1	1.8	56.7				74.0	-17.3	Pass
Vav	4880.0	41.2	39.4	33.1	1.8	36.7				54.0	-17.3	Pass
Channel 15			---	---	---	---				---	---	---
Vpk	4960.0	61.7	39.7	33.2	1.8	57.0				74.0	-17.0	Pass
Vav	4960.0	41.7	39.7	33.2	1.8	37.0				54.0	-17.0	Pass
Table Result: Pass by -17.0 dB Worst Freq: 4960.0 MHz												
Test Site: "F"		Pre-Amp: Brown		Cable: EMIR-HIGH-21		Analyzer: Orange		Antenna: Orange Horn				

Radiated Emissions Table										Curtis-Straus LLC		
Date: 26-Jul-07			Company: Intersense							Work Order: H0825		
Engineer: David Harris			EUT Desc: Wireless Wand									
Frequency Range: 1-18GHz							Measurement Distance: 3 m					
Notes: Radiated Spurious Emissions 10Hz VBW							EUT Max Freq: 2.4GHz					
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dBμV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dBμV/m)	---			FCC Class B		
							Limit (dBμV/m)	Margin (dB)	Result (Pass/Fail)	Limit (dBμV/m)	Margin (dB)	Result (Pass/Fail)
Channel 15 Vpk	4955.5	52.9	39.6	33.2	1.8	48.3				54.0	-5.7	Pass
Table Result:			Pass	by	-5.7 dB					Worst Freq: 4955.5 MHz		
Test Site: "F"		Pre-Amp: Brown		Cable: EMIR-HIGH-21		Analyzer: Orange		Antenna: Orange Horn				

No emissions were found in the range 18-25GHz.

Conducted Spurious Emissions

LIMITS

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth that contains the highest level of desired power...


[15.247(d)]

MEASUREMENTS / RESULTS

RBW = 100kHz


VBW = 3MHz

EUT was in TX/RX mode. All Spurious and Harmonic emission are at least 20dB below that of the fundamental; therefore the EUT passes the requirement. See plots for data.



* Agilent 16:32:16 Jul 29, 2007


R T



30-1000MHz Channel 0

* Agilent 16:29:08 Jul 29, 2007


R T



1-5GHz Channel 0

Agilent 16:39:27 Jul 29, 2007


R T



30-1000MHz Channel 7

Agilent 14:08:28 Jul 29, 2007


R T



1-5GHz Channel 7

Agilent 16:38:17 Jul 29, 2007


R T



5-25GHz Channel 7

Agilent 16:47:38 Jul 29, 2007


R T



30-1000MHz Channel 15

* Agilent 16:44:38 Jul 29, 2007


R T



1-5GHz Channel 15

* Agilent 16:46:17 Jul 29, 2007

R T



5-25GHz Channel 15

Power Spectral Density

LIMIT


...the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
[15.247(e)]

MEASUREMENTS / RESULTS

Highest Power Spectral Density – Channel 0 = -20.72dBm
Channel 7 = -20.09dBm
Channel 15 = -19.79dBm

All measurements are below the 8dBm limit therefore the EUT meets the requirement.


PLOTS



Channel 0 Power Spectral Density

* Agilent 17:17:51 Jul 29, 2007

R T


Mkr1 2.44008625 GHz
-20.09 dBm

C:\SCREN473.GIF file saved

Channel 7 Power Spectral Density

* Agilent 17:06:21 Jul 29, 2007

R T

Mkr1 2.47975500 GHz
-19.79 dBm

C:\SCREN472.GIF file saved

Channel 15 Power Spectral Density

AC Line Conducted Emissions**LIMITS**

Frequency of emission (MHz)	Quasi-peak limit (dBμV)	Average limit (dBμV)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

[47 CFR 15.207(a)]

MEASUREMENTS / RESULTS

AC line conducted emissions test is Not Applicable on the EUT because the EUT is battery powered. However the battery charger was tested with the EUT Charging.

AC Mains Conducted Emissions											Curtis-Straus LLC		
Date: 19-Jul-07			Company: Intersense					Work Order: H0825					
Engineer: David Harris			EUT Desc: Charger Dock					Test Site: EMI 2					
Notes:													
Measurement Device: Yellow-Black LISN													
Range: 0.15-30MHz													
Spectrum Analyzer: Yellow													
Frequency (MHz)	Q.P. Readings		Ave. Readings		Impedance Factor	---		FCC Part 15.209		FCC Part 15.209		Overall Result (Pass/Fail)	
	QP1 (dBµV)	QP2 (dBµV)	AV1 (dBµV)	AV2 (dBµV)		Limit (dBµV)	Margin dB	qp Limit (dBµV)	qp Margin dB	AVE Limit (dBµV)	AVE Margin dB		
0.15	29.0	29.5	8.0	11.5	20.6	---	---	66.0	-15.9	56.0	-23.9	Pass	
1.00	0.7	1.0	0.4	0.3	20.1	---	---	56.0	-34.9	46.0	-25.5	Pass	
5.00	2.4	2.6	1.6	1.4	20.1	---	---	56.0	-33.3	46.0	-24.3	Pass	
10.00	3.0	3.2	1.5	1.3	20.1	---	---	60.0	-36.7	50.0	-28.4	Pass	
15.00	3.2	3.2	1.4	1.4	20.2	---	---	60.0	-36.6	50.0	-28.4	Pass	
25.00	3.2	3.3	1.2	1.3	20.3	---	---	60.0	-36.4	50.0	-28.4	Pass	
Table Result: Pass by -15.89 dB Worst Freq: 0.15 MHz													

Voltage Variations

REQUIREMENT

Measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery powered equipment, the equipment tests shall be performed using a new battery.

[15.31(e)]

MEASUREMENTS / RESULTS

Voltage Variations test is Not Applicable because the EUT is battery powered.


Occupied Bandwidth

REQUIREMENT

When an occupied bandwidth is no specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99% emission bandwidth, as calculated or measured.
[RSS-GEN 4.6.1]

Agilent 17:59:44 Jul 29, 2007

R T




Transmit Freq Error -2.767 kHz
x dB Bandwidth 2.863 MHz*

C:\temp.gif file saved

99% Occupied Bandwidth Channel 0

* Agilent 18:02:49 Jul 29, 2007

R T



Center 2.44 GHz Span 3 MHz
#Res BW 30 kHz #VBW 300 kHz Sweep 5.288 ms (401 pts)

Occupied Bandwidth
2.3258 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error 7.915 kHz
x dB Bandwidth 2.806 MHz*

C:\temp.gif file saved

99% Occupied Bandwidth Channel 7

* Agilent 18:06:38 Jul 29, 2007

R T



Center 2.48 GHz Span 3 MHz
#Res BW 30 kHz #VBW 300 kHz Sweep 5.288 ms (401 pts)

Occupied Bandwidth
2.3785 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -14.794 kHz
x dB Bandwidth 2.804 MHz*

C:\temp.gif file saved

99% Occupied Bandwidth Channel 15

Test Equipment Used

REV. 30-JUL-2007

SPECTRUM ANALYZERS / RECEIVERS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	9kHz-1.8GHz	8591E	Agilent	3441A03559	00024	I	08-JAN-2008
WHITE	9kHz-22GHz	8593E	Agilent	3547U01252	00022	I	06-OCT-2007
BLUE	9kHz-1.8GHz	8591E	Agilent	3223A00227	00070	I	18-DEC-2007
YELLOW	9kHz-2.9GHz	8594E	Agilent	3523A01958	00100	I	08-JUN-2008
GREEN	9kHz-26.5GHz	8593E	Agilent	3829A03618	00143	I	Out of Cal
BLACK	9kHz-12.8GHz	8596E	Agilent	3710A00944	00337	I	Out of Cal
TELECOM 3585A	20Hz-40.0MHz	3585A	Agilent	2504A05219	00030	I	15-FEB-2008
TELECOM 3585A	20Hz-40.0MHz	3585A	Agilent	1750A03418	00558	I	Out of Service
TELECOM 3585A	20Hz-40.0MHz	3585A	Agilent	1750A02762	01067	I	Out of Service
ORANGE	9kHz-26.5GHz	E4407B	Agilent	US39440975	00394	I	Out of Service
GOLD	100Hz-26.5 GHz	E4407B	Agilent	MY45113816	1284	I	25-JUL-2008
REFERENCE EMI TEST RECEIVER	20-1000MHz	ESVS30	R&S	827957/001	01098	I	To be determined
RENTAL SA #1 (BROWN)	9kHz-26.5GHz	E4407B	Agilent	SG44210511	Rental	I	01-FEB-2008
RENTAL SA #2	100Hz-26.5 GHz	E7405A	Agilent	MY44212795	Rental	I	28-DEC-2007
RENTAL SA #3	9kHz-1.8GHz	8591EM	Agilent	3536A00617	Rental	I	25-JUL-2008
RENTAL SA #4	100Hz-3 GHz	E7402A	Agilent	MY45103221	Rental	I	23-JUL-2008

LISNS/MEASUREMENT PROBES	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	9kHz-50MHz	8012-50-R-24-BNC	SOLAR	956348	00753	I	06-JUN-2008
BLUE (DC)	50kHz-50MHz	8012-50-R-24-BNC	SOLAR	956349	00752	I	06-JUN-2008
YELLOW-BLACK	9kHz-50MHz	8012-50-R-24-BNC	SOLAR	0411657	00248	I	24-MAY-2008
ORANGE	9kHz-30MHz	8012-50-R-24-BNC	SOLAR	903707	00754	I	07-MAY-2008
GOLD (DC)	9kHz-50MHz	8012-50-R-24-BNC	SOLAR	984734	00247	I	13-JUN-2008
BROWN	50kHz-50MHz	8012-50-R-24-BNC	SOLAR	0411656	00986	I	12-JUN-2008
GREEN	9kHz-50MHz	8012-50-R-24-BNC	SOLAR	984735	00987	I	12-JUN-2008
YELLOW	9kHz-50MHz	8012-50-R-24-BNC	SOLAR	0411658	1080	I	06-JUN-2008
WHITE-BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972019	00678	I	17-MAY-2008
BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972017	00675	I	18-MAY-2008
RED-BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972016	00677	I	18-MAY-2008
BLUE-BLACK	10kHz-30MHz	8610-50-TS-100-N	SOLAR	972018	00676	I	17-MAY-2008
BLUE MONITORING PROBE	0.01-150MHz	91550-2	TEGAM	12350	00807	I	31-MAY-2009
YELLOW MONITORING PROBE	0.01-150MHz	91550-2	ETS	50972	00493	I	23-JAN-2008
GREEN CURRENT TRANSFORMER	40Hz-20MHz	150	PEARSON	10226	00793	I	19-APR-2009
BLUE CISPR LINE PROBE	10kHz-50MHz	N/A	C-S	N/A	00805	II	08-JUN-2009
BLACK CISPR LINE PROBE	10kHz-50MHz	N/A	C-S	N/A	1254	II	08-JUN-2009
CISPR TELCO VOLTAGE PROBE	10kHz-30MHz	CS A/C-10	C-S	CS01	00296	II	17-NOV-2007
CISPR 22 TELCO ISN	9kHz-30MHz	FCC-TLISN-T4	FISCHER	20115	00746	I	15-NOV-2007

OPEN AREA TEST SITES (OATS)	FCC CODE	IC CODE	VCCI CODE	CAT	CALIBRATION DUE
SITE F	93448	IC 2762A-1	R-1688	II	23-JUN-2008
SITE T	93448	IC 2762A-2	R-905	II	23-JUN-2008
SITE A	93448	IC 2762-A	R-903	II	20-JUN-2008
SITE M	93448	IC 2762-M	R-904	II	19-JUN-2008
SITE J	93448	IC 2762A-3	R-2377	II	12-APR-2008

CONDUCTED TEST SITES (MAINS / TELCO)	FCC CODE	IC CODE	VCCI CODE	CAT	CALIBRATION DUE
EMI 1	93448	N/A	C-1801, T-268	III	NA
EMI 2	93448	N/A	C-1802, T-269	III	NA
EMI 3	93448	N/A	C-1803, T-270	III	NA

MIXERS/DIPLEXERS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
MIXER / HORN	26.5-40 GHz	11970A/28-442-6	HP/ATM	2332A01695/A046903-01	1087	I	23-AUG-2007
MIXER / HORN	26.5-40 GHz	11970A/28-442-6	HP/ATM	3003A07825/A046903-01	1086	I	19-SEP-2007
MIXER / HORN	40-60 GHz	M19HW/A	OML	U30110-1	00821	I	29-JUN-2009
MIXER	33-50 GHz	11970Q	HP	3003A03155	00104	I	08-NOV-2007
MIXER / HORN	50-75 GHz	11970V /QWH-VPRROO	HP/QUINSTAR	2521A01197/8794001	1179	I	15-NOV-2007
MIXER	75-110 GHz	11970W	HP	2521A01334	00105	I	22-NOV-2007
MIXER / HORN	60-90 GHz	M12HW/A	OML	E30110-1	00822	I	29-JUN-2009
MIXER / HORN	90-140 GHz	MO8HW/A	OML	F21206-1	00811	I	29-JUN-2009
MIXER / HORN	140-220 GHz	MO5HW/A	OML	G21206-1	00812	I	29-JUN-2009

DIPLEXER	40-220 GHz	DPL.26	OML	N/A	00813	I	29-JUN-2009
----------	------------	--------	-----	-----	-------	---	-------------

ABSORBING CLAMPS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
FISCHER CLAMP	30-1000MHZ	F-201-23MM	FISCHER	10	00081	I	20-JAN-2008

HARMONIC & FLICKER ANALYZER	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
HFTS	HP6842A	HP	3531A-00169	00738	II	OUT OF CAL
10001I/2 AC POWER SYSTEM	(2) 500I	CALIFORNIA INSTRUMENTS	HK53687/HK53688	00376	II	09-JAN-2008

PREAMPS / ATTENUATORS / FILTERS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	0.009-2000MHZ	ZFL-1000-LN	C-S	N/A	00798	II	20-APR-2008
BLUE	0.009-2000MHZ	ZFL-1000-LN	C-S	N/A	00759	II	17-APR-2008
BLUE-BLACK	0.009-2000MHZ	ZFL-1000-LN	C-S	N/A	00800	II	18-JAN-2008
GREEN	0.009-2000MHZ	ZFL-1000-LN	C-S	N/A	00802	II	02-MAY-2008
BLACK	0.009-2000MHZ	ZFL-1000-LN	C-S	N/A	00799	II	19-JUL-2008
ORANGE	0.009-2000MHZ	ZFL-1000-LN	C-S	N/A	00765	II	02-MAY-2008
RED-WHITE	0.009-2000MHZ	ZFL-1000-LN	C-S	N/A	1258	II	08-MAY-2008
WHITE	1-20GHZ	SMC-12A	C-S	426643	00760	II	09-JUL-2008
BROWN	1-20GHZ	PM2-38-218-4R5-17-15-SFF	C-S	PL1655	1132	II	02-APR-2008
YELLOW-BLACK	1-20GHZ	SMC-12A	C-S	535055	00801	II	OUT OF SERVICE
RED-GREEN	1-20GHZ	PM2-38-218-4R5-17-15-SFF	C-S	N/A	1256	II	14-AUG-2007
RED-BLUE	1-20GHZ	PE2-38-218-4R5-17-15-SFF	C-S	PL3177	1257	II	19-APR-2008
HF (YELLOW)	18-26.5GHZ	AFS4-18002650-60-8P-4	C-S	467559	1266	I	23-AUG-2007
HIGH PASS FILTER	1-18 GHZ	SPA-F-55204	K&L	36	00817	II	05-JAN-2008
LOW PASS FILTER	1-9 GHZ	11SL10-4100/X4400-O/O	K&L	4	00816	II	05-JAN-2008
HIGH PASS FILTER	2.3-5.5 GHZ	VHP-19	MINI-CIRCUITS	NA	1287	II	05-JAN-2008
HIGH PASS FILTER	1.9-2.7 GHZ	VHP-16	MINI-CIRCUITS	NA	1288	II	05-JAN-2008
HF 20dB 50W ATTENUATOR	0.03-20 GHZ	PE 7019-20	PASTERNAK	01	00791	II	08-MAY-2009
HF 30dB 50W ATTENUATOR	0.03-20 GHZ	PE 7019-30	PASTERNAK	02	1168	II	08-MAY-2009
40dB 100W ATTENUATOR	0.09-4000MHZ	BW-40N100W+	MINI-CIRCUITS	V N014900638	1231	II	08-NOV-2007
RFI-Low 130 KHz LPF	10-100kHz PASS	130 KHz LPF	KIWA	NA	1235	II	12-MAR-2008

ANTENNAS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
GREEN BILOG	30-2000MHZ	CBL6112B	CHASE	2742	00620	II	13-JAN-2008
GREEN-BLACK BILOG	30-2000MHZ	CBL6112B	CHASE	2412	00127	II	13-JAN-2008
GREEN-RED BILOG	30-2000MHZ	CBL6112B	CHASE	2435	00990	I	12-APR-2008
BLUE BILOG	30-1000MHZ	3143	EMCO	1271	00803	II	06-MAY-2009
GRAY BILOG	20-2000MHZ	3141	EMCO	9703-1038	00066	II	07-MAY-2009(EMI) / 04-FEB-2008(RFI2)
YELLOW-BLACK BILOG	20-2000MHZ	CBL6140A	CHASE	1112	00126	II	07-MAY-2009(EMI) / 20-APR-2008(RFI)
RED-WHITE BILOG	30-2000MHZ	JB1	SUNOL	A091604-1	01105	I	07-NOV-2008
RED-BLACK BILOG	30-2000MHZ	JB1	SUNOL	A091604-2	01106	I	20-OCT-2008
RED-BROWN BILOG	30-2000MHZ	JB1	SUNOL	A0032406	1218	I	04-AUG-2008
YELLOW HORN	1-18GHZ	3115	EMCO	9608-4898	00037	I	31-MAY-2009(EMI) / 14-JUN-2008 (RFI)
BLACK HORN	1-18GHZ	3115	EMCO	9703-5148	00056	I	22-JUN-2009(EMI) / 16-MAY-2008 (RFI)
ORANGE HORN	1-18GHZ	3115	EMCO	0004-6123	00390	I	12-JUN-2009 (EMI) / 16-MAY-2008 (RFI)
HF (WHITE) HORN	18-26.5GHZ	801-WLM	WAVELINE	00758	00758	I	26-AUG-2007
SMALL LOOP	10kHz-30MHz	PLA-130/A	ARA	1024	00755	I	22-FEB-2008
LARGE LOOP	20Hz-5MHz	6511	EMCO	9704-1154	00067	I	23-JAN-2008
ACTIVE MONOPOLE	30Hz-30MHz	3301B	EMCO	3824	00068	II	14-JUN-2008
INDUCTION COIL	50-60Hz	1000-4-8	C-S	N/A	00778	II	26-SEP-2007
ADJUSTABLE DIPOLE	30-1000MHZ	3121C	EMCO	1370	00757	I	26-OCT-2008
ADJUSTABLE DIPOLE	30-1000MHZ	3121C	EMCO	1371	00756	I	09-NOV-2008
RE101 LOOP SENSOR	30Hz-100kHz	RE101-13.3CM	C-S	N/A	00818	II	22-MAR-2009
RS101 RADIATING LOOP	30Hz-100kHz	RS101-12CM	C-S	N/A	00819	II	22-MAR-2009
RS101 LOOP SENSOR	30Hz-100kHz	RS101-4CM	C-S	N/A	00820	II	22-MAR-2009

EFT	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
CAS 3025 BURST	INA 265A/266	SCHAFFNER	20096	00947	II	28-JUN-2008
VERIFICATION ATTENUATORS	N/A	C-S	01	00794	II	19-JUL-2008
EFT DIRECT COUPLING CAP	MODULA6150	TESEQ	34525	1268	I	11-JUL-2008
RED BESTEMC-2	711-1100	SCHAFFNER	200122-074SC	00623	II	13-APR-2008
EMC PRO PLUS	EMC PRO PLUS	KEYTEK	0608208	RENTAL	II	17-MAY-2008

ESD GENERATORS	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
GREEN	NSG435	SCHAFFNER	000839	00763	I	25-OCT-2007
RED	NSG435	SCHAFFNER	001625	00762	I	06-FEB-2008
YELLOW	930D	ETS	201	00673	I	18-AUG-2007

DIPS AND INTERRUPTS	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
MODULA6150	MODULA6150	TESEQ	34525	1268	I	11-JUL-2008
INA 6502 AUTOMATIC STEPTRANSFORMER	INA 6502	TESEQ	105	1269	I	11-JUL-2008
10001I/2 AC POWER SYSTEM	(2) 500I	CALIFORNIA INSTRUMENTS	HK53687/HK53688	00376	II	21-JUN-2008
RED BESTEMC-2	711-1100	SCHAFFNER	200122-074SC	00623	II	17-APR-2008

CHAMBERS AND STRIPLINE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RFI 1 CHAMBER	3 METER COMPACT	PANASHIELD	N/A	00797	II	20-APR-2008
RFI 2 CHAMBER	04' x 07' SHIELDING SYSTEM	LINDGREN	13329	00795	II	04-FEB-2008
RFI 3 STRIPLINE	N/A	C-S	N/A	00796	III	NA
ENVIRONMENTAL (SAFETY)	ECL5	B-M-A INC.	2041	00029	I	03-JAN-2008
ENVIRONMENTAL (SAFETY)	SGTH-31S	B-M-A INC.	2245	00321	I	03-JAN-2008

AMPLIFIERS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	0.5-1000MHz	10W1000B	AR	18708	00032	II	28-JAN-2008 (RFI1)
GREEN	0.5-1000MHz	10W1000B	AR	23423	00123	II	04-FEB-2008 (RFI2)
BLUE	0.01-250MHz	75A250	AR	19165	00039	II	03-NOV-2007 (EU CRFI) / 19-JUN-2008 (NEBS CRFI)
BLACK	0.01-250MHz	75A250	AR	23411	00122	II	29-DEC-07 (EU CRFI) / 19-JUN-08 (NEBS) / 20-APR-08 (RFI1)
ORANGE	0.01-250MHz	75A250	AR	26827	00367	II	28-JUN-08 (NEBS CRFI) / 29-JUN-2008 (EU)
BROWN 150W	0.1-250MHz	150A250	AR	313454	1255	II	04-FEB-2008 (RFI2)
GTC 1-2.6	1.0-2.6 GHz	GRF5016A	GTC	1221	RENTAL	II	14-JUN-2008 (YELLOW & ORANGE HORN) / 28-JUN-2008 (BLK)
HUGHES 10W	2.0-4.0GHz	1177H01	HUGHES	055	RENTAL	II	14-JUN-2008 (YELLOW HORN) / 16-MAY-2008 (BLK & ORANGE)
HUGHES 10W	4.0-8.0GHz	8010H02F	HUGHES	240	RENTAL	II	14-JUN-2008 (YELLOW HORN) / 16-MAY-2008 (BLK & ORANGE)
HUGHES 10W	8-10.0GHz	80108	HUGHES	138	RENTAL	II	14-JUN-2008 (YELLOW HORN) / 17-MAY-2008 (BLK & ORANGE)
HP495A	7.0-10.0GHz	HP495A	HP	304-00237	00086	II	OUT OF SERVICE (SPARE)
AUDIO AMP	AUDIO FREQ	MPA-200	RADIO SHACK	700438	NONE	III	NA
AUDIO AMP	AUDIO FREQ	MPA-200	RADIO SHACK	708545	00862	III	NA

FIELD PROBES	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	0.01-1000MHz	HI-4422	HOLADAY	90369	00031	I	23-MAR-2008
GREEN	0.01-1000MHz	HI-4422	HOLADAY	97363	00136	I	25-JUL-2007
BLUE	0.01-1000MHz	HI-4422	HOLADAY	95696	01100	I	18-APR-2008
Reference Laser Field Probe	0.1-6000MHz	FL7006 Star Probe	AR	321700	1252	I	23-FEB-2008
MICROWAVE SURVEY METER	2450MHz	HI-1501	HOLADAY	00075464	1244	I	09-JAN-2008

SIGNAL GENERATORS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
RED	0.09-2000MHz	HP8648B	Agilent	3847U02192	00366	I	03-APR-2008
BLUE	0.1-1000MHz	HP8648A	Agilent	3426A00548	00034	I	23-AUG-2007
GREEN	0.09-2000MHz	HP8648B	Agilent	3623A02072	00125	I	16-OCT-2007
ORANGE	0.1-1000MHz	HP8648B	Agilent	3537A01210	00025	I	19-JUN-2008
BROWN	0.01Hz-15MHz	HP33120A	Agilent	US36016621	1211	I	OUT OF SERVICE
WHITE	0.01Hz-15MHz	HP33120A	Agilent	US36048143	1219	I	17-MAY-2008
BROWN-WHITE	0.01Hz-15MHz	HP33120A	Agilent	SG40019842	1232	I	10-NOV-2007
BLUE-WHITE	0.1Hz-13MHz	HP3312A	Agilent	1432A07632	00775	I	21-MAR-2008
SWEEPER	0.01-20.0GHz	HP83752A	Agilent	3610A01133	00087	II	08-MAY-2008
AM/FM STEREO SIG. GEN.	0.1-170MHz	LG3236	LEADER	3687301	00959	I	To be determined
IMPULSE GENERATOR	1-100Hz	CIG-25	ELECTRO-METRICS	290	00942	I	To be determined

BULK INJECTION CLAMPS	RANGE	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
GREEN (NEBS CRFI)	0.01-30MHz	95236-1	ETS	50215	00118	II	19-JUN-2008(BLUE) 19-JUN-2008(BLK) 29-JUN-2008(ORANGE)
GREEN (EU CRFI)	0.15-80MHz	95236-1	ETS	50215	00118	II	03-NOV-2007(BLUE) 29-DEC-2007(BLK) 28-JUN-2008(ORANGE)
RED (NEBS CRFI)	0.01-30MHz	95236-1	ETS	34026	1020	II	19-JUN-2008(BLUE) 19-JUN-2008(BLK) 29-JUN-2008(ORANGE)
RED (EU CRFI)	0.15-80MHz	95236-1	ETS	34026	1020	II	04-NOV-2007(BLUE) 02-JAN-2008(BLK) 28-JUN-2008(ORANGE)
BLUE (RTCA/DO-160E)	2-450MHz	9142-1N	SOLAR	063824	1237	II	CALIBRATE BEFORE USE
RENTAL (RTCA/DO-160E)	2-450MHz	9142-1N	SOLAR	008508	RENTAL	II	10-AUG-2007

ANSI T1.315	MFR	ASSET	CAT	CALIBRATION DUE
SBC NOISE CART	C-S	1285	III	CALIBRATION NOT REQUIRED
SBC TRANSIENT CART	C-S	1286	III	WAVESHAPE VERIFIED BEFORE USE

OSCILLOSCOPES	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
EMC 100MHZ	TDS 220	TEKTRONIX	C036986	1166	I	25-APR-2008
ESD REFERENCE 1GHZ	TDS 684B	TEKTRONIX	B011287	RENTAL	I	03-APR-2008
400MHZ E*SCOPE	TDS 3044B	TEKTRONIX	C010074	1275	I	19-JUL-2008
PRODUCT SAFETY 100 MHZ	TDS 340	TEKTRONIX	B012357	00737	I	03-OCT-2007
TELECOM 100 MHZ	54645A	HP/AGILENT	US36320452	00103	I	OUT OF SERVICE
REFERENCE 500MHZ 10X PROBE	P6139A	TEKTRONIX	NA	1280	I	19-JUL-2008
REFERENCE 500MHZ 10X PROBE	P6139A	TEKTRONIX	NA	1281	I	19-JUL-2008
500MHZ 10X PROBE	P6139A	TEKTRONIX	NA	1282	I	19-JUL-2008
500MHZ 10X PROBE	P6139A	TEKTRONIX	NA	1283	I	19-JUL-2008
REFERENCE HV 1000X PROBE	P6015A	TEKTRONIX	B056555	1277	I	20-JUL-2008
REFERENCE HV 1000X PROBE	P6015A	TEKTRONIX	B056590	1278	I	20-JUL-2008

CDN NETWORKS	RANGE	MN	MFR	ASSET	CAT	CALIBRATION DUE
BLUE	0.10-100MHZ	20A M-3	C-S	00806	II	03-NOV-2007 (BLUE AMP) 29-DEC-2007 (BLK) 28-JUN-2008 (ORANGE)
RED	0.10-100MHZ	15A M-3	C-S	00780	II	03-NOV-2007 (BLUE AMP) 29-DEC-2007 (BLK) 28-JUN-2008 (ORANGE)
YELLOW-BLACK	0.10-100MHZ	15A M-3	C-S	00784	II	03-NOV-2007 (BLUE AMP) 29-DEC-2007 (BLK) 28-JUN-2008 (ORANGE)
GREEN	0.10-100MHZ	30A M-3	C-S	00779	II	03-NOV-2007 (BLUE AMP) 04-AUG-2007 (BLK) 28-JUN-2008 (ORANGE)
YELLOW	0.10-100MHZ	30A M-5	C-S	00804	II	03-NOV-2007 (BLUE AMP) 28-JUN-2008 (ORANGE)
BROWN	0.10-100MHZ	M-3	C-S	1169	II	03-NOV-2007 (BLUE AMP) 29-DEC-2007 (BLK) 28-JUN-2008 (ORANGE)
BROWN-WHITE	0.10-100MHZ	M-3	C-S	1170	II	03-NOV-2007 (BLUE AMP) 29-DEC-2007 (BLK) 28-JUN-2008 (ORANGE)
BROWN-BLACK	0.10-100MHZ	M-2 (DC)	C-S	1171	II	03-NOV-2007 (BLUE AMP) 29-DEC-2007 (BLK) 28-JUN-2008 (ORANGE)
RED-BLACK	0.10-100MHZ	M-2 (DC)	C-S	1177	II	03-NOV-2007 (BLUE AMP) 29-DEC-2007 (BLK) 28-JUN-2008 (ORANGE)
GREEN-WHITE	0.10-100MHZ	M-2 (DC)	C-S	1259	II	03-NOV-2007 (BLUE AMP) 29-DEC-2007 (BLK) 28-JUN-2008 (ORANGE)
YELLOW (RES)	0.10-100MHZ	100Ω RESISTOR	C-S	00810	II	04-NOV-2007 (BLUE AMP) 02-JAN-2008 (BLK) 28-JUN-2008 (ORANGE)
GREEN (RES)	0.10-100MHZ	100Ω RESISTOR	C-S	1172	II	03-NOV-2007 (BLUE AMP) 02-JAN-2008 (BLK) 28-JUN-2008 (ORANGE)
ARTIFICIAL HAND	510Ω / 220PF	CS-AH	C-S	1262	II	04-JUN-2008
ARTIFICIAL HAND	510Ω / 220PF	CS-AH	C-S	1263	II	04-JUN-2008

RMS VOLTMETERS/CURRENT CLAMP	MN	MNFR	SN	ASSET	CAT	CALIBRATION DUE
TRUE-RMS MULTIMETER	79III	FLUKE	71700298	00769	I	27-OCT-2007
TRUE RMS MULTIMETER	179	FLUKE	89280616	1228	III	NOT CAL'D TO 17025
TRUE-RMS MULTIMETER (REFERENCE)	177	FLUKE	83390024	00973	I	22-MAR-2008
TRUE-RMS MULTIMETER	177	FLUKE	83390025	00974	I	22-MAR-2008
TRUE-RMS MULTIMETER (TELECOM)	177	FLUKE	83430419	00975	I	22-MAR-2008
AC/DC CURRENT PROBE	A622	TEKTRONIX	08DD 6275DV	1246	I	31-JAN-2008

SURGE GENERATORS	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
TRANSIENT WAVEFORM MONITOR	TWM-5	CDI	003982	00323	II	05-JUN-2008
UNIVERSAL SURGE GENERATOR	M5	CDI	003966	00324	II	CAL BEFORE USE
THREE PHASE COUPLING NWK	3CN	CDI	003455	00325	II	CAL BEFORE USE
1.2x50uS PLUGIN MODULE	1.2x50uS PLUGIN	CDI	N/A	00842	II	CAL BEFORE USE
10x160uS PLUGIN MODULE	10x160uS PLUGIN	C-S	N/A	00843	II	CAL BEFORE USE
10x560uS PLUGIN MODULE	10x560uS PLUGIN	C-S	N/A	00841	II	CAL BEFORE USE
PSURGE CONTROLLER MODULE	PSURGE 8000	HAEFELY	150267	00879	II	05-JUN-2008
COUPLING/DECOUPLING MODULE	PCD 900	HAEFELY	149213	00880	II	05-JUN-2008
IMPULSE MODULE	PIM 900	HAEFELY	149202	00881	II	05-JUN-2008
HIGH VOLTAGE CAP NWK 5KVDC, 18μF	CS-HVCC	C-S	01	00772	II	09-APR-2008
NEBS SURGE GENERATOR	N/A	C-S	N/A	00088	II	18-OCT-2007
2x10uS SURGE GENERATOR	2x10uS	C-S	N/A	00846	II	CAL BEFORE USE
10x700uS SURGE GENERATOR	10x700uS	C-S	N/A	00847	II	06-JUN-2008
12 PAIR SURGE RESISTOR MODULE	N/A	C-S	N/A	00768	II	18-OCT-2007
VSS 500-M	TSS 500 M12 S2	EMTEST	V0502100032	1155	II	CAL BEFORE USE
TSS 500-M	TSS500 M10	EMTEST	V0502100031	1156	II	CAL BEFORE USE
NSG 2050 SURGE GENERATOR	NSG 2050	TESEQ	200720-605LU	1273	I	11-JUL-2008
PNW 2050 1.2x50 IMPULSE NETWORK	PNW 2050	TESEQ	200711-604LU	1279	I	11-JUL-2008
CDN 133 3 PHASE COUPLING NETWORK	CDN 133	TESEQ	34416	1274	I	11-JUL-2008
MODULA6150	MODULA6150	TESEQ	34525	1268	I	11-JUL-2008
RED BEST EMC-2	711-1100	SCHAFFNER	200122-074SC	00623	II	13-APR-2008
SURGE CURRENT MONITOR	CM-1-L	ION PHYSICS	896730	1276	II	26-JUL-2008

POWER/NOISE METERS	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
POWER METER	435B	HP	2445A11012	00773	I	03-APR-2008
POWER METER	437B	HP	2912A01367	01099	I	03-APR-2008
POWER SENSOR	8481A	HP	2702A61351	00774	I	04-APR-2008

POWER METER	4232A	BOONTON	11000	1260	I	24-JUL-2008
POWER SENSOR	51013-4E	BOONTON	34457	1261	I	24-JUL-2008
PSOPHOMETER	2429	BRUEL & KJAER	1237642	00585	II	23-FEB-2009
TRANSMISSION LINE TESTER (DBRNC)	185T	AMREL	18507030010	1236	II	20-APR-2008
TRANSMISSION LINE TESTER (DBRNC)	185T	AMREL	998658	00823	II	03-JUL-2008
OVERVOLTAGE CHAMBERS						
	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
72KW POWER FAULT SIMULATOR	OV1	C-S	N/A	00792	III	N/A
POWER FAULT SIMULATOR	OV2	C-S	N/A	00116	III	N/A
DIPOLE TAPE MEASURES						
	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
26FT TAPE #1	2338CME	LUFKIN	C3166-1	00776	II	22-MAR-2009
26FT TAPE #2	2338CME	LUFKIN	C3166-2	00777	II	22-MAR-2009
METEOROLOGICAL METERS						
	MN	MFR	SN	ASSET	CAT	CALIBRATION DUE
TEMP./HUMIDITY/ATM. PRESSURE GAUGE	7400 PERCEPTION II	DAVIS	N/A	00965	II	09-FEB-2009
TEMPERATURE /HUMIDITY GAUGE	THG-912	HUGER	4000562	00789	I	31-JAN-2009
WEATHER CLOCK (PRESSURE ONLY)	BA928	OREGON SCIENTIFIC	C3166-1	00831	I	08-FEB-2009
CONSUMABLES						
	SPEC.	MFR	STOCK/MN	ASSET	CAT	CALIBRATION DUE
NEBS CHEESECLOTH	26-28M/KG	ED&D	ACC-01	N/A	III	N/A
NEBS CARBON BLOCK	3-MIL-GAP 1KV SURGE	RELIABLE	3AB	N/A	III	N/A

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Conditions Of Testing

[Bureau Veritas Consumer Products Services, Inc., a Massachusetts corporation], and/or its affiliates (collectively, the "Company") will conduct, at the request of the Submitter ("Client"), the tests specified on the submitted Test Request Form or equivalent in accordance with, and subject to, the following terms and conditions (collectively, "Conditions"):

1. All orders for tests are subject to acceptance by the Company, and no order will constitute a binding commitment of the Company unless and until such order is accepted by it, as evidenced by the issuance of a written report ("Test Report") by the Company. The Test Report is issued solely by the Company, is intended for the exclusive use of Client and shall not be published, used for advertising purposes, copied or replicated for distribution to any other person or entity or otherwise publicly disclosed without the prior written consent of the Company. By submitting a request for services to the Company, Client consents to the disclosure to accreditation bodies of those records of Client relevant to the accreditation body's assessment of the Company's competence and compliance with relevant accreditation criteria. The Company shall not be liable for any loss or damage whatsoever resulting from the failure of the Company to provide its services within any time period for completion estimated by the Company. If Client anticipates using the Test Report in any legal proceeding, arbitration, dispute resolution forum or other proceeding, it shall so notify the Company prior to submitting the Test Report in such proceeding. The Company has no obligation to provide a fact or expert witness at such proceeding unless the Company agrees in advance to do so for a separate and additional fee.
2. The Test Report will set forth the findings of the Company solely with respect to the test samples identified therein. Unless specifically and expressly indicated in the Test Report, the results set forth in such Test Report are not intended to be indicative or representative of the quality or characteristics of the lot from which a test sample is taken, and Client shall not rely upon the Test Report as being so indicative or representative of the lot or of the tested product in general. The Test Report will reflect the findings of the Company at the time of testing only, and the Company shall have no obligation to update the Test Report after its issuance. The Test Report will set forth the results of the tests performed by the Company based upon the written information provided to the Company. The Test Report will be based solely on the samples and written information submitted to the Company by Client, and the Company shall not be obligated to conduct any independent investigation or inquiry with respect thereto.
3. The Company may, in its sole discretion, destroy samples which have been furnished to the Company for testing and which have not been destroyed in the course of testing. The Company may delegate the performance of all or a portion of the services contemplated hereunder to an affiliate, agent or subcontractor of the Company, and Client consents to such delegation.
4. These Conditions and the Test Report represent the entire understanding of the parties hereto with respect to the subject matter hereof and of the Test Report, and no modification, variance or extrapolation with respect thereto shall be permitted without the prior written consent of the Company.
5. The names, service marks, trademarks and copyrights of the Company and its affiliates, including the names "BUREAU VERITAS," "BUREAU VERITAS CONSUMER PRODUCTS SERVICES," "BVCPS," "MTL," "ACTS," "MTL-ACTS" and "CURTIS-STRAUS" (collectively, the "Marks") are and shall remain the sole property of the Company or its affiliates and shall not be used by Client except solely to the extent that Client obtains the prior written approval of the Company and then only in the manner prescribed by the Company. Client shall not contest the validity of the Marks or take any action that might impair the value or goodwill associated with the Marks or the image or reputation of the Company or its affiliates.
6. Payment in full shall be due 30 days after the date of invoice. Interest shall be due on overdue amounts from the due date until paid at an interest rate of 1.5% per month or, if less, the maximum rate permitted by law. The Company reserves the right, at any time and from time to time, to revoke any credit extended to Client. Client shall reimburse the Company for any costs it incurs in collecting past due amounts, including court costs and fees and expenses of attorneys and collection agencies. The Test Report may not be used or relied upon by Client if and for so long as Client fails to pay when due any invoice issued by the Company or any affiliate of it to Client or any affiliate or subsidiary of Client together with interest and penalties, if any, accrued thereon.
7. The Company disclaims any and all responsibility or liability arising out of or in connection with e-mail transmissions of such information.
8. Client understands and agrees that the Company is neither an insurer nor a guarantor, that the Company does not take the place of Client or any designer, manufacturer, agent, buyer, distributor or transportation or shipping company, and that the Company disclaims all liability in such capacities. Client further understands that if it seeks assurance against loss or damage, it should obtain appropriate insurance.
9. Client agrees that the Company, by providing the services, does not take the place of Client nor any third party, nor does the Company release them from any of their obligations, nor does the Company otherwise assume, abridge, abrogate or undertake to discharge any duty of any third party to Client or any duty of Client or any third party to any other third party, and Client will not release any third party from its obligations and duties with respect to the tested goods.
10. Client shall, on a timely basis, (a) provide adequate instructions to the Company in order to enable the Company to perform properly its services, (b) provide, or cause Client's suppliers and contractors to provide, the Company with all documents necessary to enable the Company to perform its services, (c) furnish the Company with all relevant information regarding Client's intended use and purposes of the tested goods, (d) advise the Company of essential dates and deadlines relevant to the tested goods and (e) fully exercise all rights and remedies available to Client against third parties in respect of the tested goods.
11. The Company shall undertake due care and ordinary skill in the performance of its services to Client, and the Company shall accept responsibility only where such skill has not been exercised and, even in such event, only to the extent of the limitation of liability set forth herein.
12. If Client desires to assert a claim arising from or relating to (i) the performance, purported performance or non-performance of any services by the Company or (ii) the sale, resale, manufacture, distribution or use of any tested goods, it must submit that claim to the Company in a writing that sets forth with particularity the basis for such claim within 60 days from discovery of the potential claim and not more than six months after the date of issuance of the Test Report to Client. Client waives any and all such claims including, without limitation, claims that the Test Report is inaccurate, incomplete or misleading or that additional or different testing is required, unless and then only to the extent that Client submits a written claim to the Company within both such time periods.
13. CLIENT SHALL, EXCEPT TO THE EXTENT OF COMPANY'S LIABILITY TO CLIENT HEREUNDER (WHICH IN NO EVENT SHALL EXCEED THE LIMITATION OF LIABILITY HEREIN), HOLD HARMLESS AND INDEMNIFY THE COMPANY, ITS

AFFILIATES AND THEIR RESPECTIVE DIRECTORS, OFFICERS, EMPLOYEES, AGENTS AND SUBCONTRACTORS AGAINST ALL ACTUAL OR ALLEGED THIRD PARTY CLAIMS FOR LOSS, DAMAGE OR EXPENSE OF WHATSOEVER NATURE AND HOWSOEVER ARISING FROM OR RELATING TO (i) THE PERFORMANCE, PURPORTED PERFORMANCE OR NON-PERFORMANCE OF ANY SERVICES BY THE COMPANY OR (ii) THE SALE, RESALE, MANUFACTURE, DISTRIBUTION OR USE OF ANY TESTED GOODS.

14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN OR IN ANY TEST REPORT, NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE, IS MADE.

15. (A) IN NO EVENT WHATSOEVER SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, EXEMPLARY OR PUNITIVE DAMAGES IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE TEST REPORT OR THE SERVICES PROVIDED BY THE COMPANY HEREUNDER, INCLUDING WITHOUT LIMITATION LOSS OF OR DAMAGE TO PROPERTY; LOSS OF INCOME, PROFIT OR USE; OR ANY CLAIMS OR DEMANDS MADE AGAINST CLIENT OR ANY OTHER PERSON BY ANY THIRD PARTY IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE SERVICES PROVIDED BY THE COMPANY HEREUNDER.

(B) NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN, AND IN RECOGNITION OF THE RELATIVE RISKS AND BENEFITS TO CLIENT AND THE COMPANY ASSOCIATED WITH THE TESTING SERVICES CONTEMPLATED HEREBY, THE RISKS HAVE BEEN ALLOCATED SUCH THAT UNDER NO CIRCUMSTANCES WHATSOEVER SHALL THE LIABILITY OF THE COMPANY TO CLIENT OR ANY THIRD PARTY IN RESPECT OF ANY CLAIM FOR LOSS, DAMAGE OR EXPENSE, OF WHATSOEVER NATURE OR MAGNITUDE, AND HOWSOEVER ARISING, EXCEED AN AMOUNT EQUAL TO FIVE (5) TIMES THE AMOUNT OF THE FEES PAID TO THE COMPANY FOR THE SPECIFIC SERVICES WHICH GAVE RISE TO SUCH CLAIM OR U.S.\$10,000, WHICHEVER IS THE LESSER AMOUNT.

16. The Company shall not be liable for any loss or damage resulting from any delay or failure in performance of its obligations hereunder resulting directly or indirectly from any event of force majeure or any event outside the control of the Company. If any such event occurs, the Company may immediately cancel or suspend its performance hereunder without incurring any liability whatsoever to Client.

17. Company's services, including these Conditions, shall be governed by, and construed in accordance with, the local laws of the country where the Company performs the tests or, in the case of tests performed in the United States of America, the laws of Massachusetts without regard to conflicts of laws principles. If any aspect(s) of these Conditions is found to be illegal or unenforceable, the validity, legality and enforceability of all remaining aspects of these Conditions shall not in any way be affected or impaired thereby. Any proceeding related to the subject matter hereof shall be brought, if at all, in the courts of the country where the Company performs the tests or, in the case of tests performed in the United States of America, in the courts of Massachusetts. Client waives the right to interpose any counterclaim or setoffs of any nature in any litigation arising hereunder.

Rev.160009121(2)_#684340 v13CS

A2LA Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC 17025:1999

CURTIS-STRAUS¹
527 Great Road
Littleton, MA 01460
Barry Quinlan Phone: 978-486-8880
ELECTRICAL

Valid until: September 30, 2007

Certificate Number: 1627.01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following Electromagnetic Compatibility (EMC), Telecommunications, and Product Safety tests:

Electromagnetic Compatibility (EMC)

Radiated emissions testing (electric and magnetic fields)*; Conducted emissions testing (voltage and current)*; Electrostatic Discharge testing*; Electrical Fast Transient testing*; Radiated Immunity testing*; Conducted Immunity testing*; Lightning Immunity testing*; Voltage Dips*, Interrupts and Voltage Variations testing*; Magnetic Immunity testing*; RF Power measurements*; Frequency Stability Measurements*; Longitudinal Induction measurements*; Harmonic emissions testing*; Light flicker testing*; Low frequency disturbance voltage testing*; Disturbance Power measurements*; Power Cross Overvoltage testing*;

Test Type	Test Method(s)
Emissions	
Radiated and Conducted Emissions	FCC 47 CFR Parts 15 & 18; C63.4; CISPR 22; EN55022; SABS CISPR 22; AS/NZS CISPR 22; AS/NZS 3548; Canada ICES-003; CNS13438; KN 22 (RRL No. 2005-82, September 29, 2005); CISPR 11; EN 55011; SABS CISPR 11; AS/NZS CISPR 11; AS/NZS 2064; Canada ICES-001; CNS13803; CISPR 13; EN 55013; SABS CISPR 13; AS/NZS CISPR 13; AS/NZS 1053; CISPR 14-1; EN 55014-1; SABS CISPR 14; AS/NZS CISPR 14; AS/NZS 1044; CNS 13439; CISPR 15; EN 55015; GR-1089-CORE; CSA C108.8-M1983;
Harmonics	EN 61000-3-2; AS/NZS 61000.3.2
Flicker	EN 61000-3-3; AS/NZS 61000.3.3

1 Note: This accreditation covers testing performed at the laboratory listed above and the satellite facility located at 168 Ayer Rd, Littleton, MA 01460 and, for test types marked with an asterisk, at other sites as defined in "A2LA specific criteria for the accreditation of site testing and site calibration laboratories."

(A2LA Cert. No. 1627.01) 3/27/06

Page 1 of 10

Immunity	RRL No. 2005-130 (December 27, 2005)
Electrostatic Discharge (ESD)	EN 61000-4-2; AS/NZS 61000.4.2; KN61000-4-2
Radiated Immunity (RFI)	EN 61000-4-3; AS/NZS 61000.4.3; KN61000-4-3
Electrical Fast Transient Bursts (EFT)	EN 61000-4-4; AS/NZS 61000.4.4; KN61000-4-4
Surge	EN 61000-4-5; AS/NZS 61000.4.5; KN61000-4-5
Conducted Immunity	EN 61000-4-6; AS/NZS 61000.4.6; KN61000-4-6
Magnetic Immunity	EN 61000-4-8; AS/NZS 61000.4.8; KN61000-4-8
Voltage Dips and Interrupts	EN 61000-4-11; KN61000-4-11
Low Frequency Conducted Disturbances	EN 61000-2-2

Family Product or Industry Specific Specifications including emissions and/or immunity	GR-1089-CORE; GR-78-CORE (ESD) EN50081-1; EN50081-2; EN50082-2; EN50082-1; EN 61000-6-1; EN 61000-6-2; EN 61000-6-3; EN 61000-6-4; EN 50091-2; EN 55024; CISPR 24 EN 55103-1; EN 55103-2; EN 61326; EN 61547; EN 50130-4; EN 50083-2; EN 60601-1-2; EN 60601-2-2; EN 60601-2-24; EN 60601-2-32; EN 60601-2-38; EN 60601-2-47; IEC 1800-3; EN 61800-3; EN 55020; CISPR 20; EN 60555 Part 2; EN 60555 Part 3; ETS 300 386-1; EN 300 386-2; EN 300 386, ETS 300 132-1; ETS 300 132-2; EN 60669-2-1; AS/NZS 3200.1.2; CNS 13783-1; ETR 283; C62.41
--	---

Radiocommunications	
EU R&TTE Radio Standards;	EN 300 220-1; EN 300 220-3; EN 300 330-1; EN 300 330-2; EN 300 440-1; EN 300 440-2; EN 300 328; EN 300 385; EN 301 893
EU R&TTE EMC Standards	EN 300 339; EN 301 489-01; EN 301 489-03; EN 301 489-17
Canada Radio Standards	RSS-102; RSS-117; RSS-118; RSS-119; RSS-123; RSS-125; RSS-128; RSS-129; RSS-130; RSS-131; RSS-132; RSS-133; RSS-134; RSS-135; RSS-136; RSS-137; RSS-138; RSS-141; RSS-142; RSS-170; RSS-181; RSS-182; RSS-187; RSS-188; RSS-191; RSS-192; RSS-193; RSS-195; RSS-210; RSS-212; RSS-213; RSS-215; RSS-243; RSS-GEN; RSS-310; GL-36;
Australia/New Zealand Radio Standards	AS/NZS 4268; AS/NZS 4771; RFS29; Radiocommunications (Data Transmission Equipment Using Spread Spectrum Modulation Techniques); Radiocommunications (Spread Spectrum Devices); Radiocommunications (Short Range Devices); Radiocommunications (Low Interference Potential Devices);

(A2LA Cert. No. 1627.01) 3/27/06

Page 2 of 10

Other Radio Standards	RTTE 01 (DGT-Taiwan);
-----------------------	-----------------------

FCC Standards and Test methods Support TCB Status--

FCC Scope A - Unlicensed Radio Frequency Devices

A1	1. 47 CFR Parts 11, 15 and 18 2. FCC MP-5, 3. ANSI C63.4-2003,
A2	1. 47 CFR Part 15, 2. ANSI C63.4-2003,
A3	1. 47 CFR Part 15, 2. ANSI C63.17-1998, 3. ANSI C63.4-2003,
A4	1. 47 CFR Part 15, 2. ANSI C63.4-2003,
FCC Scope B - Licensed Radio Service Equipment	
B1	1. 47 CFR Parts 2, 22, 24, 25, and 27 2. ANSI/TIA-603-C (2004)
B2	1. 47 CFR Parts 2, 22, 74, 90, 95, and 97 2. ANSI/TIA-603-C (2004)
B3	1. 47 CFR Parts 2, 80, and 87 2. ANSI/TIA-603-C (2004)
B4	1. 47 CFR Parts 2, 21, 74, and 101 2. ANSI/TIA-603-C (2004)

Country Specific Standards and Other	
ITU EMC Standards	K.20; K.21; K.41; K.44
Swedish EMC Standards	BAKOM 3336.3
South African EMC Standards other than CISPR equivalents	SABS 1718-1; SANS 211/SABS CISPR 11; SANS 224/SABS CISPR 24; SANS 213/SABS CISPR 13; SANS 2200; SANS214-1/SABS CISPR 14-1; SANS214-2/SABS CISPR 14-2; SANS 215/SABS CISPR 15; SANS 222/SABS CISPR 22
Hong Kong EMC Standards	HKTA 1006; HKTA 1007; HKTA 1008; HKTA 1010; HKTA 1015; HKTA 1026; HKTA 1035; HKTA 1039; HKTA 1041; HKTA 1042; HKTA 1045
Singapore EMC Standards	IDA TS SRD; IDA TS EMC
Japanese VCCI Standards	VCCI V-3, VCCI V-4

(A2LA Cert. No. 1627.01) 3/27/06

Page 3 of 10

Telecommunications

Telecommunications Registration; General test methods; Lightning surge*; Drop testing*; Balance testing*; Signal power (metallic and longitudinal)*; Frequency measurements*; Pulse templates*; Leakage testing*; Impedance testing*; Hearing Aid Compatibility testing (excluding volume control)*; Protocol analysis* and Jitter testing*.

Telecom Standards

	Title
North American standards	
FCC 47 CFR Part 68 Telephone Terminal Equipment CS-03 Issue 9	Connection of terminal equipment to the telephone network. Analog and Digital Equipment. TCB Scope C1. Specification for terminal equipment, terminal systems, Network protection devices, connection arrangements and hearing aids compatibility. Bulletin Part 68 Rationale and Measurement Guidelines (Feb 1998)
TIA/EIA TSB31-B 1998	Telecommunications Telephone Terminal Equipment Technical Requirements for Connection of Terminal Equipment to the Telephone Network
TIA-968-A, A1, A2, A3	Technical Requirements for SHDSL, HDLSL2, HDLSL4 Digital Subscriber Line Terminal Equipment to Prevent Harm to the Telephone Network Industry
T1.TRQ.6-2001	
Australia standards	
AS/ACIF S002-2001	Analogue interworking and non-interference requirements for Customer Equipment for connection to the Public Switched Telephone Network
AS/ACIF S016-2001	Requirements for Customer Equipment for connection to hierarchical digital interfaces
AS/ACIF S031-2001	Requirements for ISDN Basic Access Interface
AS/ACIF S038-2001	Requirements for ISDN Primary Rate Access Interface
AS/ACIF S043-2001	Requirements for Customer Equipment for Connection to a Metallic Local Loop Interface of a Telecommunications Network — Part 1: General Part 2: Broadband Part 3: DC, Low Frequency AC and Voice band
International standards	
ITU-T G.703	Physical/electrical characteristics of hierarchical Digital interfaces
Hong Kong standards	
HKTA 2011	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to Direct Exchange Lines (DEL) of the Public Switched Telephone Network (PSTN) in Hong Kong
HKTA 2014	Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Network (PTN) in Hong Kong using ISDN Basic Rate Access (BRA) based on ITU-T Recommendations

(A2LA Cert. No. 1627.01) 3/27/06

Page 4 of 10

<p><u>Telecom Standards</u></p> <p>HKTA 2028</p> <p>HKTA 2029</p> <p>HKTA 2030</p> <p>HKTA 2031</p> <p>HKTA 2032</p> <p>HKTA 2033</p> <p><u>European standards</u></p> <p>TBR 1: 1995</p> <p>TBR 2: 1997</p> <p>TBR 3: 1995 + Amdt : 1997</p> <p>TBR 4: 1995 + Amdt : 1997</p> <p>TBR 012: 1993 + Amdt : 1996</p> <p>TBR 013: 1996</p> <p>(A2LA Cert. No. 1627.01) 3/27/06</p> <p>Page 5 of 10</p>	<p><u>Title</u></p> <p>Network connection specification for connection of CPE to the PTNs in Hong Kong using digital leased circuits at data rate of 1544 kbit/s</p> <p>Network connection specification for connection of CPE to the PTNs in Hong Kong using digital leased circuits at data rate of 2048 kbit/s</p> <p>Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Network (PTN) in Hong Kong using Digital Leased Circuits at nx64 kbit/s</p> <p>Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Network (PTN) in Hong Kong using Digital Leased Circuits below 64 kbit/s</p> <p>Network Connection Specification for Connection of Customer Premises Equipment (CPE) to the Public Telecommunications Networks in Hong Kong using Asymmetric Digital Subscriber Lines (ADSL) based on ITU-T Recommendation G.992.1</p> <p>Network Connection Specification for Connection of Customer Premises Equipment (CPE) to Fixed Telecommunications Networks in Hong Kong using Splitterless Asymmetric Digital Subscriber Lines (ADSL) based on ITU-T Recommendation G.992.2</p> <p>Attachment requirements for terminal equipment to be connected to circuit switched data networks and Leased circuits using a CCITT Recommendation X.21 interface, or at an interface physically, functionally and electrically compatible with CCITT Recommendation X.21 but operating at any data signaling rate up to, and including, 1 984 kbit/s</p> <p>Attachment requirements for Data Terminal Equipment (DTE) to connect to Packet Switched Public Data Networks (PSPDNs) for CCITT Recommendation X.25 interfaces at data signaling rates up to 1 920 kbit/s utilizing interfaces derived from CCITT Recommendations X.21 and X.21 bit Integrated Services Digital Network (ISDN);</p> <p>Attachment requirements for terminal equipment to connect to an ISDN using ISDN basic access</p> <p>Integrated Services Digital Network (ISDN);</p> <p>Attachment requirements for terminal equipment to connect to an ISDN using ISDN primary rate access</p> <p>Business Telecommunications (BT); Open Network Provision (ONP) technical requirements; 2 048 kbit/s digital unstructured leased line (D2048U) Attachment requirements for terminal equipment</p> <p>Business Telecommunications (BTC); 2 048 kbit/s digital structured leased lines (D2048S); Attachment requirements for terminal equipment interface</p> <p><u>European standards (cont'd)</u></p> <p>TBR 21: 1998</p> <p>TBR 24: 1997</p> <p><u>Taiwan standards (DGT)</u></p> <p>ADSL01</p> <p>ID0002</p> <p>IS6100</p> <p>PSSTN01 (non-voice only)</p> <p><u>New Zealand standards</u></p> <p>PTC 200 (non-voice only)</p> <p>PTC 217</p> <p>TNA 117</p> <p>PTC 270</p> <p><u>Singapore Standards</u></p> <p>IDA TS ADSL</p> <p>IDA TS ADSL 2</p> <p>IDA TS DLCN 1</p> <p>IDA TS ISDN 1</p> <p>IDA TS ISDN 2</p> <p>IDA TS PSTN (non-voice only)</p> <p><u>South Africa standards</u></p> <p>TE-001 (non-voice only)</p> <p>Terminal Equipment (TE); Attachment requirements For pan-European approval for connection to the Analogue Public Switched Telephone Networks (PSTNs) of TE (excluding TE supporting the voice telephony service) in which network addressing, if provided, is by means of Dual Tone Multi Frequency (DTMF) signaling</p> <p>Business Telecommunications (BTC); 34 Mbit/s Digital Unstructured and structured leased lines (D34U and D34S); Attachment requirements for Terminal equipment interface</p> <p>Asymmetric Digital Subscriber Line Terminal Equipment and POTS Splitter Technical Specifications</p> <p>DS1 Equipment Type Approval Guidelines</p> <p>ISDN Terminal Equipment Technical Specifications</p> <p>Technical Specifications for Terminal Equipment for Connection to Public Switched Telephone Network</p> <p>Requirements for Connection of Customer Equipment to Analogue Lines</p> <p>Requirements for Bandwidth Management Devices</p> <p>Telecom 2048 kbit/s Standard Network Interface</p> <p>Interim arrangements for ADSL CPE</p> <p>Type Approval Specification for Asymmetric Digital Subscriber Line (Full-rate ADSL) Modems</p> <p>Type Approval Specification for Asymmetric Digital Subscriber Line Splitterless (G-Lite) Modems</p> <p>Type Approval Specification for Digital Interfaces based on hierarchical bit rates of 2048 kbit/s, 34 368 kbit/s and 139 264 kbit/s</p> <p>Type Approval Specification for connection of Terminal Equipment to Integrated Services Digital Network (ISDN) Basic Access</p> <p>Type Approval Specification for connection of Terminal Equipment to Integrated Services Digital Network (ISDN) Primary Rate Access (PRA)</p> <p>Type Approval Specification for connection of Terminal Equipment to Public Switched Telephone Network (PSTN)</p> <p>Standard for Telecommunication Line Terminal Equipment (TLTE) for Connection to the Public Switched Telephone Network (PSTN)</p> <p>(A2LA Cert. No. 1627.01) 3/27/06</p> <p>Page 6 of 10</p>
<p><u>Product Safety</u></p> <p>General test methods:</p> <p>Power input*, Permanence of marking*, Accessibility*, Permissibly limits*, Energy hazard measurement*, SELV circuits*, TNV limits*, Limited current*, Capacitor Discharge / voltage limitation*, Ring signal*, Humidity conditioning*, Creepage / Clearance / Distance thru Insulation (excluding CTT)*, Limited power measurement*, Ground Bond/Earthing*, Ground continuity*, Temperature*, Stability*, Applied force*, Steel sphere impact*, Mold stress*, Battery reverse current*, Ball pressure*, Leakage current*, Component abnormal*, Electric strength*, Impulse*, Overvoltage*, Acoustic sound pressure*, 130mm / 20mm flame*, Needle flame*, Hot flaming oil*, Locked rotor/motor armature*, Vibration, Bump, Drop*, Strain relief*, Torque*, Insulation resistance*, Sound level*, Handle loading*, Liquid overflow*, Spillage*, Liquid leakage*, Transformer shorts/overloads*, Rain test*, Wall mount*, Laser radiation (excluding x-ray)*, Voltage surge*, Functionality*, Protective impedance abnormal*, Capacitor short circuit abnormal*, Output abnormal*, Multi-supply abnormal*, Cooling abnormal*, Heating device abnormal*, Interlock abnormal*, Rigidity*, Cleaning*</p> <p><u>Product Safety Standards</u></p> <p><u>Specific Product Safety Standards</u></p> <p>UL 60950 2000</p> <p>IEC 60950 1999</p> <p>EN 60950 2000</p> <p>IEC 60950-1 2001</p> <p>UL 60950-1 2003</p> <p>CSA C22.2 No. 60950-00</p> <p>CSA C22.2 No. 60950-1 03</p> <p>IEC 61010-1 1993</p> <p>EN 61010-1 1993, 2001</p> <p>IEC 61010-1 2001</p> <p>UL 61010B-1 2003</p> <p>CAN/CSA 1010-1 1999 (Including AM 2)</p> <p>IEC 60601-1 1995</p> <p>EN 60601-1 1995 (Including AM 2)</p> <p>UL 2601-1 1997</p> <p>IEC 60065 1998, 2000</p> <p>ANSI/UL 6500: 1998</p> <p>CAN/CSA 60065-00</p> <p>AS/NZS 60065 2000</p> <p>Canadian C22.2 No. 1-94 (1-98)</p> <p>1994, 1998</p> <p>EN 60065 1994</p> <p>IEC 60825 1990</p> <p>EN 60825-1 1994</p> <p>(A2LA Cert. No. 1627.01) 3/27/06</p> <p>Page 7 of 10</p>	<p><u>Product Safety Standards</u></p> <p>IEC 60825-1 2001</p> <p>IEC 60825-2 2000-5</p> <p>IEC 60825-4 1997-11</p> <p>21 CFR 1040.10</p> <p>IEC 60335-1 1995</p> <p>(Including AM2 – 1997 & AM 12 – 1997)</p> <p>EN 60335-1 2001</p> <p>UL 60335-1 1998</p> <p>CAN/CSA E335-1 1994</p> <p>UL 61010A-1: 2002</p> <p>EN 61010-1: 2001</p> <p>AS/NZS 60950: 2000</p> <p>EN 60950-1: 2001</p> <p>AS/NZS 60950.1: 2003</p> <p>UL 61010 -1: 2004</p> <p>UL 60601-1: 2003</p> <p>IEC 60601-1-1: 2000</p> <p>EN 60601-1-1: 2001</p> <p>UL 60065: 2003</p> <p>CSA 60065: 2003</p> <p>IEC 60065: 2001</p> <p>EN 60065: 2002</p> <p>EN 60204 -1: 1998</p> <p>HKTA 2001</p> <p><u>Title</u></p> <p>Classification, requirements and user's guide.</p> <p>Safety of laser products – Part 2: Safety of optical communication systems</p> <p>Safety of laser products – Part 4: Laser guards</p> <p>Performance standard for laser products</p> <p>Safety of household and similar electrical appliances</p> <p>Part 1: General requirements</p> <p>Electrical equipment for laboratory use; part 1: General requirements</p> <p>Safety requirements for electrical equipment for measurement, control, and laboratory use - Part 1: General requirements</p> <p>Safety information technology equipment</p> <p>Information Technology Equipment – Safety – Part 1: General Requirements</p> <p>Information Technology Equipment – Safety – General requirements</p> <p>Electrical Equipment for Measurement, Control and Laboratory Use; Part 1: General Requirements</p> <p>Medical Electrical Equipment, Part 1: General Requirements for Safety</p> <p>Medical Electrical Equipment - Part 1: General Requirements For Safety 1: Collateral Standard: Safety Requirements For Medical Electrical Systems</p> <p>Medical Electrical Equipment - Part 1: General Requirements for Safety – Section 1-1. Collateral Standard: Safety Requirements For Medical Electrical Systems</p> <p>Audio, Video and Similar Electronic Apparatus – Safety Requirements</p> <p>Audio, Video and Similar Electronic Apparatus – Safety Requirements</p> <p>Audio, Video and Similar Electronic Apparatus – Safety Requirements</p> <p>Audio, Video and Similar Electronic Apparatus – Safety Requirements</p> <p>Safety of Machinery – Electrical Equipment of Machines – Part 1: Specification for General Requirements</p> <p>Compliance Test Specification – Safety and Electrical Protection Requirements for Subscriber Equipment Connected to the Public Telecommunications Networks In Hong Kong</p> <p>(A2LA Cert. No. 1627.01) 3/27/06</p> <p>Page 8 of 10</p>

<i>Environmental Simulation</i>			<p>Note 1. For standards or methods listed on the scope of accreditation without a revision date, laboratories are expected to be competent in the use of the current version within one year of the date of publication of the standard test method or upon the date specified by the standard test method originator when the originator has implementation authority. When a superseded standard or method is required for an accredited test, the scope will include the superseded date/version. For those that support the TCB/CB status of the organization acting as a certifier on behalf of the FCC or IC the expectation is currency within 30 days of Federal Register publication of changes for FCC and 30 days after IC website update. This note shall not be construed as an Accreditation Body implication to adopt a more current standard than is required in a regulation or code (i.e. the legal requirement) which is adopted by the lab under their responsibility.</p> <p>* On-site test service is available for this technology, test, or method.</p>
<u>Test Technology</u>	<u>Test Standard</u>	<u>Supporting Standards</u>	
Accessibility*	IEC 60529	IP-0x thru IP-6x	<p>MFG & Hygroscopic Dust</p>
Acoustic Noise*	GR-63-CORE Sec 4.6		
Airborne Contaminants	GR-63-CORE Sec 4.5		<p>IEC 60068-2-1 IP-x1 & IP-x2 IEC 60068-2-32</p>
Altitude	GR-63-CORE Sec 4.1.3		
Cold Start*	ETS 300 019		<p>IP-5x & IP-6x</p>
Drip	IEC 60529		
Drops*	ETS 300 019		<p>Fire & Needle Flame</p>
Dust	GR-63-CORE Sec 4.3		
Firearms Resistance Testing	IEC 60529		<p>IEC 60068-2-1 IEC 60068-2-2 IEC 60068-2-14 IEC 60068-2-56</p>
Fire Resistance	GR-487		
Heat Dissipation*	ANSI T1.319		<p>IP-x3 & IP-x4 IEC 60068-2-1 IEC 60068-2-2 IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-56</p>
Illumination	GR-63-CORE Sec 4.2		
Operational Temperature & Humidity (OpTH)*	GR-63-CORE Sec 4.1.4		<p>GR-63-CORE Sec 4.1.2 ASTM B117</p>
	GR-63-CORE Sec 4.7		
Salt Fog & Spray	ETS 300 019		<p>Earthquake, Office & Transportation IP-x7 & IP-x8 IP-x5 & IP-x6</p>
Spatial*	GR-63-CORE Sec 2.0 & 3.0		
Spraying-Splashing	IEC 60529		<p>IEC 60068-2-6 IEC 60068-2-27 IEC 60068-2-29 IEC 60068-2-32 IEC 60068-2-57 IEC 60068-2-64</p>
Storage (Temperature & Humidity)*	ETS 300 019		
Vibration	GR-63-CORE Sec 4.1.1		<p>Water Immersion</p>
	ETS 300 019		
Water Immersion	GR-63-CORE Sec 4.4		<p>Water Jet</p>
Water Jet	IEC 60529		
	IEC 60529		

(A2LA Cert. No. 1627.01) 3/27/06

Page 9 of 10

(A2LA Cert. No. 1627.01) 3/27/06

Page 10 of 10