

## FCC ID Label Material Data Sheet

# SIEMENS

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: 1) this device may not cause harmful interference, and 2) this device must accept any interference received, including interference that may cause undesired operation.

FCC ID: TKD-5630001  
IC:267AS-5630001



**Fasson® Trans-Therm® 1C/S2501/40# SCK**

**Spec# 12906**

**Facestock:**

Fasson® Trans-Therm® 1C is an ultra smooth coated facestock which provides premium barcode printing for high and medium speed printers. This sheet will also print on UV letterpress equipment and offers some water resistance. Smudge resistance has been optimized for a coated paper, but caution is recommended with contact scanners.

Basis Weight:	49.5# per ream $\pm$ 10% (500 sheets 25" x 38")
Caliper:	0.0032 inches $\pm$ 10%
Tensile:	MD 30# per inch width CD 18# per inch width
Tear:	MD 44 grams CD 50 grams
Stiffness:	MD 105 mg CD 65 mg

**Adhesive:**

Fasson® S2501 is a versatile, general purpose permanent adhesive designed for excellent adhesion to corrugated and superior adhesion to plastics. Excellent initial tack without sacrificing high speed converting.

Type:	Emulsion Acrylic
Minimum Application Temperature:	+25°F
Service Temperature Range:	-65°F to +200°F

**Typical Performance Data:** 50# Uncoated Paper at room temperature on standard lab panels

**Recycled Corrugated**

Loop Tack:	0.8 - 1.1 lbs
Peel Adhesion:	0.6 - 0.8 lbs

**Rigid HDPE**

Loop Tack:	1.6 - 2.4 lbs
Peel Adhesion:	1.1 - 1.6 lbs

**Treated LDPE**

Loop Tack:	1.1 - 1.6 lbs
Peel Adhesion:	1.2 - 1.6 lbs

**PVC Film**

Loop Tack:	2.1 lbs
Peel Adhesion:	2.5 - 2.7 lbs

**Glass**

Loop Tack:	3.1 - 3.3 lbs
Peel Adhesion:	1.9 lbs

**Liner:**

40# SCK is a semi-bleached, super-calendered kraft paper featuring high internal strength, toughness, and tear resistance. Excellent for diecutting and stripping; used primarily for roll to-roll-applications.

Basis Weight:	42.5# per ream $\pm$ 10% (500 sheets 24" x 36")
---------------	--

Caliper:	0.0025 inches $\pm$ 10%
----------	-------------------------

Tensile:	MD 38# per inch width CD 22.5# per inch width
----------	--

Tear:	MD 34 grams CD 37 grams
-------	----------------------------

**Total Construction Caliper (approximate): 0.0065 inches ±10%**

**Applications and Uses**

Product is suitable for use in applications where high quality barcode printing is critical. Material provides reduced mottle flexographic floodcoating and high speed wide-web converting. Fasson® S2501is suitable for applications where compliance with FDA 175.105 is required (section covers applications where incidental contact between food and adhesive could occur). Product has been tested and approved by Underwriters Laboratories as a base stock for labels for use as Type "L" listing or classification marks. Product has not been approved for any other type of UL application. Note that file numbers are not assigned by UL to base materials that merely meet the Type "L" requirements.

**Shelf Life**

Unless specified otherwise in this document, one year when stored at 72°F at 50% RH

**Statement of Practical Use**

*As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.*

**Warranty**

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined suitability of such products for its purposes. AVERY DENNISON products are warranted to the original purchaser to be free from defects in material or workmanship for a period of one year from date of shipment. Purchaser's sole and exclusive remedy for breach of this warranty shall be the replacement of the defective products or, at AVERY DENNISON's option, the issuance of a credit or refund in an amount up to the purchase price of the defective product. In no event shall AVERY DENNISON be responsible for claims beyond the purchase price of the defective product.

THE WARRANTY SPECIFICALLY SET FORTH ABOVE IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OR MERCHANTABILITY, FITNESS FOR ANY PARTICULAR USE AND/OR NON-INFRINGEMENT. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. IN NO EVENT SHALL AVERY DENNISON BE LIABLE TO PURCHASER OR ANY OTHER PARTY FOR INDIRECT, CONSEQUENTIAL, INCIDENTAL, SPECIAL OR PUNITIVE DAMAGES.

No representative or agent of AVERY DENNISON is authorized to give any guarantee or warranty or make any representation contrary to the above. No waiver, alteration, addition or modification of the foregoing conditions shall be valid unless made in writing and signed by an executive officer of AVERY DENNISON.

---

**Fasson Roll North America**  
**Phone: 800-944-8511**  
**[www.fasson.com](http://www.fasson.com)**