




TEST REPORT

| | | |
|--|---|---|
| Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr | Report No.: KR23-SRF0036 Page (1) of (19) |  KCTL |
|--|---|---|

1. Client

- Name : SUPREMA INC
- Address : 17F-5, Parkview officetower,, 248, Jeongjail-ro, Bundang-gu, Seongnam-si, Gyeonggi-do 13554 Korea (Republic Of)
- Date of Receipt : 2022-11-03

2. Use of Report : FCC Class II permissive change

3. Name of Product / Model : FaceStation F2 / FSF2-AB

4. Manufacturer / Country of Origin : SUPREMA INC / Korea

5. FCC ID : TKWFSF2-AB

6. IC Certificate No. : 23080-FSF2AB

7. Date of Test : 2022-11-26 to 2022-11-30

8. Location of Test : Permanent Testing Lab On Site Testing
 (Address:65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)
 FCC Part 15 Subpart C, 15.209

9. Test method used : RSS-210 Issue 10 April 2020
 RSS-Gen Issue 5 February 2021

10. Test Result : Refer to the test result in the test report

| | | |
|-------------|------------------------------|------------------------------|
| Affirmation | Tested by | Technical Manager |
| | Name : Minki Kim (Signature) | Name : Heesu Ahn (Signature) |

2023-01-17

Eurofins KCTL Co.,Ltd.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by Eurofins KCTL Co.,Ltd.

REPORT REVISION HISTORY

| Date | Revision | Page No |
|------------|-------------------|---------|
| 2023-01-17 | Originally issued | - |
| | | |
| | | |
| | | |
| | | |

This report shall not be reproduced except in full, without the written approval of Eurofins KCTL Co.,Ltd. This document may be altered or revised by Eurofins KCTL Co.,Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by Eurofins KCTL Co.,Ltd. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

General remarks for test reports

Statement concerning the uncertainty of the measurement systems used for the tests

(may be required by the product standard or client)

Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:


Procedure number, issue date and title:

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

Statement not required by the standard or client used for type testing

CONTENTS

| | | |
|------|---|----|
| 1. | General information | 4 |
| 2. | Device information | 4 |
| 2.1. | Information about derivative model | 5 |
| 2.2. | Frequency/channel operations | 5 |
| 3. | Antenna requirement | 6 |
| 4. | Summary of tests | 7 |
| 5. | Measurement uncertainty | 8 |
| 6. | Test results | 9 |
| 6.1. | Field Strength of Fundamental and Spurious Emission | 9 |
| 6.2. | 20dB Bandwidth & Occupied Bandwidth | 14 |
| 6.3. | AC Conducted emission | 16 |
| 7. | Measurement equipment | 19 |



1. General information

Client : SUPREMA INC
Address : 17F-5, Parkview officetower,, 248, Jeongjail-ro, Bundang-gu, Seongnam-si, Gyeonggi-do 13554 Korea (Republic Of)
Manufacturer : SUPREMA INC
Address : 17F-5, Parkview officetower,, 248, Jeongjail-ro, Bundang-gu, Seongnam-si, Gyeonggi-do 13554 Korea (Republic Of)
Laboratory : Eurofins KCTL Co.,Ltd.
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132
VCCI Registration No. : R-20080, G-20078, C-20059, T-20056
CAB Identifier: KR0040, ISED Number: 8035A
KOLAS No.: KT231

2. Device information

Equipment under test : FaceStation F2
Model : FSF2-AB
Derivative Model : FSF2-DB, FSF2-ABT10, FSF2-DBT10
Frequency range : 13.56 MHz (NFC)
125 kHz (RFID)
2 402 MHz ~ 2 480 MHz (Bluetooth Low Energy)
Modulation technique : ASK (NFC,RFID), GFSK (Bluetooth Low Energy)
Number of channels : 40 ch (Bluetooth Low Energy), 1 ch (NFC, RFID)
Power source : DC 12 V, DC 24 V
Antenna specification : PCB Loop antenna (NFC)
Coil antenna (RFID)
PCB Pattern antenna (Bluetooth Low Energy)
Antenna gain : 3.03 dBi (Bluetooth Low Energy)
Software version : V2.1.1
Hardware version : V2.0.0
Operation temperature : -20 °C ~ 50 °C

2.1. Information about derivative model

The difference between basic model and derivative models is:

- 1) PCB are added to the basic model (FSF2-AB). All other internal components are the same as in the previous model. The added part does not affect the wireless part of the product.
- 2) Radio Hardware such as circuits and electrical components and Software are the same.

| Component | Basic model | Variant model |
|-----------------|--------------------|---------------------------|
| LED board | FSF2_WHITE-LED_PS1 | FSF2_WHITE-LED_V02 |
| IR LED board | FSF2_IR_LED_PS1 | FSF2_IR_LED_V01 |
| Main board | FSF2_MAIN_PS1 | FSF2_MAIN_V04 |
| RF board | FSF2_RFBD_DB_PS1 | FSF2_RFBD_DB_V02 |
| USB board | FSF2_AB_DB-USB_PS1 | FSF2_AB_DB-USB_V01 |
| Camera 1 module | SV-SUE1-ET020S | SV-SUE1-ET020S |
| Camera 2 module | SV-SUE1L-ET020S | SV-SUE1L-ET020S |


2.2. Frequency/channel operations

This device contains the following capabilities:

RFID(125 kHz)

| Ch. | Frequency (kHz) |
|-----|-----------------|
| 01 | 125 |

Table 2.2.1. RFID

| | | |
|---|--|---|
| <p>Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr</p> | <p>Report No.: KR23-SRF0036 Page (6) of (19)</p> |  |
|---|--|---|

3. Antenna requirement

Requirement of FCC part section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Requirement of RSS-Gen Section 6.8:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

-The transmitter has permanently attached Coil antenna (internal antenna) on board.

4. Summary of tests

| FCC Part section(s) | IC Rule reference | Parameter | Test results |
|---------------------|--------------------------|---|--------------|
| 15.209(a) | RSS-210 Issue 9 (8.9) | Field Strength of Fundamental and Spurious Emission | Pass |
| 2.1049 | - | 20dB Bandwidth | Pass |
| - | RSS-Gen Issue 5 (6.7) | Occupied Bandwidth | Pass |
| 15.203 | RSS-Gen Issue 5 (6.8) | Antenna requirement | Pass |
| 15.207(a) | RSS-Gen Issue 5 (8.8) | AC Conducted Emission | Pass |

Notes: (N/T: Not Tested, N/A: Not Applicable)

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- These tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
- The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that Y orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in Y orientation.
- The test procedure(s) in this report were performed in accordance as following.
 - ANSI C63.10-2013
- The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.
- The radiated test was performed with and without passive tag. The test results shown in the following sections represent the worst case emissions.
 - Worst Case : Without passive tag

5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

| Parameter | Expanded uncertainty (\pm) | |
|-----------------------------|--------------------------------|--------|
| Radiated spurious emissions | 9 kHz ~ 30 MHz | 2.4 dB |
| | 30 MHz ~ 1 000 MHz | 2.3 dB |
| | 1 000 MHz ~ 18 000 MHz | 5.6 dB |
| | Above 18 000 MHz | 5.7 dB |
| Conducted Emissions | 9 kHz ~ 150 kHz | 1.6 dB |
| | 150 kHz ~ 30 MHz | 1.7 dB |




6. Test results

6.1. Field Strength of Fundamental and Spurious Emission

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



Limit FCC

According to section 15.209(a), RSS-Gen(8.9) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field strength ($\mu\text{V}/\text{m}$) | Measurement distance (m) |
|-----------------|---|--------------------------|
| 0.009 - 0.490 | 2 400/F(kHz) | 300 |
| 0.490 - 1.705 | 24 000/F(kHz) | 30 |
| 1.705 - 30 | 30 | 30 |
| 30 - 88 | 100** | 3 |
| 88 - 216 | 150** | 3 |
| 216 - 960 | 200** | 3 |
| Above 960 | 500 | 3 |

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section 15.231 and 15.241.

IC

According to section RSS-Gen(8.9), except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter’s fundamental emission.

Table 5 – General field strength limits at frequencies above 30 MHz

| Frequency (MHz) | Field strength (µV/m at 3 m) |
|-----------------|------------------------------|
| 30 – 88 | 100 |
| 88 – 216 | 150 |
| 216 – 960 | 200 |
| Above 960 | 500 |

Table 6 – General field strength limits at frequencies below 30 MHz

| Frequency | Magnetic field strength (H-Field) (µA/m) | Measurement distance (m) |
|--------------------------|--|--------------------------|
| 9 - 490 kHz ¹ | 6.37/F (F in kHz) | 300 |
| 490 - 1705 kHz | 63.7/F (F in kHz) | 30 |
| 1.705 - 30 MHz | 0.08 | 30 |

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

Test procedure

ANSI C63.10-2013

Test settings

Test Procedures for emission from 9 kHz to 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
- c. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- d. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode.
- e. Below 30 MHz frequency range, all orientations about parallel, perpendicular, and ground-parallel were investigated then reported and the worse orientations of Face-on and Face-off were set for final test.
 - Face-on = Parallel, Face-off = Perpendicular

Notes:

1. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/D_s)$

Where:

F_d = Distance factor in dB

D_m = Measurement distance in meters

D_s = Specification distance in meters

2. The test measurement distance is 3 meter

3. Limit (dB($\mu V/m$)) = For 0.009 MHz - 0.490 MHz, $20 \cdot \log(2400/F(\text{kHz}))$ dB($\mu V/m$)
For 0.490 MHz - 1.705 MHz, $20 \cdot \log(24000/F(\text{kHz}))$ dB($\mu V/m$)
For 1.705 MHz - 30 MHz, $20 \cdot \log(30) = 29.54$ dB($\mu V/m$)



Test results

**[DC 12 V]
 Radiated Emissions Fundamental & 9 kHz to 30 MHz**

[Face-on]


| Frequency | Reading | Detector Mode | Ant. Factor | Amp. + Cable | Distance factor | Factor | Result | Limit | Margin |
|-----------|----------|---------------|-------------|--------------|-----------------|--------|------------|------------|--------|
| (MHz) | (dB(μV)) | | (dB) | (dB) | (dB) | (dB) | (dB(μV/m)) | (dB(μV/m)) | (dB) |
| 0.124 | 96.20 | PK | 19.99 | -32.43 | 80.00 | -92.44 | 3.76 | 45.74 | 41.98 |
| 0.124 | 95.80 | AV | 19.99 | -32.43 | 80.00 | -92.44 | 3.36 | 25.74 | 22.38 |
| 0.213 | 72.60 | PK | 19.94 | -32.32 | 80.00 | -92.38 | -19.78 | 41.04 | 60.82 |
| 0.213 | 69.80 | AV | 19.94 | -32.32 | 80.00 | -92.38 | -22.58 | 21.04 | 43.62 |
| 0.616 | 54.20 | QP | 19.92 | -32.20 | 40.00 | -52.28 | 1.92 | 31.81 | 29.89 |
| 25.810 | 36.50 | QP | 20.87 | -30.54 | 40.00 | -49.67 | -13.17 | 30.00 | 43.17 |

[Face-off]

| Frequency | Reading | Detector Mode | Ant. Factor | Amp. + Cable | Distance factor | Factor | Result | Limit | Margin |
|-----------|----------|---------------|-------------|--------------|-----------------|--------|------------|------------|--------|
| (MHz) | (dB(μV)) | | (dB) | (dB) | (dB) | (dB) | (dB(μV/m)) | (dB(μV/m)) | (dB) |
| 0.124 | 91.10 | PK | 19.99 | -32.43 | 80.00 | -92.44 | -1.34 | 45.74 | 47.08 |
| 0.124 | 90.80 | AV | 19.99 | -32.43 | 80.00 | -92.44 | -1.64 | 25.74 | 27.38 |
| 0.187 | 66.20 | PK | 19.96 | -32.34 | 80.00 | -92.38 | -26.18 | 42.17 | 68.35 |
| 0.187 | 64.90 | AV | 19.96 | -32.34 | 80.00 | -92.38 | -27.48 | 22.17 | 49.65 |

Note.

- 1) Factor(dB) = Antenna Factor + Amp. Gain + Cable Loss + distance factor(dB)
- 2) -80 is distance factor = $40 \cdot \log(3/300)$, -40 is distance factor = $40 \cdot \log(3/30)$
- 3) The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω.
 For example, the measurement frequency X kHz resulted in a level of Y dBμV/m, which is equivalent to $Y - 51.5 = Z$ dBμA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to the 15.209(a) limit



[DC 24 V]
Radiated Emissions Fundamental & 9 kHz to 30 MHz
[Face-on]


| Frequency (MHz) | Reading (dB(μV)) | Detector Mode | Ant. Factor (dB) | Amp. + Cable (dB) | Distance factor (dB) | Factor (dB) | Result (dB(μV/m)) | Limit (dB(μV/m)) | Margin (dB) |
|--------------------|---------------------|------------------|---------------------|----------------------|----------------------------|----------------|----------------------|---------------------|----------------|
| 0.124 | 96.50 | PK | 19.99 | -32.43 | 80.00 | -92.44 | 4.06 | 45.74 | 41.68 |
| 0.124 | 96.00 | AV | 19.99 | -32.43 | 80.00 | -92.44 | 3.56 | 25.74 | 22.18 |
| 0.187 | 73.50 | PK | 19.96 | -32.34 | 80.00 | -92.38 | -18.88 | 42.17 | 61.05 |
| 0.187 | 69.50 | AV | 19.96 | -32.34 | 80.00 | -92.38 | -22.88 | 22.17 | 45.05 |
| 0.557 | 50.90 | QP | 19.91 | -32.20 | 40.00 | -52.29 | -1.39 | 32.69 | 34.08 |
| 0.616 | 54.10 | QP | 19.92 | -32.20 | 40.00 | -52.28 | 1.82 | 31.81 | 29.99 |
| 25.810 | 36.40 | QP | 20.87 | -30.54 | 40.00 | -49.67 | -13.27 | 30.00 | 43.27 |

[Face-off]

| Frequency (MHz) | Reading (dB(μV)) | Detector Mode | Ant. Factor (dB) | Amp. + Cable (dB) | Distance factor (dB) | Factor (dB) | Result (dB(μV/m)) | Limit (dB(μV/m)) | Margin (dB) |
|--------------------|---------------------|------------------|---------------------|----------------------|----------------------------|----------------|----------------------|---------------------|----------------|
| 0.124 | 91.20 | PK | 19.99 | -32.43 | 80.00 | -92.44 | -1.24 | 45.74 | 46.98 |
| 0.124 | 91.00 | AV | 19.99 | -32.43 | 80.00 | -92.44 | -1.44 | 25.74 | 27.18 |
| 0.370 | 56.50 | PK | 19.90 | -32.26 | 80.00 | -92.36 | -35.86 | 36.24 | 72.10 |
| 0.370 | 53.00 | AV | 19.90 | -32.26 | 80.00 | -92.36 | -39.36 | 16.24 | 55.60 |
| 0.613 | 44.90 | QP | 19.92 | -32.20 | 40.00 | -52.28 | -7.38 | 31.86 | 39.24 |


Note.

- 1) Factor(dB) = Antenna Factor + Amp. Gain + Cable Loss + distance factor(dB)
- 2) -80 is distance factor = $40 \cdot \log(3/300)$, -40 is distance factor = $40 \cdot \log(3/30)$
- 3) The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω .
 For example, the measurement frequency X kHz resulted in a level of Y dBμV/m, which is equivalent to $Y - 51.5 = Z$ dBμA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to the 15.209(a) limit



6.2. 20dB Bandwidth & Occupied Bandwidth

Test setup



Limit

For reporting purpose only

Test settings

The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

- The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

A peak, or peak hold, may be used in place of the sampling detector as this may produce a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold may be necessary to determine the occupied bandwidth if the device is not transmitting continuously.


The trace data points are recovered and are directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded.

The difference between the two recorded frequencies is the 99% occupied bandwidth.

Test results

| Power source | Frequency (kHz) | 20dB Bandwidth (kHz) | Occupied Bandwidth (kHz) | Limit |
|--------------|-----------------|----------------------|--------------------------|------------------------|
| DC 12 V | 125 | 0.86 | 15.755 8 | Reporting purpose only |
| DC 24 V | 125 | 0.81 | 15.205 8 | Reporting purpose only |


Test Plots



Note. Because the measured signal is CW/CW-like, adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

6.3. AC Conducted emission

Test setup



Limit


According to 15.207(a) and RSS-Gen(8.8), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

| Frequency of Emission (MHz) | Conducted limit (dB μ V/m) | |
|-----------------------------|--------------------------------|----------|
| | Quasi-peak | Average |
| 0.15 – 0.50 | 66 - 56* | 56 - 46* |
| 0.50 – 5.00 | 56 | 46 |
| 5.00 – 30.0 | 60 | 50 |

Measurement procedure

1. The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
2. Each current-carrying conductor of the EUT power cord was individually connected through a 50 Ω /50 μ H LISN, which is an input transducer to a spectrum analyzer or an EMI/Field Intensity Meter, to the input power source.
3. Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
4. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
5. The measurements were made with the detector set to peak amplitude within a bandwidth of 10 kHz or to quasi-peak and average within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

Test results
[DC 12 V]



Final Result


--- N Phase ---

| No. | Frequency [MHz] | Reading QP [dB(uV)] | Reading CAV [dB(uV)] | c. f [dB] | Result QP [dB(uV)] | Result CAV [dB(uV)] | Limit QP [dB(uV)] | Limit AV [dB(uV)] | Margin QP [dB] | Margin CAV [dB] |
|-----|-----------------|---------------------|----------------------|-----------|--------------------|---------------------|-------------------|-------------------|----------------|-----------------|
| 1 | 0.18424 | 37.6 | 21.3 | 10.0 | 47.6 | 31.3 | 64.3 | 54.3 | 16.7 | 23.0 |
| 2 | 0.27523 | 31.2 | 16.9 | 9.6 | 40.8 | 26.5 | 61.0 | 51.0 | 20.2 | 24.5 |
| 3 | 0.49762 | 31.4 | 22.5 | 9.8 | 41.2 | 32.3 | 56.0 | 46.0 | 14.8 | 13.7 |
| 4 | 0.83781 | 13.4 | 3.7 | 9.8 | 23.2 | 13.5 | 56.0 | 46.0 | 32.8 | 32.5 |
| 5 | 3.19135 | 9.8 | 2.5 | 9.7 | 19.5 | 12.2 | 56.0 | 46.0 | 36.5 | 33.8 |
| 6 | 12.41446 | 10.1 | 4.4 | 9.9 | 20.0 | 14.3 | 60.0 | 50.0 | 40.0 | 35.7 |

--- L1 Phase ---

| No. | Frequency [MHz] | Reading QP [dB(uV)] | Reading CAV [dB(uV)] | c. f [dB] | Result QP [dB(uV)] | Result CAV [dB(uV)] | Limit QP [dB(uV)] | Limit AV [dB(uV)] | Margin QP [dB] | Margin CAV [dB] |
|-----|-----------------|---------------------|----------------------|-----------|--------------------|---------------------|-------------------|-------------------|----------------|-----------------|
| 1 | 0.15644 | 28.4 | 6.8 | 9.8 | 38.2 | 16.6 | 65.7 | 55.7 | 27.5 | 39.1 |
| 2 | 0.28977 | 27.5 | 14.2 | 9.6 | 37.1 | 23.8 | 60.5 | 50.5 | 23.4 | 26.7 |
| 3 | 0.44877 | 20.9 | 8.9 | 9.8 | 30.7 | 18.7 | 56.9 | 46.9 | 26.2 | 28.2 |
| 4 | 0.62961 | 21.4 | 13.9 | 9.8 | 31.2 | 23.7 | 56.0 | 46.0 | 24.8 | 22.3 |
| 5 | 1.15707 | 14.4 | 7.9 | 9.7 | 24.1 | 17.6 | 56.0 | 46.0 | 31.9 | 28.4 |
| 6 | 11.74437 | 14.0 | 8.6 | 9.8 | 23.8 | 18.4 | 60.0 | 50.0 | 36.2 | 31.6 |

[DC 24 V]



Final Result

| --- N Phase --- | | | | | | | | | | |
|-----------------|-----------------|---------------------|----------------------|----------|--------------------|---------------------|-------------------|-------------------|----------------|-----------------|
| No. | Frequency [MHz] | Reading QP [dB(uV)] | Reading CAV [dB(uV)] | c.f [dB] | Result QP [dB(uV)] | Result CAV [dB(uV)] | Limit QP [dB(uV)] | Limit AV [dB(uV)] | Margin QP [dB] | Margin CAV [dB] |
| 1 | 0.15369 | 36.9 | 18.0 | 9.8 | 46.7 | 27.8 | 65.8 | 55.8 | 19.1 | 28.0 |
| 2 | 0.19009 | 32.9 | 18.5 | 10.0 | 42.9 | 28.5 | 64.0 | 54.0 | 21.1 | 25.5 |
| 3 | 0.22269 | 28.2 | 15.9 | 9.7 | 37.9 | 25.6 | 62.7 | 52.7 | 24.8 | 27.1 |
| 4 | 0.45536 | 32.3 | 26.0 | 9.8 | 42.1 | 35.8 | 56.8 | 46.8 | 14.7 | 11.0 |
| 5 | 0.65347 | 22.2 | 15.5 | 9.8 | 32.0 | 25.3 | 56.0 | 46.0 | 24.0 | 20.7 |
| 6 | 23.27255 | 22.5 | 17.5 | 9.9 | 32.4 | 27.4 | 60.0 | 50.0 | 27.6 | 22.6 |

| --- L1 Phase --- | | | | | | | | | | |
|------------------|-----------------|---------------------|----------------------|----------|--------------------|---------------------|-------------------|-------------------|----------------|-----------------|
| No. | Frequency [MHz] | Reading QP [dB(uV)] | Reading CAV [dB(uV)] | c.f [dB] | Result QP [dB(uV)] | Result CAV [dB(uV)] | Limit QP [dB(uV)] | Limit AV [dB(uV)] | Margin QP [dB] | Margin CAV [dB] |
| 1 | 0.21805 | 30.1 | 17.0 | 9.8 | 39.9 | 26.8 | 62.9 | 52.9 | 23.0 | 26.1 |
| 2 | 0.24406 | 27.4 | 16.8 | 9.6 | 37.0 | 26.4 | 62.0 | 52.0 | 25.0 | 25.6 |
| 3 | 0.44334 | 33.0 | 26.5 | 9.8 | 42.8 | 36.3 | 57.0 | 47.0 | 14.2 | 10.7 |
| 4 | 0.8322 | 20.7 | 14.3 | 9.8 | 30.5 | 24.1 | 56.0 | 46.0 | 25.5 | 21.9 |
| 5 | 2.58446 | 20.4 | 14.5 | 9.7 | 30.1 | 24.2 | 56.0 | 46.0 | 25.9 | 21.8 |
| 6 | 24.75495 | 22.6 | 18.0 | 10.0 | 32.6 | 28.0 | 60.0 | 50.0 | 27.4 | 22.0 |

7. Measurement equipment

| Equipment Name | Manufacturer | Model No. | Serial No. | Next Cal. Date |
|-------------------------|------------------|------------|-----------------|----------------|
| Spectrum Analyzer | R&S | FSV30 | 100808 | 23.07.11 |
| DC Power Supply | AGILENT | E3632A | MY40004791 | 23.09.14 |
| EMI TEST RECEIVER | R&S | ESC17 | 100732 | 23.03.04 |
| AMPLIFIER | SONOMA | 310N | 284608 | 23.08.18 |
| ISOLATION TRANSFORMER | ONETECH CO., LTD | OT-IT500VA | OTR1-16026 | 23.03.28 |
| Loop Antenna | R&S | HFH2-Z2 | 100355 | 24.08.10 |
| Vector Signal Generator | R&S | SMBV100A | 257566 | 23.07.04 |
| Signal Generator | R&S | SMB100A | 176206 | 23.01.19 |
| TWO-LINE V - NETWORK | R&S | ENV216 | 101358 | 23.09.29 |
| EMI TEST RECEIVER | R&S | ESC13 | 100001 | 23.08.18 |
| Antenna Mast | Innco Systems | MA4000-EP | 303 | - |
| Turn Table | Innco Systems | CO3000 | 1175/45850319/P | - |

End of test report