

# Radio Exposure Evaluation Report

**FCC ID** : TKZAW7915NP1

**Equipment** : WiFi6 11ax 4T4R module 2400Mbps

**Brand Name** : AsiaRF Co., Ltd.

**Model Name** : AW7915-NP1

**Applicant** : AsiaRF Co., Ltd.  
1F, 7, Houde Street, Yonghe Dist. New Taipei City  
Taiwan 23455

**Manufacturer** : AsiaRF Co., Ltd.  
1F, 7, Houde Street, Yonghe Dist. New Taipei City  
Taiwan 23455

**Standard** : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Aug. 30, 2021, and testing was started from Sep. 18, 2021 and completed on Nov. 03, 2021. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

**SPORTON INTERNATIONAL INC. Hsinhua Laboratory**  
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



## Table of Contents

**HISTORY OF THIS TEST REPORT .....3**

**1 GENERAL DESCRIPTION .....5**

1.1 Information.....5

1.2 Testing Location .....6

**2 MAXIMUM PERMISSIBLE EXPOSURE .....7**

2.1 Limit of Maximum Permissible Exposure .....7

2.2 MPE Calculation Method .....7

2.3 Calculated Result and Limit.....8

### Photographs of EUT V01



### History of this test report

<b>Report No.</b>	<b>Version</b>	<b>Description</b>	<b>Issued Date</b>
FA162806-01	01	Initial issue of report	Nov. 10, 2021



### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
None

Reviewed by: Sam Tsai

Report Producer: Amber Chiu

# 1 General Description

## 1.1 Information

### 1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)

### 1.1.2 Antenna Information

Group	Ant.	Brand	Model Name	Antenna Type	Connector	Support
Group 1	1-4	Asiarf	ANT010-DAU	PCB	I-Pex	2.4G+5G
Group 2	5-8	Asiarf	ANT003	PCB	I-Pex	2.4G+5G
Group 3	9-12	Asiarf	A245005N	PCB	I-Pex	2.4G+5G
Group 4	13-16	Asiarf	A2405N	PCB	I-Pex	2.4G
Group 5	17-20	Asiarf	A5005N	PCB	I-Pex	5G
Group 6	21-24	Asiarf	A245004	Dipole	I-Pex	2.4G+5G
Group 7	25-28	Asiarf	A245002	Dipole	I-Pex	2.4G+5G



Group	Ant.	Gain (dBi)	
		2.4G	5G
Group 1	1-4	5.2	5.5
Group 2	5-8	2.5	2.5
Group 3	9-12	4	5.1
Group 4	13-16	5.2	-
Group 5	17-20	-	5
Group 6	21-24	4	5.1
Group 7	25-28	2	2

Note 1: EUT can match with above antennas for using. Higher gain in each type of antenna was used to perform the worst configuration and result of that was recorded as the final test result.

**For 2.4GHz function:**

For IEEE 802.11 b/g/n/VHT/ax mode (4TX/4RX)

Group 1, Group 2, Group 3, Group 4, Group 6 or Group 7 could transmit/receive.

**For 5GHz function:**

For IEEE 802.11 a/n/ac/ax mode (4TX/4RX)

Group 1, Group 2, Group 3, Group 5, Group 6 or Group 7 could transmit/receive.

### 1.2 Testing Location

Test Lab. : Sporton International Inc. Hsinhua Laboratory		
<input checked="" type="checkbox"/>	Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.) TEL: 886-3-327-3456      FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.		
<input type="checkbox"/>	Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: 886-3-318-0787      FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.		

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

### 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Wi-Fi 2.4GHz Function

<Non-Beamforming>

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
2.4G;G1D	5.20	26.99	32.19	0.50	32.69	1.85780	20	0.36960	1.00000
2.4G;D1D	5.20	24.49	29.69	0.50	30.19	1.04472	20	0.20784	1.00000

<Beamforming>

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
2.4G;D1D	11.22	18.22	29.44	0.50	29.94	0.98628	20	0.19621	1.00000

Wi-Fi 5GHz Function

<Non-Beamforming>

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
5.2G;D1D	5.50	19.18	24.68	0.50	25.18	0.32961	20	0.06557	1.00000
5.8G;D1D	5.50	19.62	25.12	0.50	25.62	0.36475	20	0.07256	1.00000

<Beamforming>

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
5.2G;D1D	11.52	13.16	24.68	0.50	25.18	0.32961	20	0.06557	1.00000
5.8G;D1D	11.52	12.36	23.88	0.50	24.38	0.27416	20	0.05454	1.00000

————THE END————