



# RF EXPOSURE REPORT

**REPORT NO.:** SA980611L03

**MODEL NO.:** AW-BT261

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** AzureWave Technologies, Inc.

**ADDRESS:** 8F, No. 94, Baozhong Rd., Xindian, Taipei, Taiwan 231

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.) Ltd.,  
Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,  
Taipei Hsien 244, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan  
Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No evaluation required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.580
High	2.480	

Maximum measured transmitter power:

Pout (dBm)	Pout (mW)	
Conducted Power	5.18	3.296
EIRP Power	5.75	3.758

**\*Note:** The antenna is printed antenna with 0.57dBi gain

Threshold for no SAR evaluation is 24.580mW  
 Transmitter power is 3.758mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold