



# RF Exposure Evaluation Report

**Equipment** : IEEE 802.11 1X1 ac/a/b/g/n Wireless LAN +Bluetooth NGFF Module

**Brand Name** : AzureWave

**Model No.** : AW-CM286NF

**FCC ID** : TLZ-CM286NF

**Standard** : 47 CFR Part 2.1091

**Applicant** : AzureWave Technologies, Inc.  
8F., No.94, Baozhong Rd. , Xindian Dist., New Taipei City , Taiwan 231

**Manufacturer** : AzureWave Technologies, Inc.  
8F., No.94, Baozhong Rd. , Xindian Dist., New Taipei City , Taiwan 231

The product sample received on Nov. 03, 2016 and completely tested on Nov. 22, 2016. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091 and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

  
Cliff Chang  
SPORTON INTERNATIONAL INC.





## TABLE OF CONTENTS

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>4</b>
1.1	EUT General Information .....	4
1.2	Testing Location .....	4
<b>2</b>	<b>MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>5</b>
2.1	Limit of Maximum Permissible Exposure .....	5
2.2	MPE Calculation Method .....	5
2.3	Calculated Result and Limit.....	6
	<b>PHOTOGRAPHS OF EUT V02</b>	



**REVISION HISTORY**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA6O2108	Rev. 01	Initial issue of report	Jun. 13, 2017
FA6O2108	Rev. 02	Changing the Photographs of EUT	Jun. 15, 2017



# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: DSSS (GFSK)

## 1.2 Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
2.4G;G1D	1.04	19.53	20.57	0.11402	20	0.02268	1
2.4G;BT-LE	1.04	14.23	15.27	0.03365	20	0.00669	1
2.4G;BT-EDR	1.04	5.54	6.58	0.00455	20	0.00091	1
5.2G;D1D	1.42	18.55	19.97	0.09931	20	0.01976	1
5.3G;D1D	1.42	18.20	19.62	0.09162	20	0.01823	1
5.6G;D1D	2.59	19.50	22.09	0.16181	20	0.03219	1
5.8G;D1D	2.59	16.34	18.93	0.07816	20	0.01555	1

Simultaneous Transmission Analysis Mode: Bluetooth+WLAN 2.4GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
2.4G;G1D	1.04	19.53	20.57	0.11402	20	0.02268	1	0.02268
2.4G;BT-LE	1.04	14.23	15.27	0.03365	20	0.00669	1	0.00669
							Sum Ratio	0.02937
							Ratio Limit	1

Simultaneous Transmission Analysis Mode: Bluetooth+WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
5.6G;D1D	2.59	19.50	22.09	0.16181	20	0.03219	1	0.03219
2.4G;BT-LE	1.04	14.23	15.27	0.03365	20	0.00669	1	0.00669
							Sum Ratio	0.03888
							Ratio Limit	1