

FCC RF Exposure Report

FCC ID : TLZ-CM299

Equipment : IEEE 802.11 1X1 ac/a/b/g/n Wireless LAN +

Bluetooth Module

Model No. : AW-CM299

Brand Name : AzureWave

Applicant : AzureWave Technologies, Inc.

Address : 8F, No. 94, Baozhong Rd., Xindian Dist., New

Taipei City, Taiwan 231

Standard : 47 CFR FCC Part 2.1091

Received Date : Jul. 18, 2017

Tested Date : Nov. 07 ~ Dec. 26, 2017

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen Assistant Manager Gary Chang / Manager

Testing Laboratory 2732

Report No.: FA771801 Page: 1 of 6



Table of Contents

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	4
1.2	MPE EVALUATION FORMULA	4
1.3	MPE EVALUATION RESULTS	5
2	TEST LABORATORY INFORMATION	6

Report No.: FA771801

Page : 2 of 6



Release Record

Report No.	Version	Description	Issued Date
FA771801	Rev. 01	Initial issue	Jan. 31, 2018

Report No.: FA771801 Page: 3 of 6



1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)		
300~1500	F/1500	30		
1500~100000	1.0	30		

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4*Pi*R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in mW Pi= 3.1416

R= Measurement distance

Report No.: FA771801 Page: 4 of 6



1.3 MPE EVALUATION RESULTS

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)		
For WLAN								
2412~2462	17.15	17.5	2.09	20	0.018	1		
5180~5240	15.97	16.0	4.32	20	0.021	1		
5260~5320	16.49	16.5	4.32	20	0.024	1		
5500~5700	16.47	16.5	4.32	20	0.024	1		
5745~5825	16.47	16.5	4.32	20	0.024	1		
For BT								
2402~2480 EDR	12.38	12.5	2.09	20	0.006	1		
2402~2480 LE	11.59	12.0	2.09	20	0.005	1		

Report No.: FA771801 Page : 5 of 6



2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City,

Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FA771801 Page: 6 of 6