




FCC RADIO TEST REPORT

FCC ID : TLZ-CU462
Equipment : IEEE 802.11 b/g/n 1T1R WLAN and Bluetooth Low Energy Microcontroller Module
Brand Name : AzureWave
Model Name : AW-CU462
Applicant : AzureWave Technologies, Inc.
8F., No.94, Baozhong Rd. , Xindian Dist., New Taipei City , Taiwan 231
Standard : 47 CFR FCC Part 15.247

The product was received on May 19, 2020, and testing was started from May 27, 2020 and completed on Jun. 24, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.


Approved by: Cliff Chang

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....3

Summary of Test Result.....4

1 General Description5

1.1 Information.....5

1.2 Applicable Standards7

1.3 Testing Location Information.....7

1.4 Measurement Uncertainty7

2 Test Configuration of EUT8

2.1 Test Channel Mode8

2.2 The Worst Case Measurement Configuration.....9

2.3 EUT Operation during Test10

2.4 Accessories10

2.5 Support Equipment.....11

2.6 Test Setup Diagram12

3 Transmitter Test Result15

3.1 AC Power-line Conducted Emissions15

3.2 DTS Bandwidth17

3.3 Maximum Conducted Output Power18

3.4 Power Spectral Density21

3.5 Emissions in Non-restricted Frequency Bands23

3.6 Emissions in Restricted Frequency Bands.....24

4 Test Equipment and Calibration Data28

Appendix A. Test Results of AC Power-line Conducted Emissions

Appendix B. Test Results of DTS Bandwidth

Appendix C. Test Results of Maximum Conducted Output Power

Appendix D. Test Results of Power Spectral Density

Appendix E. Test Results of Emissions in Non-restricted Frequency Bands

Appendix F. Test Results of Emissions in Restricted Frequency Bands

Appendix G. Test Photos

Photographs of EUT v01



History of this test report

Report No.	Version	Description	Issued Date
FR051942AA	01	Initial issue of report	Jul. 08, 2020



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(a)	DTS Bandwidth	PASS	-
3.3	15.247(b)	Maximum Conducted Output Power	PASS	-
3.4	15.247(e)	Power Spectral Density	PASS	-
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	-
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: **Sam Chen**

Report Producer: **Wendy Pan**



1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-LE(1Mbps)	1	1
2.4-2.4835GHz	BT-LE(2Mbps)	2	1

Note:

- ♦ Bluetooth LE uses a GFSK modulation.
- ♦ BWch is the nominal channel bandwidth.

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
1	Azurewave	AW-CU462	PCB Printing Antenna	N/A	2.1	1TX/1RX

Note: The above information was declared by manufacturer.

1.1.3 Mode Test Duty Cycle

Mode	DC	DCF(dB)	T(s)	VBW(Hz) ≥ 1/T
BT-LE(1Mbps)	0.856	0.68	2.139m	1k
BT-LE(2Mbps)	0.559	2.53	1.081m	1k

Note:

- ♦ DC is Duty Cycle.
- ♦ DCF is Duty Cycle Factor.



1.1.4 EUT Operational Condition

EUT Power Type	From host system	
Function	<input checked="" type="checkbox"/> Point-to-multipoint	<input type="checkbox"/> Point-to-point
Test Software Version	RtlBluetoothMP.dll Version : 5.2.2.51 / RTLBTAPP Version : 5.2.2.34	
Support Mode	<input checked="" type="checkbox"/> LE 1M PHY: 1 Mb/s	
	<input type="checkbox"/> LE Coded PHY (S=2): 500 Kb/s	
	<input type="checkbox"/> LE Coded PHY (S=8): 125 Kb/s	
	<input checked="" type="checkbox"/> LE 2M PHY: 2 Mb/s	

Note: The above information was declared by manufacturer.

1.1.5 Table for EUT source

The EUT has two source which are identical to each other in all aspects except for the following table:

Item	EUT 1 (Main Source)				
	Flash	X'tal	Power Inductor	RF Inductor	capacitance
Brand Name	GigaDevice	SIWARD	TDK	TDK	Murata
Model Name	GD25Q32CTIGR	XTL571100-A 263-101	MLP2012S2R2M T0S1	MLG0603P1N0B T000 MLG0603P2N2B T000	GRM0335C1E1R5C D01D
Item	EUT 2 (Second Source)				
	Flash	X'tal	Power Inductor	RF Inductor	capacitance
Brand Name	XTX	TXC	TAI-TECH	Sunlord	EYANG
Model Name	XT25F32B-S	7M40000010	PI201210UF-2R2 M-0A8-NB	SDCL0603Q1N0 BT02B01 SDCL0603Q2N2 BT02B01	C0201C0G1R5C500 NTA



1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15
- ◆ ANSI C63.10-2013

The following reference test guidance is not within the scope of accreditation of TAF.

- ◆ FCC KDB 558074 D01 v05r02
- ◆ FCC KDB 414788 D01 v01r01

1.3 Testing Location Information

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH03-CB	Brian Sin	24-24.6°C / 64-70%	May 27, 2020 ~ May 28, 2020
Radiated<1GHz	03CH01-CB	Paul Chen	28.4-29.2°C / 58-63	Jun. 19, 2020
Radiated>1GHz	03CH03-CB	Brian Sin	23.9-24.8°C / 65-68	May 27, 2020
AC Conduction	CO01-CB	Ryo Fan	23~24°C / 62~63%	Jun. 24, 2020

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086D with Industry Canada.

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.0 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	5.1 dB	Confidence levels of 95%
Conducted Emission	2.4 dB	Confidence levels of 95%
Output Power Measurement	1.5 dB	Confidence levels of 95%
Power Density Measurement	2.4 dB	Confidence levels of 95%
Bandwidth Measurement	2%	Confidence levels of 95%



2 Test Configuration of EUT

2.1 Test Channel Mode

Mode	Power Setting
BT-LE(1Mbps)	-
2402MHz	0x39
2440MHz	0x38
2480MHz	0x2c
BT-LE(2Mbps)	-
2402MHz	0x39
2440MHz	0x39
2480MHz	0x2a



2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	Normal Link
1	EUT 1
2	EUT 2
For operating mode 1 is the worst case and it was record in this test report.	

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains
The EUT has two sources, after evaluating, main source has been evaluated to be the worst case, so it was selected to test and record in this test report.	
Test Mode	EUT 1

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emissions in Restricted Frequency Bands
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	Normal Link
1	EUT 1 in Z axis
2	EUT 1 in Y axis
Mode 1 has been evaluated to be the worst case between Mode 1~2, thus measurement for Mode 3 will follow this same test mode.	
3	EUT 2 in Z axis
For operating mode 1 is the worst case and it was record in this test report.	
Operating Mode > 1GHz	CTX
<ol style="list-style-type: none"> The EUT was performed at X axis, Y axis and Z axis position test, and the worst case was found at Z axis. So the measurement will follow this same test configuration. The EUT has two sources, after evaluating, main source has been evaluated to be the worst case, so it was selected to test and record in this test report. 	
1	EUT 1 in Z axis



2.3 EUT Operation during Test

For CTX Mode:

The EUT was programmed to be in continuously transmitting mode.

For Normal Link:

During the test, the EUT operation to normal function.

2.4 Accessories

N/A



2.5 Support Equipment

For AC Conduction:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Fixture	Azurewave	AW-CU462-11	N/A
B	NB	DELL	E6430	N/A
C	Earphone	e-Power	S90W	N/A
D	Mouse	HP	FM100	N/A
E	AP Router	ASUS	RP-N53	MSQ-RPN53
F	Smart phone	Samsung	Galaxy J2	A3LSMJ200F
G	AP NB	DELL	E6430	N/A


For Radiated (below 1GHz):

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Notebook	DELL	E4300	N/A
B	Fixture	Azurewave	AW-CU462-11	N/A
C	Earphone	e-Power	S90W	N/A
D	Mouse	Logitech	M-U0026	N/A
E	WLAN AP	NETGEAR	WNDR3300v2	PY309300116
F	Notebook	DELL	E4300	N/A
G	Smart phone	Samsung	Galaxy J2	A3LSMJ200F


For Radiated (above 1GHz) and RF Conducted:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Notebook	DELL	E4300	N/A
B	Fixture	Azurewave	AW-CU462-11	N/A

2.6 Test Setup Diagram




Test Setup Diagram - Radiated Test < 1GHz



Item	Connection	Shielded	Length
1	USB cable	Yes	1.8m
2	Audio cable	No	1.4m
3	USB cable	Yes	1.8m
4	RJ-45 cable	No	1.5m
5	Power Cable	No	2.6m

Test Setup Diagram - Radiated Test > 1GHz



Item	Connection	Shielded	Length
1	USB cable	Yes	1.8m
2	Power Cable	No	2.6m



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



1.1.1. Measurement Results Calculation

The measured Level is calculated using:

- a. Corrected Reading (dBuV) = LISN Factor + Cable Loss + Read Level = Level
- b. Margin = - Limit + (Read Level + LISN Factor + Cable Loss)

3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
Systems using digital modulation techniques:
<ul style="list-style-type: none"> ▪ 6 dB bandwidth \geq 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
<ul style="list-style-type: none"> ▪ For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B



3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	<ul style="list-style-type: none"> ▪ If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	<ul style="list-style-type: none"> ▪ Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	<ul style="list-style-type: none"> ▪ Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> ▪ Smart antenna system (SAS):
	<ul style="list-style-type: none"> - Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> - Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> - Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
<p>P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.</p>	

3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.



3.3.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> ▪ Maximum Peak Conducted Output Power 	
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.1.1 & C63.10 clause 11.9.1.1 (RBW ≥ EBW method).
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.1.3 & C63.10 clause 11.9.1.3 (peak power meter).
<ul style="list-style-type: none"> ▪ Maximum Conducted Output Power 	
[duty cycle ≥ 98% or external video / power trigger]	
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.2 Method AVGSA-1.
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.3 Method AVGSA-1A. (alternative)
duty cycle < 98% and average over on/off periods with duty factor	
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.4 Method AVGSA-2.
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.5 Method AVGSA-2A (alternative)
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.6 Method AVGSA-3
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.7 Method AVGSA-3A (alternative)
Measurement using a power meter (PM)	
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.1 Method AVGPM (using an RF average power meter).
	<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.2 Method AVGPM-G (using an gate RF average power meter).
<ul style="list-style-type: none"> ▪ For conducted measurement. 	
	<ul style="list-style-type: none"> ▪ If the EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
	<ul style="list-style-type: none"> ▪ If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C



3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
<ul style="list-style-type: none"> Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10 Method Max. PSD. [duty cycle ≥ 98% or external video / power trigger]
<ul style="list-style-type: none"> For conducted measurement.
<ul style="list-style-type: none"> If The EUT supports multiple transmit chains using options given below: <ul style="list-style-type: none"> <input type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace. <input type="checkbox"/> Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits, <input type="checkbox"/> Option 3: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Refer as FCC KDB 558074, clause 8.5 for unwanted emissions into non-restricted bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E



3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.




3.6.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> ▪ The average emission levels shall be measured in [duty cycle \geq 98 or duty factor]. 	
<ul style="list-style-type: none"> ▪ Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band. 	
<ul style="list-style-type: none"> ▪ For the transmitter unwanted emissions shall be measured using following options below: 	
	<ul style="list-style-type: none"> ▪ Refer as FCC KDB 558074, clause 8.6 for unwanted emissions into restricted bands.
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.1(trace averaging for duty cycle \geq 98%).
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.2(trace averaging + duty factor).
	<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.3(Reduced VBW \geq 1/T).
	<input type="checkbox"/> Refer as ANSI C63.10, clause 11.12.2.5.3 (Reduced VBW). VBW \geq 1/T, where T is pulse time.
	<input type="checkbox"/> Refer as ANSI C63.10, clause 7.5 average value of pulsed emissions.
	<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.4 measurement procedure peak limit.
<ul style="list-style-type: none"> ▪ For the transmitter band-edge emissions shall be measured using following options below: 	
	<ul style="list-style-type: none"> ▪ Refer as FCC KDB 558074 clause 8.7 & c63.10 clause 11.13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	<ul style="list-style-type: none"> ▪ Refer as FCC KDB 558074, clause 8.7 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements.
	<ul style="list-style-type: none"> ▪ Refer as FCC KDB 558074, clause 8.7 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
	<ul style="list-style-type: none"> ▪ For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB
	<ul style="list-style-type: none"> ▪ For FCC KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.

3.6.4 Test Setup





3.6.5 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor (if applicable) = Level.

3.6.6 Emissions in Restricted Frequency Bands (Below 30MHz)

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to KDB414788 Radiated Test Site, and the result came out very similar.

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10 harmonic or 40 GHz, whichever is appropriate.

3.6.7 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F



4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.45GHz	Feb. 26, 2020	Feb. 25, 2021	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 25, 2019	Dec. 24, 2020	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Feb. 25, 2020	Feb. 24, 2021	Conduction (CO01-CB)
Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz ~ 30MHz	Jan. 31, 2020	Jan. 30, 2021	Conduction (CO01-CB)
COND Cable	Woken	Cable	Low cable-CO01	9kHz ~ 30MHz	May 20, 2020	May 19, 2021	Conduction (CO01-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	N.C.R.	Conduction (CO01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Apr. 13, 2020	Apr. 12, 2021	Radiation (03CH01-CB)
Bilog Antenna with 6dB Attenuator	Schaffner & EMCI	CBL6112 & N-6-06	2888 & AT-N0611	30MHz ~ 1GHz	Oct. 12, 2019	Oct. 11, 2020	Radiation (03CH01-CB)
Pre-Amplifier	EMCI	EMC330N	980332	20MHz ~ 3GHz	May 21, 2020	May 20, 2021	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Apr. 16, 2020	Apr. 15, 2021	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS	826547/017	9kHz ~ 2.75GHz	May 13, 2020	May 12, 2021	Radiation (03CH01-CB)
RF Cable-low	Woken	RG402	Low Cable-16+17	30 MHz ~ 1 GHz	Feb. 01, 2020	Jan. 31, 2021	Radiation (03CH01-CB)
Horn Antenna	ETS • Lindgren	3115	6821	750MHz~18GHz	Jan. 20, 2020	Jan. 19, 2021	Radiation (03CH03-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jun. 27, 2019	Jun. 26, 2020	Radiation (03CH03-CB)
Pre-Amplifier	EMCI	EMC12630SE	980383	1GHz ~ 26.5GHz	Aug. 02, 2019	Aug. 01, 2020	Radiation (03CH03-CB)
Pre-Amplifier	MITEQ	TTA1840-35-HG	1864479	18GHz ~ 40GHz	Jul. 03, 2019	Jul. 02, 2020	Radiation (03CH03-CB)
Spectrum Analyzer	R&S	FSP40	100019	9kHz ~ 40GHz	Jun. 19, 2019	Jun. 18, 2020	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-20+27	1GHz ~ 18GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-27	1GHz ~ 18GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-40G#1	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-40G#2	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH03-CB)
Spectrum analyzer	R&S	FSV40	101028	9kHz~40GHz	Nov. 01, 2019	Oct. 31, 2020	Conducted (TH03-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
Power Sensor	Anritsu	MA2411B	1726195	300MHz~40GHz	Aug. 13, 2019	Aug. 12, 2020	Conducted (TH03-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Aug. 13, 2019	Aug. 12, 2020	Conducted (TH03-CB)
RF Cable-high	Woken	RG402	High Cable-11	1 GHz – 26.5 GHz	Oct. 07, 2019	Oct. 06, 2020	Conducted (TH03-CB)
RF Cable-high	Woken	RG402	High Cable-12	1 GHz – 26.5 GHz	Oct. 07, 2019	Oct. 06, 2020	Conducted (TH03-CB)
RF Cable-high	Woken	RG402	High Cable-13	1 GHz – 26.5 GHz	Oct. 07, 2019	Oct. 06, 2020	Conducted (TH03-CB)
RF Cable-high	Woken	RG402	High Cable-14	1 GHz – 26.5 GHz	Oct. 07, 2019	Oct. 06, 2020	Conducted (TH03-CB)
RF Cable-high	Woken	RG402	High Cable-15	1 GHz – 26.5 GHz	Oct. 07, 2019	Oct. 06, 2020	Conducted (TH03-CB)


Note: Calibration Interval of instruments listed above is one year.


N.C.R. means Non-Calibration required.



Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition
Mode 1	Pass	QP	168k	50.14	65.06	-14.92	9.86	Neutral







Summary



Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	660k	1.029M	1M03F1D	658.75k	1.024M
BT-LE(2Mbps)	1.125M	2.046M	2M05F1D	1.12M	2.039M



Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	660k	1.028M
2440MHz	Pass	500k	658.75k	1.024M
2480MHz	Pass	500k	658.75k	1.029M
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	500k	1.12M	2.039M
2440MHz	Pass	500k	1.125M	2.041M
2480MHz	Pass	500k	1.123M	2.046M

Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;






BT-LE(2Mbps)

EBW

2440MHz

28/05/2020




BT-LE(2Mbps)

EBW

2480MHz

28/05/2020





Summary

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	16.96	0.04966
BT-LE(2Mbps)	17.15	0.05188

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	2.10	16.96	30.00
2440MHz	Pass	2.10	16.60	30.00
2480MHz	Pass	2.10	9.01	30.00
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	2.10	17.11	30.00
2440MHz	Pass	2.10	17.15	30.00
2480MHz	Pass	2.10	7.95	30.00

DG = Directional Gain; Port X = Port X output power



Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	0.64
BT-LE(2Mbps)	-0.72




RBW=3 kHz.




Result

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	2.10	0.64	8.00
2440MHz	Pass	2.10	-0.93	8.00
2480MHz	Pass	2.10	-8.96	8.00
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	2.10	-0.72	8.00
2440MHz	Pass	2.10	-1.11	8.00
2480MHz	Pass	2.10	-10.58	8.00

DG = Directional Gain; RBW=3 kHz;

PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X power density;











Summary



Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.40221G	16.38	-13.62	573.73M	-54.45	2.39976G	-43.54	2.4G	-42.22	2.48693G	-53.60	16.35291G	-47.68	1
BT-LE(2Mbps)	Pass	2.44G	16.51	-13.49	824.3M	-54.18	2.39997G	-16.62	2.4G	-18.64	2.50099G	-53.13	16.58631G	-48.02	1

Result

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.40221G	16.38	-13.62	573.73M	-54.45	2.39976G	-43.54	2.4G	-42.22	2.48693G	-53.60	16.35291G	-47.68	1
2440MHz	Pass	2.40221G	16.38	-13.62	2.11063G	-53.82	2.39984G	-48.73	2.4G	-49.34	2.48709G	-52.71	24.49102G	-48.09	1
2480MHz	Pass	2.40221G	16.38	-13.62	362.82M	-54.54	2.39996G	-51.13	2.4G	-52.51	2.48399G	-51.17	16.51601G	-48.05	1
BT-LE(2Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
2402MHz	Pass	2.44G	16.51	-13.49	824.3M	-54.18	2.39997G	-16.62	2.4G	-18.64	2.50099G	-53.13	16.58631G	-48.02	1
2440MHz	Pass	2.44G	16.51	-13.49	2.14559G	-53.29	2.39947G	-47.73	2.4G	-50.79	2.49G	-52.89	16.40634G	-48.04	1
2480MHz	Pass	2.44G	16.51	-13.49	1.82628G	-53.93	2.39956G	-52.49	2.4G	-52.42	2.48365G	-52.00	17.39337G	-47.19	1











Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 1	Pass	PK	520.82M	42.82	46.00	-3.18	Horizontal



Mode 1

19/06/2020



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV/m)	AF (dB/m)	CL (dB)	PA (dB)
PK	31.94M	36.04	40.00	-3.96	-8.67	3	Horizontal	360	1.50	-	44.71	23.03	0.70	32.40
PK	480.08M	39.96	46.00	-6.04	-6.35	3	Horizontal	144	1.50	-	46.31	23.25	2.56	32.16
PK	492.69M	33.45	46.00	-12.55	-6.16	3	Horizontal	86	1.00	-	39.61	23.42	2.59	32.17
PK	520.82M	42.82	46.00	-3.18	-5.69	3	Horizontal	1	1.50	"Worst"	48.51	23.99	2.64	32.32
PK	764.29M	36.72	46.00	-9.28	-3.01	3	Horizontal	84	1.00	-	39.73	25.83	3.30	32.14
PK	950.53M	36.53	46.00	-9.47	-0.69	3	Horizontal	324	2.00	-	37.22	26.91	3.80	31.40




Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
BT-LE(2Mbps)	Pass	AV	2.4835G	52.94	54.00	-1.06	3	Horizontal	319	1.15	-

BT-LE(1Mbps)

26/05/2020

2402MHz_TX




EUT Z_1TX
Setting 0x39
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.322G	55.42	74.00	-18.58	24.92	3	Vertical	129	2.77	-	27.34	3.16	-
AV	2.322G	45.76	54.00	-8.24	15.26	3	Vertical	129	2.77	-	27.34	3.16	-
PK	2.4016G	111.03	Inf	-Inf	80.32	3	Vertical	129	2.77	-	27.51	3.20	-
AV	2.402G	109.58	Inf	-Inf	78.87	3	Vertical	129	2.77	-	27.51	3.20	-
PK	2.4904G	55.73	74.00	-18.27	24.62	3	Vertical	129	2.77	-	27.86	3.25	-
AV	2.4888G	43.55	54.00	-10.45	12.45	3	Vertical	129	2.77	-	27.86	3.24	-

BT-LE(1Mbps)

26/05/2020

2402MHz_TX



EUT Z_1TX
Setting 0x39
01-C-P-2


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.322G	57.74	74.00	-16.26	27.24	3	Horizontal	320	1.04	-	27.34	3.16	-
AV	2.322G	51.25	54.00	-2.75	20.75	3	Horizontal	320	1.04	-	27.34	3.16	-
PK	2.4016G	115.50	Inf	-Inf	84.79	3	Horizontal	320	1.04	-	27.51	3.20	-
AV	2.402G	113.91	Inf	-Inf	83.20	3	Horizontal	320	1.04	-	27.51	3.20	-
PK	2.4952G	54.73	74.00	-19.27	23.60	3	Horizontal	320	1.04	-	27.88	3.25	-
AV	2.4948G	43.54	54.00	-10.46	12.41	3	Horizontal	320	1.04	-	27.88	3.25	-



BT-LE(1Mbps)

26/05/2020

2402MHz_TX



EUT Z_1TX
Setting 0x39
01-C-P-2


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.8037G	44.79	74.00	-29.21	41.42	3	Vertical	257	3.00	-	32.41	5.70	34.74
AV	4.8041G	32.61	54.00	-21.39	29.24	3	Vertical	257	3.00	-	32.41	5.70	34.74



BT-LE(1Mbps)

26/05/2020

2402MHz_TX




EUT Z_1TX
Setting 0x39
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.80668G	44.89	74.00	-29.11	41.51	3	Horizontal	297	1.00	-	32.41	5.70	34.73
AV	4.80404G	32.10	54.00	-21.90	28.73	3	Horizontal	297	1.00	-	32.41	5.70	34.74

BT-LE(1Mbps)

26/05/2020

2440MHz_TX




EUT Z_1TX
Setting 0x38
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.36G	56.28	74.00	-17.72	25.68	3	Vertical	138	3.00	-	27.42	3.18	-
AV	2.3596G	45.49	54.00	-8.51	14.89	3	Vertical	138	3.00	-	27.42	3.18	-
PK	2.44G	110.84	Inf	-Inf	79.96	3	Vertical	138	3.00	-	27.66	3.22	-
AV	2.44G	109.28	Inf	-Inf	78.40	3	Vertical	138	3.00	-	27.66	3.22	-
PK	2.4976G	55.80	74.00	-18.20	24.66	3	Vertical	138	3.00	-	27.89	3.25	-
AV	2.4996G	43.51	54.00	-10.49	12.36	3	Vertical	138	3.00	-	27.90	3.25	-

BT-LE(1Mbps)

26/05/2020

2440MHz_TX




EUT Z_1TX
Setting 0x38
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.36G	58.53	74.00	-15.47	27.93	3	Horizontal	96	1.03	-	27.42	3.18	-
AV	2.36G	52.55	54.00	-1.45	21.95	3	Horizontal	96	1.03	-	27.42	3.18	-
PK	2.4396G	115.88	Inf	-Inf	85.00	3	Horizontal	96	1.03	-	27.66	3.22	-
AV	2.44G	114.44	Inf	-Inf	83.56	3	Horizontal	96	1.03	-	27.66	3.22	-
PK	2.4884G	55.15	74.00	-18.85	24.06	3	Horizontal	96	1.03	-	27.85	3.24	-
AV	2.498G	43.65	54.00	-10.35	12.51	3	Horizontal	96	1.03	-	27.89	3.25	-

BT-LE(1Mbps)

26/05/2020

2440MHz_TX



EUT Z_1TX
Setting 0x38
01-C-P-2


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	7.31612G	51.21	74.00	-22.79	41.42	3	Vertical	270	3.00	-	37.28	7.39	34.88
AV	7.31934G	38.76	54.00	-15.24	28.96	3	Vertical	270	3.00	-	37.28	7.40	34.88



BT-LE(1Mbps)

26/05/2020

2440MHz_TX




EUT Z_1TX
Setting 0x38
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	7.3208G	54.46	74.00	-19.54	44.66	3	Horizontal	87	1.08	-	37.28	7.40	34.88
AV	7.31932G	43.53	54.00	-10.47	33.73	3	Horizontal	87	1.08	-	37.28	7.40	34.88

BT-LE(1Mbps)

26/05/2020

2480MHz_TX




EUT_Z_1TX
Setting 0x2c
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4798G	103.14	Inf	-Inf	72.08	3	Vertical	138	2.94	-	27.82	3.24	-
AV	2.48G	101.67	Inf	-Inf	70.61	3	Vertical	138	2.94	-	27.82	3.24	-
PK	2.4835G	56.91	74.00	-17.09	25.84	3	Vertical	138	2.94	-	27.83	3.24	-
AV	2.4835G	49.15	54.00	-4.85	18.08	3	Vertical	138	2.94	-	27.83	3.24	-

BT-LE(1Mbps)

26/05/2020

2480MHz_TX




EUT_Z_1TX
Setting 0x2c
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4798G	107.20	Inf	-Inf	76.14	3	Horizontal	95	1.08	-	27.82	3.24	-
AV	2.48G	105.68	Inf	-Inf	74.62	3	Horizontal	95	1.08	-	27.82	3.24	-
PK	2.4835G	58.94	74.00	-15.06	27.87	3	Horizontal	95	1.08	-	27.83	3.24	-
AV	2.4835G	52.73	54.00	-1.27	21.66	3	Horizontal	95	1.08	-	27.83	3.24	-

BT-LE(1Mbps)

26/05/2020

2480MHz_TX




EUT Z_1TX
Setting 0x2c
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	7.43656G	51.76	74.00	-22.24	41.91	3	Vertical	169	1.22	-	37.24	7.52	34.91
AV	7.43828G	38.02	54.00	-15.98	28.17	3	Vertical	169	1.22	-	37.24	7.52	34.91

BT-LE(1Mbps)

26/05/2020

2480MHz_TX




EUT Z_1TX
Setting 0x2c
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	7.43578G	51.54	74.00	-22.46	41.69	3	Horizontal	116	1.02	-	37.24	7.52	34.91
AV	7.44052G	38.18	54.00	-15.82	28.33	3	Horizontal	116	1.02	-	37.24	7.52	34.91

BT-LE(2Mbps)

26/05/2020

2402MHz_TX




EUT Z_1TX
Setting 0x39
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3212G	55.37	74.00	-18.63	24.87	3	Vertical	130	2.78	-	27.34	3.16	-
AV	2.322G	45.05	54.00	-8.95	14.55	3	Vertical	130	2.78	-	27.34	3.16	-
PK	2.4024G	110.53	Inf	-Inf	79.82	3	Vertical	130	2.78	-	27.51	3.20	-
AV	2.402G	107.00	Inf	-Inf	76.29	3	Vertical	130	2.78	-	27.51	3.20	-
PK	2.4992G	55.02	74.00	-18.98	23.87	3	Vertical	130	2.78	-	27.90	3.25	-
AV	2.498G	43.45	54.00	-10.55	12.31	3	Vertical	130	2.78	-	27.89	3.25	-

BT-LE(2Mbps)

26/05/2020

2402MHz_TX




EUT Z_1TX
Setting 0x39
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3212G	57.90	74.00	-16.10	27.40	3	Horizontal	319	1.02	-	27.34	3.16	-
AV	2.322G	49.22	54.00	-4.78	18.72	3	Horizontal	319	1.02	-	27.34	3.16	-
PK	2.4024G	115.09	Inf	-Inf	84.38	3	Horizontal	319	1.02	-	27.51	3.20	-
AV	2.402G	110.90	Inf	-Inf	80.19	3	Horizontal	319	1.02	-	27.51	3.20	-
PK	2.4992G	55.58	74.00	-18.42	24.43	3	Horizontal	319	1.02	-	27.90	3.25	-
AV	2.4835G	43.85	54.00	-10.15	12.78	3	Horizontal	319	1.02	-	27.83	3.24	-

BT-LE(2Mbps)

26/05/2020

2402MHz_TX



EUT Z_1TX
Setting 0x39
01-C-P-2


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.80514G	45.33	74.00	-28.67	41.96	3	Vertical	303	1.80	-	32.41	5.70	34.74
AV	4.80226G	31.53	54.00	-22.47	28.17	3	Vertical	303	1.80	-	32.40	5.70	34.74



BT-LE(2Mbps)

26/05/2020

2402MHz_TX




EUT Z_1TX
Setting 0x39
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.80214G	45.06	74.00	-28.94	41.70	3	Horizontal	295	1.02	-	32.40	5.70	34.74
AV	4.80474G	31.77	54.00	-22.23	28.40	3	Horizontal	295	1.02	-	32.41	5.70	34.74

BT-LE(2Mbps)

26/05/2020

2440MHz_TX




EUT Z_1TX
Setting 0x39
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3604G	54.95	74.00	-19.05	24.35	3	Vertical	137	3.00	-	27.42	3.18	-
AV	2.36G	44.84	54.00	-9.16	14.24	3	Vertical	137	3.00	-	27.42	3.18	-
PK	2.4404G	111.06	Inf	-Inf	80.18	3	Vertical	137	3.00	-	27.66	3.22	-
AV	2.44G	107.44	Inf	-Inf	76.56	3	Vertical	137	3.00	-	27.66	3.22	-
PK	2.4892G	55.72	74.00	-18.28	24.62	3	Vertical	137	3.00	-	27.86	3.24	-
AV	2.4896G	43.55	54.00	-10.45	12.45	3	Vertical	137	3.00	-	27.86	3.24	-

BT-LE(2Mbps)

26/05/2020

2440MHz_TX



EUT Z_1TX
Setting 0x39
01-C-P-2


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.36G	58.88	74.00	-15.12	28.28	3	Horizontal	96	1.04	-	27.42	3.18	-
AV	2.36G	51.19	54.00	-2.81	20.59	3	Horizontal	96	1.04	-	27.42	3.18	-
PK	2.4404G	116.15	Inf	-Inf	85.27	3	Horizontal	96	1.04	-	27.66	3.22	-
AV	2.44G	112.57	Inf	-Inf	81.69	3	Horizontal	96	1.04	-	27.66	3.22	-
PK	2.4904G	55.87	74.00	-18.13	24.76	3	Horizontal	96	1.04	-	27.86	3.25	-
AV	2.498G	43.65	54.00	-10.35	12.51	3	Horizontal	96	1.04	-	27.89	3.25	-



BT-LE(2Mbps)

26/05/2020

2440MHz_TX



EUT Z_1TX
Setting 0x39
01-C-P-2


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	7.31806G	51.95	74.00	-22.05	42.16	3	Vertical	124	2.94	-	37.28	7.39	34.88
AV	7.31872G	39.20	54.00	-14.80	29.41	3	Vertical	124	2.94	-	37.28	7.39	34.88



BT-LE(2Mbps)

26/05/2020

2440MHz_TX




EUT Z_1TX
Setting 0x39
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	7.31826G	50.91	74.00	-23.09	41.12	3	Horizontal	273	2.60	-	37.28	7.39	34.88
AV	7.31866G	38.34	54.00	-15.66	28.55	3	Horizontal	273	2.60	-	37.28	7.39	34.88

BT-LE(2Mbps)

26/05/2020

2480MHz_TX




EUT_Z_1TX
Setting 0x2a
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.48G	102.04	Inf	-Inf	70.98	3	Vertical	137	2.96	-	27.82	3.24	-
AV	2.48G	98.36	Inf	-Inf	67.30	3	Vertical	137	2.96	-	27.82	3.24	-
PK	2.4835G	57.82	74.00	-16.18	26.75	3	Vertical	137	2.96	-	27.83	3.24	-
AV	2.4835G	49.91	54.00	-4.09	18.84	3	Vertical	137	2.96	-	27.83	3.24	-

BT-LE(2Mbps)

26/05/2020

2480MHz_TX




EUT_Z_1TX
Setting 0x2a
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4804G	105.74	Inf	-Inf	74.68	3	Horizontal	319	1.15	-	27.82	3.24	-
AV	2.48G	102.23	Inf	-Inf	71.17	3	Horizontal	319	1.15	-	27.82	3.24	-
PK	2.4835G	61.83	74.00	-12.17	30.76	3	Horizontal	319	1.15	-	27.83	3.24	-
AV	2.4835G	52.94	54.00	-1.06	21.87	3	Horizontal	319	1.15	-	27.83	3.24	-

BT-LE(2Mbps)

26/05/2020

2480MHz_TX




EUT Z_1TX
Setting 0x2a
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	7.44228G	52.07	74.00	-21.93	42.22	3	Vertical	99	2.61	-	37.24	7.52	34.91
AV	7.43994G	38.26	54.00	-15.74	28.41	3	Vertical	99	2.61	-	37.24	7.52	34.91

BT-LE(2Mbps)

26/05/2020

2480MHz_TX



EUT Z_1TX
Setting 0x2a
01-C-P-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	7.44046G	51.47	74.00	-22.53	41.62	3	Horizontal	88	1.05	-	37.24	7.52	34.91
AV	7.43508G	38.23	54.00	-15.77	28.38	3	Horizontal	88	1.05	-	37.24	7.52	34.91