



# RADIO EXPOSURE TEST REPORT

**FCC ID** : TLZ-CU5XX

**Equipment** : Wireless MCU with Integrated Tri-radio Wi-Fi 6 + BLE  
5.3/802.15.4 LGA module, Wireless MCU with Integrated  
Wi Fi 6 and Bluetooth Low Energy 5.3 Module

**Brand Name** : AzureWave

**Model Name** : AW-CU570, AW-CU598

**Applicant** : AzureWave Technologies, Inc.  
8F., No.94, Baozhong Rd. , Xindian Dist., New Taipei  
City , Taiwan 231

**Manufacturer** : AzureWave Technologies, Inc.  
8F., No.94, Baozhong Rd. , Xindian Dist., New Taipei  
City , Taiwan 231

**Standard** : 47 CFR Part 2.1091

The product was received on Dec. 12, 2023, and testing was started from Dec. 26, 2023 and completed on Jun. 14, 2024. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Rex Liao

**Sporton International Inc. Hsinchu Laboratory**

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



## Table of Contents

**History of this test report**.....3

**Summary of Test Result**.....4

**1 General Description** .....5

1.1 EUT General Information .....5

1.2 Antenna Information .....6

1.3 Table for Multiple Listing .....7

1.4 Accessories .....7

1.5 Applicable Standards .....7

1.6 Testing Location .....7

**2 Maximum Permissible Exposure** .....8

2.1 Limit of Maximum Permissible Exposure .....8

2.2 MPE Calculation Method .....8

2.3 MPE Exemption .....9

2.4 Calculated Result and Limit .....10

**Photographs of EUT v01**



## History of this test report

Report No.	Version	Description	Issued Date
FA3N2709	01	Initial issue of report	Jun. 28, 2024



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

**Conformity Assessment Condition:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the chapter "Measurement Uncertainty".

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

**Reviewed by: Sam Chen**

**Report Producer: Sophia Shiung**



# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850 5725-5895	5180-5240 5260-5320 5500-5720 5745-5825 5845-5885	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Bluetooth	2400-2483.5	2402-2480	LE: GFSK
Thread	2400-2483.5	2405-2480	O-QPSK



### 1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	ARISTOTLE	RFA-27-C38H1-C198	Dipole	u.FL	Note 1
2	Molex	2128600011	Dipole	u.FL	
3	LYNwave	2570	PCB	N/A	

Note 1:

Ant.	Port				Gain (dBi)			
	WLAN 2.4GHz	WLAN 5GHz	Bluetooth	Thread	WLAN 2.4GHz	WLAN 5GHz	Bluetooth	Thread
1	-	1	-	-	3	5	3	3
2	1	-	1	1	Note 2			
3	1	1	1	1	2.2	4.4	2.2	2.2

Note 2: The Ant. 2 has one RF cable (Brand: TE Connectivity / Model Name: Linx Connectivity / Remark: 11.5cm), and its gains are listed below.

Ant.	Gain (dBi)				
	WLAN 2.4GHz	WLAN 5GHz	Bluetooth	Thread	
2	Max Peak Gain	5.3	4.5	5.3	5.3
	Cable Loss	0.34	0.34	0.34	0.34
	Net Gain	4.96	4.16	4.96	4.96

Note 3: The above information was declared by manufacturer.

Note 4: The Ant. 2 in WLAN 2.4GHz / Bluetooth / Thread and the Ant. 1 in WLAN 5GHz have higher gain than others in the same band. Therefore, they were selected to perform the test.

Note 5: For 2.4GHz function:

**For IEEE 802.11 b/g/n/VHT/ax (1TX/1RX):**

Only Port 1 can be used as transmitting/receiving antenna.

**For 5GHz function:**

**For IEEE 802.11a/n/ac/ax (1TX/1RX):**

Only Port 1 can be used as transmitting/receiving antenna.

**For bluetooth function (1TX/1RX):**

Only Port 1 can be used as transmitting/receiving antenna.

**For Thread function (1TX/1RX):**

Only Port 1 can be used as transmitting/receiving antenna.



### 1.3 Table for Multiple Listing

The two EUTs are identical except for the difference listed below:

EUT	Equipment Name	Model Name	Thread Function
1	Wireless MCU with Integrated Tri-radio Wi-Fi 6 + BLE 5.3/802.15.4 LGA module	AW-CU570	V
2	Wireless MCU with Integrated Wi Fi 6 and Bluetooth Low Energy 5. 3 Module	AW-CU598	X

Note 1: From the above EUTs, EUT 1 (AW-CU570) was selected as representative EUT for the test and its data was recorded in this report.

Note 2: The above information was declared by manufacturer.

### 1.4 Accessories

N/A

### 1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1091
  - ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01
- The following reference test guidance is not within the scope of accreditation of TAF.
- ♦ 47 CFR Part 1.1307
  - ♦ 47 CFR Part 1.1310

### 1.6 Testing Location

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)
(TAF: 3787)	TEL: 886-3-656-9065      FAX: 886-3-656-9085
	Test site Designation No. TW3787 with FCC.
	Conformity Assessment Body Identifier (CABID) TW3787 with ISED.



## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$





### 2.3 MPE Exemption

Option (A): 1.1307(b)(3)(i)(A): Available maximum time-averaged power is < 1 mW

Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= Pth.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option (C): 1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance

R between the person and the antenna / radiating structure, where  $R > \lambda / 2 \pi$ .

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R <sup>2</sup> .
1.34-30	3,450 R <sup>2</sup> /f <sup>2</sup> .
30-300	3.83 R <sup>2</sup> .
300-1,500	0.0128 R <sup>2</sup> f.
1,500-100,000	19.2R <sup>2</sup> .

Note: R is in meters, f is in MHz.



## 2.4 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)
2.4G;D1D	4.96	19.46	22.27	0.50	189.234	20	B	3060.0
5.2G;D1D	5.00	18.00	20.85	0.50	136.458	20	B	3060.0
5.3G;D1D	5.00	17.94	20.79	0.50	134.586	20	B	3060.0
5.6G;D1D	5.00	19.39	22.24	0.50	187.932	20	B	3060.0
5.8G;D1D	5.00	18.89	21.74	0.50	167.494	20	B	3060.0
5.81G;D1D	5.00	19.80	22.65	0.50	206.538	20	B	3060.0
2.4G;BT-LE	4.96	9.86	12.67	0.50	20.749	20	B	3060.0
Thread	4.96	9.91	12.72	0.50	20.989	20	B	3060.0

————THE END————