

FCC RF Exposure Report

FCC ID : TLZ-NM230NF

Equipment : IEEE 802.11 b/g/n WLAN and Bluetooth combo

module

Model No. : AW-NM230NF \ AW-NM230NF-H

(Please refer to section 1.1.1 for more details.)

Brand Name : AzureWave

Applicant : AzureWave Technologies, Inc.

Address : 8 F., No. 94, Baozhong Rd., Xindian, Taipei,

Taiwan 231

Standard : 47 CFR FCC Part 2.1091

Received Date : May 07, 2015

Tested Date : Jul. 03 ~ Jul. 20, 2015

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager√

Iac-MRA

Testing Laboratory

Page: 1 of 5

Report No.: FA550703



Table of Contents

MPE EVALUATION OF MOBILE DEVICES	4
LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	4
TEST I ADODATODY INFORMATION	_
	MPE EVALUATION OF MOBILE DEVICES LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE MPE EVALUATION FORMULA MPE EVALUATION RESULTS TEST LABORATORY INFORMATION

Report No.: FA550703

Page : 2 of 5



Release Record

Report No.	Version	Description	Issued Date	
FA550703	Rev. 01	Initial issue	Jul. 30, 2015	

Report No.: FA550703 Page: 3 of 5



1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

	Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)
I	300~1500	F/1500	30
	1500~100000	1.0	30

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4*Pi*R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in Mw Pi= 3.1416

R= Measurement distance

1.3 MPE EVALUATION RESULTS

Modulation Mode	Frequency Range (MHz)	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WLAN	2412~2462	21.89	3	20	0.061	1
BT EDR	2402~2480	8.19	3	20	0.003	1
BT LE	2402~2480	6.49	3	20	0.002	1

Report No.: FA550703 Page: 4 of 5



2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan,

R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan

Hsien 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FA550703 Page: 5 of 5