

# RF EXPOSURE REPORT

**REPORT NO.:** SA990924C13

**MODEL NO.:** AW-NU153H

**FCC ID:** TLZ-NU153H

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** AzureWave Technologies, Inc.

**ADDRESS:** 8F, No. 94, Baozhong Rd., Xindian,  
Taipei, Taiwan 231.

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou  
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

## 1. RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm <sup>2</sup> )	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

## 2. MPE CALCULATION FORMULA

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

## 3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

## 4. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

TEST MODE	FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
A (Antenna 1 type : Dipole)	2412-2462	22.3	2.86	20	0.065	1.00
B (Antenna 2 type : PCB)	2412-2462	22.3	2.14	20	0.055	1.00
C (Antenna 4 type : PIFA)	2412-2462	22.3	2.98	20	0.067	1.00