Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 1 of 59

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT

INTENTIONAL RADIATOR CERTIFICATION TO FCC PART 15 SUBPART C REQUIREMENT

OF

Product Name: Blood Glucose Meter

Brand Name: IDEAL LIFE

Model Name: GMM 0001, TD-4111X(where X can be any

alphanumeric or blank)

Model Difference: Different model for different market

FCC ID: TM74111BBEM2

Report No.: ER/2009/50006

Issue Date: Jul. 29, 2009

FCC Rule Part: §15.247 / DSS

Prepared for: TaiDoc Technology Corp.

6F, No.127, Wugong 2nd Road, 24888 Wugu

Township, Taipei County, Taiwan

Prepared by: SGS Taiwan Ltd.

Electronics & Communication Laboratory

No. 134, Wu Kung Rd., Wuku Industrial

Zone, Taipei County, Taiwan





0513

Note: This report shall not be reproduced except in full, without the written approval of SGS Taiwan Ltd. This document may be altered or revised by SGS Taiwan Ltd. personnel only, and shall be noted in the revision section of the document.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有認明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 34 號



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 2 of 59

VERIFICATION OF COMPLIANCE

TaiDoc Technology Corp. **Applicant:**

6F, No.127, Wugong 2nd Road, 24888 Wugu Township, Taipei

County, Taiwan

Blood Glucose Meter Equipment Under Test:

Brand Name: IDEAL LIFE Model No.: GMM 0001

GMM 0001, TD-4111X(where X can be any alphanumeric or blank) **Model Difference:**

FCC ID: TM74111BBEM2

File Number: ER/2009/50006

Date of test: Jul. 20, 2009 ~ Jul. 27, 2009

Date of EUT Received: Jul. 20, 2009

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4:2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

11

Test By:	Jazz Huang	Date:	Jul. 29, 2009
Prepared By:	Jazz Huang / Engineer Mark Chung	Date:	Jul. 29, 2009
Approved By:	Mark Chung / Project Engineer Jun Chang	Date:	Jul. 29, 2009

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對剛武之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複數。
This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms_e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document ment is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. SGS Taiwan Ltd.

Jim Chang / Supervisor



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 3 of 59

Version

Version No.	Date	Description
00	Jul. 29, 2009	Initial creation of document



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 4 of 59

Table of Contents

1.		ERAL INFORMATION	
	1.1.	Related Submittal(s) / Grant (s)	
	1.2.	Test Methodology	
	1.3.	Test Facility	8
	1.4.	Special Accessories	8
	1.5.	Equipment Modifications	8
2.	SYST	TEM TEST CONFIGURATION	9
	2.1.	EUT Configuration	9
	2.2.	EUT Exercise	9
	2.3.	Test Procedure	9
	2.4.	Configuration of Tested System	10
3.	SUM	MARY OF TEST RESULTS	11
4.	DES	CRIPTION OF TEST MODES	11
5.	CON	DUCTED EMISSION TEST	12
	5.1.	Standard Applicable	12
	5.2.	EUT Setup	12
	5.3.	Measurement Procedure	12
	5.4.	Measurement Equipment Used:	13
	5.5.	Measurement Result	13
6.	PEA	K OUTPUT POWER MEASUREMENT	14
	6.1.	Standard Applicable	14
	6.2.	Measurement Equipment Used	14
	6.3.	Test Set-up:	14
	6.4.	Measurement Procedure:	15
	6.5.	Measurement Result	15
7.	20dB	BAND WIDTH	18
	7.1.	Standard Applicable	
	7.2.	Measurement Equipment Used	18
	7.3.	Test Set-up	18
	7.4.	Measurement Procedure:	18
	7.5.	Measurement Result:	19
200	lB Bar	nd Width Test Data CH-Low	20
		nd Width Test Data CH-Low	20

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms_e-document.htm. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at <a href="https://www.sgs.com/terms_e-document-https://www.sg



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 5 of 59

8.	100K	Hz BANDWIDTH OF BAND EDGES MEASUREMENT	22
	8.1.	Standard Applicable	22
	8.2.	Measurement Equipment Used	22
	8.3.	Test SET-UP:	23
	8.4.	Measurement Procedure	24
	8.5.	Field Strength Calculation	24
	8.6.	Measurement Result	24
9.	SPUR	RIOUS EMISSION TEST	29
	9.1.	Standard Applicable	29
	9.2.	Measurement Equipment Used:	29
	9.3.	Test SET-UP:	29
	9.4.	Measurement Procedure:	29
	9.5.	Field Strength Calculation	31
	9.6.	Measurement Result:	31
10.	FREC	QUENCY SEPARATION	4 4
	10.1.	Standard Applicable	
	10.2.	Measurement Equipment Used:	44
	10.3.	Test Set-up:	44
	10.4.	Measurement Procedure:	44
	10.5.	Measurement Result:	44
11.	NUM	BER OF HOPPING FREQUENCY	40
	11.1.	Standard Applicable	
	11.2.	Measurement Equipment Used:	46
	11.3.	Test Set-up:	46
	11.4.	Measurement Procedure:	46
	11.5.	Measurement Result:	46
12.	TIME	E OF OCCUPANCY (DWELL TIME)	48
	12.1.	Standard Applicable	
	12.2.	Measurement Equipment Used:	48
	12.3.	Test Set-up:	48
	12.4.	Measurement Procedure:	48
	12.5.	Measurement Result	49
13.	Peak :	Power Spectral Density	50
	13.1.	•	
	13.2.	Measurement Equipment Used:	56

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms_e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms_e-document.htm). Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /6±縣五股工業區五工路 134 號
(1986-2) 2309-2329.

Member of SGS Group



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 6 of 59

	13.3.	Test Set-up:	56
	13.4.	Measurement Procedure:	56
	13.5.	Measurement Result	56
14.	ANTE	ENNA REQUIREMENT	59
	14.1.	Standard Applicable	59
	14.2.	Antenna Connected Construction	59



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 7 of 59

1. GENERAL INFORMATION

General:	
Product Name:	Blood Glucose Meter
Brand Name:	IDEAL LIFE
Model Number:	GMM 0001
Model Difference:	Different model for different market
Power Supply:	Battery: 1.5V AAA battery *2.
Hardware Version:	N/A
Software Version:	N/A
Bluetooth:	
Bluetooth Version	□ V1.1 (GFSK) □ V1.2 (GFSK) □ V2.0 (GFSK) □ V2.0 + EDR (GFSK + /4DQPSK + 8DPSK) □ V2.1 + EDR (GFSK + /4DQPSK + 8DPSK)
Frequency Range	2402 – 2480MHz
Channel number	79 channels max.
Rated Power	3.92 dBm Peak
Modulation type	Frequency Hopping Spread Spectrum (FHSS)
Antenna Designation	Chip Antenna, Gain: 3 dBi.Peak

This test report applies for Bluetooth.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 8 of 59

1.1. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: <u>TM74111BBEM2</u> filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

1.2. Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4: 2003. Radiated testing was performed at an antenna to EUT distance 3 meters.

1.3. Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of SGS Taiwan Ltd. Electronics & Communication Laboratory No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003. FCC Registration Number are: 990257 and 236194, Canada Registration Number: 4620A-1

The 10 m Open Area Test Sites located on the address of SGS Taiwan Ltd. Electronics & Communication Laboratory No. 29, Pau-Tou-Tsuo Valley Chia-Pau Tsuen, Linkou Hsiang, Taipei county, which is constructed and calibrated to meet the CISPR 22/EN 55022 requirements. SGS Site No. 1(3 & 10 meters) and FCC Registration Number: 94644.

1.4. Special Accessories

Not available for this EUT intended for grant.

1.5. Equipment Modifications

Not available for this EUT intended for grant.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留的天。本報告未總本公司書面許可,不可部份複製。This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台 北縣五股工業區五工路 134 號



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 9 of 59

2. SYSTEM TEST CONFIGURATION

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

2.3. Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 7 and 13 of ANSI C63.4: 2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna. according to the reguirements in Section 8 and 13 and Sub clause 8.3.1.2 of ANSI C63.4: 2003.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。。
This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document ment is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 10 of 59

2.4. Configuration of Tested System

Fig. 2-1 Radiated Emission Configuration




Table 2-1 Equipment Used in Tested System

Item Equipment		Mfr/Brand	Model/ Type No.	Series No.	Data Cable	Power Cord
1	Notebook	IBM	T60	L3DK794	N/A	Shielded
2	Software	I.S.S.C.	EDR_RF_test_Customer	N/A	N/A	N/A
3	Test Kit	I.S.S.C	ISBTM8	CAT_V3	Shielded	N/A

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果像對關式之樣品負責,同時此樣品僅保留0天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms_and_conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms_e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 11 of 59

3. SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.207(a)	Conducted Emission	N/A
§15.247(b)(1)	Peak Output Power	Compliant
§15.247(a)	20dB Bandwidth	No Limit
§15.247(c)	100 KHz Bandwidth Of Fre-	Compliant
	quency Band Edges	
§15.209(a) (f)	Spurious Emission	Compliant
§15.247(a)(1)	Frequency Separation	Compliant
§15.247(a)(1)(iii)	Number of hopping frequency	Compliant
§15.247(a)(1)(iii)	Time of Occupancy	Compliant
§15.247	Peak Power Density	Compliant
§15.203,	Antenna Requirement	Compliant
§15.247(b)(4)(i)		

4. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low (2402MHz) · mid (2441MHz) and high (2480MHz) with highest data rate are chosen for full testing.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 12 of 59

5. CONDUCTED EMISSION TEST

5.1. Standard Applicable

According to §15.207. frequency within 150KHz to 30MHz shall not exceed the limit table as below.

Frequency range		mits (uV)
MHz	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Note

5.2. EUT Setup

- 1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4: 2003.
- 2. The EUT was plug-in the AC/DC Power adapter. The host system was placed on the center of the back edge on the test table. The peripherals was placed on the side of the host PC system. The rear of the EUT and peripherals were placed flushed with the rear of the tabletop.
- 3. The spacing between the peripherals was 10 centimeters.
- 4. External I/O cables were draped along the edge of the test table and bundle when necessary.
- 5. The host system was connected with 120Vac/60Hz power source.

5.3. Measurement Procedure

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留的天。本報告未總本公司書面許可,不可部份複製。This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台 北縣五股工業區五工路 134 號

^{1.} The lower limit shall apply at the transition frequencies

^{2.} The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 13 of 59

5.4. Measurement Equipment Used:

Conducted Emission Test Site						
EQUIPMENT	MED	MODEL	SERIAL	LAST	CAL DUE	
TYPE	MFR	NUMBER	NUMBER	CAL.	CAL DUE.	
EMI Test Receiver	R&S	ESCS30	828985/004	09/16/2008	09/15/2009	
LISN	Rolf-Heine	NNB-2/16Z	99012	04/28/2009	04/27/2010	
LISN	FCC	FCC-LISN-50/250-25-2-01	04034	04/28/2009	04/27/2010	
Coaxial Cables	N/A	WK CE Cable	N/A	10/30/2008	10/29/2009	

5.5. Measurement Result

N/A, EUT is powered by DC only.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 14 of 59

6. PEAK OUTPUT POWER MEASUREMENT

6.1. Standard Applicable

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850MHz band: 1Watt. For all other frequency hopping systems in the 2400 – 2483.5MHz band: 0.125 Watts.

6.2. Measurement Equipment Used

Conducted Emission Test Site						
EQUIPMENT	MODEL	SERIAL	LAST	CAL DUE.		
TYPE		NUMBER	NUMBER	CAL.		
Spectrum Analyzer	Agilent	E4446A	MY43360126	04/19/2008	04/18/2010	
Spectrum Analyzer	Agilent	E4440A	MY45304525	01/23/2008	01/22/2010	
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA	N/A	01/05/2009	01/04/2010	
DC Block	Agilent	BLK-18	155452	07/05/2009	07/04/2010	
Attenuator	Mini-Circuit	BW-S6W5	001	07/05/2009	07/04/2010	
Attenuator	Mini-Circuit	BW-S10W5	001	07/05/2009	07/04/2010	
Attenuator	Mini-Circuit	BW-S20W5	001	07/05/2009	07/04/2010	
Splitter	Agilent	11636B	N/A	07/05/2009	07/04/2010	

6.3. Test Set-up:



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複數。
This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document ment is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 15 of 59

6.4. Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter or spectrum. (Channel power function, RBW, VBW = 1MHz)
- 3. Record the max. reading.
- 4. Repeat above procedures until all frequency measured were complete.

6.5. Measurement Result

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
2402.00	2.32	0.00	2.32	0.00171	1
2441.00	0.45	0.00	0.45	0.00111	1
2480.00	3.92	0.00	3.92	0.00247	1


· Offset 0.5 dB



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 16 of 59

Peak Power Output Data Plot (CH Low)



Peak Power Output Data Plot (CH Mid)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未總本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at <a href="https://www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/terms.com/www.sgs.com/term



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 17 of 59

Peak Power Output Data Plot (CH High)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複數。
This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document ment is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 18 of 59

7. 20dB BAND WIDTH

7.1. Standard Applicable

For frequency hopping systems operating in the 2400MHz-2483.5 MHz no limit for 20dB bandwidth.

7.2. Measurement Equipment Used

Refer to section 6.2 for details.

7.3. Test Set-up

Refer to section 6.3 for details.

7.4. Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW=10KHz (1 % of Bandwidth.), Span=3MHz, Sweep=auto
- 4. Mark the peak frequency and –20dB (upper and lower) frequency.
- 5. Repeat above procedures until all frequency measured were complete.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 19 of 59

7.5. Measurement Result:

BDR Mode


DDK Mode						
СН	Bandwidth					
	(KHz)					
Lower	923.740					
Mid	923.774					
Higher	886.709					




Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 20 of 59

20dB Band Width Test Data CH-Low



20dB Band Width Test Data CH-Mid




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未總本公司書面許可,不可部仍複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.even if you have a subject of the company in the printed this electronic document.even is the printed that information or the printed this ele



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 21 of 59

20dB Band Width Test Data CH-High



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複數。
This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document ment is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. SGS Taiwan Ltd.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 22 of 59

8. 100KHz BANDWIDTH OF BAND EDGES MEASUREMENT

8.1. Standard Applicable

According to \$15.247(c), in any 100 KHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in \$15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

8.2. Measurement Equipment Used

8.2.1. Conducted Emission at antenna port:

Refer to section 6.2 for details.

8.2.2. Radiated emission:

966 Chamber								
EQUIPMENT	LAST	CAL DUE.						
TYPE		NUMBER	NUMBER	CAL.				
Spectrum Analyzer	R&S	FSP 40	100034	02/12/2009	02/11/2010			
Bilog Antenna	SCHWAZBECK	VULB9160	9160-3136	11/15/2008	11/14/2009			
Horn antenna	SCHWAZBECK	BBHA 9120D	9120D-320	03/14/2009	03/13/2010			
Pre-Amplifier	Agilent	8447D	1937A02834	11/30/2008	11/29/2009			
Pre-Amplifier	Agilent	8449B	3008A01973	01/05/2009	01/04/2010			
Turn Table	HD	DT420	N/A	N.C.R	N.C.R			
Antenna Tower	HD	MA240-N	240/657	N.C.R	N.C.R			
Controller	HD	HD100	N/A	N.C.R	N.C.R			
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	01/05/2009	01/04/2010			
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	01/05/2009	01/04/2010			



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 23 of 59


8.3. Test SET-UP:

8.3.1. Conducted Emission at antenna port:


Refer to section 6.3 for details.

8.3.2. Radiated emission:

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未經本公司書面許可,不可部份複製。This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台 北縣五股工業區五工路 134 號



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 24 of 59

8.4. Measurement Procedure

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = operating frequency.
- 4. Set the spectrum analyzer as RBW, VBW=100KHz, Span=25MHz, Sweep = auto
- 5. Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
- 6. Repeat above procedures until all frequency measured were complete.
- 7. Radiated Emission refer to section 9.

8.5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

8.6. Measurement Result

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未經本公司書面許可,不可部份複製。This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台 北縣五股工業區五工路 134 號




Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 25 of 59

Conducted Emission: Test Data CH-Low (BDR mode)





Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未總本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at <a href="https://www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/terms.com/www.sgs.com/term

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號


www.tw.sgs.com



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 26 of 59

Conducted Emission: Test Data CH-High



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複數。
This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document ment is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. SGS Taiwan Ltd.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 27 of 59

AV

54.00

-16.43

Peak

Peak

74.00

Radiated Emission: (BDR mode)

Operation Mode TX CH Low Test Date Jul. 23, 2009

Fundamental Frequency 2402 MHz Test By Jazz Temperature 25 Pol Ver.

-1.46

Humidity 65 %

Peak

39.03

AV

Freq.	Reading	Reading	Ant./CL	P ea k	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
2369.00	39.20		-1.46	37.74		74.00	54.00	-16.26	Peak
Operation Fundamen Temperatu	tal Frequen	2402 25	H Low MHz			Test l Test l Pol			
Humidity		65 %							
	Peak	AV		Actu	al FS	Peak	\mathbf{AV}		
Freq. (MHz)	Reading (dBuV)	Reading (dBuV)	Ant./CL CF(dB)	Peak (dBuV/m)	$\begin{array}{c} AV \\ (dBuV/m) \end{array}$	Limit (dBuV/m)	Limit (dBuV/m)	O	Remark

37.57

Actual FS

Remark	
Nemaik	

2369.00

- (1) Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (2) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS columno
- (3) Spectrum Peak Setting: 1GHz-26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- (4) Spectrum AV Setting: 1GHz-26GHz, RBW=1MHz, VBW=10Hz, Sweep time=200 ms.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 28 of 59

Radiated Emission: (BDR mode)

Operation Mode TX CH High Test Date Jul. 23, 2009

Fundamental Frequency 2480 MHz Test By Jazz Temperature 25 Pol Ver.

-0.92

Humidity 65 %

38.12

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
2483.56	48.21		-0.92	47.29		74.00	54.00	-6.71	Peak
Operation Fundament Temperatu Humidity	tal Frequen		H High MHz			Test I Test I Pol			
	P ea k	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	

37.20

Remark:

2483.56

(1) Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

74.00

54.00

-16.80

Peak

- (2) Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column_o
- (3) Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- (4) Spectrum AV Setting: 1GHz-26GHz, RBW=1MHz, VBW=10Hz, Sweep time=200 ms.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 29 of 59

9. SPURIOUS EMISSION TEST

9.1. Standard Applicable

According to §15.247(c), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

9.2. Measurement Equipment Used:

9.2.1. Conducted Emission at antenna port:

Refer to section 6.2 for details.

9.2.2. Radiated emission:

Refer to section 7.2 for details.

9.3. Test **SET-UP**:

9.3.1. Conducted Emission at antenna port:

Refer to section 6.3 for details.

9.3.2. Radiated emission:

Refer to section 7.3 for details.

9.4. Measurement Procedure:

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.
- 5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對剛武之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複數。
This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms_e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document ment is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 30 of 59

7. Repeat above procedures until all frequency measured were complete.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 31 of 59

9.5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

9.6. Measurement Result:


Note: Refer to next page spectrum analyzer data chart and tabular data sheets.




Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 32 of 59

Conducted Spurious Emission Measurement Result Ch Low 30MHz – 3GHz



Ch Low 3GHz – 26.5GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未總本公司書面許可,不可能仍複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.


SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號




Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 33 of 59

Ch Mid 30MHz - 3GHz



Ch Mid 3GHz – 26.5GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未總本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at <a href="https://www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/www.sgs.com/terms.com/terms.com/www.sgs.com/term


www.tw.sgs.com




Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 34 of 59

Ch High 30MHz – 3GHz



Ch High 3GHz – 26.5GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複數。
This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document ment is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 f (886-2) 2298-0488



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 35 of 59

Radiated Spurious Emission Measurement Result (below 1GHz) (BDR mode)

Operation Mode TX CH Low Test Date Jul. 23, 2009

Fundamental Frequency 2402MHz Test By Jazz

Temperature 25 Pol Ver./ Hor.

Humidity 65 %

	Freq.	Ant.Pol.	Detector Mode	Reading	Factor	Actual FS	Limit3m	Safe Margin
_	(MHz)	H/V	(PK/QP)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
	99.84	V	Peak	47.91	-17.01	30.90	43.50	-12.60
	164.83	V	Peak	38.77	-13.69	25.08	43.50	-18.42
	240.49	V	Peak	39.46	-14.11	25.35	46.00	-20.65
	288.99	V	Peak	40.93	-13.23	27.70	46.00	-18.30
	366.59	V	Peak	37.72	-11.17	26.55	46.00	-19.45
	599.39	V	Peak	33.31	-6.03	27.28	46.00	-18.72
	106.63	Н	Peak	44.37	-16.48	27.89	43.50	-15.61
	164.83	Н	Peak	46.41	-13.69	32.72	43.50	-10.78
	240.49	Н	Peak	44.44	-14.11	30.33	46.00	-15.67
	288.99	Н	Peak	42.26	-13.23	29.03	46.00	-16.97
	337.49	Н	Peak	39.00	-12.05	26.95	46.00	-19.05
	523.73	Н	Peak	37.67	-8.08	29.59	46.00	-16.41

Remark:

- 1 Measuring frequencies from 30 MHz to the 1GHz_o
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未經本公司書面許可,不可部份複製。This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台 北縣五股工業區五工路 134 號



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 36 of 59

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode TX CH Mid Test Date Jul. 23, 2009

Fundamental Frequency 2441MHz Test By Jazz
Temperature 25 Pol Ver./Hor.

Humidity 65 %

Freq.	Ant.Pol.	Detector Mode	Reading	Factor	Actual FS	Limit3m	Safe Margin
(MHz)	H/V	(PK/QP)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
106.63	V	Peak	47.09	-16.48	30.61	43.50	-12.89
174.53	V	Peak	41.02	-14.21	26.81	43.50	-16.69
232.73	V	Peak	45.68	-14.37	31.31	46.00	-14.69
288.99	V	Peak	41.62	-13.23	28.39	46.00	-17.61
337.49	V	Peak	38.26	-12.05	26.21	46.00	-19.79
599.39	V	Peak	33.43	-6.03	27.40	46.00	-18.60
106.63	Н	Peak	44.97	-16.48	28.49	43.50	-15.01
167.74	Н	Peak	42.48	-13.85	28.63	43.50	-14.87
240.49	Н	Peak	44.45	-14.11	30.34	46.00	-15.66
337.49	Н	Peak	41.03	-12.05	28.98	46.00	-17.02
458.74	Н	Peak	33.42	-8.61	24.81	46.00	-21.19
609.09	Н	Peak	33.37	-5.83	27.54	46.00	-18.46

Remark:

- 1 Measuring frequencies from 30 MHz to the 1GHz_o
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未經本公司書面許可,不可部份複製。This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台 北縣五股工業區五工路 134 號



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 37 of 59

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode TX CH High Test Date Jul. 23, 2009

Fundamental Frequency 2480MHz Test By Jazz
Temperature 25 Pol Ver./Hor.

Humidity 65 %

Freq.	Ant.Pol.	Detector Mode	Reading	Factor	Actual FS	Limit3m	Safe Margin
(MHz)	H/V	(PK/QP)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
106.63	V	Peak	46.51	-16.48	30.03	43.50	-13.47
164.83	V	Peak	39.48	-13.69	25.79	43.50	-17.71
232.73	V	Peak	44.95	-14.37	30.58	46.00	-15.42
288.99	V	Peak	41.51	-13.23	28.28	46.00	-17.72
337.49	V	Peak	37.76	-12.05	25.71	46.00	-20.29
106.63	Н	Peak	44.30	-16.48	27.82	43.50	-15.68
167.74	Н	Peak	46.39	-13.85	32.54	43.50	-10.96
240.49	Н	Peak	44.19	-14.11	30.08	46.00	-15.92
288.99	Н	Peak	41.93	-13.23	28.70	46.00	-17.30
337.49	Н	Peak	39.97	-12.05	27.92	46.00	-18.08
366.59	Н	Peak	37.64	-11.17	26.47	46.00	-19.53

Remark:

- 1 Measuring frequencies from 30 MHz to the 1GHz_o
- 2 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak/QP detector mode.
- 3 Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 38 of 59

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH Low Test Date Jul. 23, 2009

Fundamental Frequency 2402 MHz Test By Jazz Temperature 25 Pol Ver.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
3626.0						74.00	54.00		
4804.0	51.31	44.92	5.99	57.30	50.91	74.00	54.00	-3.09	Avg
7206.0						74.00	54.00		
9608.0						74.00	54.00		
12010.0						74.00	54.00		
14412.0						74.00	54.00		
16814.0						74.00	54.00		
19216.0						74.00	54.00		
21618.0						74.00	54.00		
24020.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- 5 Spectrum AV Setting: 1GHz-26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 39 of 59

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH Low Test Date Jul. 23, 2009

Fundamental Frequency 2402 MHz Test By Jazz Temperature 25 Pol Hor.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
3223.0						74.00	54.00		
4804.0	47.11	41.61	5.99	53.10	47.60	74.00	54.00	-6.40	Avg
9608.0						74.00	54.00		
12010.0						74.00	54.00		
14412.0						74.00	54.00		
16814.0						74.00	54.00		
19216.0						74.00	54.00		
21618.0						74.00	54.00		
24020.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms.
- 5 Spectrum AV Setting: 1GHz-26GHz, RBW=1MHz, VBW=10Hz, Sweep time=200 ms.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 40 of 59

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH Mid Test Date Jul. 23, 2009

Fundamental Frequency 2441 MHz Test By Jazz Temperature 25 Pol Ver.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
1630.5						74.00	54.00		
4882.0	53.24	45.79	6.17	59.41	51.96	74.00	54.00	-2.04	Avg
7323.0						74.00	54.00		
9764.0						74.00	54.00		
12205.0						74.00	54.00		
14646.0						74.00	54.00		
17087.0						74.00	54.00		
19528.0						74.00	54.00		
21969.0						74.00	54.00		
24410.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- 5 Spectrum AV Setting: 1GHz-26GHz, RBW=1MHz, VBW=10Hz, Sweep time=200 ms.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未總本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.buth. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.buth.

The Company's finding at the time of its intervention only and within the limits of client's i



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 41 of 59

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH Mid Test Date Jul. 23, 2009

Fundamental Frequency 2441 MHz Test By Jazz Temperature 25 Pol Hor.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
3190.5						74.00	54.00		
4882.0	53.66	46.87	6.36	60.02	53.23	74.00	54.00	-0.77	Avg
7323.0						74.00	54.00		
9764.0						74.00	54.00		
12205.0						74.00	54.00		
14646.0						74.00	54.00		
17087.0						74.00	54.00		
19528.0						74.00	54.00		
21969.0						74.00	54.00		
24410.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- 5 Spectrum AV Setting: 1GHz-26GHz, RBW=1MHz, VBW=10Hz, Sweep time=200 ms.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 42 of 59

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH High Test Date Jul. 23, 2009

Fundamental Frequency 2480 MHz Test By Jazz Temperature 25 Pol Ver.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
1448.5						74.00	54.00		
4960.0	47.36	42.41	6.36	53.72	48.77	74.00	54.00	-5.23	Avg
7440.0						74.00	54.00		
9920.0						74.00	54.00		
12400.0						74.00	54.00		
14880.0						74.00	54.00		
17360.0						74.00	54.00		
19840.0						74.00	54.00		
22320.0						74.00	54.00		
24800.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz- 26GHz, RBW= 1MHz, VBW= 3MHz, Sweep time= 200 ms
- 5 Spectrum AV Setting: 1GHz-26GHz, RBW=1MHz, VBW=10Hz, Sweep time=200 ms.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 43 of 59

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH High Test Date Jul. 23, 2009

Fundamental Frequency 2480 MHz Test By Jazz Temperature 25 Pol Hor.

Humidity 65 %

	Peak	\mathbf{AV}		Actu	al FS	Peak	\mathbf{AV}		
Freq.	Reading	Reading	Ant./CL	Peak	\mathbf{AV}	Limit	Limit	Margin	Remark
(MHz)	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)	
1968.5						74.00	54.00		
4960.0	46.53	45.21	6.36	52.89	51.57	74.00	54.00	-2.43	Avg
7440.0						74.00	54.00		
9920.0						74.00	54.00		
12400.0						74.00	54.00		
14880.0						74.00	54.00		
17360.0						74.00	54.00		
19840.0						74.00	54.00		
22320.0						74.00	54.00		
24800.0						74.00	54.00		

Remark:

- 1 Measuring frequencies from 1GHz to the 10th harmonic of highest fundamental frequency.
- 2 Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3 Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4 Spectrum Peak Setting: 1GHz-26GHz, RBW=1MHz, VBW=3MHz, Sweep time=200 ms.
- 5 Spectrum AV Setting: 1GHz-26GHz, RBW=1MHz, VBW=10Hz, Sweep time=200 ms.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 44 of 59

10. FREQUENCY SEPARATION

10.1. Standard Applicable

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.

10.2. Measurement Equipment Used:

Refer to section 6.2 for details.

10.3. Test Set-up:

Refer to section 6.3 for details.

10.4. Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = middle of hopping channel .
- 4. Set the spectrum analyzer as RBW = 430 KHz, VBW=1.3 MHz, Adjust Span to 3.0 MHz, Sweep = auto.
- 5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

10.5. Measurement Result:

Channel separation (MHz)	Limit	Result
1	>=25KHz or 2/3 times 20dB bandwidth	PASS


Note: Refer to next page for plots.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 45 of 59

Frequency Separation Test Data





Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 46 of 59

11. NUMBER OF HOPPING FREQUENCY

11.1. Standard Applicable

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

11.2. Measurement Equipment Used:

Refer to section 6.2 for details.

11.3. Test Set-up:

Refer to section 6.3 for details.

11.4. Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set spectrum analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = auto.
- 4. Set the spectrum analyzer as RBW, VBW=100KHz,
- 5. Max hold, view and count how many channel in the band.

11.5. Measurement Result:

Note: Refer to next page for plots.




Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009


Page: 47 of 59

Channel Number

2.4 GHz - 2.441GHz



2.441 GHz - 2.483GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未總本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 48 of 59

12. TIME OF OCCUPANCY (DWELL TIME)

12.1. Standard Applicable

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

12.2. Measurement Equipment Used:

Refer to section 6.2 for details.

12.3. Test Set-up:

Refer to section 6.3 for details.

12.4. Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = operating frequency.
- 4. Set the spectrum analyzer as RBW, VBW =1MHz, Span = 0Hz, Adjust Sweep = 30s.
- 5. Repeat above procedures until all frequency measured were complete.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 49 of 59

12.5. Measurement Result

A period time = 0.4 (ms) * 79 = 31.6 (s)

CH Low: DH1 time slot = 0.3952 (ms) * (1600/(1*79)) * 31.6 = 252.928 (ms)

DH3 time slot = 1.653 (ms) * (1600/(3*79)) * 31.6 = 352.64 (ms)

DH5 time slot = 2.900 (ms) * (1600/(5*79)) * 31.6 = 371.2 (ms)

CH Mid: DH1 time slot = 0.3952 (ms) * (1600/(1*79)) * 31.6 = 252.928 (ms)

DH3 time slot = 1.653(ms) * (1600/(3*79)) * 31.6 = 352.64 (ms)

DH5 time slot = 2.900 (ms) * (1600/(5*79)) * 31.6 = 371.2 (ms)

CH High: DH1 time slot = 0.3952 (ms) * (1600/(1*79)) * 31.6 = 252.928 (ms)

DH3 time slot = 1.653 (ms) * (1600/(3*79)) * 31.6 = 352.64 (ms)

DH5 time slot = 2.900 (ms) * (1600/(5*79)) * 31.6 = 371.2 (ms)


Note: Refer to next page for plots.




Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 50 of 59

CH-Low DH1



DH3




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未總本公司書面許可,不可能仍複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 51 of 59

DH5







Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 52 of 59

CH-Mid DH1



DH3




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未總本公司書面許可,不可能仍複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 53 of 59

DH5




Member of SGS Group




Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 54 of 59

CH-High DH1



DH3




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測式之樣品負責,同時此樣品僅保留0天。本報告未總本公司書面許可,不可能仍複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/terms e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.onsite.com/authentication. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 55 of 59

DH5





Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 56 of 59

13. Peak Power Spectral Density

13.1. Standard Applicable

According to §15.247(d), for direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3kHz band during any time interval of continuous transmission.

13.2. Measurement Equipment Used:

Refer to section 6.2 for details.

13.3. Test Set-up:

Refer to section 6.3 for details.

13.4. Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW = 3KHz, VBW = 10KHz, Span = 1.5MHz, Sweep=100s
- 4. Record the max. reading.
- 5. Repeat above procedures until all frequency measured were complete.

13.5. Measurement Result

СН	RF Power Density	Cable loss	RF Power Density	Maximum Limit
	Reading (dBm)	(dB)	Level (dBm)	(dBm)
Low	-8.68	0.00	-8.68	8
Mid	-11.36	0.00	-11.36	8
High	-7.32	0.00	-6.82	8

^{*}Offset = 0.5 dBm


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告报權的過程。 同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms_ad_conditions.htm) and Terms and Conditions for Service (www.sgs.com/terms_e-document.htm). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at <a href="https://www.sgs.com/terms_e-document_intermon_reflects the Companys's findings at the time of its intervention only and within the limits of client's instructions, if any. The Companys's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents.




Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 57 of 59

Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複數。
This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document ment is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. SGS Taiwan Ltd.


No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 58 of 59

Power Spectral Density Test Plot (CH-High)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This test report cannot be reproduced, except in full, without prior written permission of the Company. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複數。
This document is issued by the Company subject to its General Conditions of Service (www.sgs.com/terms and conditions.htm) and Terms and Conditions for Electronic Documents is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. Even if printed this electronic document is to be treated as an original within the meaning of UCP 600 article 20b. The authenticity of this document may be verified at www.sgs.com/authentication. Any holder of this document ment is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. SGS Taiwan Ltd.



Report No.: ER/2009/50006 Issue Date: Jul. 29, 2009

Page: 59 of 59

14. ANTENNA REQUIREMENT

14.1. Standard Applicable

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than furnished by the responsible party shall be used with the device.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

14.2. Antenna Connected Construction

The directional gains of antenna used for transmitting is 3dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Please see EUT photo for details.