

## Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at device output terminal: \_\_\_\_\_\_dBm

Cable and Jumper loss: 0.0 dB

Maximum peak output power at antenna input terminal: 26.12 dBm

409.2606597 mW

Single Antenna gain (typical): 9 dBi

Number of Antennae: 1

Total Antenna gain (typical): 9 dBi

7.943282347 (numeric)

Prediction distance: 20 cm
Prediction frequency: 2475 MHz

MPE limit for uncontrolled exposure at prediction frequency: \_\_\_\_\_\_\_1 mW/cm<sup>2</sup>

Power density at prediction frequency: 0.646741 mW/cm<sup>2</sup>

6.467406 W/m<sup>2</sup>

Tx On time: 1.000000 ms
Tx period time: 1.000000 ms

Average Factor: 100.000000 %

Average Power density at prediction frequency: 6.467406 W/m²

Maximum allowable antenna gain: 10.89269855 dBi

Margin of Compliance: 1.892698554 dB