

SECUREMESH 1 WATT RADIO MODULE



INSTALLATION INSTRUCTIONS

January 12, 2016

The Trilliant 1 Watt SecureMesh Radio Module is a 2.4GHz 802.15.4 transceiver radio module intended for use in electric meters, gas meters, and network product and in home products for utility applications. The module contains castellations for connections to external antenna board, such as the 1.1 dBi "L" shaped antenna. The module also allows direct connection for an optional U.FL connector. Power is supplied by a host module with a nominal voltage of 3.3 volts.

Specification of the radio module:

- IEEE standard: 802.15.4
- Power Output : +30 dBm
- Radio Sensitivity: -99 dBm
- RF Data Rate: 250 kbps
- Operating Frequency: 2.400-2.483GHz
- Network Topology: Mesh
- Modulation: O-QPSK
- Physical Dimensions: 1.400" x 2.075"
- Antenna Options: Castellations to External Board, U.FL

Trilliant Responsibilities to comply with FCC and Industry Canada Regulations

The **SecureMesh 1 Watt Radio** Module has been certified for integration into products only by a professional under the following conditions:

1. The antenna(s) must be installed such that a minimum separation distance of 20cm is maintained between the radiator (antenna) and all persons at all times.
2. The transmitter module must not be co-located or operating in conjunction with any other antenna or transmitter.

As long as the two conditions above are met, further transmitter testing will not be required. However, Trilliant is still responsible for testing their end-product for any additional compliance requirements required with this module installed (for example, digital device emissions, PC peripheral requirements, etc.).

IMPORTANT NOTE: In the event that these conditions cannot be met (for certain configurations or co-location with another transmitter), then the FCC and Industry Canada authorizations are no longer considered valid and the FCC ID and IC Certification Number cannot be used on the final product. In these circumstances, Trilliant integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate FCC and Industry Canada authorization.

Trilliant will not provide information to the end user regarding how to install or remove this RF module or change RF related parameters in the user manual of the end product. The module will be professionally installed inside a meter. The meter will be professionally installed by employees of a utility – who are professionals in their field.

Product Labeling

The Trilliant SecureMesh 1 Watt Radio Module is labeled with its own FCC ID and IC Certification Number. If the FCC ID and IC Certification Number are not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. In that case, the final end product must be labeled in a visible area with the following:

" Contains Transmitter Module FCC ID: TMB-EM0069"
" Contains Transmitter Module IC: 6028A-EM0069"

or

" Contains FCC ID: TMB-EM0069"
" Contains IC: 6028A-EM0069"

Since the Trilliant SecureMesh 1 Watt Radio Module is so small, the following statement shall be placed in the finish product user manual:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

User Manual Statements

The user manual of the finish product shall include the following statements:

Federal Communication Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

The following statement must be included as a CAUTION statement to alert users of FCC RF exposure compliance:

To satisfy FCC RF Exposure requirements for mobile and base station transmission devices, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during operation. To ensure compliance, operation at closer than this distance is not recommended.

Industry Canada Statements

This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

The following statement must be included as a CAUTION statement to alert users of Industry Canada RF exposure compliance:

To satisfy Industry Canada RF Exposure requirements for mobile and base station transmission devices, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during operation. To ensure compliance, operation at closer than this distance is not recommended.

Pour satisfaire les requis d'industrie Canada sur les expositions aux radiofréquences pour les appareils mobiles et les stations de transmission, une distance de 20 cm ou plus doit être maintenue entre l'antenne de cet appareil et les personnes durant l'opération. Pour assurer la conformité, les opérations à des distances inférieures ne sont pas recommandées.

The Trilliant SecureMesh 1 Watt Radio Module must only use the approved antenna(s) listed above, which have been certified with this module.

Antennas Approved for use

This device has been designed to operate with the antennas listed below, and having a maximum gain of 6.0 dB. Antennas not included in this list or having a gain greater than 6.0 dB are strictly prohibited for use with this device. The required antenna impedance is 50 ohms. The maximum gain antenna is the Mobile Mark OD6-2400 (6dbi gain).

- Mobile Mark OD6-2400 (6dBi gain)
- PCB Trace Inverted-L Antenna (1.1 dBi gain)
- Mobile Mark CVS-2400-2SA-BLK-13

Copyright © 2012 - Trilliant Inc.

Terms and product names in this document may be trademarks of others.

All specifications are nominal and may change as design improvements are introduced. Trilliant Inc. shall not be liable for damages resulting from misapplication or misuse of its products.

Marks bearing [®] and/or [™] are registered trademarks of Trilliant Inc. and/or its partners.

Corporate Headquarters:
1100 Island Drive
Redwood City, CA
USA 94065
Tel. 650-204-5050
Fax. 650-508-8096

Canadian Operations
610 du Luxembourg
Granby, Quebec
Canada J2J 2V2
Tel. 450-375-0556
Fax. 450-375-8746