



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Blackboard, Inc.

Model: WR5000

Description: Security Access systems and as an attendance wall reader

Serial Number: N/A

FCC ID: TMEWR5000X012

To

FCC Part 1.1310

Date of Issue: January 18, 2018

On the behalf of the applicant:

Blackboard, Inc.
22601 N 19th Ave
Phoenix, AZ 85027

Attention of:

Tim Mattson, Sr. Engineer
Ph: (623)476-1141
Email: Tim.Mattson@blackboard.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1770014

Alex Macon
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	January 18, 2018	Alex Macon	Original Document

ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: WR5000

Description: Security Access systems and as an attendance wall reader

Firmware: N/A

Software: N/A

Serial Number: N/A

Additional Information: The device incorporated an NFC transmitter at 13.56MHz and a pre-certified 2.4GHz module.

Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Radiated Field Strength (dBuV/m)
13.56	36.83

$\text{dBuV} - 107 = \text{dBm}$

$36.83 - 107 = -70.17 \text{ dBm}$

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)
13.56	9.62×10^{-8}

KDB 447498 D01

4.3.1

3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion, and as illustrated in Appendix C:²⁸

- a) The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f_{\text{(MHz)}})]$ for *test separation distances* > 50 mm and < 200 mm
- b) The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for *test separation distances* ≤ 50 mm

The exclusion found in the table for Annex C at 10 Mhz and < 50 mm is 474mW.

The EUT's output power is well below this threshold

END OF TEST REPORT