

# Johnson Health Tech. Co., Ltd.

## RF TEST REPORT

**Report Type:**

FCC Part 15.247 & ISED RSS-247 RF report

**Model:**

XUR-C, XIR-02-C, XER-02-C

**REPORT NUMBER:**

201001480SHA-001

**ISSUE DATE:**

June 8, 2022

**DOCUMENT CONTROL NUMBER:**

TTRF15.247-02\_V1 © 2018 Intertek



**Applicant:** Johnson Health Tech. Co., Ltd.  
No. 999, Sec. 2, Dongda Rd., Daya Dist., Taichung City 428

**Manufacturer:** Johnson Health Tech. Co., Ltd.  
No. 999, Sec. 2, Dongda Rd., Daya Dist., Taichung City 428

**Factory 1:** Johnson Health Tech. Co., Ltd.  
No. 999, Sec. 2, Dongda Rd., Daya Dist., Taichung City 428

**Factory 2:** Johnson Industries (Shanghai) CO., LTD.  
A1, Export Processing Zone, No. 4500 Bao Qian Rd., Jia Ding, Shanghai.

**FCC ID:** TN7XUR

### SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

**47CFR Part 15 (2020):** Radio Frequency Devices (Subpart C)

**ANSI C63.10 (2013):** American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

**PREPARED BY:**

**REVIEWED BY:**



Project Engineer  
Eric Li



Reviewer  
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT**

**Content**

**REVISION HISTORY..... 5**

**MEASUREMENT RESULT SUMMARY ..... 6**

**1 GENERAL INFORMATION ..... 7**

1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) ..... 7

1.2 TECHNICAL SPECIFICATION ..... 7

1.3 DESCRIPTION OF TEST FACILITY ..... 8

**2 TEST SPECIFICATIONS..... 9**

2.1 STANDARDS OR SPECIFICATION ..... 9

2.2 MODE OF OPERATION DURING THE TEST ..... 9

2.3 TEST SOFTWARE LIST ..... 9

2.4 TEST PERIPHERALS LIST ..... 10

2.5 TEST ENVIRONMENT CONDITION:..... 10

2.6 INSTRUMENT LIST ..... 11

2.7 MEASUREMENT UNCERTAINTY ..... 13

**3 MINIMUM 6DB BANDWIDTH..... 14**

3.1 LIMIT ..... 14

3.2 MEASUREMENT PROCEDURE ..... 14

3.3 TEST CONFIGURATION ..... 14

3.4 TEST RESULTS OF MINIMUM 6DB BANDWIDTH ..... 14

**4 MAXIMUM CONDUCTED OUTPUT POWER AND E.I.R.P..... 15**

4.1 LIMIT ..... 15

4.2 MEASUREMENT PROCEDURE ..... 15

4.3 TEST CONFIGURATION ..... 15

4.4 TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER..... 15

**5 POWER SPECTRUM DENSITY ..... 16**

5.1 LIMIT ..... 16

5.2 MEASUREMENT PROCEDURE ..... 16

5.3 TEST CONFIGURATION ..... 16

5.4 TEST RESULTS OF POWER SPECTRUM DENSITY ..... 16

**6 EMISSION OUTSIDE THE FREQUENCY BAND ..... 17**

6.1 LIMIT ..... 17

6.2 MEASUREMENT PROCEDURE ..... 17

6.3 TEST CONFIGURATION ..... 18

6.4 THE RESULTS OF EMISSION OUTSIDE THE FREQUENCY BAND..... 18

**7 RADIATED EMISSIONS IN RESTRICTED FREQUENCY BANDS..... 19**

7.1 LIMIT ..... 19

7.2 MEASUREMENT PROCEDURE ..... 19

7.3 TEST CONFIGURATION ..... 21

7.4 TEST RESULTS OF RADIATED EMISSIONS ..... 23

**8 POWER LINE CONDUCTED EMISSION..... 25**

8.1 LIMIT ..... 25

8.2 TEST CONFIGURATION ..... 25

8.3 MEASUREMENT PROCEDURE ..... 26

8.4 TEST RESULTS OF POWER LINE CONDUCTED EMISSION..... 27

**TEST REPORT**

**9 OCCUPIED BANDWIDTH ..... 29**

9.1 LIMIT ..... 29

9.2 MEASUREMENT PROCEDURE ..... 29

9.3 TEST CONFIGURATION ..... 29

9.4 THE RESULTS OF OCCUPIED BANDWIDTH ..... 29

**10 ANTENNA REQUIREMENT ..... 30**

**APPENDIX A: TEST RESULTS ..... 31**

## Revision History

Report No.	Version	Description	Issued Date
201001480SHA-001	Rev. 01	Initial issue of report	June 8, 2022

## Measurement result summary

TEST ITEM	FCC REFERANCE	RESULT
Minimum 6dB Bandwidth	15.247(a)(2)	Pass
Maximum conducted output power and e.i.r.p.	15.247(b)(3)	Pass
Power spectrum density	15.247(e)	Pass
Emission outside the frequency band	15.247(d)	Pass
Radiated Emissions in restricted frequency bands	15.247(d), 15.205&15.209	Pass
Power line conducted emission	15.207(a)	Pass
Occupied bandwidth	-	Tested
Antenna requirement	15.203	Pass

Notes: 1: NA =Not Applicable

**TEST REPORT**

**1 GENERAL INFORMATION**

**1.1 Description of Equipment Under Test (EUT)**

Product name:	Fitness equipment console
Type/Model:	XUR-C, XIR-02-C, XER-02-C
Radio Module:	AP6398S
Description of EUT:	EUT is a Fitness equipment console, there are three models, all models are the same except the model name, the display size and ratings, we test XUR-C as representative and list the worst results in this report.
Rating:	12Vdc, 4A for XUR-C; 12Vdc, 3A for XIR-02-C; 12Vdc, 3A for XER-02-C.
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	December 21, 2019
Date of test:	December 23, 2019 ~ December 29, 2019

**1.2 Technical Specification**

Frequency Band:	2400MHz to 2483.5MHz
Support Standards:	Bluetooth Low Energy
Operating Frequency:	2402MHz to 2480MHz
Type of Modulation:	GFSK
Channel Number:	40
Channel Separation:	2MHz
Antenna Information:	PCB Antenna, 4.8dBi

**TEST REPORT**

**1.3 Description of Test Facility**

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02



**TEST REPORT**

**2 TEST SPECIFICATIONS**

**2.1 Standards or specification**

47CFR Part 15 (2020)  
 ANSI C63.10 (2013)  
 KDB 558074 (v05r02)

**2.2 Mode of operation during the test**

The lowest, middle and highest channel were tested as representatives.

Frequency Band (MHz)				2402 ~ 2480			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
<b>0</b>	<b>2402</b>	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	<b>19</b>	<b>2440</b>	29	2460	<b>39</b>	<b>2480</b>

**Data rate VS Power:**

The test setting software is offered by the manufactory. The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases.

Test software and Power Setting parameter			
Test Software	Combo Tool		
Working Mode	BLE		
Test Channel	2402MHz	2440MHz	2480MHz
Power Setting	Default	Default	Default

**2.3 Test software list**

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

**TEST REPORT**

**2.4 Test peripherals list**

Item No.	Name	Band and Model	Description
1	Adapter	TC-33097	Power supply only
2	Display Screen	Dell S2316Hc	Display
3	Mouse	Dell MS116p	Controller

**2.5 Test environment condition:**

Test items	Temperature	Humidity
Minimum 6dB Bandwidth	24°C	54%RH
Maximum conducted output power and e.i.r.p.		
Power spectrum density		
Emission outside the frequency band		
Occupied bandwidth		
Radiated Emissions in restricted frequency bands	23°C	53%RH
Power line conducted emission	23°C	53%RH

**TEST REPORT**

**2.6 Instrument list**

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESCS 30	EC 2107	2020-07-08
<input checked="" type="checkbox"/>	A.M.N.	R&S	ESH2-Z5	EC 3119	2020-11-10
<input type="checkbox"/>	A.M.N.	R&S	ENV 216	EC 3393	2020-07-08
<input type="checkbox"/>	A.M.N.	R&S	ENV4200	EC 3558	2020-06-11
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESIB 26	EC 3045	2020-09-16
<input checked="" type="checkbox"/>	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2020-09-25
<input checked="" type="checkbox"/>	Pre-amplifier	R&S	AFS42-00101800-25-S-42	EC5262	2020-06-11
<input type="checkbox"/>	Horn antenna	R&S	HF 906	EC 3049	2020-01-17
<input checked="" type="checkbox"/>	Horn antenna	ETS	3117	EC 4792-1	2020-03-15
<input checked="" type="checkbox"/>	Horn antenna	TOYO	HAP18-26W	EC 4792-3	2020-07-09
<input checked="" type="checkbox"/>	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2020-03-24
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2020-03-16
<input type="checkbox"/>	Power sensor	Agilent	U2021XA	EC 5338-1	2020-03-16
<input type="checkbox"/>	Vector Signal Generator	Agilent	N5182B	EC 5175	2020-03-16
<input type="checkbox"/>	Universal Radio Communication Tester	R&S	CMW500	EC5944	2020-12-09
<input type="checkbox"/>	MXG Analog Signal Generator	Agilent	N5181A	EC 5338-2	2020-03-16
<input type="checkbox"/>	Mobile Test System	Litepoint	lqxel	EC 5176	2020-01-16
<input type="checkbox"/>	Test Receiver	R&S	ESCI 7	EC 4501	2020-09-16
<input type="checkbox"/>	Climate chamber	GWS	MT3065	EC 6021	2020-03-05
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9030B	EC 6078	2020-06-10
Tet Site					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Shielded room	Zhongyu	-	EC 2838	2020-01-12
<input type="checkbox"/>	Shielded room	Zhongyu	-	EC 2839	2020-01-12

**TEST REPORT**

<input checked="" type="checkbox"/>	Semi-anechoic chamber	Albatross project	-	EC 3048	2020-07-14
<input type="checkbox"/>	Fully-anechoic chamber	Albatross project	-	EC 3047	2020-07-14
<b>Additional instrument</b>					
<b>Used</b>	<b>Equipment</b>	<b>Manufacturer</b>	<b>Type</b>	<b>Internal no.</b>	<b>Due date</b>
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3783	2020-03-03
<input type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3481	2020-01-05
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3442	2020-01-05
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3324	2020-09-05
<input type="checkbox"/>	Pressure meter	YM3	Shanghai Mengde	EC 3320	2020-09-09

**TEST REPORT****2.7 Measurement uncertainty**

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

<b>Test item</b>	<b>Measurement uncertainty</b>
Maximum peak output power	$\pm 0.74\text{dB}$
Radiated Emissions in restricted frequency bands below 1GHz	$\pm 4.90\text{dB}$
Radiated Emissions in restricted frequency bands above 1GHz	$\pm 5.02\text{dB}$
Emission outside the frequency band	$\pm 2.89\text{dB}$
Power line conducted emission	$\pm 3.19\text{dB}$

**TEST REPORT****3 Minimum 6dB bandwidth****Test result: Pass****3.1 Limit**

For systems using digital modulation techniques that may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands, the minimum 6 dB bandwidth shall be at least 500 kHz.

**3.2 Measurement Procedure**

The EUT was tested according to Subclause 11.8 of ANSI C63.10.

- a) Set RBW = 100 kHz.
- b) Set VBW  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**3.3 Test Configuration****3.4 Test Results of Minimum 6dB bandwidth**

Please refer to Appendix A

**TEST REPORT****4 Maximum conducted output power and e.i.r.p.****Test result: Pass****4.1 Limit**


For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 W. (The e.i.r.p. shall not exceed 4 W)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 30dBm and 30+ (6 –antenna gain-beam forming gain).

**4.2 Measurement Procedure**

The EUT was tested according to Subclause 11.9.1.1 of ANSI C63.10.

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq 3 \times$  RBW.
- c) Set span  $\geq 3 \times$  RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

**4.3 Test Configuration****4.4 Test Results of Maximum conducted output power**

Please refer to Appendix A

**TEST REPORT**

**5 Power spectrum density**

**Test result: Pass**

**5.1 Limit**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 8dBm/MHz and 8+ (6 –antenna gain-beam forming gain).

**5.2 Measurement Procedure**

The EUT was tested according to Subclause 11.10 of ANSI C63.10.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to:  $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
- d) Set the VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

**5.3 Test Configuration**



**5.4 Test Results of Power spectrum density**

Please refer to Appendix A



**TEST REPORT****6 Emission outside the frequency band****Test result: Pass****6.1 Limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

**6.2 Measurement Procedure**

The EUT was tested according to Subclause 11.11 of ANSI C63.10.

**Reference level measurement**

Establish a reference level by using the following procedure:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to  $\geq 1.5$  times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW  $\geq 3 \times$  RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.


**Emission level measurement**

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq 3 \times$  RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

**TEST REPORT**

**6.3 Test Configuration**



**6.4 The results of Emission outside the frequency band**

Please refer to Appendix A

**TEST REPORT**

**7 Radiated Emissions in restricted frequency bands**

**Test result: Pass**

**7.1 Limit**

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

<b>Frequencies (MHz)</b>	<b>Field Strength (microvolts/meter)</b>	<b>Measurement Distance (meters)</b>
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**7.2 Measurement Procedure**

The EUT was tested according to Subclause 11.12 of ANSI C63.10.

**For Radiated emission below 30MHz:**

- a) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) Both X and Y axes of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

**NOTE:**

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

**TEST REPORT****For Radiated emission above 30MHz:**

- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detector function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


**Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or  $3 \times \text{RBW}$  (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were and the worst-case emissions were reported.


**TEST REPORT**

**7.3 Test Configuration**

For Radiated emission below 30MHz:




For Radiated emission 30MHz to 1GHz:



**TEST REPORT**

**For Radiated emission above 1GHz:**




**TEST REPORT**


**7.4 Test Results of Radiated Emissions**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Horizontal



Vertical



**TEST REPORT**

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	30.00	30.10	40.00	9.90	PK
H	63.05	37.60	40.00	2.40	PK
H	146.91	38.70	43.50	4.80	QP
H	300.20	41.10	46.00	4.90	QP
H	498.48	41.30	46.00	4.70	QP
H	914.47	42.80	46.00	3.20	QP
V	47.49	24.50	40.00	15.50	PK
V	76.65	24.50	40.00	15.50	PK
V	121.36	34.20	43.50	9.30	PK
V	300.20	36.70	46.00	9.30	PK
V	498.48	41.10	46.00	4.90	QP
V	747.05	37.40	46.00	8.60	QP

**Test result above 1GHz:**

The emission was conducted from 1GHz to 25GHz

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2402	83.70	Fundamental	/	PK
	H	2390	52.30	74.00	21.70	PK
M	H	2440	83.60	Fundamental	/	PK
H	H	2480	83.30	Fundamental	/	PK
	H	2483.5	51.20	74.00	22.80	PK

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.  
 2. Corrected Reading = Original Receiver Reading + Correct Factor  
 3. Margin = Limit - Corrected Reading  
 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB, Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV, Limit = 40.00dBuV/m.  
 Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;  
 Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;  
 Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.



**TEST REPORT**

**8 Power line conducted emission**


Test result: Pass

**8.1 Limit**

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

**8.2 Test Configuration**



**TEST REPORT****8.3 Measurement Procedure**


Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50  $\Omega$  LISN port (to which the EUT is connected), where permitted, terminated into a 50  $\Omega$  measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50  $\Omega$  measuring port is terminated by a measuring instrument having 50  $\Omega$  input impedance. All other ports are terminated in 50  $\Omega$  loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

**TEST REPORT**

**8.4 Test Results of Power line conducted emission**




**Test Data:**

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.58	49.65	56.00	6.35	40.53	46.00	5.47
0.64	46.67	56.00	9.33	40.72	46.00	5.28
0.66	48.05	56.00	7.95	41.17	46.00	4.83
0.86	47.17	56.00	8.83	35.41	46.00	10.59
1.13	46.53	56.00	9.47	36.98	46.00	9.02
1.21	46.45	56.00	9.55	37.85	46.00	8.15

**TEST REPORT**

N Line



**Test Data:**

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.40	47.47	57.94	10.47	40.30	47.94	7.64
0.58	49.62	56.00	6.38	39.54	46.00	6.46
0.68	47.16	56.00	8.84	41.08	46.00	4.92
0.80	46.56	56.00	9.44	36.84	46.00	9.16
0.84	47.38	56.00	8.62	36.28	46.00	9.72
1.22	46.41	56.00	9.59	36.96	46.00	9.04

- Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.  
 2. Corrected Reading = Original Receiver Reading + Correct Factor  
 3. Margin = Limit - Corrected Reading  
 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

**TEST REPORT****9 Occupied Bandwidth****Test result:**      **Tested****9.1 Limit**


None

**9.2 Measurement Procedure**

The occupied bandwidth per RSS-Gen was measured using the Spectrum Analyzer.

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

**9.3 Test Configuration****9.4 The results of Occupied Bandwidth**

Please refer to Appendix A

**TEST REPORT****10 Antenna requirement****Requirement:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**Result:**

EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

## TEST REPORT


### Appendix A: Test results

#### 1. Conducted Output Power

##### 1.1 Test Data

BLE Maximum Output Power		
Test Frequency	Power(dBm)	Result
2402	-12.55	Pass
2440	-12.39	Pass
2480	-13.38	Pass

##### 1.2 Test Plots




## TEST REPORT

### 2. Power Spectral Density

#### 1.3 Test Data

BLE Peak Power Spectral Density		
Test Frequency	PSD(dBm/100kHz)	Result
2402	-13.31	Pass
2440	-13.12	Pass
2480	-14.15	Pass

#### 1.4 Test Plots






## TEST REPORT

### 3. Minimum 6dB bandwidth

#### 3.1 Test Data

BLE Occupied 6dB Bandwidth			
Test Frequency (MHz)	Occupied Bandwidth (kHz)	Min Limit (kHz)	Result
2402	722.3	500	Pass
2440	719.9	500	Pass
2480	722.8	500	Pass

#### 3.2 Test Plots



## TEST REPORT

### 4. Occupied Bandwidth

#### 4.1 Test Data

BLE 99% Occupied Bandwidth		
Test Frequency (MHz)	99% Occupied Bandwidth (MHz)	Result
2402	1.0545	Pass
2440	1.0547	Pass
2480	1.0564	Pass

#### 4.2 Test Plots




## TEST REPORT

### 5. Emission outside the frequency band


#### 5.1 Test Data

BLE Transmitter Spurious Emission			
Test Frequency (MHz)	Test Range	Power (dBm)	Result
2402	1MHz~2310MHz	-48.15	Pass
2402	2500MHz~5000MHz	-55.08	Pass
2402	5000MHz~25000MHz	-44.32	Pass
2402	Band Edge	-58.59	Pass
2402	Reference Level	-13.36	Pass
2440	1MHz~2310MHz	-57.35	Pass
2440	2500MHz~5000MHz	-54.72	Pass
2440	5000MHz~25000MHz	-43.97	Pass
2440	Band Edge	-58.75	Pass
2440	Reference Level	-13.15	Pass
2480	1MHz~2310MHz	-57.44	Pass
2480	2500MHz~5000MHz	-54.37	Pass
2480	5000MHz~25000MHz	-42.97	Pass
2480	Band Edge	-58.97	Pass
2480	Reference Level	-14.15	Pass


#### 9.2 Test Plots




## TEST REPORT



## TEST REPORT



TEST REPORT



\*\*\*\*\* END \*\*\*\*\*