



Flom Test Labs

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268
fax: (480) 926-3598
<http://www.flomlabs.com>
info@flomlabs.com

Date: June 20, 2008

Applicant: RF Central
99 Garden Pkwy
Carlisle, PA 17013

Attention of: Keith Blaisdell, Director of Engineering and Production
Ph: (717)249-4900 Fax: (717)249-3630
Email: keith.blaisdell@rfcentral.com

Equipment: ODU
FCC ID: TO4-RFXDFL2007
FCC Rules: Radio Frequency Radiation Exposure Limits
47 CFR 1.1310
MPE - Mobiles X Fixed Based Station

Gentlemen:

Enclosed please find your copy of the Supplemental Test Data Report, the whole for Environmental Assessment (MPE) of the referenced equipment as shown.

Please allow from 8-12 weeks to hear from the Commission, who may request additional data or information, and even a sample for pre-grant audit testing.

Should you need any clarification, just fax or phone. Thank you again for this order - it has been a pleasure to be of service.

Sincerely yours,

Certifying Engineer:

Hoosamuddin S. Bandukwala, Lab Director



Flom Test Labs
EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268
fax: (480) 926-3598
<http://www.flomlabs.com>
info@flomlabs.com

Date: June 20, 2008

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: RF Central
Equipment: ODU
FCC ID: TO4-RFXDFL2007
FCC Rules: Radio Frequency Radiation Exposure Limits
47 CFR 1.1310
MPE - Mobiles X Fixed Based Station _____

Gentlemen:

On behalf of the Applicant, enclosed please find the Supplemental Test Data Report, the whole for Environmental Assessment (MPE) of the referenced equipment as shown.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

Certifying Engineer:

Hoosamuddin S. Bandukwala, Lab Director

Flom Test Labs
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(866) 311-3268 phone, (480) 926-3598 fax

p0810010, d0860028 Rev 1.0



Flom Test Labs
EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268
fax: (480) 926-3598
<http://www.flomlabs.com>
info@flomlabs.com

Environmental Assessment

for

Mobiles

for

FCC ID: TO4-RFXDFL2007

Model:ODU

to

Federal Communications Commission

47 CFR 1.1310

Radio Frequency Radiation Exposure Limits

Date Of Report: June 20, 2008

On the Behalf of the Applicant: RF Central

At the Request of: RF Central
99 Garden Pkwy
Carlisle, PA 17013

Attention of: Keith Blaisdell, Director of Engineering and Production
Ph: (717)249-4900 Fax: (717)249-3630
Email: keith.blaisdell@rfcentral.com

Sincerely yours,

Hoosamuddin S. Bandukwala, Lab Director

Certifying Engineer:

Flom Test Labs
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(866) 311-3268 phone, (480) 926-3598 fax

p0810010, d0860028 Rev 1.0

Revision History

Revision	Date	Revised By	Reason for revision
1.0	June 20, 2008	J. Erhard	Original Document

Testimonial and Statement of Certification

This is to certify that:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Sincerely yours,




Hoosamuddin S. Bandukwala, Lab Director

Certifying Engineer:

Table of Contents

Rule	Description	Page
	Test Report	1
	Identification of the Equipment Under Test	2
	Standard Test Conditions and Engineering Practices	2
1.1310	Environmental Assessment	2

Required information per ISO 17025-2005, paragraph 5.10:

- a) **Test Report (Supplemental)**
- b) Laboratory: Flom Test Labs
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85225
- c) Report Number: d0860028
- d) Client: RF Central
99 Garden Pkwy
Carlisle, PA 17013
- e) Identification: ODU
Description: 7 GHz Part 74 Transmitter
- f) EUT Condition: Not required unless specified in individual tests.
- g) Report Date: June 20, 2008
- h, j, k): As indicated in individual tests.
- i) Sampling method: No sampling procedure used.
- l) Uncertainty: In accordance with MFA internal quality manual.
- m) Supervised by:
- 
Hoosamuddin S. Bandukwala
- n) Results: The results presented in this report relate only to the item tested.
- o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.



toll-free: (866) 311-3268
 fax: (480) 926-3598
<http://www.flomlabs.com>
info@flomlabs.com

Identification of the Equipment Under Test (EUT)

Name and Address of Applicant: RF Central
 99 Garden Pkwy
 Carlisle, PA 17013

Manufacturer: RF Central
 99 Garden Pkwy
 Carlisle, PA 17013

FCC ID: TO4-RFXDFL2007

Model Number: ODU

Description: 7 GHz Part 74 Transmitter

Type of Emission: 25M0D7W

Frequency Range, MHz: 6436 – 7120MHz

Power Rating, Watts: ~0.340W
 Switchable Variable N/A

Modulation:
 AMPS
 TDMA
 CDMA
 OTHER

Antenna:
 Helical
 Monopole
 Whip
 Other

Note: For RF Safety test antenna gain taken at the upper range of expected gain (i.e. 0 dBd) and RF Power set to highest nominal power across all channels.

A2LA

“A2LA has accredited Flom Test Labs, Inc. Chandler, AZ for technical competence in the field of Electrical testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO 17025:2005 ‘General Requirements for the Competence of Testing and Calibration Laboratories’ and any additional program requirements in the identified field of testing.”

Please refer to www.a2la.org for current scope of accreditation.

Certificate number: 2152.01



Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-2004 and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.

Name of Test: Environmental Assessment

Specification: FCC: 47 CFR 1.1310

Measurement Guide: ANSI/IEEE C95.1 1992

Name of Test: R.F. Radiation Exposure

FCC Rules: 1.1307, 1.1310, 1.1311, 2.1091

Limits: Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)	0.3-1.234 MHz:	Limit [mW/cm ²] = 100
	1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
	30-300 MHz:	Limit [mW/cm ²] = 0.2
	300-1500 MHz:	Limit [mW/cm ²] = f/1500
	1500-100,000 MHz:	Limit [mW/cm ²] = 1.0

Test Frequencies, MHz	6772
Power, Conducted, W (P)	340 mW
Antenna Gain Isotropic	43.9 dBi
Antenna Gain Numeric (G)	24547.09
Antenna Type	3m Semi-parabolic*
Distance (R)	20 cm

Power Density Calculations	Formula =	$S = PG / 4\pi R^2$
	Power Density (S) =	1660.43
	Limit =	1.0

*The antenna is tower mounted.

Sincerely yours,



Hoosamuddin S. Bandukwala, Lab Director

Certifying Engineer: