



SAR Exclusion Letter

FCC ID:	TO8-TKR-373MPPLUS
Customer	TJ Media Co., Ltd.
Model Name	TKR-373MP PLUS
Product name	MIC Karaoke

According to the FCC KDB 447498 D01 v06 section 4.3.1, for 10MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\frac{\text{MaxPowerofChannel(mW)}}{\text{TestSeparationDistance(mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0(1\text{g SAR}), 7.5(10\text{g SAR})$$

where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Calcultaion Result:

Tx Frequency range: 502.0 MHz ~ 521.5MHz

Min. test separation distance: 5 mm

Maximum Output Power: 8.92 dBm (7.80mW)

RF Channel transmit frequency: 502.0 MHz, 511.1 MHz, 521.5 MHz

Frequency [MHz]	Maximum Allowed Power [mW]	Separation Distance [mm]	≤ 3.0 1-g SAR
502	7.8	5	1.11
511.1	6.01		0.86
521.5	7.24		1.05