



Product Service

Choose certainty.
Add value.

Report On

RF Exposure Assessment of the
Funk-Electronic Piciorgros GmbH
TMO-100 Tetra Modem

FCC ID: TO9TMO100
IC ID: 10682ATMO100

Document 75915769 Report 03 Issue 1

November 2012



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuv-sud.co.uk

REPORT ON

RF Exposure Assessment of the
Funk-Electronic Piciorgros GmbH
TMO-100 Tetra Modem

Document 75915769 Report 03 Issue 1

November 2012

PREPARED FOR

Funk-Electronic Piciorgros GmbH
Clausiatasse 5
D-51149
Cologne-Porz
Germany

PREPARED BY


M Whiting
Project Manager

APPROVED BY


M Jenkins
Authorised Signatory

DATED

28 November 2012



Product Service

CONTENTS

| Section | Page No |
|---|-----------|
| 1 REPORT SUMMARY | 3 |
| 1.1 Introduction | 4 |
| 1.2 Brief Summary of Results | 5 |
| 1.3 Product Information | 7 |
| 1.4 Summary | 7 |
| 2 TEST DETAILS | 8 |
| 2.1 Rationale for Assessment of the RF Exposure | 9 |
| 2.2 Defined Limits | 10 |
| 2.3 Establishing Wavelength and 1/4 Wavelength | 10 |
| 2.4 Far Field Calculations | 11 |
| 3 DISCLAIMERS AND COPYRIGHT | 12 |
| 3.1 Disclaimers and Copyright..... | 13 |



Product Service

SECTION 1

REPORT SUMMARY

RF Exposure Assessment of the
Funk-Electronic Piciorgros GmbH
TMO-100 Tetra Modem



Product Service

1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the Funk-Electronic Piciorgros GmbH TMO-100 Tetra Modem to the requirements of the applied test specifications.

| | |
|-------------------------------|---|
| Objective | To perform RF Exposure Assessment to determine the Equipment Under Test's (EUT's) compliance of the applied rules. |
| Applicant | Funk-Electronic Piciorgros GmbH |
| Manufacturer | Funk-Electronic Piciorgros GmbH |
| Manufacturing Description | Tetra Modem |
| Model Number(s) | TMO-100 |
| Test Specification/Issue/Date | EN 62311:2008 OET Bulletin 65 Edition 97-01 August 1997 RSS-102 Issue 4 March 2010 Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard: 2003 |
| Related Document(s) | Council Recommendation 1999/519/EC:1999 FCC CFR 47 Part 1: 2010 FCC CFR 47 Part 2.1091: 2011 Health Canada's Safety Code 6 ARPANSA ICNIRP 1998 National Council on Radiation Protection and Measurements (NRP) - Report No. 86(1986) EN 50383:2002 IEEE Std C95.1-2005 Australian Standard 2772.2 – 1988 |



Product Service

1.2 BRIEF SUMMARY OF RESULTS

1.2.1 General Public Exposure Levels

| Antenna Gain (Numeric) | Peak Output Power (mW) | Field | Calculated RF Exposure at 0.2 m (20cm) | General Public Exposure Limit | Application |
|------------------------|------------------------|-------|--|-------------------------------|---------------------------|
| 1.259 | 3000 | S | 1.88 W/m ² | 2.250 W/m ² | ICNIRP |
| | | S | 0.188 mW/cm ² | 0.300 mW/cm ² | FCC 47 CFR § 1.1310 |
| | | S | 1.88 W/m ² | 3.000 W/m ² | Canada's RF Safety Code 6 |
| | | S | 1.88 W/m ² | 2.250 W/m ² | ARPANSA |
| | | E | 13.31 V/m | 29.168 V/m | ICNIRP |
| | | E | 13.31 V/m | N/A V/m | FCC 47 CFR § 1.1310 |
| | | E | 13.31 V/m | 33.623 V/m | Canada's RF Safety Code 6 |
| | | E | 13.31 V/m | 29.062 V/m | ARPANSA |
| | | H | 0.04 A/m | 0.078 A/m | ICNIRP |
| | | H | 0.04 A/m | N/A A/m | FCC 47 CFR § 1.1310 |
| | | H | 0.04 A/m | 0.089 A/m | Canada's RF Safety Code 6 |
| | | H | 0.04 A/m | 0.077 A/m | ARPANSA |

The calculations have shown that they **meet** the General Public Exposure Levels described in the ICNIRP Guidelines, FCC 47 CFR § 1.1310 Guidelines, Health Canada's RF exposure guideline Safety Code 6 and the Australian ARPANSA limits at **20cm**, the point of investigation.



Product Service

1.2.2 Occupational Exposure Levels

| Antenna Gain (Numeric) | Peak Output Power (mW) | Field | Calculated RF Exposure at 0.2 m (20cm) | Occupational Exposure Limit | Application |
|------------------------|------------------------|-------|--|-----------------------------|---------------------------|
| 1.259 | 3000 | S | 1.88 W/m ² | 11.250 W/m ² | ICNIRP |
| | | S | 0.188 mW/cm ² | 1.500 mW/cm ² | FCC 47 CFR § 1.1310 |
| | | S | 1.88 W/m ² | 15.000 W/m ² | Canada's RF Safety Code 6 |
| | | S | 1.88 W/m ² | 11.250 W/m ² | ARPANSA |
| | | E | 13.31 V/m | 63.640 V/m | ICNIRP |
| | | E | 13.31 V/m | N/A V/m | FCC 47 CFR § 1.1310 |
| | | E | 13.31 V/m | 75.095 V/m | Canada's RF Safety Code 6 |
| | | E | 13.31 V/m | 65.125 V/m | ARPANSA |
| | | H | 0.04 A/m | 0.170 A/m | ICNIRP |
| | | H | 0.04 A/m | N/A A/m | FCC 47 CFR § 1.1310 |
| | | H | 0.04 A/m | 0.199 A/m | Canada's RF Safety Code 6 |
| | | H | 0.04 A/m | 0.173 A/m | ARPANSA |

The calculations have shown that they **meet** the Occupational Exposure Levels described in the ICNIRP Guidelines, FCC 47 CFR § 1.1310 Guidelines, Health Canada's RF exposure guideline Safety Code 6 and the Australian ARPANSA limits at **20 cm**, the point of investigation.



Product Service

1.3 PRODUCT INFORMATION

1.3.1 Attestation

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields (10 MHz - 300 MHz) - General public. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s).

1.3.2 Technical Description

The Equipment under test was a Funk-Electronic Piciorgros GmbH TMO-100 Tetra Modem. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the TMO-100 Tetra Modem to demonstrate compliance with the applied test specification(s) the sample assessed was found to comply with the requirements of the applied rules.

1.4 SUMMARY

The RF exposure assessment is based upon the following criteria:

The TMO-100 Tetra Modem operates in the frequency range of 450 – 470 MHz.

| | |
|------------|---------------|
| Gain | 1 dBi |
| Power | 3 W |
| Distance | 0.2 m (20 cm) |
| Duty Cycle | 25% |



Product Service

SECTION 2

TEST DETAILS



Product Service

2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields.

The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in EN50383:2002 Clause 5.2; E-field or H-field calculation. The method of calculation used is defined in EN50383:2002; Clause 8.2.2, 8.2.3 and 8.2.4.

The calculated values have been compared with limits provided in the ICNIRP guidelines.

Calculations can be made in three separate regions, based on distance from the antenna. These are called:

- far-field region,
- radiating near-field region,
- reactive near-field region.

The theory that defines these regions is given in EN50383:2002 Annex A.

Far-field region

As shown in EN50383 Annex A, the far-field calculations are accurate when the distance, r , from an antenna of length D to a point of investigation is greater than

$$r = \frac{2D^2}{\lambda}$$

Where, r is the distance from the antenna to the point of investigation.

Radiating near-field region

The radiating near-field region of an antenna of length D as shown in EN50383 Annex A, this region is defined by

$$\frac{\lambda}{4} < r > \frac{2D^2}{\lambda}$$

Reactive near-field region

The reactive near-field region of an antenna as shown in EN50383 Annex A, this region is defined by

$$r \leq \frac{\lambda}{4}$$

Where, r is the distance from the antenna to the point of investigation.

Recommend $\lambda/4$ as the boundary between the radiated near-field and reactive near-field for RF exposure compliance assessment.



Product Service

2.2 DEFINED LIMITS

Normative Reference: ICNIRP Advice on Limiting Exposure to Electromagnetic Fields (0-300GHz). Table A4, Reference Levels for General Public Exposure to Time Varying Electric & Magnetic Fields. Vol 15 No.2. 2004. The defined limits are in accordance with 47 CFR § 1.1310 Radiofrequency radiation exposure limits.

Reference levels for general public exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 450 MHz

| | | |
|-------------------------------------|----------|--|
| Power density (W/m ²) | = 2.250 | ICNIRP |
| Power density (mW/cm ²) | = 0.300 | FCC 47 CFR § 1.1310 |
| Power density (W/m ²) | = 3.000 | Canada's RF Safety Code 6 |
| Power density (W/m ²) | = 2.250 | Australian Radiation Protection Series Publication No. 3 |
| E-Field (Vm-1) | = 29.168 | ICNIRP |
| E-Field (Vm-1) | = N/A | FCC 47 CFR § 1.1310 |
| E-Field (Vm-1) | = 33.623 | Canada's RF Safety Code 6 |
| E-Field (Vm-1) | = 29.062 | Australian Radiation Protection Series Publication No. 3 |
| H-Field (Am-1) | = 0.078 | ICNIRP |
| H-Field (Am-1) | = N/A | FCC 47 CFR § 1.1310 |
| H-Field (Am-1) | = 0.089 | Canada's RF Safety Code 6 |
| H-Field (Am-1) | = 0.077 | Australian Radiation Protection Series Publication No. 3 |

Reference levels for occupational exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 450 MHz

| | | |
|-------------------------------------|----------|--|
| Power density (W/m ²) | = 11.250 | ICNIRP |
| Power density (mW/cm ²) | = 1.500 | FCC 47 CFR § 1.1310 |
| Power density (W/m ²) | = 15.000 | Canada's RF Safety Code 6 |
| Power density (W/m ²) | = 11.250 | Australian Radiation Protection Series Publication No. 3 |
| E-Field (Vm-1) | = 63.640 | ICNIRP |
| E-Field (Vm-1) | = N/A | FCC 47 CFR § 1.1310 |
| E-Field (Vm-1) | = 75.095 | Canada's RF Safety Code 6 |
| E-Field (Vm-1) | = 65.125 | Australian Radiation Protection Series Publication No. 3 |
| H-Field (Am-1) | = 0.170 | ICNIRP |
| H-Field (Am-1) | = N/A | FCC 47 CFR § 1.1310 |
| H-Field (Am-1) | = 0.199 | Canada's RF Safety Code 6 |
| H-Field (Am-1) | = 0.173 | Australian Radiation Protection Series Publication No. 3 |

2.3 ESTABLISHING WAVELENGTH AND 1/4 WAVELENGTH

| Frequency (MHz) | $\lambda = \frac{3 \times 10^8}{f}$ | | $\frac{\lambda}{4}$ | |
|--------------------|-------------------------------------|-------------------|---------------------|-------------------|
| | m | cm | m | cm |
| 450 | 0.6666666666666667 | 66.66666666666667 | 0.1666666666666667 | 16.66666666666667 |
| 460 | 0.652173913043478 | 65.2173913043478 | 0.16304347826087 | 16.304347826087 |
| 480 | 0.625 | 62.5 | 0.15625 | 15.625 |



Product Service

2.4 FAR FIELD CALCULATIONS

The following calculations are based on: 1 dBi gain antenna

P = 3 (Power (Watts)) or 3000 (Power milliwatts)
G = 1.259 (Numeric Gain)
r = 20 (Distance (centimetres)) or 0.2(Distance (meters))

The power flux:

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2} \quad S = 1.88 \text{ W/m}^2$$
$$S = 0.188 \text{ mW/cm}^2$$

The electric field strength:

$$E = \frac{\sqrt{30PG_{(\theta, \phi)}}}{r} \quad E = 13.31 \text{ V/m}$$

The magnetic field strength:

$$H = \frac{E}{\eta_o} \quad H = 0.04 \text{ A/m}$$

The calculations meet the General Public Exposure Levels described in the ICNIRP Guidelines.

The calculations meet the General Public Exposure Levels described in the FCC 47CFR§1.1310.

The calculations meet the General Public Exposure Levels described in the Canada's RF Safety Code 6.

The calculations meet the General Public Exposure Levels described in the Australian Radiation Protection Series Publication No. 3

The calculations meet the Occupational Exposure Levels described in the ICNIRP Guidelines.

The calculations meet the Occupational Exposure Levels described in the FCC 47CFR§1.1310

The calculations meet the Occupational Exposure Levels described in the Canada's RF Safety Code 6

The calculations meet the Occupational Exposure Levels described in the Australian Radiation Protection Series Publication No. 3



Product Service

SECTION 3

DISCLAIMERS AND COPYRIGHT



Product Service

3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service

© 2012 TÜV SÜD Product Service