



Product Service

---

Choose certainty.  
Add value.

# Report On

RF Exposure Assessment of the  
Funk-Electronic Piciorgros GmbH  
TMO-100/DAN Tetra Modem

FCC ID: TO9TMO100  
IC ID: 10682A-TMO100

Document 75915769 Report 03 Issue 5

April 2013



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,  
Fareham, Hampshire, United Kingdom, PO15 5RL  
Tel: +44 (0) 1489 558100. Website: [www.tuv-sud.co.uk](http://www.tuv-sud.co.uk)

**REPORT ON**

RF Exposure Assessment of the  
Funk-Electronic Piciorgros GmbH  
TMO-100/DAN Tetra Modem


Document 75915769 Report 03 Issue 5

March 2013

**PREPARED FOR**

Funk-Electronic Piciorgros GmbH  
Clausiatasse 5  
D-51149  
Cologne-Porz  
Germany

**PREPARED BY**

  
**M Whiting**  
Project Manager

**APPROVED BY**

  
**M Jenkins**  
Authorised Signatory

**DATED**

11 April 2013

**This report has been up-issued to Issue 5 to change the Antenna Gain and Duty Cycle**



Product Service

## CONTENTS

Section	Page No
<b>1 REPORT SUMMARY .....</b>	<b>3</b>
1.1 Introduction .....	4
1.2 Brief Summary of Results .....	5
1.3 Product Information .....	5
1.4 Summary .....	7
<b>2 TEST DETAILS .....</b>	<b>8</b>
2.1 Rationale for Assessment of the RF Exposure .....	9
2.2 Defined Limits .....	10
2.3 Establishing Wavelength and 1/4 Wavelength .....	10
2.4 Far Field Calculations .....	11
<b>3 DISCLAIMERS AND COPYRIGHT .....</b>	<b>12</b>
3.1 Disclaimers and Copyright.....	13



Product Service

## **SECTION 1**

### **REPORT SUMMARY**

RF Exposure Assessment of the  
Funk-Electronic Piciorgros GmbH  
TMO-100/DAN Tetra Modem



Product Service

## 1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the Funk-Electronic Piciorgros GmbH TMO-100/DAN Tetra Modem to the requirements of the applied test specifications.

Objective	To perform RF Exposure Assessment to determine the Equipment Under Test's (EUT's) compliance of the applied rules.
Applicant	Funk-Electronic Piciorgros GmbH
Manufacturer	Funk-Electronic Piciorgros GmbH
Manufacturing Description	Tetra Modem
Model Number(s)	TMO-100/DAN
Declared Variants	TMO-100/DA1, TMO-100/DA2, TMO-100/DA3, TMO-100/DA4, TMO-100/DA5, TMO-100/DVI
Test Specification/Issue/Date	EN 62311:2008 OET Bulletin 65 Edition 97-01 August 1997 RSS-102 Issue 5 March 2010 Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard: 2003
Related Document(s)	Council Recommendation 1999/519/EC:1999 FCC CFR 47 Part 1: 2011 FCC CFR 47 Part 2: 2011 Health Canada's Safety Code 6 ARPANSA ICNIRP 1998 National Council on Radiation Protection and Measurements (NRPC) - Report No. 86(1986) EN 50383:2002 IEEE Std C95.1-2005 Australian Standard 2772.2 – 1988



Product Service

## 1.2 BRIEF SUMMARY OF RESULTS

### 1.2.1 General Public Exposure Levels

Antenna Gain (Numeric)	Peak Output Power (mW)	Field	Calculated RF Exposure at 1.9 m (190cm)	General Public Exposure Limit	Application
19.953	5047	S	2.22 W/m <sup>2</sup>	2.280 W/m <sup>2</sup>	ICNIRP
		S	0.222 mW/cm <sup>2</sup>	0.304 mW/cm <sup>2</sup>	FCC 47 CFR § 1.1310
		S	2.22 W/m <sup>2</sup>	3.040 W/m <sup>2</sup>	Canada's RF Safety Code 6
		S	2.22 W/m <sup>2</sup>	2.280 W/m <sup>2</sup>	ARPANSA
		E	28.93 V/m	29.362 V/m	ICNIRP
		E	28.93 V/m	N/A V/m	FCC 47 CFR § 1.1310
		E	28.93 V/m	33.846 V/m	Canada's RF Safety Code 6
		E	28.93 V/m	29.255 V/m	ARPANSA
		H	0.08 A/m	0.079 A/m	ICNIRP
		H	0.08 A/m	N/A A/m	FCC 47 CFR § 1.1310
		H	0.08 A/m	0.090 A/m	Canada's RF Safety Code 6
		H	0.08 A/m	0.078 A/m	ARPANSA

The calculations have shown that they **meet** the General Public Exposure Levels described in the ICNIRP Guidelines, FCC 47 CFR § 1.1310 Guidelines, Health Canada's RF exposure guideline Safety Code 6 and the Australian ARPANSA limits at 190cm, the point of investigation.



Product Service

### 1.2.2 Occupational Exposure Levels

Antenna Gain (Numeric)	Peak Output Power (mW)	Field	Calculated RF Exposure at 1.9 m (190cm)	Occupational Exposure Limit	Application
19.953	5047	S	2.22 W/m <sup>2</sup>	11.400 W/m <sup>2</sup>	ICNIRP
		S	0.222 mW/cm <sup>2</sup>	1.520 mW/cm <sup>2</sup>	FCC 47 CFR § 1.1310
		S	2.22 W/m <sup>2</sup>	15.200 W/m <sup>2</sup>	Canada's RF Safety Code 6
		S	2.22 W/m <sup>2</sup>	11.400 W/m <sup>2</sup>	ARPANSA
		E	28.93 V/m	64.062 V/m	ICNIRP
		E	28.93 V/m	N/A V/m	FCC 47 CFR § 1.1310
		E	28.93 V/m	75.594 V/m	Canada's RF Safety Code 6
		E	28.93 V/m	65.557 V/m	ARPANSA
		H	0.08 A/m	0.171 A/m	ICNIRP
		H	0.08 A/m	N/A A/m	FCC 47 CFR § 1.1310
		H	0.08 A/m	0.201 A/m	Canada's RF Safety Code 6
		H	0.08 A/m	0.174 A/m	ARPANSA

The calculations have shown that they **meet** the Occupational Exposure Levels described in the ICNIRP Guidelines, FCC 47 CFR § 1.1310 Guidelines, Health Canada's RF exposure guideline Safety Code 6 and the Australian ARPANSA limits at **190 cm**, the point of investigation.



Product Service

## 1.3 PRODUCT INFORMATION

### 1.3.1 Attestation

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s).

### 1.3.2 Technical Description

The Equipment under test was a Funk-Electronic Piciorgros GmbH TMO-100/DAN Tetra Modem. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the TMO-100/DAN Tetra Modem to demonstrate compliance with the applied test specification(s) the sample assessed was found to comply with the requirements of the applied rules.

## 1.4 SUMMARY

The RF exposure assessment is based upon the following criteria:

The TMO-100/DAN Tetra Modem operates in the frequency range of 450 – 470 MHz.

Antenna Gain	13 dBi
Radio RF Transmit Power	5 W
Distance	1.9 m (190 cm)
Duty Cycle	100%



Product Service

## **SECTION 2**

### **TEST DETAILS**



Product Service

## 2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields.

The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in EN50383:2002 Clause 5.2; E-field or H-field calculation. The method of calculation used is defined in EN50383:2002; Clause 8.2.2, 8.2.3 and 8.2.4.

The calculated values have been compared with limits provided in the ICNIRP guidelines.

Calculations can be made in three separate regions, based on distance from the antenna. These are called:

- far-field region,
- radiating near-field region,
- reactive near-field region.

The theory that defines these regions is given in EN50383:2002 Annex A.

### Far-field region

As shown in EN50383 Annex A, the far-field calculations are accurate when the distance,  $r$ , from an antenna of length  $D$  to a point of investigation is greater than

$$r = \frac{2D^2}{\lambda}$$

Where,  $r$  is the distance from the antenna to the point of investigation.

### Radiating near-field region

The radiating near-field region of an antenna of length  $D$  as shown in EN50383 Annex A, this region is defined by

$$\frac{\lambda}{4} < r > \frac{2D^2}{\lambda}$$

### Reactive near-field region

The reactive near-field region of an antenna as shown in EN50383 Annex A, this region is defined by

$$r \leq \frac{\lambda}{4}$$

Where,  $r$  is the distance from the antenna to the point of investigation.

Recommend  $\lambda/4$  as the boundary between the radiated near-field and reactive near-field for RF exposure compliance assessment.



Product Service

## 2.2 DEFINED LIMITS

Normative Reference: ICNIRP Advice on Limiting Exposure to Electromagnetic Fields (0-300GHz). Table A4, Reference Levels for General Public Exposure to Time Varying Electric & Magnetic Fields. Vol 15 No.2. 2004. The defined limits are in accordance with 47 CFR § 1.1310 Radiofrequency radiation exposure limits.

Reference levels for general public exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 456 MHz

Power density (W/m <sup>2</sup> )	= 2.280	ICNIRP
Power density (mW/cm <sup>2</sup> )	= 0.304	FCC 47 CFR § 1.1310
Power density (W/m <sup>2</sup> )	= 3.040	Canada's RF Safety Code 6
Power density (W/m <sup>2</sup> )	= 2.280	Australian Radiation Protection Series Publication No. 3
E-Field (Vm-1)	= 29.362	ICNIRP
E-Field (Vm-1)	= N/A	FCC 47 CFR § 1.1310
E-Field (Vm-1)	= 33.846	Canada's RF Safety Code 6
E-Field (Vm-1)	= 29.255	Australian Radiation Protection Series Publication No. 3
H-Field (Am-1)	= 0.079	ICNIRP
H-Field (Am-1)	= N/A	FCC 47 CFR § 1.1310
H-Field (Am-1)	= 0.090	Canada's RF Safety Code 6
H-Field (Am-1)	= 0.078	Australian Radiation Protection Series Publication No. 3

Reference levels for occupational exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 456 MHz

Power density (W/m <sup>2</sup> )	= 11.400	ICNIRP
Power density (mW/cm <sup>2</sup> )	= 1.520	FCC 47 CFR § 1.1310
Power density (W/m <sup>2</sup> )	= 15.200	Canada's RF Safety Code 6
Power density (W/m <sup>2</sup> )	= 11.400	Australian Radiation Protection Series Publication No. 3
E-Field (Vm-1)	= 64.062	ICNIRP
E-Field (Vm-1)	= N/A	FCC 47 CFR § 1.1310
E-Field (Vm-1)	= 75.594	Canada's RF Safety Code 6
E-Field (Vm-1)	= 65.557	Australian Radiation Protection Series Publication No. 3
H-Field (Am-1)	= 0.171	ICNIRP
H-Field (Am-1)	= N/A	FCC 47 CFR § 1.1310
H-Field (Am-1)	= 0.201	Canada's RF Safety Code 6
H-Field (Am-1)	= 0.174	Australian Radiation Protection Series Publication No. 3

## 2.3 ESTABLISHING WAVELENGTH AND 1/4 WAVELENGTH

Frequency (MHz)	$\lambda = \frac{3 \times 10^8}{f}$		$\frac{\lambda}{4}$	
	m	cm	m	cm
456	0.657894736842105	65.7894736842105	0.164473684210526	16.4473684210526
458	0.655021834061135	65.5021834061135	0.163755458515284	16.3755458515284
460	0.652173913043478	65.2173913043478	0.16304347826087	16.304347826087



Product Service

## 2.4 FAR FIELD CALCULATIONS

The following calculations are based on: 13 dBi gain antenna

P = 5.000 (Power (Watts)) or 5000 (Power milliwatts)  
G = 19.953 (Numeric Gain)  
r = 190 (Distance (centimetres)) or 1.9(Distance (meters))

The power flux:

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2} \quad S = 2.22 \text{ W/m}^2$$
$$S = 0.222 \text{ mW/cm}^2$$

The electric field strength:

$$E = \frac{\sqrt{30PG_{(\theta, \phi)}}}{r} \quad E = 28.93 \text{ V/m}$$

The magnetic field strength:

$$H = \frac{E}{\eta_o} \quad H = 0.08 \text{ A/m}$$

The calculations meet the General Public Exposure Levels described in the ICNIRP Guidelines.

The calculations meet the General Public Exposure Levels described in the FCC 47CFR§1.1310.

The calculations meet the General Public Exposure Levels described in the Canada's RF Safety Code 6.

The calculations meet the General Public Exposure Levels described in the Australian Radiation Protection Series Publication No. 3

The calculations meet the Occupational Exposure Levels described in the ICNIRP Guidelines.

The calculations meet the Occupational Exposure Levels described in the FCC 47CFR§1.1310

The calculations meet the Occupational Exposure Levels described in the Canada's RF Safety Code 6

The calculations meet the Occupational Exposure Levels described in the Australian Radiation Protection Series Publication No. 3



Product Service

## **SECTION 3**

### **DISCLAIMERS AND COPYRIGHT**



Product Service

### 3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of  
TÜV SÜD Product Service

© 2013 TÜV SÜD Product Service