



FCC Test Report

FCC ID : TOR-C250
Equipment : 802.11 a/n/ac/ax + b/g/n/ax Access Point
Brand Name : Arista
Model Name : C-250
Applicant : Arista Networks, Inc.
5453 Great America Parkway, Santa Clara, CA 95054
Manufacturer : Arista Networks, Inc.
5453 Great America Parkway, Santa Clara, CA 95054
Standard : 47 CFR FCC Part 15.247

The product was received on May 09, 2019, and testing was started from Jun. 14, 2019 and completed on Jul. 05, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

HISTORY OF THIS TEST REPORT	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Information.....	5
1.2 Testing Applied Standards	8
1.3 Testing Location Information	8
1.4 Measurement Uncertainty	8
2 TEST CONFIGURATION OF EUT.....	9
2.1 Test Condition	9
2.2 Test Channel Mode	9
2.3 The Worst Case Measurement Configuration.....	10
2.4 Support Equipment.....	11
2.5 Test Setup Diagram	12
3 TRANSMITTER TEST RESULT	13
3.1 AC Power-line Conducted Emissions	13
3.2 DTS Bandwidth.....	14
3.3 Maximum Conducted Output Power	15
3.4 Power Spectral Density	17
3.5 Emissions in Non-restricted Frequency Bands	18
3.6 Emissions in Restricted Frequency Bands.....	19
4 TEST EQUIPMENT AND CALIBRATION DATA	22
APPENDIX A. TEST RESULTS OF AC POWER-LINE CONDUCTED EMISSIONS	
APPENDIX B. TEST RESULTS OF DTS BANDWIDTH	
APPENDIX C. TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER	
APPENDIX D. TEST RESULTS OF POWER SPECTRAL DENSITY	
APPENDIX E. TEST RESULTS OF EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	
APPENDIX F. TEST RESULTS OF EMISSIONS IN RESTRICTED FREQUENCY BANDS	
APPENDIX G. TEST PHOTOS	
PHOTOGRAPHS OF EUT V01	



History of this test report

[illegible]

Summary of Test Result

Report Clause	Ref. Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	FCC 15.203
3.1	15.207	AC Power-line Conducted Emissions	PASS	FCC 15.207
3.2	15.247(a)	DTS Bandwidth	PASS	≥500kHz
3.3	15.247(b)	Maximum Conducted Output Power	PASS	Power [dBm]:30
3.4	15.247(e)	Power Spectral Density	PASS	PSD [dBm/3kHz]:8
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	Non-Restricted Bands: >30 dBc
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	Restricted Bands: FCC 15.209

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and explanations:

For 802.11n and 802.11ac, CDD mode and Beamforming mode are presented in power output test item. For other test items, CDD mode is the worst case for final tests after pretesting.

Reviewed by: Jackson Tsai

Report Producer: Amber Chiu

1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-LE(1Mbps)	1.0	1TX

Note:

- ♦ Bluetooth LE uses a GFSK (1Mbps) modulation for DSSS.
- ♦ BWch is the nominal channel bandwidth.

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Support
1	Arista	C-250	PIFA antenna	I-PEX	5G
2	Arista	C-250	PIFA antenna	I-PEX	5G
3	Arista	C-250	PIFA antenna	I-PEX	5G
4	Arista	C-250	PIFA antenna	I-PEX	5G
5	Arista	C-250	PIFA antenna	I-PEX	5G
6	Arista	C-250	PIFA antenna	I-PEX	5G
7	Arista	C-250	PIFA antenna	I-PEX	5G
8	Arista	C-250	PIFA antenna	I-PEX	5G
9	Arista	C-250	PIFA antenna	I-PEX	2.4G
10	Arista	C-250	PIFA antenna	I-PEX	2.4G
11	Arista	C-250	PIFA antenna	I-PEX	2.4G
12	Arista	C-250	PIFA antenna	I-PEX	2.4G
13	Arista	C-250	PIFA antenna	I-PEX	2.4G+5G
14	Arista	C-250	PIFA antenna	I-PEX	2.4G+5G
15	Arista	C-250	PIFA antenna	I-PEX	BT

Ant.	Gain (dBi)				
	Radio 0	Radio 1	Radio 2		Radio 3
	5G	2.4G	2.4G	5G	BT LE
1	5	-	-	-	
2	5	-	-	-	-
3	5	-	-	-	-
4	5	-	-	-	-
5	5	-	-	-	-
6	5	-	-	-	-
7	5	-	-	-	-
8	5	-	-	-	-
9	-	4	-	-	-
10	-	4	-	-	-
11	-	4	-	-	-
12	-	4	-	-	-
13	-	-	3.5	5	-
14	-	-	3.5	5	-
15	-	-	-	-	3.5

For 2.4GHz function:

For IEEE 802.11 b/g/n/ac/ax mode (4TX/4RX)(Radio1)

Ant. 9~ 12 could transmit/receive simultaneously.

For IEEE 802.11 b/g/n mode (2TX/2RX)(Radio2)

Ant. 13 and Ant. 14 could transmit/receive simultaneously.

For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)(Radio 3)

Ant. 15 could transmit/receive simultaneously.

For 5GHz function:

For IEEE 802.11 a/n/ac/ax mode (8TX/8RX)(Radio 0)

Ant. 1~8 could transmit/receive simultaneously.

For IEEE 802.11 a/n/ac/ax mode (4TX/4RX)(Radio 0)

Ant. 1~4 could transmit/receive simultaneously.

For IEEE 802.11 a/n/ac mode (2TX/2RX)(Radio 2)

Ant. 13 and Ant. 14 could transmit/receive simultaneously.

1.1.3 EUT Information

Operational Condition			
EUT Power Type	From AC Adapter		
EUT Function	☒ Point-to-multipoint	☐ Point-to-point	
Type of EUT			
☒	Stand-alone		
☐	Combined (EUT where the radio part is fully integrated within another device)		
	Combined Equipment - Brand Name / Model No.: ...		
☐	Plug-in radio (EUT intended for a variety of host systems)		
	Host System - Brand Name / Model No.: ...		
☐	Other:		

1.1.4 Mode Test Duty Cycle

Mode	DC	DCF(dB)	T(s)	VBW(Hz) ≥ 1/T
BT-LE(1Mbps)	0.621	2.07	405u	3k

Note. If DC < 0.98, the DCF was added while measuring Output power and PSD.

1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013
- ♦ KDB 558074 D01 v05r02

1.3 Testing Location Information

Testing Location			
☒	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
☐	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH06-HY	Tim	21~24°C / 61~66%	14/Jun/2019~ 23/Jun/2019
Radiated	03CH02-HY	Andy	21.6~23.8°C / 52.6~54.8%	15/Jun/2019~ 20/Jun/2019
AC Conduction	CO04-HY	Jeff	21.2~23.2°C / 51.8~53.6%	05/Jul/2019

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.54 dB	Confidence levels of 95%
Radiated Emission (9kHz ~ 30MHz)	1.6 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.9 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.3 dB	Confidence levels of 95%
Temperature	0.7 °C	Confidence levels of 95%
Humidity	4 %	Confidence levels of 95%

2 Test Configuration of EUT

2.1 Test Condition

RF Conducted	Abbreviation	Remark
TnomVnom	Tnom	20°C
-	Vnom	120V

2.2 Test Channel Mode

Test Software Version	QSPR
-----------------------	------

Mode	PowerSetting
BT-LE(1Mbps)	-
2402MHz	8
2440MHz	8
2480MHz	7

2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	CTX
1	Adapter mode; BT LE, Radio 3

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests			
Tests Item	Emissions in Restricted Frequency Bands		
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
Operating Mode < 1GHz	CTX		
1	Adapter mode; BT LE, Radio 3		
Operating Mode > 1GHz	CTX		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Worst Planes of EUT		V	

The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis
Operating Mode	CTX
1	Bluetooth+ WLAN 2.4GHz(Radio 1)+ WLAN 2.4G(Radio 2)+ WLAN 5G(Radio 0)
2	Bluetooth+ WLAN 2.4GHz(Radio 1)+ WLAN 5G(Radio 2)+ WLAN 5G(Radio 0)
Refer to Sporton Test Report No.: FA950730 for Co-location RF Exposure Evaluation.	

2.4 Support Equipment

Support Equipment – AC Conduction				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Load	N/A	N/A	N/A
2	AC adapter	Powertron Electronics Corp	PA1045-120HUB	N/A



Support equipment No.2 was provided by customer.

Support Equipment – RF Conducted				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	E5410	DoC
2	Adapter for NB	DELL	HA65NM130	DoC

Support Equipment – Radiated Emission				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Load	N/A	N/A	N/A
2	AC adapter	Powertron Electronics Corp	PA1045-120HUB	N/A

Support equipment No.2 was provided by customer.

2.5 Test Setup Diagram



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
Refer as ANSI C63.10-2013, clause 6.2 foray power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit	
Systems using digital modulation techniques:	
▪	6 dB bandwidth $\geq$ 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
▪ For the emission bandwidth shall be measured using one of the options below:	
☒	Refer as KDB 558074, clause 8.2 (11.8 of ANSI C63.10) DTS bandwidth measurement.
☐	Refer as RSS-Gen, clause 6.7 for occupied bandwidth testing.
☐	Refer as ANSI C63.10, clause 6.9.3 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	Smart antenna system (SAS):
	- Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
e.i.r.p. Power Limit:	
	2400-2483.5 MHz Band
	Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)
	Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm
	Smart antenna system (SAS)
	- Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	- Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	- Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
Maximum Peak Conducted Output Power	
☐	Refer as KDB 558074, clause 8.3.1.1 (11.9.1.1 of ANSI C63.10) RBW ≥ EBW method.
☐	Refer as KDB 558074, clause 8.3.1.2 (11.9.1.2 of ANSI C63.10) integrated band power method.
☐	Refer as KDB 558074, clause 8.3.1.3 (11.9.1.3 of ANSI C63.10) peak power meter.
Maximum Average Conducted Output Power	
☐	Refer as KDB 558074, clause 8.3.2.2 (11.9.2.2 of ANSI C63.10) using a spectrum analyzer.
☒	Refer as KDB 558074, clause 8.3.2.3 (11.9.2.3 of ANSI C63.10) using a power meter.
For conducted measurement.	
If the EUT supports multiple transmit chains using options given below: Refer as KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.	
If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$	

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C

3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit	
▪	Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
▪	Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
☒	Refer as KDB 558074, clause 8.4 (11.10 of ANSI C63.10) Method PKPSD.
▪	For conducted measurement.
▪	If The EUT supports multiple transmit chains using options given below:
▪	Measure and sum the spectra across the outputs. Refer as KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30
Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak level. Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average level.	


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
Refer as KDB 558074, clause 8.5 (11.11 of ANSI C63.10) for non-restricted frequency bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E

3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.


3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Test Method	
- The average emission levels shall be measured in [duty cycle ≥ 98 or duty factor]. - Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.	For the transmitter unwanted emissions shall be measured using following options below:
	Refer as KDB 558074, clause 8.6 (11.12 of ANSI C63.10) for restricted frequency bands.
For the transmitter band-edge emissions shall be measured using following options below:	Refer as KDB 558074 clause 8.7.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	Refer as KDB 558074, clause 8.7.2 (6.10.6 of ANSI C63.10) for marker-delta method for band-edge measurements.
	Refer as KDB 558074, clause 8.7.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels.
	Use the following spectrum analyzer settings:
	Set RBW=100 kHz for $f < 1$ GHz; VBW=3 * RBW; Sweep = auto; Detector function = peak; Trace = max hold.
	Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement. For average measurement, refer as 1.1.4.

3.6.4 Test Setup





3.6.5 Test Result of Emissions in Restricted Frequency Bands (Below 30MHz)

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.6.6 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F

4 Test Equipment and Calibration Data

Instrument for AC Conduction

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
EMC Receiver	R&S	ESR3	102052	9kHz ~ 3.6GHz	09/Apr/2019	08/Apr/2020
LISN	R&S	ENV216	101295	9kHz ~ 30MHz	08/Nov/2018	07/Nov/2019
RF Cable-CON	MTJ	RG142	CB002-CO	9kHz ~ 200MHz	17/Sep/2018	16/Sep/2019
AC POWER	APC	AFC-11005G	F310050055	47Hz~63Hz 5~300V	NCR	NCR
Impuls Begrenzer Pulse Limiter	SCHWARZBECK	VTSD 9561-F	9561-F041	9 kHz ~ 30 MHz	12/Oct/2018	11/Oct/2019

NCR : Non-Calibration Require

Instrument for Radiated Test

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30MHz ~ 1GHz 3m	19/Oct/2018	18/Oct/2019
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	1GHz ~ 18GHz 3m	17/Oct/2018	16/Oct/2019
Amplifier	Agilent	8447D	2944A11149	100kHz ~ 1.3GHz	27Jul/2018	02/Jul/2019
Amplifier	KEYSIGHT	83017A	MY53270197	1GHz ~ 26.5GHz	30/Nov/2018	29/Nov/2019
Spectrum Analyzer	Rohde & Schwarz	FSP40	100593	9KHz - 40GHz	27/Dec/2018	26/Dec/2019
EMI Test Receiver	R&S	ESR3	102052	9kHz ~ 3.6GHz	09/Apr/2019	08/Apr/2020
RF Cable-R03m	Jye Bao	RG142	CB017	9kHz ~ 1GHz	26/Mar/2019	25/Mar/2020
RF Cable-high 6m	SUHNER	SUCOFLEX104	10567868 / SN805193/4	1GHz~40GHz	9/Apr/2019	8/Apr/2020
RF Cable-high 7m	SUHNER	SUCOFLEX104	10567868 / SN805192/4	1GHz~40GHz	9/Apr/2019	8/Apr/2020
Bilog Antenna & 5dB Attenuator	SCHAFFNER / MTJ	CBL 6112B / MTJ6102-05	2723 / 2	30MHz ~ 1GHz	08/Sep/2018	07/Sep/2019
Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA 9170221	15GHz ~ 40GHz	22/Mar/2019	21/Mar/2020
Loop Antenna	TESEQ	HLA 6120	31244	9k-30MHz	15/Mar/2019	14/Mar/2020
Double Ridged Guide Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 01543	1GHz ~ 18GHz	03/Jun/2019	02/Jun/2020


Instrument for Conducted Test

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Spectrum Analyzer	R&S	FSV 40	101500	10Hz~40GHz	18/Jul/2018	17/Jul/2019
Power Sensor	Anritsu	MA2411B	1339407	300MHz ~ 40GHz	17/Nov/2018	16/Nov/2019
Power Meter	Anritsu	ML2495A	1517010	300MHz ~ 40GHz	17/Nov/2018	16/Nov/2019
Cable 0.2m	HUBER	MY10710/4	RF Cable - 01	30MHz ~18G	10/Jan/2019	09/Jan/2020
Cable 0.2m	HUBER	MY10711/4	RF Cable - 02	30MHz ~18G	10/Jan/2019	09/Jan/2020
Cable 0.5m	HUBER	MY39470/4	RF Cable - 29	30MHz ~18G	10/Jan/2019	09/Jan/2020
SMB100A Signal Generator	R&S	SMB100A03	181147	100kHz~40GHz	12/Nov/2018	10/Nov/2020

AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Neutral
Operating Function	Adapter mode ; BT LE_Radio 3, TX		

05/07/2019




Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)			
QP	150k	58.82	66.00	-7.18	19.48	Neutral	"Worst"	39.34	9.60	0.01	9.87			
AV	150k	41.77	56.00	-14.23	19.48	Neutral	-	22.29	9.60	0.01	9.87			
QP	190.46k	52.33	64.01	-11.68	19.47	Neutral	-	32.86	9.59	0.01	9.87			
AV	190.46k	36.82	54.01	-17.19	19.47	Neutral	-	17.35	9.59	0.01	9.87			
QP	227.818k	44.71	62.52	-17.81	19.47	Neutral	-	25.24	9.59	0.01	9.87			
AV	227.818k	27.49	52.52	-25.03	19.47	Neutral	-	8.02	9.59	0.01	9.87			
QP	283.569k	38.95	60.70	-21.75	19.48	Neutral	-	19.47	9.59	0.01	9.88			
AV	283.569k	24.08	50.70	-26.62	19.48	Neutral	-	4.60	9.59	0.01	9.88			
QP	500k	32.32	56.00	-23.68	19.48	Neutral	-	12.84	9.59	0.01	9.88			
AV	500k	24.92	46.00	-21.08	19.48	Neutral	-	5.44	9.59	0.01	9.88			
QP	2.075M	24.74	56.00	-31.26	19.53	Neutral	-	5.21	9.61	0.03	9.89			
AV	2.075M	19.97	46.00	-26.03	19.53	Neutral	-	0.44	9.61	0.03	9.89			

AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Line
Operating Function	Adapter mode ; BT LE_Radio 3, TX		

05/07/2019



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)			
QP	150k	59.09	66.00	-6.91	19.48	Line	"Worst"	39.61	9.60	0.01	9.87			
AV	150k	41.80	56.00	-14.20	19.48	Line	-	22.32	9.60	0.01	9.87			
QP	190.46k	52.30	64.01	-11.71	19.48	Line	-	32.82	9.60	0.01	9.87			
AV	190.46k	36.94	54.01	-17.07	19.48	Line	-	17.46	9.60	0.01	9.87			
QP	232.398k	44.98	62.37	-17.39	19.48	Line	-	25.50	9.60	0.01	9.87			
AV	232.398k	28.07	52.37	-24.30	19.48	Line	-	8.59	9.60	0.01	9.87			
QP	269.806k	38.10	61.12	-23.02	19.48	Line	-	18.62	9.60	0.01	9.87			
AV	269.806k	21.54	51.12	-29.58	19.48	Line	-	2.06	9.60	0.01	9.87			
QP	495.058k	35.22	56.08	-20.86	19.48	Line	-	15.74	9.59	0.01	9.88			
AV	495.058k	27.31	46.08	-18.77	19.48	Line	-	7.83	9.59	0.01	9.88			
QP	1.013M	29.92	56.00	-26.08	19.50	Line	-	10.42	9.60	0.02	9.88			
AV	1.013M	24.70	46.00	-21.30	19.50	Line	-	5.20	9.60	0.02	9.88			

**Summary**

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	700k	1.027M	1M03F1D	692.5k	1.024M

Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz_TnomVnom	Pass	500k	693.75k	1.027M
2440MHz_TnomVnom	Pass	500k	700k	1.026M
2480MHz_TnomVnom	Pass	500k	692.5k	1.024M


Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

BT-LE(1Mbps)
2402MHz

23/06/2019


BT-LE(1Mbps)
2440MHz

23/06/2019




BT-LE(1Mbps)

2480MHz

EBW

23/06/2019





Summary

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	7.05	0.00507



Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz_TnomVnom	Pass	3.50	6.26	30.00
2440MHz_TnomVnom	Pass	3.50	7.05	30.00
2480MHz_TnomVnom	Pass	3.50	4.81	30.00

DG = Directional Gain; **Port X** = Port X output power



Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-8.19

RBW=3 kHz.



Result

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz_TnomVnom	Pass	3.50	-11.04	8.00
2440MHz_TnomVnom	Pass	3.50	-8.19	8.00
2480MHz_TnomVnom	Pass	3.50	-10.53	8.00

DG = Directional Gain; RBW=3 kHz;


PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; **Port X** = Port X power density;

BT-LE(1Mbps)

PSD

2402MHz

23/06/2019




Sum	PD	Port 1
(dBm/Hz)	(dBm/Hz)	(dBm/Hz)
-11.04	-11.04	-11.04

BT-LE(1Mbps)

PSD

2440MHz

23/06/2019




Sum	PD	Port 1
(dBm/Hz)	(dBm/Hz)	(dBm/Hz)
-8.19	-8.19	-8.19

BT-LE(1Mbps)

PSD

2480MHz

23/06/2019



Sum	PD	Port 1
(dBm/Hz)	(dBm/Hz)	(dBm/Hz)
-10.53	-10.53	-10.53



Summary

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.44008G	7.36	-22.64	2.13663G	-53.81	2.39846G	-53.75	2.48351G	-52.41	16.85538G	-41.84	1



Result


Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.44008G	7.36	-22.64	1.98538G	-54.27	2.39876G	-43.97	2.48487G	-53.11	16.58802G	-43.09	1
2440MHz_TnomVnom	Pass	2.44008G	7.36	-22.64	878.93M	-54.87	2.39937G	-53.16	2.48449G	-53.42	17.47171G	-42.57	1
2480MHz_TnomVnom	Pass	2.44008G	7.36	-22.64	2.13663G	-53.81	2.39846G	-53.75	2.48351G	-52.41	16.85538G	-41.84	1

BT-LE(1Mbps)


CSE NdB

2402MHz

23/06/2019



Port1

RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak


Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44008G	7.36	-22.64	1.98538G	-54.27	2.39876G	-43.97	2.48487G	-53.11	16.58802G	-43.09	1

BT-LE(1Mbps)


CSE NdB

2440MHz

23/06/2019



Port1

RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak

Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44008G	7.36	-22.64	878.93M	-54.87	2.39937G	-53.16	2.48449G	-53.42	17.47171G	-42.57	1



BT-LE(1Mbps)

2480MHz

CSE NdB

23/06/2019

Port1



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak

Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44008G	7.36	-22.64	2.13663G	-53.81	2.39846G	-53.75	2.48351G	-52.41	16.85538G	-41.84	1



Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	QP	600.36M	42.85	46.00	-3.15	-1.03	3	Vertical	96	1.02	-


Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-
2440MHz	Pass	PK	43.58M	36.66	40.00	-3.34	-11.29	3	Vertical	360	1.00	-
2440MHz	Pass	PK	383.08M	33.82	46.00	-12.18	-4.35	3	Vertical	360	1.00	-
2440MHz	Pass	PK	480.08M	34.10	46.00	-11.90	-2.34	3	Vertical	360	1.00	-
2440MHz	Pass	PK	547.98M	34.68	46.00	-11.32	-1.15	3	Vertical	360	1.00	-
2440MHz	Pass	QP	600.36M	42.85	46.00	-3.15	-1.03	3	Vertical	96	1.02	-
2440MHz	Pass	QP	730.34M	39.19	46.00	-6.81	0.50	3	Vertical	146	1.13	-
2440MHz	Pass	PK	39.7M	29.43	40.00	-10.57	-9.61	3	Horizontal	0	1.00	-
2440MHz	Pass	PK	103.72M	28.20	43.50	-15.30	-9.86	3	Horizontal	0	1.00	-
2440MHz	Pass	PK	383.08M	33.58	46.00	-12.42	-4.35	3	Horizontal	0	1.00	-
2440MHz	Pass	PK	480.08M	38.19	46.00	-7.81	-2.34	3	Horizontal	0	1.00	-
2440MHz	Pass	PK	600.36M	42.61	46.00	-3.39	-1.03	3	Horizontal	0	1.00	-
2440MHz	Pass	PK	730.34M	42.29	46.00	-3.71	0.50	3	Horizontal	0	1.00	-

BT-LE(1Mbps)

20/06/2019

2440MHz_Adapter




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	43.58M	36.66	40.00	-3.34	-11.29	3	Vertical	360	1.00	-				
PK	383.08M	33.82	46.00	-12.18	-4.35	3	Vertical	360	1.00	-				
PK	480.08M	34.10	46.00	-11.90	-2.34	3	Vertical	360	1.00	-				
PK	547.98M	34.68	46.00	-11.32	-1.15	3	Vertical	360	1.00	-				
QP	600.36M	42.85	46.00	-3.15	-1.03	3	Vertical	96	1.02	-				
QP	730.34M	39.19	46.00	-6.81	0.50	3	Vertical	146	1.13	-				

BT-LE(1Mbps)

20/06/2019

2440MHz_Adapter



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	39.7M	29.43	40.00	-10.57	-9.61	3	Horizontal	0	1.00	-				
PK	103.72M	28.20	43.50	-15.30	-9.86	3	Horizontal	0	1.00	-				
PK	383.08M	33.58	46.00	-12.42	-4.35	3	Horizontal	0	1.00	-				
PK	480.08M	38.19	46.00	-7.81	-2.34	3	Horizontal	0	1.00	-				
PK	600.36M	42.61	46.00	-3.39	-1.03	3	Horizontal	0	1.00	-				
PK	730.34M	42.29	46.00	-3.71	0.50	3	Horizontal	0	1.00	-				



Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	AV	2.4835G	53.08	54.00	-0.92	32.48	3	Horizontal	44	1.44	-


Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	AV	2.383G	45.87	54.00	-8.13	32.06	3	Vertical	28	1.18	-
2402MHz	Pass	AV	2.4022G	99.35	Inf	-Inf	32.14	3	Vertical	28	1.18	-
2402MHz	Pass	PK	2.389G	56.95	74.00	-17.05	32.09	3	Vertical	28	1.18	-
2402MHz	Pass	PK	2.4024G	100.85	Inf	-Inf	32.14	3	Vertical	28	1.18	-
2402MHz	Pass	AV	2.3588G	45.88	54.00	-8.12	31.96	3	Horizontal	44	1.28	-
2402MHz	Pass	AV	2.402G	102.31	Inf	-Inf	32.14	3	Horizontal	44	1.28	-
2402MHz	Pass	PK	2.3668G	56.61	74.00	-17.39	31.99	3	Horizontal	44	1.28	-
2402MHz	Pass	PK	2.4024G	103.79	Inf	-Inf	32.14	3	Horizontal	44	1.28	-
2402MHz	Pass	AV	4.80424G	33.16	54.00	-20.84	8.35	3	Vertical	0	2.02	-
2402MHz	Pass	PK	4.81312G	45.68	74.00	-28.32	8.37	3	Vertical	0	2.02	-
2402MHz	Pass	AV	4.80496G	33.03	54.00	-20.97	8.35	3	Horizontal	233	1.50	-
2402MHz	Pass	PK	4.7989G	45.27	74.00	-28.73	8.34	3	Horizontal	233	1.50	-
2440MHz	Pass	AV	2.3896G	45.73	54.00	-8.27	32.09	3	Vertical	42	1.16	-
2440MHz	Pass	AV	2.4404G	100.35	Inf	-Inf	32.30	3	Vertical	42	1.16	-
2440MHz	Pass	AV	2.496G	46.24	54.00	-7.76	32.53	3	Vertical	42	1.16	-
2440MHz	Pass	PK	2.3824G	56.91	74.00	-17.09	32.06	3	Vertical	42	1.16	-
2440MHz	Pass	PK	2.44G	102.17	Inf	-Inf	32.30	3	Vertical	42	1.16	-
2440MHz	Pass	PK	2.4908G	57.29	74.00	-16.71	32.51	3	Vertical	42	1.16	-
2440MHz	Pass	AV	2.3628G	45.74	54.00	-8.26	31.98	3	Horizontal	51	1.03	-
2440MHz	Pass	AV	2.44G	103.33	Inf	-Inf	32.30	3	Horizontal	51	1.03	-
2440MHz	Pass	AV	2.4924G	46.22	54.00	-7.78	32.52	3	Horizontal	51	1.03	-
2440MHz	Pass	PK	2.3776G	56.36	74.00	-17.64	32.03	3	Horizontal	51	1.03	-
2440MHz	Pass	PK	2.44G	104.90	Inf	-Inf	32.30	3	Horizontal	51	1.03	-
2440MHz	Pass	PK	2.4892G	56.20	74.00	-17.80	32.50	3	Horizontal	51	1.03	-
2440MHz	Pass	AV	4.87956G	34.06	54.00	-19.94	8.52	3	Vertical	0	2.00	-
2440MHz	Pass	PK	4.88056G	46.02	74.00	-27.98	8.53	3	Vertical	0	2.00	-
2440MHz	Pass	AV	4.87951G	33.98	54.00	-20.02	8.52	3	Horizontal	16	2.85	-
2440MHz	Pass	PK	4.88058G	46.48	74.00	-27.52	8.53	3	Horizontal	16	2.85	-
2480MHz	Pass	AV	2.4802G	98.89	Inf	-Inf	32.46	3	Vertical	35	1.13	-
2480MHz	Pass	AV	2.4835G	51.18	54.00	-2.82	32.48	3	Vertical	35	1.13	-
2480MHz	Pass	PK	2.4798G	100.48	Inf	-Inf	32.46	3	Vertical	35	1.13	-
2480MHz	Pass	PK	2.4835G	58.83	74.00	-15.17	32.48	3	Vertical	35	1.13	-
2480MHz	Pass	AV	2.4802G	101.16	Inf	-Inf	32.46	3	Horizontal	44	1.44	-
2480MHz	Pass	AV	2.4835G	53.08	54.00	-0.92	32.48	3	Horizontal	44	1.44	-
2480MHz	Pass	PK	2.4798G	102.75	Inf	-Inf	32.46	3	Horizontal	44	1.44	-
2480MHz	Pass	PK	2.4835G	60.03	74.00	-13.97	32.48	3	Horizontal	44	1.44	-
2480MHz	Pass	AV	4.96042G	34.57	54.00	-19.43	8.71	3	Vertical	355	1.23	-
2480MHz	Pass	PK	4.96006G	45.68	74.00	-28.32	8.70	3	Vertical	355	1.23	-
2480MHz	Pass	AV	4.9606G	33.88	54.00	-20.12	8.71	3	Horizontal	217	2.93	-
2480MHz	Pass	PK	4.95448G	46.49	74.00	-27.51	8.69	3	Horizontal	217	2.93	-

BT-LE(1Mbps)

20/06/2019

2402MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	2.383G	45.87	54.00	-8.13	32.06	3	Vertical	28	1.18	-				
AV	2.4022G	99.35	Inf	-Inf	32.14	3	Vertical	28	1.18	-				
PK	2.389G	56.95	74.00	-17.05	32.09	3	Vertical	28	1.18	-				
PK	2.4024G	100.85	Inf	-Inf	32.14	3	Vertical	28	1.18	-				

BT-LE(1Mbps)

20/06/2019

2402MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	2.3588G	45.88	54.00	-8.12	31.96	3	Horizontal	44	1.28	-				
AV	2.402G	102.31	Inf	-Inf	32.14	3	Horizontal	44	1.28	-				
PK	2.3668G	56.61	74.00	-17.39	31.99	3	Horizontal	44	1.28	-				
PK	2.4024G	103.79	Inf	-Inf	32.14	3	Horizontal	44	1.28	-				

BT-LE(1Mbps)

20/06/2019

2402MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	4.80424G	33.16	54.00	-20.84	8.35	3	Vertical	0	2.02	-				
PK	4.81312G	45.68	74.00	-28.32	8.37	3	Vertical	0	2.02	-				

BT-LE(1Mbps)

20/06/2019

2402MHz_TX




Type	Freq (Hz)	Level (dBm)	Limit (dBm)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	4.80496G	33.03	54.00	-20.97	8.35	3	Horizontal	233	1.50	-				
PK	4.7989G	45.27	74.00	-28.73	8.34	3	Horizontal	233	1.50	-				

BT-LE(1Mbps)

20/06/2019

2440MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	2.3896G	45.73	54.00	-8.27	32.09	3	Vertical	42	1.16	-				
AV	2.4404G	100.35	Inf	-Inf	32.30	3	Vertical	42	1.16	-				
AV	2.496G	46.24	54.00	-7.76	32.53	3	Vertical	42	1.16	-				
PK	2.3824G	56.91	74.00	-17.09	32.06	3	Vertical	42	1.16	-				
PK	2.44G	102.17	Inf	-Inf	32.30	3	Vertical	42	1.16	-				
PK	2.4908G	57.29	74.00	-16.71	32.51	3	Vertical	42	1.16	-				

BT-LE(1Mbps)

2440MHz_TX

20/06/2019




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	2.3628G	45.74	54.00	-8.26	31.98	3	Horizontal	51	1.03	-				
AV	2.44G	103.33	Inf	-Inf	32.30	3	Horizontal	51	1.03	-				
AV	2.4924G	46.22	54.00	-7.78	32.52	3	Horizontal	51	1.03	-				
PK	2.3776G	56.36	74.00	-17.64	32.03	3	Horizontal	51	1.03	-				
PK	2.44G	104.90	Inf	-Inf	32.30	3	Horizontal	51	1.03	-				
PK	2.4892G	56.20	74.00	-17.80	32.50	3	Horizontal	51	1.03	-				

BT-LE(1Mbps)

20/06/2019

2440MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	4.87956G	34.06	54.00	-19.94	8.52	3	Vertical	0	2.00	-				
PK	4.88056G	46.02	74.00	-27.98	8.53	3	Vertical	0	2.00	-				

BT-LE(1Mbps)

20/06/2019

2440MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	4.87951G	33.98	54.00	-20.02	8.52	3	Horizontal	16	2.85	-				
PK	4.88058G	46.48	74.00	-27.52	8.53	3	Horizontal	16	2.85	-				

BT-LE(1Mbps)

20/06/2019

2480MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	2.4802G	98.89	Inf	-Inf	32.46	3	Vertical	35	1.13	-				
AV	2.4835G	51.18	54.00	-2.82	32.48	3	Vertical	35	1.13	-				
PK	2.4798G	100.48	Inf	-Inf	32.46	3	Vertical	35	1.13	-				
PK	2.4835G	58.83	74.00	-15.17	32.48	3	Vertical	35	1.13	-				

BT-LE(1Mbps)

20/06/2019

2480MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	2.4802G	101.16	Inf	-Inf	32.46	3	Horizontal	44	1.44	-				
AV	2.4835G	53.08	54.00	-0.92	32.48	3	Horizontal	44	1.44	-				
PK	2.4798G	102.75	Inf	-Inf	32.46	3	Horizontal	44	1.44	-				
PK	2.4835G	60.03	74.00	-13.97	32.48	3	Horizontal	44	1.44	-				

BT-LE(1Mbps)

20/06/2019

2480MHz_TX




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	4.96042G	34.57	54.00	-19.43	8.71	3	Vertical	355	1.23	-				
PK	4.96006G	45.68	74.00	-28.32	8.70	3	Vertical	355	1.23	-				

BT-LE(1Mbps)

20/06/2019

2480MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
AV	4.9606G	33.88	54.00	-20.12	8.71	3	Horizontal	217	2.93	-				
PK	4.95448G	46.49	74.00	-27.51	8.69	3	Horizontal	217	2.93	-				