

OPERATIONAL DESCRIPTION

1.1. Product description of the CERTIS 2

CERTIS II

FINGERPRINT READER



GENERAL DESCRIPTION

CERTIS™ is a fingerprint reader. This device offers basically high quality image of fingerprint using TWAIN standard API.



KEY FEATURES

- 500 dpi fingerprint image
- USB 2.0 full speed
- TWAIN compatible API
- User friendly
- Sweeping thermal sensor
- Red/green LED for biometrics operations on the top.
- Plug & Play installation

SPECIFICATIONS

- Size 67 x 49 x 24 mm
- FCC, CE Marking.
- 500 dpi FingerChip™ based imaging system.
- Finger motion speed : 15 cm/s max.
- Operating Power consumption :max 200mA, typical 50 mA
- Operating temperature : 0 – 50° C
- Drivers : Windows 2000 SP3, XP SP1
- API TWAIN : image acquisition

APPLICATION DOMAINS

- Easy logon
- Computer & laptop access
- E mail signature
- ...

Real size

CERTIS IMAGE RANGE

- Certis Image is delivered with a TWAIN driver to perform high quality fingerprint images acquisition to be used with a wide range of biometrics software.
- Certis Image Developer Pack includes a Certis Image reader and a Software Development Kit constituted of a driver, a programmer documentation, an example program (Visual C++ 6.0 or higher) and one year of technical support.
- Certis image is also available in bulk package.

CERTIS BIO RANGE

- Certis Bio is delivered with a biometrics logon and a Windows 2000 & XP compliant driver.
- Certis Bio Developer Pack includes a Certis Bio, a Software Development Kit constituted of drivers Image & Bio with enrollment, verification and identification functionalities, a programmer documentation, an example program (Visual C++ 6.0 or higher) and one year of technical support.
- Certis Bio is also available in bulk package.

BIOMETRICS SUITES (AVAILABLE ON WWW.ORCANTHUS.COM)

- Biometrics secure logon
- Single Sign On
- File encryption

CERTIS is a trademark of id3 Semiconductors. All other trade-names, trademarks and registered trademarks are the property of their respective owners.

1.2. Related Submittal(s) / Grant(s)

All host equipment used in the test configuration are FCC granted, when relevant.

1.3. Tested System Details

The FCC IDs for all equipment, plus description of all cables used in the tested system are:

Trade Mark – Model Number (Serial number)	FCC ID	Description	Cable description
Erreur ! Source du renvoi introuvable. * (sn : Erreur ! Source du renvoi introuvable.)	IGTUAX220MIC	Professional USB Audio Interface	USB cable 1m
COMPAQ Deskpro PIII (Win XP) Sn: 8146FR4Z02GN	DoC	Personal computer	Power cord unshielded. All other cable shielded.
Hewlett Packard P/N:D2846 (sn: JP74001000)	DoC	Monitor	Power cord unshielded. Video cable shielded with ferrites
LOGITEK M-C43 (sn: Sn: B21A70LBUMFOAF)	DZL211146	Mouse	PS2 cable (1.5m)
COMPAQ M/N: KB-9963 (sn: B21A70LBUMFOAF)	DoC	Keyboard	PS2 cable (1.2m)
Hewlett Packard DESKJET 895cxi (sn: MY9761915S)	DoC	Parallel printer	Power cord unshielded. All other cable shielded.
TELEX 700373-000	None	Microphone	Audio cable (2m)

*: Equipment under test.

1.4. Test Methodology

Radiated testing was performed according to the procedures in ANSI C63.4-2003, FCC Part 15 Subpart B.

Radiated testing was performed at an antenna to EUT distance of 3 meters.

During testing, all equipment's and cables were moved relative to each other in order to identify the worst case set-up.

1.5. Test facility

Tests have been performed on May 28th, 2007.

The test facility used to collect all the test data is the **LCIE** facility, located ZI des Blanchisseries, 38500 VOIRON, France.

This test facility has been fully described in a report and accepted by FCC as compliant with the radiated and AC line conducted test site criteria in ANSI C63.4-2003 in a letter dated July 14, 2005 (registration number 94821).

This test facility has also been accredited by COFRAC (French accreditation authority for European union test lab accreditation organization) according to NF EN ISO/IEC 17025, accreditation number 1-1633 as compliant with test site criteria and competence in 47 CFR Part 15/ANSI C63.4 and EN55022/CISPR22 norms for 89/336/EEC European EMC Directive application. All pertinent data for this test facility remains unchanged.