

Report Number: F690501/RF-RTL013309

Page:

1 of

6

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: TQ8-ACB10GHGN

Equipment Under Test : DIGITAL CAR AUDIO SYSTEM

Model Name : ACB10GHGN

Variant Model Names : ACB10GHBB, ACB10GHGL

Applicant : Hyundai Mobis Co., Ltd.

Manufacturer : Hyundai Mobis Co., Ltd.

Date of Receipt : 2018.12.11

Date of Test(s) : 2018.12.11 ~ 2018.12.19

Date of Issue : 2018.12.19

In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Date:

2018.12.19

Murphy Kim

Harim Lee

Technical Manager:

Date:

2018.12.19



Report Number: F690501/RF-RTL013309 Page: 2 of 6

INDEX

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	5



Report Number: F690501/RF-RTL013309 Page: 3 of 6

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Phone No. : +82 31 688 0901 Fax No. : +82 31 688 0921

1.2. Details of applicant

Applicant : Hyundai Mobis Co., Ltd.

Address : 203, Teheran-ro, Gangnam-gu, Seoul, 06141, South Korea

Contact Person : Choe, Seung-Hoon Phone No. : +82 31 260 0098

1.3. Details of manufacturer

Company : Same as applicant Address : Same as applicant

1.4. Description of EUT

Kind of Product	DIGITAL CAR AUDIO SYSTEM	
Model Name	ACB10GHGN	
Variant Model Names	ACB10GHBB, ACB10GHGL	
Power Supply	DC 14.4 V	
Frequency Range	2 402 Mb ~ 2 480 Mb (Bluetooth)	
Modulation Technique	GFSK, π/4DQPSK, 8DPSK	
Number of Channels	79 channels (Bluetooth)	
Antenna Type Pattern Antenna		
Antenna Gain	-0.01 dBi	



Report Number: F690501/RF-RTL013309 Page: 4 of 6

1.5. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL013309	2018.12.19	Initial

1.6. Information of Variant Models

Мо	del Name	HMC PART NO	MOBIS PART NO	вт	RDS	AMP	Language	Freq.
Basic model	ACB10GHGN	96150-R1100	R196150100	0	Х	Internal	English	General
Variant	ACB10GHBB	96150-R1000	R196150000	0	0	Internal	Portuguese	Brazil
model	ACB10GHGL	96150-R1200	R196150200	0	X	Internal	English	Colombia



Report Number: F690501/RF-RTL013309 Page: 5 of 6

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (썐)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (ﷺ)	Average Time			
	(A) Limits for Occupational/Controlled Exposure						
0.3 – 3.0	614	1.63	*100	6			
3.0 – 30	1842/f	4.89/f	*900/f ²	6			
30 – 300	61.4	0.163	1.0	6			
300 – 1 500	-	-	f/300	6			
1 500 – 100 000	-	-	5	6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3 – 1.34	614	1.63	*100	30			
1.34 – 30	824/f	2.19/f	*180/f ²	30			
30 – 300	27.5	0.073	0.2	30			
300 – 1 500	-	-	f/1500	30			
<u>1 500 – 100 000</u>	-	-	1.0	<u>30</u>			

2.1.1. Friis transmission formula: $Pd = (Pout*G)/(4*pi*R^2)$

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Report Number: F690501/RF-RTL013309 Page: 6 of 6

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Bluetooth

- Maximum tune up tolerance

Operating Frequency (酏)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm)	Limits (ﷺ)
2 402 ~ 2 480	4	-0.01	0.000 499	1

Remark:

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 $\,$ cm $\,$ between the radiator and your body.
- The antenna gain of this transmitter is less than $6\,\mathrm{dB}\,i$ and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

- End of the Test Report -