

TEST REPORT

FCC MPE Test for ADB10HSAN
Certification

APPLICANT
HYUNDAI MOBIS CO., LTD.

REPORT NO.
HCT-RF-2004-FI006

DATE OF ISSUE
April 10, 2020

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

<h1>TEST REPORT</h1> <p>FCC MPE Test for ADB10HSAN</p>	REPORT NO. HCT-RF-2004-FI006
	DATE OF ISSUE April 10, 2020
	Additional Model ADB30HSAN, ADB10HSGG, ADB11HSGG, ADB10HSGN, ADB10HSGL, DA350HSGG, ADB10HSMG, ADB10HSEG, ADB20HSFN, ADB10HSEP, ADB11HSEP, ADBC0HSEP, DA350HSEP, ADB10HSUG, ADB10HSRP

Applicant	HYUNDAI MOBIS CO., LTD. 203, Teheran-ro, Gangnam-gu, Seoul, 135-977, South Korea
Eut Type Model Name	Car Audio System ADB10HSAN
FCC ID	TQ8-ADB10HSAN
Date of Receipt	February 18, 2020
Frequency range	2 402 MHz ~ 2 480 MHz (Bluetooth) 2 412 MHz ~ 2 462 MHz (WLAN) 5 180 MHz ~ 5 825 MHz (UNII)

This test results were applied only to the test methods required by the standard.

Tested by
Jeong Ho Kim


(signature)

Technical Manager
Jong Seok Lee


(signature)

HCT CO., LTD.

Soo Chon Lee
SooChun Lee / CEO

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	April 10, 2020	Initial Release

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance

RF Exposure Statement

1. Limit

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

3. RESULTS

3-1. Bluetooth

Average output Power at antenna input terminal	4.00	dBm
Average output Power at antenna input terminal	2.51	mW
Prediction distance	20.00	cm
Prediction frequency	2402 – 2480	MHz
Antenna Gain(typical)	-0.18	dBi
Antenna Gain(numeric)	0.959	-
Power density at prediction frequency(S)	0.0005	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

2.1091

EIRP	3.82 (dBm)
ERP	1.67 (dBm)
ERP	0.001 (W)
ERP Limit	3.00 (W)
MARGIN	33.10 (dB)

3-2. DTS

Average output Power at antenna input terminal	7.00	dBm
Average output Power at antenna input terminal	5.01	mW
Prediction distance	20.00	cm
Prediction frequency	2412 – 2462	MHz
Antenna Gain(typical)	-0.01	dBi
Antenna Gain(numeric)	0.998	-
Power density at prediction frequency(S)	0.0010	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

2.1091

EIRP	6.99 (dBm)
ERP	4.84 (dBm)
ERP	0.003 (W)
ERP Limit	3.00 (W)
MARGIN	29.93 (dB)

3-3. UNII

Average output Power at antenna input terminal	11.00	dBm
Average output Power at antenna input terminal	12.59	mW
Prediction distance	20.00	cm
Prediction frequency	5180 – 5825	MHz
Antenna Gain(typical)	-0.18	dBi
Antenna Gain(numeric)	0.959	-
Power density at prediction frequency(S)	0.0024	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

2.1091

EIRP	10.82 (dBm)
ERP	8.67 (dBm)
ERP	0.007 (W)
ERP Limit	3.00 (W)
MARGIN	26.10 (dB)

3-4. CDMA BC0

Average output Power at antenna input terminal	25.00	dBm
Average output Power at antenna input terminal	316.23	mW
Prediction distance	20.000	cm
Prediction frequency	824-849	MHz
Cable Loss	-1.71	dB
Antenna Gain(typical)	2.680	dBi
Antenna Gain(numeric)	1.854	-
Power density at prediction frequency(S)	0.1166	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.549	mW/cm ²

2.1091

EIRP	27.68 (dBm)
ERP	25.53 (dBm)
ERP	0.36 (W)
ERP Limit	1.50 (W)
MARGIN	6.23 (dB)

3-5. CDMA BC1

Average output Power at antenna input terminal	25.00	dBm
Average output Power at antenna input terminal	316.23	mW
Prediction distance	20.000	cm
Prediction frequency	1850-1910	MHz
Cable Loss	-3.300	dB
Antenna Gain(typical)	2.260	dBi
Antenna Gain(numeric)	1.683	-
Power density at prediction frequency(S)	0.1059	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

2.1091

EIRP	27.26 (dBm)
ERP	25.11 (dBm)
ERP	0.324 (W)
ERP Limit	3.00 (W)
MARGIN	9.66 (dB)

3-6. LTE B4

Average output Power at antenna input terminal	24.00	dBm
Average output Power at antenna input terminal	251.19	mW
Prediction distance	20.000	cm
Prediction frequency	1710-1755	MHz
Cable Loss	-3.300	dB
Antenna Gain(typical)	2.700	dBi
Antenna Gain(numeric)	1.862	-
Power density at prediction frequency(S)	0.0931	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

2.1091

EIRP	26.70 (dBm)
ERP	24.55 (dBm)
ERP	0.285 (W)
ERP Limit	3.00 (W)
MARGIN	10.22 (dB)

3-7. LTE B13

Average output Power at antenna input terminal	24.00	dBm
Average output Power at antenna input terminal	251.19	mW
Prediction distance	20.000	cm
Prediction frequency	777-787	MHz
Cable Loss	-1.710	dB
Antenna Gain(typical)	1.880	dBi
Antenna Gain(numeric)	1.542	-
Power density at prediction frequency(S)	0.0770	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.518	mW/cm ²

2.1091

EIRP	25.88 (dBm)
ERP	23.73 (dBm)
ERP	0.24 (W)
ERP Limit	1.50 (W)
MARGIN	8.03 (dB)

3-8. LTE B5

Average output Power at antenna input terminal	24.00	dBm
Average output Power at antenna input terminal	251.19	mW
Prediction distance	20.000	cm
Prediction frequency	824-849	MHz
Cable Loss	-1.71	dB
Antenna Gain(typical)	2.680	dBi
Antenna Gain(numeric)	1.854	-
Power density at prediction frequency(S)	0.0926	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.549	mW/cm ²

2.1091

EIRP	26.68 (dBm)
ERP	24.53 (dBm)
ERP	0.28 (W)
ERP Limit	1.50 (W)
MARGIN	7.23 (dB)

3-9. LTE B2

Average output Power at antenna input terminal	24.00	dBm
Average output Power at antenna input terminal	251.19	mW
Prediction distance	20.000	cm
Prediction frequency	1850-1910	MHz
Cable Loss	-3.300	dB
Antenna Gain(typical)	2.260	dBi
Antenna Gain(numeric)	1.683	-
Power density at prediction frequency(S)	0.0841	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

2.1091

EIRP	26.26 (dBm)
ERP	24.11 (dBm)
ERP	0.258 (W)
ERP Limit	3.00 (W)
MARGIN	10.66 (dB)

Worst Case: Simultaneous MPE 20cm is

5G WLAN (0.0024) +BT (0.0005) + CDMA BC0 (0.1166 /0.549) + LTE B5 (0.0926/0.549)= 0.3840 < 1