

Report Number: F690501/RF-RTL014546

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: TQ8-ADB20HYAN

Equipment Under Test

: DISPLAY CAR SYSTEM

Model Name

: ADB20HYAN

Variant Model Names

: ADB11GZGG, ADB10GZMG, ADB30HYAN, ADB30HCAN, ADB20HYFN, ADB10HYFL. ADB20HCAN, ADB10GZGG, ADB11GZGG,

ADB10GZMG, ADB10GZGP, ADB10GZGN,

ADB10GZBB

Applicant

: Hyundai Mobis Co., Ltd.

Manufacturer

: Hyundai Mobis Co., Ltd.

Date of Receipt

: 2019.09.23

Date of Test(s)

2019.10.09 ~ 2019.10.30

Date of Issue

2019.11.22

In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Date:

2019.11.22

Page:

10

Jinhyoung Cho

Technical Manager:

Date:

2019.11.22

Jungmin Yang

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014546 Page: 2 of 10

INDEX

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	6



Report Number: F690501/RF-RTL014546 Page: 3 of 10

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

+82 31 688 0901 Telephone **FAX** +82 31 688 0921

1.2. Details of Applicant

Hyundai Mobis Co., Ltd. **Applicant**

Address 203, Teheran-ro, Gangnam-gu, Seoul, South Korea, 135-977

Contact Person : Choe, Seung-hoon Phone No. +82 31 260 0098

1.3. Details of Manufacturer

Same as applicant Company Address Same as applicant

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm × 297 mm)



Report Number: F690501/RF-RTL014546 Page: 4 of 10

1.4. Description of EUT

Kind of Product	DISPLAY CAR SYSTEM				
Model Name	ADB20HYAN				
Variant Model Name	ADB11GZGG, ADB10GZMG, ADB30HYAN, ADB30HCAN, ADB20HYFN, ADB10HYFL, ADB20HCAN, ADB10GZGG, ADB11GZGG, ADB10GZMG, ADB10GZGP, ADB10GZGN, ADB10GZBB				
Power Supply	DC 14.4 V				
Frequency Range	2 402 Mbz ~ 2 480 Mbz (Bluetooth) 2 412 Mbz ~ 2 462 Mbz (11b/g/n_HT20) 5 180 Mbz ~ 5 240 Mbz (Band 1: 11a/n_HT20, 11ac_VHT20) 5 190 Mbz ~ 5 230 Mbz (Band 1: 11n_HT40, 11ac_VHT40) 5 210 Mbz (Band 1: 11ac_VHT80) 5 260 Mbz ~ 5 320 Mbz (Band 2A: 11a/n_HT20, 11ac_VHT20) 5 270 Mbz ~ 5 310 Mbz (Band 2A: 11n_HT40, 11ac_VHT40) 5 290 Mbz (Band 2A: 11ac_VHT80) 5 500 Mbz ~ 5 720 Mbz (Band 2C: 11a/n_HT20, 11ac_VHT20) 5 510 Mbz ~ 5 710 Mbz (Band 2C: 11n_HT40, 11ac_VHT40) 5 530 Mbz ~ 5 690 Mbz (Band 2C: 11ac_VHT80) 5 745 Mbz ~ 5 825 Mbz (Band 3: 11a/n_HT20, 11ac_VHT40) 5 775 Mbz (Band 3: 11ac_VHT80)				
Modulation Technique	DSSS, OFDM, GFSK, π/4DQPSK, 8DPSK				
Number of Channels	79 channels (Bluetooth) 11 channels (11b/g/n_HT20) 4 channels (Band 1: 11a/n_HT20, 11ac_VHT20) 2 channels (Band 1: 11n_HT40, 11ac_VHT40) 1 channel (Band 1: 11ac_VHT80) 4 channels (Band 2A: 11a/n_HT20, 11ac_VHT20) 2 channels (Band 2A: 11n_HT40, 11ac_VHT40) 1 channel (Band 2A: 11ac_VHT80) 9 channels (Band 2C: 11a/n_HT20, 11ac_VHT20) 4 channels (Band 2C: 11a/n_HT20, 11ac_VHT40) 2 channels (Band 2C: 11ac_VHT80) 5 channels (Band 3: 11a/n_HT20, 11ac_VHT20) 2 channels (Band 3: 11a/n_HT40, 11ac_VHT40) 1 channel (Band 3: 11ac_VHT80)				
Antenna Type	Pattern antenna				
Antenna Gain	2 400 Mb ~ 2 483.5 Mb: -0.18 dB i (Bluetooth) 2 400 Mb ~ 2 483.5 Mb: -0.01 dB i (WLAN 2.4 G) 5 150 Mb ~ 5 250 Mb: -0.61 dB i (WLAN 5G) 5 250 Mb ~ 5 350 Mb: -0.18 dB i (WLAN 5G) 5 470 Mb ~ 5 725 Mb: -0.77 dB i (WLAN 5G) 5 725 Mb ~ 5 850 Mb: -0.18 dB i (WLAN 5G)				

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 http://www.sgsgroup.kr



Report Number: F690501/RF-RTL014546 Page: 5 of 10

1.5. Information of Variant Models

			Description								
ľ	Model I	Names	LOCAL	BT/WiFi	UI	RDS	DAB	SXM	HD	HANDLE	FM/AM Code
Basic Model	FCC	ADB20HYAN	U.S.A	BT, WiFi	GEN	X	Χ	Χ	0	LHD	A2
		ADB11GZGG	GEN	ВТ	GEN	0	Χ	Х	X	RHD	A1
		ADB10GZMG	Mid East	ВТ	GEN	0	Х	Х	Х	LHD	A1
		ADB20HYFN	MEXICO	BT, WiFi	GEN	0	Х	Х	0	LHD	A2
		ADB10HYFL	Colombia	BT, WiFi	GEN	Χ	Χ	Х	Х	LHD	A5
		ADB20HCAN	U.S.A	BT, WiFi	HEV	Х	Х	Х	0	LHD	A2
		ADB10GZGG	GEN	BT, WiFi	GEN	Χ	Х	Х	Х	LHD	A1
Variant Models	FCC	ADB11GZGG	GEN	BT, WiFi	GEN	0	Х	Х	Х	RHD	A1
		ADB10GZMG	Mid East	BT, WiFi	GEN	0	Х	Х	Х	LHD	A1
		ADB10GZGP	GEN	BT, WiFi	GEN	Х	Х	Х	Х	LHD	A8
		ADB10GZGN	GEN	BT, WiFi	GEN	Χ	Х	Х	Χ	LHD	A2
		ADB10GZBB	Brazil	BT, WiFi	GEN	Х	Х	Х	Х	LHD	A7
		ADB30HYAN	U.S.A	BT, WiFi, Tele	GEN	Х	Х	0	0	LHD	A2
		ADB30HCAN	U.S.A	BT, WiFi, Tele	HEV	Х	Х	0	0	LHD	A2

BAND	CODE	FREQUENCY RANGE	STEP	LOCAL	CODE	FREQUENCY RANGE	STEP	LOCAL																			
FM	A1	87.5-108.0 MHz	100 kHz	DOM/GEN	A5	87.5-107.9 MHz	100 kHz	COLOMBIA																			
AM	AI	531-1602 kHz	9 kHz		DOIVI/GEN	DOW/GEN	DOM/GEN	AS	530-1710 kHz	10 kHz	COLOIVIBIA																
FM	A2	87.5-107.9 MHz	200 kHz	NA/GEN	NA/GEN	NA/GEN		A6	87.5-107.9 MHz	200 kHz	GUAM																
AM	A2	530-1710 kHz	10 kHz					NA/GEN	NA/GEN	NA/GEN	NA/OLIV	NAGEN	NAGLIN	NA/GEN	NA OLIV	NVOLIV	NOCEN	IW VOLIN		INA/GEN		10 V OLIV	TWVOLIN			TWVOEN	1000011
FM	A3	87.5-108.0 MHz	50 kHz	EU	F11	-	A7	76.1-107.9 MHz	100 kHz	BRAZIL																	
AM	AS	522-1620 kHz	9 kHz		A	530-1710 kHz	10 kHz	DRAZIL																			
FM	A4	76.0~90.0 MHz	100 kHz	IADAN		A8	87.5-108.0 MHz	100 kHz	EU																		
AM	A4	522~1629 KHz	9 kHz	JAPAN	Ao	522-1620 kHz	9 kHz	EU																			

1.6. Test Report Revision

Revision	Report Number	Date of Issue	Description
0	F690501/RF-RTL014546	2019.11.22	Initial

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 http://www.sgsgroup.kr



Report Number: F690501/RF-RTL014546 Page: 6 of 10

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (쌘)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm)	Average Time			
(A) Limits for Occupational/Controlled Exposure							
0.3-3.0	0.3-3.0 614 1.63 *100						
3.0-30	1842/f	4.89/f	*900/f ²	6			
30-300	61.4	0.163	1.0	6			
300-1 500	-	-	f/300	6			
1 500-100 000	-	-	5	6			
	(B) Limits for Ger	neral Population/Unco	ntrolled Exposure				
0.3-1.34	614	1.63	*100	30			
1.34-30	824/f	2.19/f	*180/f ²	30			
30-300	27.5	0.073	0.2	30			
<u>300-1 500</u>	-	-	<u>f/1500</u>	<u>30</u>			
1 500-100 000	-	-	1.0	<u>30</u>			

2.1.1. Friis transmission formula: $Pd = (Pout*G)/(4*pi*R^2)$

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014546 Page: 7 of 10

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode: Normal Operation

2.1.3. Test information of Cable Loss and Antenna Gain

Test Item	Frequency (MHz)	Cable Loss (dB)	Antenna Gain (dB i)	Final Antenna Gain (dB i)
CDMA - BC0	824 ~ 849	-1.79	0.89	-0.90
CDMA - BC1	1 850 ~ 1 910	-2.62	2.92	0.30
LTE - Band 2	1 850 ~ 1 910	-2.62	2.92	0.30
LTE - Band 4	1 710 ~ 1 755	-2.62	1.81	-0.81
LTE - Band 5	824 ~ 849	-1.79	0.89	-0.90
LTE - Band 13	777 ~ 787	-1.79	0.42	-1.37

Note;

- Final Antenna Gain (dBi) = Cable Loss (dB) + Antenna Gain (dBi)



Report Number: F690501/RF-RTL014546 Page: 8 of 10

2.1.4. Output Power into Antenna & RF Exposure Evaluation Distance

Bluetooth

- Maximum tune up tolerance

Frequency (脈)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (ﷺ/ﷺ)	Limits (nW/cn²)
2 402 ~ 2 480	4	-0.18	0.000 479	1

WLAN (2.4G)

- Maximum tune up tolerance

Frequency (飐)	Power to Antenna		Power Density at 20 cm (ﷺ/ﷺ)	Limits (mW/cm²)
2 412 ~ 2 462	12	-0.01	0.003 146	1

WLAN (5G)

- Maximum tune up tolerance

Frequency (쌘)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (㎡/c㎡)	Limits (mW/cm²)
5 180 ~ 5 240	9	-0.61	0.001 373	1
5 260 ~ 5 320	9	-0.18	0.001 516	1
5 500 ~ 5 720	9	-0.77	0.001 324	1
5 745 ~ 5 825	9	-0.18	0.001 516	1

CDMA - BC0

- Maximum Tune Up Tolerance

Frequency Range (썐)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (㎡/c㎡)	Limits (ﷺ)
824 ~ 849	25.7	-0.90	0.060 080	0.55

CDMA - BC1

- Maximum Tune Up Tolerance

Frequency Range (싼)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (㎡/c㎡)	Limits (nW/cn²)
1 850 ~ 1 910	25.7	0.30	0.079 201	1

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL014546 Page: 9 of 10

LTE - Band 2

- Maximum Tune Up Tolerance

Frequency Range (싼)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (₪/c㎡)	Limits (mW/cm²)
1 850 ~ 1 910	25.7	0.30	0.079 201	1

LTE - Band 4

- Maximum Tune Up Tolerance

Frequency Range (싼)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (㎡/c㎡)	Limits (nW/cn²)
1 710 ~ 1 755	25.7	-0.81	0.061 338	1

LTE - Band 5

- Maximum Tune Up Tolerance

Frequency Range (싼)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (₪/cᡤ)	Limits (ﷺ)
824 ~ 849	25.7	-0.90	0.060 080	0.55

LTE - Band 13

- Maximum Tune Up Tolerance

Frequency Range (船)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (₪/cπ/)	Limits (mW/cm²)
777 ~ 787	25.7	-1.37	0.053 918	0.52

Note;

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 cm between the radiator and your body.
- The antenna gain of this transmitter is less than $6\,\mathrm{dB}\,\mathrm{i}$ and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.



Report Number: F690501/RF-RTL014546 Page: 10 of 10

Simultaneous transmission of RF Exposure test exclusion for worst case configuration.

Bluetooth: the ratio is 0.000 479 / 1 WLAN: the ratio is 0.003 146 / 1 WWLAN: the ratio is 0.060 080 / 0.55

Confirm the sum result of individual MPEs ratio is ≤ 1.0;

Bluetooth + WLAN + WWLAN: (0.000 479 / 1) + (0.003 146 / 1) + (0.060 080 / 0.55)

= 0.112 861 ≤ 1.0

- End of the Test Report -