

# TEST REPORT

FCC/IC DTS Test for ADB25SNAN&ADB25SNKN  
Certification

**APPLICANT**  
HYUNDAI MOBIS CO., LTD.

**REPORT NO.**  
HCT-RF-1908-FI027

**DATE OF ISSUE**  
August 14, 2019

**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 Fax. +82 31 645 6401



REPORT NO.  
HCT-RF-1908-FI027

DATE OF ISSUE  
August 14, 2019

Other Model  
FCC: ADB15SNAU

Applicant **HYUNDAI MOBIS CO., LTD.**  
203, Teheran-ro, Gangnam-gu, Seoul, 135-977, South Korea

|                      |   |
|----------------------|---|
| Eut Type             | Car Audio System  |
| FCC Model Name       | ADB25SNAN   |
| IC Model Name        | ADB25SNKN   |
| FCC ID               | TQ8-ADB25SNAN   |
| IC                   | 5074A-ADB25SNKN   |
| Max. RF Output Power | 802.11b : 15.66 dBm / 802.11g : 17.66 dBm / 802.11n(HT20) : 18.05 dBm |
| Modulation type      | CCK/DSSS/OFDM   |
| FCC Classification   | Digital Transmission System(DTS)                                      |
| FCC Rule Part(s)     | Part 15.247   |
| ISED Rule Part(s)    | RSS-247 Issue 2 (February 2017), RSS-Gen Issue 5(April 2018)          |

This test results were applied only to the test methods required by the standard.

Tested by  
Se Wook Park

(signature)

Technical Manager  
Jong Seok Lee

(signature)

HCT CO., LTD.

*Soo Chan Lee*  
SooChan Lee / CEO

## REVISION HISTORY

The revision history for this test report is shown in table.

| Revision No. | Date of Issue   | Description     |
|--------------|-----------------|-----------------|
| 0            | August 14, 2019 | Initial Release |

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

### Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC / IC Rules under normal use and maintenance.

## CONTENTS

|  |    |
|--|----|
| 1. EUT DESCRIPTION   | 5  |
| 2. TEST METHODOLOGY  | 6  |
| EUT CONFIGURATION  | 6  |
| EUT EXERCISE   | 6  |
| GENERAL TEST PROCEDURES  | 6  |
| DESCRIPTION OF TEST MODES  | 7  |
| 3. INSTRUMENT CALIBRATION  | 7  |
| 4. FACILITIES AND ACCREDITATIONS   | 7  |
| FACILITIES   | 7  |
| EQUIPMENT  | 7  |
| 5. ANTENNA REQUIREMENTS  | 8  |
| 6. MEASUREMENT UNCERTAINTY   | 8  |
| 7. DESCRIPTION OF TESTS  | 9  |
| 7.1. Duty Cycle  | 9  |
| 7.2. 6dB Bandwidth & 99 % Bandwidth  | 10 |
| 7.3. Output Power  | 11 |
| 7.4. Power Spectral Density  | 12 |
| 7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions | 13 |
| 7.6. Radiated Test   | 15 |
| 7.7. AC Power line Conducted Emissions   | 23 |
| 7.8. Receiver Spurious Emissions   | 24 |
| 7.9. Worst case configuration and mode   | 27 |
| 8. SUMMARY TEST OF RESULTS   | 28 |
| 9. TEST RESULT   | 30 |
| 9.1 DUTY CYCLE   | 30 |
| 9.2 6dB BANDWIDTH & 99 % BANDWIDTH   | 33 |
| 9.3 OUTPUT POWER   | 39 |
| 9.4 POWER SPECTRAL DENSITY   | 45 |
| 9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS                                    | 48 |
| 9.6 RADIATED SPURIOUS EMISSIONS  | 59 |
| 9.7 RADIATED RESTRICTED BAND EDGES   | 69 |
| 10. LIST OF TEST EQUIPMENT   | 72 |
| 11. ANNEX A_ TEST SETUP PHOTO  | 74 |

## 1. EUT DESCRIPTION

|   |  |
|---|--|
| FCC Model   | ADB25SNAN  |
| IC Model  | ADB25SNKN  |
| FCC Additional Model                                | ADB15SNAU  |
| EUT Type  | Car Audio System   |
| Power Supply  | DC 14.4 V  |
| Frequency Range                                     | 2412 MHz - 2462 MHz  |
| Max. RF Output Power                                | <b>Peak Power</b><br>802.11b : 15.66 dBm<br>802.11g : 17.66 dBm<br>802.11n(HT20) : 18.05 dBm<br><b>Average Power</b><br>802.11b : 9.64 dBm<br>802.11g : 9.47 dBm<br>802.11n(HT20) : 9.07 dBm |
| Modulation Type                                     | DSSS/CCK : 802.11b<br>OFDM : 802.11g, 802.11n  |
| Number of Channels                                  | 11 Channels  |
| Antenna Specification                               | Antenna type: Pattern Antenna<br>Peak Gain : -0.01 dBi   |
| Date(s) of Tests                                    | July 04, 2019~ August 14, 2019   |
| PMN<br>(Product Marketing Number)                   | ADB25SNKN  |
| HVIN<br>(Hardware Version<br>Identification Number) | ADB25SNKN  |
| FVIN<br>(Firmware Version<br>Identification Number) | N/A  |
| HMN<br>(Host Marketing Name)                        | N/A  |

## 2. TEST METHODOLOGY

FCC KDB 558074 D01 15.247 Meas Guidance v05r02 dated April 02, 2019 entitled “guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10(Version : 2013) ‘the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices’.

### EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

### GENERAL TEST PROCEDURES

#### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

#### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013)

## DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

## 3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

## 4. FACILITIES AND ACCREDITATIONS

### FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

**For ISED, test facility was accepted dated February 14, 2019 (CAB identifier: KR0032).**

### EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 5. ANTENNA REQUIREMENTS

### According to FCC 47 CFR § 15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

\* The antennas of this E.U.T are permanently attached.

\* The E.U.T Complies with the requirement of § 15.203

## 6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of

ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicate a 95 % level of confidence.

The measurement data shown herein meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.


| Parameter                                | Expanded Uncertainty ( $\pm$ dB) |
|--|----------------------------------|
| Conducted Disturbance (150 kHz ~ 30 MHz) | 1.82                             |
| Radiated Disturbance (9 kHz ~ 30 MHz)    | 3.40                             |
| Radiated Disturbance (30 MHz ~ 1 GHz)    | 4.80                             |
| Radiated Disturbance (1 GHz ~ 18 GHz)    | 5.70                             |
| Radiated Disturbance (18 GHz ~ 40 GHz)   | 5.05                             |



## 7. DESCRIPTION OF TESTS

### 7.1. Duty Cycle

#### Test Configuration



#### Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to the zero-span measurement method.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if  $T \leq 6.25$  microseconds. ( $50/6.25 = 8$ )

The zero-span method was used because all measured T data are  $> 6.25$  microseconds and both RBW and VBW are  $> 50/T$ .


1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz ( $\geq$  RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep  $> 100$
6. Trace mode = Clear write
7. Measure  $T_{total}$  and  $T_{on}$
8. Calculate Duty Cycle =  $T_{on}/T_{total}$  and Duty Cycle Factor =  $10 \cdot \log(1/\text{Duty Cycle})$

## 7.2. 6dB Bandwidth & 99 % Bandwidth

### Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

### Test Configuration



### Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 8.2 in KDB 558074 v05r01,

Procedure 11.8.1 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW  $\geq$  3 x RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize
- 7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.

### Test Procedure (99 % Bandwidth for IC)

The transmitter output is connected to the spectrum analyzer.

RBW = 1% ~ 5% of the occupied bandwidth

VBW  $\approx$  3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize


Note : We tested OBW using the automatic bandwidth measurement capability of a spectrum analyzer.

### 7.3. Output Power

#### Limit

The maximum permissible conducted output power is 1 Watt.

#### Test Configuration



#### Test Procedure

The transmitter output is connected to the Power Meter.

- Peak Power (Procedure 11.9.1.3 in ANSI 63.10-2013)  
: Measure the peak power of the transmitter.
  
- Average Power (Procedure 11.9.2.3 in ANSI 63.10-2013)
  - 1) Measure the duty cycle.
  - 2) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
  - 3) Add  $10 \log(1/x)$ , where  $x$  is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

#### Sample Calculation


- Conducted Output Power(Peak) = Reading Value + ATT loss + Cable loss
- Conducted Output Power(Average) = Reading Value + ATT loss + Cable loss + Duty Cycle Factor

## 7.4. Power Spectral Density

### Limit

The transmitter power density average over 1-second interval shall not be greater than 8dBm in any 3kHz BW.

### Test Configuration



### Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to Procedure 8.4 in KDB 558074 v05r02, Procedure 11.10 in ANSI 63.10-2013.

The spectrum analyzer is set to :

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set span to at least 1.5 times the OBW.
- 3)  $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$ .
- 4)  $VBW \geq 3 \times RBW$ .
- 5) Sweep = auto couple
- 6) Detector = power averaging (rms) or sample detector (when rms not available).
- 7) Ensure that the number of measurement points in the sweep  $\geq [2 \times \text{span} / RBW]$ .
- 8) Employ trace averaging (rms) mode over a minimum of 100 traces
- 9) Use the peak marker function to determine the maximum amplitude level.
- 10) Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### Sample Calculation

- Power Spectral Density = Reading Value + ATT loss + Cable loss

## 7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions


### Limit

The maximum conducted (Average) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least

30 dB relative to the maximum in-band peak PSD level in 100 kHz.

[ Conducted > 20 dBc ]

### Test Configuration



### Test Procedure

The transmitter output is connected to the spectrum analyzer.

(Procedure 11.11 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW  $\geq 3 \times$  RBW
- 3) Set span to encompass the spectrum to be examined
- 4) Detector = Peak
- 5) Trace Mode = max hold
- 6) Sweep time = auto couple
- 7) Ensure that the number of measurement points  $\geq 2 \times$  Span/RBW
- 8) Allow trace to fully stabilize.
- 9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

**Factors for frequency**

| Freq(MHz) | Factor(dB) |
|-----------|------------|
| 30        | 21.17      |
| 100       | 19.7       |
| 200       | 20.06      |
| 300       | 20         |
| 400       | 20.1       |
| 500       | 20.12      |
| 600       | 20.19      |
| 700       | 20.22      |
| 800       | 20.22      |
| 900       | 20.21      |
| 1000      | 20.26      |
| 2000      | 20.51      |
| 2400*     | 21.52      |
| 2500*     | 21.54      |
| 3000      | 21.55      |
| 4000      | 21.76      |
| 5000      | 21.94      |
| 6000      | 21.93      |
| 7000      | 22.22      |
| 8000      | 22.19      |
| 9000      | 22.35      |
| 10000     | 22.43      |
| 11000     | 22.43      |
| 12000     | 22.55      |
| 13000     | 22.7       |
| 14000     | 22.77      |
| 15000     | 22.85      |
| 16000     | 22.91      |
| 17000     | 22.89      |
| 18000     | 22.95      |
| 19000     | 22.94      |
| 20000     | 23.01      |
| 21000     | 23.04      |
| 22000     | 23.18      |
| 23000     | 23.47      |
| 24000     | 23.21      |
| 25000     | 23.4       |
| 26000     | 23.89      |

Note : 1. ‘\*’ is fundamental frequency range.  
 2. Factor = Attenuator loss + Cable loss

## 7.6. Radiated Test

### Limit

#### FCC

| Frequency (MHz) | Field Strength (uV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 0.009 – 0.490   | 2400/F(kHz)           | 300                      |
| 0.490 – 1.705   | 24000/F(kHz)          | 30                       |
| 1.705 – 30      | 30                    | 30                       |

#### IC


| Frequency (MHz) | Field Strength (uA/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 0.009 – 0.490   | 6.37/F(kHz)           | 300                      |
| 0.490 – 1.705   | 63.7/F(kHz)           | 30                       |
| 1.705 – 30      | 0.08                  | 30                       |

#### FCC&IC


| Frequency (MHz) | Field Strength (uV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 30-88           | 100                   | 3                        |
| 88-216          | 150                   | 3                        |
| 216-960         | 200                   | 3                        |
| Above 960       | 500                   | 3                        |

## Test Configuration

Below 30 MHz




30 MHz - 1 GHz





Above 1 GHz



### Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) =  $40 \cdot \log(3 \text{ m}/300 \text{ m}) = - 80 \text{ dB}$   
Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) =  $40 \cdot \log(3 \text{ m}/30 \text{ m}) = - 40 \text{ dB}$   
Measurement Distance : 3 m
8. Spectrum Setting
  - Frequency Range = 9 kHz ~ 30 MHz
  - Detector = Peak
  - Trace = Maxhold
  - RBW = 9 kHz
  - VBW  $\geq 3 \cdot$ RBW
9. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

### **KDB 414788 OFS and Chamber Correlation Justification**

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

(Worst case: semi-anechoic chamber(10 m chamber))

### **Test Procedure of Radiated spurious emissions(Below 1GHz)**

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

#### 5. Spectrum Setting

##### (1) Measurement Type(Peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 100 kHz
- VBW  $\geq$  3\*RBW

##### (2) Measurement Type(Quasi-peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

\*In general, (1) is used mainly

6. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)

### **Test Procedure of Radiated spurious emissions (Above 1 GHz)**

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).  
\*Distance extrapolation factor =  $20 \cdot \log(\text{test distance} / \text{specific distance})$  (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting (Method 8.6 in KDB 558074 v05r02, Procedure 11.12 in ANSI 63.10-2013)

(1) Measurement Type(Peak):

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW  $\geq 3 \cdot$ RBW

(2) Measurement Type(Average): Duty cycle  $\geq 98\%$

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW  $\geq 3 \cdot$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

(3) Measurement Type(Average): Duty cycle  $< 98\%$ , duty cycle variations are less than  $\pm 2\%$

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz

- $VBW \geq 3 \cdot RBW$
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle  $\geq$  98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle < 98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)  
+ Duty Cycle Factor

### Test Procedure of Radiated Restricted Band Edge

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).  
\*Distance extrapolation factor =  $20 \cdot \log(\text{test distance} / \text{specific distance})$  (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.

#### 9. Spectrum Setting

##### (1) Measurement Type(Peak):

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW  $\geq 3 \cdot$ RBW

##### (2) Measurement Type(Average): Duty cycle $\geq 98\%$ ,

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW  $\geq 3 \cdot$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

##### (3) Measurement Type(Average): Duty cycle $< 98\%$ , duty cycle variations are less than $\pm 2\%$

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW  $\geq 3 \cdot$ RBW

- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle  $\geq$  98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle < 98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

+ Duty Cycle Factor

## 7.7. AC Power line Conducted Emissions

### Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN).

| Frequency Range (MHz) | Limits (dB $\mu$ V) |           |
|-----------------------|---------------------|-----------|
|                       | Quasi-peak          | Average   |
| 0.15 to 0.50          | 66 to 56*           | 56 to 46* |
| 0.50 to 5             | 56                  | 46        |
| 5 to 30               | 60                  | 50        |

\*Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

### Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

### Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

## 7.8. Receiver Spurious Emissions

### Limit

| Frequency (MHz) | Field Strength (uV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 30-88           | 100                   | 3                        |
| 88-216          | 150                   | 3                        |
| 216-960         | 200                   | 3                        |
| Above 960       | 500                   | 3                        |


Note:

Measurements for compliance with the limits in table may be performed at distances other than 3 meters.




### Test Configuration

30 MHz - 1 GHz



Above 1 GHz



### **Test Procedure of Radiated spurious emissions (Above 1 GHz)**

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).  
\*Distance extrapolation factor =  $20 \cdot \log(\text{test distance} / \text{specific distance})$  (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting
  - (1) Measurement Type(Peak):
    - Measured Frequency Range : 1 GHz – 25 GHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 3 \cdot$ RBW
  - (2) Measurement Type(Average):
    - We performed using a reduced video BW method was done with the analyzer in linear mode
    - Measured Frequency Range : 1 GHz – 25 GHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds
    - The actual setting value of VBW = 1 kHz
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
11. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

## 7.9. Worst case configuration and mode

### Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.
  - Mode : Stand alone
  - Worstcase : Stand alone
2. EUT Axis
  - Radiated Spurious Emissions : X
  - Radiated Restricted Band Edge : X
3. Duty cycle factor applies only 802.11g/n(Duty cycle < 98%).
4. All data rate of operation were investigated and the test results are worst case in lowest datarate of each mode.
  - 802.11b : 1Mbps
  - 802.11g : 6Mbps
  - 802.11n\_HT20 : MCS0

### AC Power line Conducted Emissions

We don't perform powerline conducted emission test. Because this EUT is used with vehicle

### Conducted test

1. The EUT was configured with data rate of highest power.

\*

## 8. SUMMARY TEST OF RESULTS

### FCC Part

| Test Description                    | FCC Part Section(s)               | Test Limit           | Test Condition | Test Result |
|-------------------------------------|-----------------------------------|----------------------|----------------|-------------|
| 6 dB Bandwidth                      | § 15.247(a)(2)                    | > 500 kHz            | Conducted      | PASS        |
| Conducted Maximum Peak Output Power | § 15.247(b)(3)                    | < 1 Watt             |                | PASS        |
| Power Spectral Density              | § 15.247(e)                       | < 8 dBm / 3 kHz Band |                | PASS        |
| Band Edge (Out of Band Emissions)   | § 15.247(d)                       | Conducted > 30 dBc   |                | PASS        |
| AC Power line Conducted Emissions   | § 15.207                          | cf. Section 7.7      |                | N/A         |
| Radiated Spurious Emissions         | § 15.247(d),<br>15.205,<br>15.209 | cf. Section 7.6      | Radiated       | PASS        |
| Radiated Restricted Band Edge       | § 15.247(d),<br>15.205,<br>15.209 | cf. Section 7.6      |                | PASS        |

**IC Part**

| Test Description                                 | IC Part Section(s) | Test Limit                    | Test Condition | Test Result |
|--|--------------------|-------------------------------|----------------|-------------|
| 6 dB Bandwidth                                   | RSS-247, 5.2       | > 500 kHz                     | Conducted      | PASS        |
| 99% Bandwidth                                    | RSS-GEN, 6.7       | N/A                           |                | PASS        |
| Conducted Maximum Peak Output Power And e.i.r.p. | RSS-247, 5.4.      | < 1 Watt<br><4 Watt(e.i.r.p.) |                | PASS        |
| Power Spectral Density                           | RSS-247, 5.2       | < 8 dBm / 3 kHz Band          |                | PASS        |
| Band Edge(Out of Band Emissions)                 | RSS-247, 5.5       | Conducted > 30 dBc            |                | PASS        |
| AC Power line Conducted Emissions                | RSS-GEN, 8.8       | cf. Section 7.7               |                | N/A         |
| Radiated Spurious Emissions                      | RSS-GEN, 8.9       | cf. Section 7.6               |                | Radiated    |
| Receiver Spurious Emissions                      | RSS-GEN, 7         | cf. Section 7.8               | PASS           |             |
| Radiated Restricted Band Edge                    | RSS-GEN, 8.10      | cf. Section 7.6               | PASS           |             |


## 9. TEST RESULT

### 9.1 DUTY CYCLE


| Mode              | Data Rate (Mbps) | T <sub>on</sub> (ms) | T <sub>total</sub> (ms) | Duty Cycle | Duty Cycle Factor (dB) |
|-------------------|------------------|----------------------|-------------------------|------------|------------------------|
| 802.11b           | 1                | 12.421               | 12.522                  | 0.99198984 | 0.035                  |
|                   | 2                | 6.218                | 6.311                   | 0.98513800 | 0.065                  |
|                   | 5.5              | 2.318                | 2.412                   | 0.96119403 | 0.172                  |
|                   | 11               | 1.206                | 1.300                   | 0.92797784 | 0.325                  |
| 802.11g           | 6                | 2.063                | 2.165                   | 0.95258921 | 0.211                  |
|                   | 9                | 1.385                | 1.486                   | 0.93203230 | 0.306                  |
|                   | 12               | 1.045                | 1.147                   | 0.91162235 | 0.402                  |
|                   | 18               | 0.704                | 0.805                   | 0.87472036 | 0.581                  |
|                   | 24               | 0.532                | 0.634                   | 0.83901515 | 0.762                  |
|                   | 36               | 0.364                | 0.466                   | 0.78178694 | 1.069                  |
|                   | 48               | 0.276                | 0.378                   | 0.73093220 | 1.361                  |
|                   | 54               | 0.248                | 0.350                   | 0.70938215 | 1.491                  |
| 802.11n<br>(HT20) | 6.5 (MCS0)       | 1.919                | 2.021                   | 0.94970140 | 0.224                  |
|                   | 13 (MCS1)        | 0.981                | 1.082                   | 0.90682196 | 0.425                  |
|                   | 19.5 (MCS2)      | 0.664                | 0.765                   | 0.86823529 | 0.614                  |
|                   | 26 (MCS3)        | 0.508                | 0.610                   | 0.83267717 | 0.795                  |
|                   | 39 (MCS4)        | 0.352                | 0.454                   | 0.77513228 | 1.106                  |
|                   | 52 (MCS5)        | 0.272                | 0.373                   | 0.72888040 | 1.373                  |
|                   | 58.5 (MCS6)      | 0.248                | 0.349                   | 0.71008431 | 1.487                  |
|                   | 65 (MCS7)        | 0.228                | 0.329                   | 0.69265065 | 1.595                  |

▣ Test Plots


Duty cycle plot (802.11b(1Mbps))



Duty cycle plot (802.11g(6Mbps))



Duty cycle plot (802.11n(MCS0))



**Note:**

In order to simplify the report, attached plots were only the most lowest datarate.



## 9.2 6dB BANDWIDTH & 99 % BANDWIDTH

### FCC


| 802.11b Mode    |             | Measured Bandwidth [MHz] | Minimum Bandwidth [MHz] |
|-----------------|-------------|--------------------------|-------------------------|
| Frequency [MHz] | Channel No. |                          |                         |
| 2412            | 1           | 7.116                    | 0.5                     |
| 2437            | 6           | 7.124                    | 0.5                     |
| 2462            | 11          | 7.128                    | 0.5                     |

| 802.11g Mode    |             | Measured Bandwidth [MHz] | Minimum Bandwidth [MHz] |
|-----------------|-------------|--------------------------|-------------------------|
| Frequency [MHz] | Channel No. |                          |                         |
| 2412            | 1           | 16.34                    | 0.5                     |
| 2437            | 6           | 16.08                    | 0.5                     |
| 2462            | 11          | 16.30                    | 0.5                     |


| 802.11n Mode    |             | Measured Bandwidth [MHz] | Minimum Bandwidth [MHz] |
|-----------------|-------------|--------------------------|-------------------------|
| Frequency [MHz] | Channel No. |                          |                         |
| 2412            | 1           | 17.01                    | 0.5                     |
| 2437            | 6           | 17.56                    | 0.5                     |
| 2462            | 11          | 17.35                    | 0.5                     |

▣ Test Plots


6dB Bandwidth plot (802.11b-CH 1)



6dB Bandwidth plot (802.11g-CH 6)



6dB Bandwidth plot (802.11n\_HT20-CH 1)



**Note:**

In order to simplify the report, attached plots were only the most narrow 6 dB BW channel.

IC


| 802.11b Mode       |             | OBW<br>Bandwidth<br>[MHz] | Limit<br>[MHz] |
|--------------------|-------------|---------------------------|----------------|
| Frequency<br>[MHz] | Channel No. |                           |                |
| 2412               | 1           | 10.382                    | N/A            |
| 2437               | 6           | 10.371                    | N/A            |
| 2462               | 11          | 10.350                    | N/A            |

| 802.11g Mode       |             | OBW<br>Bandwidth<br>[MHz] | Limit<br>[MHz] |
|--------------------|-------------|---------------------------|----------------|
| Frequency<br>[MHz] | Channel No. |                           |                |
| 2412               | 1           | 17.097                    | N/A            |
| 2437               | 6           | 17.047                    | N/A            |
| 2462               | 11          | 17.084                    | N/A            |


| 802.11n(HT20) Mode |             | OBW<br>Bandwidth<br>[MHz] | Limit<br>[MHz] |
|--------------------|-------------|---------------------------|----------------|
| Frequency<br>[MHz] | Channel No. |                           |                |
| 2412               | 1           | 18.166                    | N/A            |
| 2437               | 6           | 18.140                    | N/A            |
| 2462               | 11          | 18.122                    | N/A            |

▣ Test Plots


99% Bandwidth plot (802.11b-CH 1)



99% Bandwidth plot (802.11g-CH 1)



99% Bandwidth plot (802.11n\_HT20-CH 1)



**Note:**

In order to simplify the report, attached plots were only the most wide 99% Bandwidth channel.

### 9.3 OUTPUT POWER

**Peak Power**

1. Power Meter offset = Attenuator loss + Cable loss
2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.

| 802.11b Mode   |             | Rate (Mbps) | Measured Power(dBm) | Limit (dBm) |
|----------------|-------------|-------------|---------------------|-------------|
| Frequency[MHz] | Channel No. |             |                     |             |
| 2412           | 1           | 1           | 12.10               | 30.00       |
|                |             | 2           | 12.37               | 30.00       |
|                |             | 5.5         | 13.92               | 30.00       |
|                |             | 11          | 15.66               | 30.00       |
| 2437           | 6           | 1           | 11.69               | 30.00       |
|                |             | 2           | 11.90               | 30.00       |
|                |             | 5.5         | 13.45               | 30.00       |
|                |             | 11          | 15.23               | 30.00       |
| 2462           | 11          | 1           | 11.36               | 30.00       |
|                |             | 2           | 11.59               | 30.00       |
|                |             | 5.5         | 13.11               | 30.00       |
|                |             | 11          | 14.89               | 30.00       |

| 802.11g Mode   |             | Rate (Mbps) | Measured Power(dBm) | Limit (dBm) |
|----------------|-------------|-------------|---------------------|-------------|
| Frequency[MHz] | Channel No. |             |                     |             |
| 2412           | 1           | 6           | 17.46               | 30.00       |
|                |             | 9           | 17.41               | 30.00       |
|                |             | 12          | 17.26               | 30.00       |
|                |             | 18          | 16.89               | 30.00       |
|                |             | 24          | 17.53               | 30.00       |
|                |             | 36          | 17.61               | 30.00       |
|                |             | 48          | 17.66               | 30.00       |
|                |             | 54          | 17.25               | 30.00       |
| 2437           | 6           | 6           | 17.36               | 30.00       |
|                |             | 9           | 17.27               | 30.00       |
|                |             | 12          | 17.14               | 30.00       |
|                |             | 18          | 16.76               | 30.00       |
|                |             | 24          | 16.95               | 30.00       |
|                |             | 36          | 17.06               | 30.00       |
|                |             | 48          | 17.07               | 30.00       |
|                |             | 54          | 17.03               | 30.00       |
| 2462           | 11          | 6           | 17.07               | 30.00       |
|                |             | 9           | 17.02               | 30.00       |
|                |             | 12          | 16.89               | 30.00       |
|                |             | 18          | 16.56               | 30.00       |
|                |             | 24          | 16.63               | 30.00       |
|                |             | 36          | 16.75               | 30.00       |
|                |             | 48          | 16.81               | 30.00       |
|                |             | 54          | 16.73               | 30.00       |



| 802.11n Mode   |             | MCS Index | Measured Power(dBm) | Limit (dBm) |
|----------------|-------------|-----------|---------------------|-------------|
| Frequency[MHz] | Channel No. |           |                     |             |
| 2412           | 1           | 0         | 17.06               | 30.00       |
|                |             | 1         | 16.99               | 30.00       |
|                |             | 2         | 17.04               | 30.00       |
|                |             | 3         | 17.04               | 30.00       |
|                |             | 4         | 17.95               | 30.00       |
|                |             | 5         | 17.96               | 30.00       |
|                |             | 6         | 18.03               | 30.00       |
|                |             | 7         | 18.05               | 30.00       |
| 2437           | 6           | 0         | 16.73               | 30.00       |
|                |             | 1         | 16.73               | 30.00       |
|                |             | 2         | 16.81               | 30.00       |
|                |             | 3         | 17.62               | 30.00       |
|                |             | 4         | 17.58               | 30.00       |
|                |             | 5         | 17.60               | 30.00       |
|                |             | 6         | 17.88               | 30.00       |
|                |             | 7         | 17.57               | 30.00       |
| 2462           | 11          | 0         | 16.76               | 30.00       |
|                |             | 1         | 16.41               | 30.00       |
|                |             | 2         | 16.41               | 30.00       |
|                |             | 3         | 17.21               | 30.00       |
|                |             | 4         | 17.15               | 30.00       |
|                |             | 5         | 17.14               | 30.00       |
|                |             | 6         | 17.88               | 30.00       |
|                |             | 7         | 17.14               | 30.00       |

**Average Power**

1. Power Meter offset = Attenuator loss + Cable loss
2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.

| 802.11b Mode    |             | Rate (Mbps) | Measured Power (dBm) | Duty Cycle Factor | Measured Power(dBm) + Duty Cycle Factor | Limit (dBm) |
|-----------------|-------------|-------------|----------------------|-------------------|---|-------------|
| Frequency [MHz] | Channel No. |             |                      |                   |   |             |
| 2412            | 1           | 1           | 9.64                 | 0.035             | 9.68                                    | 30.00       |
|                 |             | 2           | 9.64                 | 0.065             | 9.70                                    | 30.00       |
|                 |             | 5.5         | 9.51                 | 0.172             | 9.68                                    | 30.00       |
|                 |             | 11          | 9.38                 | 0.325             | 9.70                                    | 30.00       |
| 2437            | 6           | 1           | 9.21                 | 0.035             | 9.25                                    | 30.00       |
|                 |             | 2           | 9.21                 | 0.065             | 9.27                                    | 30.00       |
|                 |             | 5.5         | 9.07                 | 0.172             | 9.24                                    | 30.00       |
|                 |             | 11          | 8.93                 | 0.325             | 9.25                                    | 30.00       |
| 2462            | 11          | 1           | 8.85                 | 0.035             | 8.89                                    | 30.00       |
|                 |             | 2           | 8.90                 | 0.065             | 8.97                                    | 30.00       |
|                 |             | 5.5         | 8.72                 | 0.172             | 8.89                                    | 30.00       |
|                 |             | 11          | 8.63                 | 0.325             | 8.95                                    | 30.00       |

| 802.11g Mode    |             | Rate (Mbps) | Measured Power (dBm) | Duty Cycle Factor | Measured Power(dBm) + Duty Cycle Factor | Limit (dBm) |
|-----------------|-------------|-------------|----------------------|-------------------|---|-------------|
| Frequency [MHz] | Channel No. |             |                      |                   |   |             |
| 2412            | 1           | 6           | 9.47                 | 0.211             | 9.69                                    | 30.00       |
|                 |             | 9           | 9.34                 | 0.306             | 9.64                                    | 30.00       |
|                 |             | 12          | 9.34                 | 0.402             | 9.74                                    | 30.00       |
|                 |             | 18          | 8.69                 | 0.581             | 9.27                                    | 30.00       |
|                 |             | 24          | 8.91                 | 0.762             | 9.67                                    | 30.00       |
|                 |             | 36          | 8.57                 | 1.069             | 9.64                                    | 30.00       |
|                 |             | 48          | 8.34                 | 1.361             | 9.70                                    | 30.00       |
|                 |             | 54          | 7.86                 | 1.491             | 9.35                                    | 30.00       |
| 2437            | 6           | 6           | 9.45                 | 0.211             | 9.66                                    | 30.00       |
|                 |             | 9           | 9.30                 | 0.306             | 9.60                                    | 30.00       |
|                 |             | 12          | 9.20                 | 0.402             | 9.60                                    | 30.00       |
|                 |             | 18          | 8.54                 | 0.581             | 9.12                                    | 30.00       |
|                 |             | 24          | 8.34                 | 0.762             | 9.10                                    | 30.00       |
|                 |             | 36          | 8.02                 | 1.069             | 9.09                                    | 30.00       |
|                 |             | 48          | 7.86                 | 1.361             | 9.22                                    | 30.00       |
|                 |             | 54          | 7.70                 | 1.491             | 9.20                                    | 30.00       |
| 2462            | 11          | 6           | 9.07                 | 0.211             | 9.29                                    | 30.00       |
|                 |             | 9           | 8.97                 | 0.306             | 9.28                                    | 30.00       |
|                 |             | 12          | 8.93                 | 0.402             | 9.33                                    | 30.00       |
|                 |             | 18          | 8.37                 | 0.581             | 8.96                                    | 30.00       |
|                 |             | 24          | 7.97                 | 0.762             | 8.74                                    | 30.00       |
|                 |             | 36          | 7.69                 | 1.069             | 8.76                                    | 30.00       |
|                 |             | 48          | 7.53                 | 1.361             | 8.89                                    | 30.00       |
|                 |             | 54          | 7.35                 | 1.491             | 8.84                                    | 30.00       |

| 802.11n Mode    |             | MCS Index | Measured Power (dBm) | Duty Cycle Factor | Measured Power(dBm) + Duty Cycle Factor | Limit (dBm) |
|-----------------|-------------|-----------|----------------------|-------------------|---|-------------|
| Frequency [MHz] | Channel No. |           |                      |                   |   |             |
| 2412            | 1           | 0         | 9.07                 | 0.224             | 9.29                                    | 30.00       |
|                 |             | 1         | 8.91                 | 0.425             | 9.33                                    | 30.00       |
|                 |             | 2         | 8.88                 | 0.614             | 9.49                                    | 30.00       |
|                 |             | 3         | 8.74                 | 0.795             | 9.54                                    | 30.00       |
|                 |             | 4         | 8.93                 | 1.106             | 10.03                                   | 30.00       |
|                 |             | 5         | 8.67                 | 1.373             | 10.05                                   | 30.00       |
|                 |             | 6         | 8.50                 | 1.487             | 9.99                                    | 30.00       |
|                 |             | 7         | 8.30                 | 1.595             | 9.90                                    | 30.00       |
| 2437            | 6           | 0         | 8.62                 | 0.224             | 8.84                                    | 30.00       |
|                 |             | 1         | 8.54                 | 0.425             | 8.96                                    | 30.00       |
|                 |             | 2         | 8.36                 | 0.614             | 8.97                                    | 30.00       |
|                 |             | 3         | 8.46                 | 0.795             | 9.26                                    | 30.00       |
|                 |             | 4         | 8.22                 | 1.106             | 9.33                                    | 30.00       |
|                 |             | 5         | 7.98                 | 1.373             | 9.35                                    | 30.00       |
|                 |             | 6         | 8.10                 | 1.487             | 9.58                                    | 30.00       |
|                 |             | 7         | 7.75                 | 1.595             | 9.34                                    | 30.00       |
| 2462            | 11          | 0         | 8.76                 | 0.224             | 8.98                                    | 30.00       |
|                 |             | 1         | 8.23                 | 0.425             | 8.65                                    | 30.00       |
|                 |             | 2         | 8.09                 | 0.614             | 8.70                                    | 30.00       |
|                 |             | 3         | 8.12                 | 0.795             | 8.91                                    | 30.00       |
|                 |             | 4         | 7.79                 | 1.106             | 8.90                                    | 30.00       |
|                 |             | 5         | 7.56                 | 1.373             | 8.94                                    | 30.00       |
|                 |             | 6         | 8.08                 | 1.487             | 9.57                                    | 30.00       |
|                 |             | 7         | 7.34                 | 1.595             | 8.93                                    | 30.00       |

#### 9.4 POWER SPECTRAL DENSITY

| Mode    | Frequency (MHz) | Channel No. | Test Result        |                   |                                       |             |
|---------|-----------------|-------------|--------------------|-------------------|---------------------------------------|-------------|
|         |                 |             | Measured PSD (dBm) | Duty Cycle Factor | Measured PSD(dBm) + Duty Cycle Factor | Limit (dBm) |
| 802.11b | 2412            | 1           | -12.169            | 0.065             | -12.104                               | 8           |
|         | 2437            | 6           | -12.653            | 0.065             | -12.588                               | 8           |
|         | 2462            | 11          | -13.320            | 0.065             | -13.255                               | 8           |
| 802.11g | 2412            | 1           | -16.555            | 0.402             | -16.153                               | 8           |
|         | 2437            | 6           | -13.902            | 0.211             | -13.691                               | 8           |
|         | 2462            | 11          | -13.680            | 0.402             | -13.278                               | 8           |
| 802.11n | 2412            | 1           | -16.491            | 1.373             | -15.118                               | 8           |
|         | 2437            | 6           | -16.815            | 1.487             | -15.328                               | 8           |
|         | 2462            | 11          | -15.719            | 1.487             | -14.232                               | 8           |

**Note :**

1. Spectrum reading values are not plot data.


The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.

2. Spectrum offset = Attenuator loss + Cable loss


3. 21.52 dB is offset for 2.4 GHz Band.

▣ Test Plots


Power Spectral Density (802.11b-CH 1)



Power Spectral Density (802.11g-CH 11)



Power Spectral Density (802.11n\_HT20 -CH 11)



**Note :**

In order to simplify the report, attached plots were only the worstcase PSD channel.

## 9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS


Test Result : please refer to the plot below.

In order to simplify the report, attached plots were only the worst case channel and data rate.




▣ Test Plots(BandEdge)


Band Edge (802.11b-CH1)




Band Edge (802.11b-CH11)




Band Edge (802.11g-CH1)




Band Edge (802.11g-CH11)



Band Edge (802.11n(HT20)-CH1)




Band Edge (802.11n(HT20)-CH11)



▣ Test Plots(Conducted Spurious Emission)


30 MHz ~ 1 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)




1 GHz ~ 3 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)




3 GHz ~ 5 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)




5 GHz ~ 7 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)




7 GHz ~ 9 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)




9 GHz ~ 11 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)




11 GHz ~ 13 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)




13 GHz ~ 15 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)




15 GHz ~ 17 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)



17 GHz ~ 19 GHz


Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)






19 GHz ~ 21 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)




21 GHz ~ 23 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)



23 GHz ~ 25 GHz

Conducted Spurious Emission (802.11n(20M)\_Ch.1\_7 Mbps)



**9.6 RADIATED SPURIOUS EMISSIONS**

**Frequency Range : 9 kHz – 30MHz**

| Frequency               | Reading | Ant. factor | Cable loss | Ant. POL | Total  | Limit  | Margin |
|-------------------------|---------|-------------|------------|----------|--------|--------|--------|
| MHz                     | dBuV/m  | dBm/m       | dBm        | (H/V)    | dBuV/m | dBuV/m | dB     |
| No Critical peaks found |         |             |            |          |        |        |        |

**Note:**

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor =  $40 \cdot \log(\text{specific distance} / \text{test distance})$  (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor
4. Radiated test is performed with hopping off.
5. The test results for below 30 MHz is correlated to an open site.  
The result on OFS is about 2 dB higher than semi-anechoic chamber(10 m chamber)

**Frequency Range : Below 1 GHz**

| Frequency               | Reading | Ant. factor | Cable loss | Ant. POL | Total  | Limit  | Margin |
|-------------------------|---------|-------------|------------|----------|--------|--------|--------|
| MHz                     | dBuV/m  | dBm/m       | dBm        | (H/V)    | dBuV/m | dBuV/m | dB     |
| No Critical peaks found |         |             |            |          |        |        |        |

**Note:**

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

**Frequency Range : Above 1 GHz**

|                     |         |
|---------------------|---------|
| Operation Mode:     | 802.11b |
| Transfer Rate:      | 1 Mbps  |
| Operating Frequency | 2412    |
| Channel No.         | 01 Ch   |

| Frequency [MHz] | Reading dBuV | AN.+CL-AMP G [dB] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|--------------|-------------------|----------------|----------------|----------------|-------------|--------|
| 4824            | 44.51        | 2.74              | V              | 47.25          | 73.98          | 26.73       | PK     |
| 4824            | 32.33        | 2.74              | V              | 35.07          | 53.98          | 18.91       | AV     |
| 7236            | 47.25        | 8.72              | V              | 55.97          | 73.98          | 18.01       | PK     |
| 7236            | 39.69        | 8.72              | V              | 48.41          | 53.98          | 5.57        | AV     |
| 4824            | 44.39        | 2.74              | H              | 47.13          | 73.98          | 26.85       | PK     |
| 4824            | 32.19        | 2.74              | H              | 34.93          | 53.98          | 19.05       | AV     |
| 7236            | 47.18        | 8.72              | H              | 55.90          | 73.98          | 18.08       | PK     |
| 7236            | 39.11        | 8.72              | H              | 47.83          | 53.98          | 6.15        | AV     |

|                     |         |
|---------------------|---------|
| Operation Mode:     | 802.11g |
| Transfer Rate:      | 6 Mbps  |
| Operating Frequency | 2412    |
| Channel No.         | 01 Ch   |

| Frequency [MHz] | Reading dBuV | Duty Cycle Factor | AN.+CL-AMP G [dB] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|--------------|-------------------|-------------------|----------------|----------------|----------------|-------------|--------|
| 4824            | 44.36        | 0.00              | 2.74              | V              | 47.10          | 73.98          | 26.88       | PK     |
| 4824            | 32.26        | 0.21              | 2.74              | V              | 35.21          | 53.98          | 18.77       | AV     |
| 7236            | 56.50        | 0.00              | 8.72              | V              | 65.22          | 73.98          | 8.76        | PK     |
| 7236            | 34.11        | 0.21              | 8.72              | V              | 43.04          | 53.98          | 10.94       | AV     |
| 4824            | 44.28        | 0.00              | 2.74              | H              | 47.02          | 73.98          | 26.96       | PK     |
| 4824            | 32.12        | 0.21              | 2.74              | H              | 35.07          | 53.98          | 18.91       | AV     |
| 7236            | 55.98        | 0.00              | 8.72              | H              | 64.70          | 73.98          | 9.28        | PK     |
| 7236            | 33.99        | 0.21              | 8.72              | H              | 42.92          | 53.98          | 11.06       | AV     |

Operation Mode: 802.11n (HT20)  
 Transfer MCS Index: 0  
 Operating Frequency 2412  
 Channel No. 01 Ch

| Frequency [MHz] | Reading dBuV | Duty Cycle Factor | AN.+CL-AMP G [dB] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|--------------|-------------------|-------------------|----------------|----------------|----------------|-------------|--------|
| 4824            | 44.58        | 0.00              | 2.74              | V              | 47.32          | 73.98          | 26.66       | PK     |
| 4824            | 32.35        | 0.22              | 2.74              | V              | 35.31          | 53.98          | 18.67       | AV     |
| 7236            | 58.63        | 0.00              | 8.72              | V              | 67.35          | 73.98          | 6.63        | PK     |
| 7236            | 33.31        | 0.22              | 8.72              | V              | 42.25          | 53.98          | 11.73       | AV     |
| 4824            | 44.45        | 0.00              | 2.74              | H              | 47.19          | 73.98          | 26.79       | PK     |
| 4824            | 32.26        | 0.22              | 2.74              | H              | 35.22          | 53.98          | 18.76       | AV     |
| 7236            | 57.97        | 0.00              | 8.72              | H              | 66.69          | 73.98          | 7.29        | PK     |
| 7236            | 33.28        | 0.22              | 8.72              | H              | 42.22          | 53.98          | 11.76       | AV     |

Operation Mode: 802.11b  
 Transfer Rate: 1 Mbps  
 Operating Frequency 2437  
 Channel No. 06 Ch

| Frequency [MHz] | Reading dBuV | AN.+CL-AMP G [dB] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|--------------|-------------------|----------------|----------------|----------------|-------------|--------|
| 4874            | 43.65        | 2.78              | V              | 46.43          | 73.98          | 27.55       | PK     |
| 4874            | 31.91        | 2.78              | V              | 34.69          | 53.98          | 19.29       | AV     |
| 7311            | 45.24        | 9.01              | V              | 54.25          | 73.98          | 19.73       | PK     |
| 7311            | 36.80        | 9.01              | V              | 45.81          | 53.98          | 8.17        | AV     |
| 4874            | 43.62        | 2.78              | H              | 46.40          | 73.98          | 27.58       | PK     |
| 4874            | 31.84        | 2.78              | H              | 34.62          | 53.98          | 19.36       | AV     |
| 7311            | 45.22        | 9.01              | H              | 54.23          | 73.98          | 19.75       | PK     |
| 7311            | 36.58        | 9.01              | H              | 45.59          | 53.98          | 8.39        | AV     |

Operation Mode: 802.11g  
 Transfer Rate: 6 Mbps  
 Operating Frequency 2437  
 Channel No. 06 Ch

| Frequency [MHz] | Reading dBuV | Duty Cycle Factor | AN.+CL-AMP G [dB] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|--------------|-------------------|-------------------|----------------|----------------|----------------|-------------|--------|
| 4874            | 43.58        | 0.00              | 2.78              | V              | 46.36          | 73.98          | 27.62       | PK     |
| 4874            | 31.85        | 0.21              | 2.78              | V              | 34.84          | 53.98          | 19.14       | AV     |
| 7311            | 53.48        | 0.00              | 9.01              | V              | 62.49          | 73.98          | 11.49       | PK     |
| 7311            | 32.52        | 0.21              | 9.01              | V              | 41.74          | 53.98          | 12.24       | AV     |
| 4874            | 43.60        | 0.00              | 2.78              | H              | 46.38          | 73.98          | 27.60       | PK     |
| 4874            | 31.53        | 0.21              | 2.78              | H              | 34.52          | 53.98          | 19.46       | AV     |
| 7311            | 53.43        | 0.00              | 9.01              | H              | 62.44          | 73.98          | 11.54       | PK     |
| 7311            | 32.38        | 0.21              | 9.01              | H              | 41.60          | 53.98          | 12.38       | AV     |

Operation Mode: 802.11n (HT20)  
 Transfer MCS Index: 0  
 Operating Frequency: 2437  
 Channel No.: 06 Ch

| Frequency [MHz] | Reading [dBuV] | Duty Cycle Factor | AN.+CL-AMP G [dB] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|----------------|-------------------|-------------------|----------------|----------------|----------------|-------------|--------|
| 4874            | 43.78          | 0.00              | 2.78              | V              | 46.56          | 73.98          | 27.42       | PK     |
| 4874            | 31.69          | 0.22              | 2.78              | V              | 34.69          | 53.98          | 19.29       | AV     |
| 7311            | 53.28          | 0.00              | 9.01              | V              | 62.29          | 73.98          | 11.69       | PK     |
| 7311            | 32.01          | 0.22              | 9.01              | V              | 41.24          | 53.98          | 12.74       | AV     |
| 4874            | 43.61          | 0.00              | 2.78              | H              | 46.39          | 73.98          | 27.59       | PK     |
| 4874            | 31.48          | 0.22              | 2.78              | H              | 34.48          | 53.98          | 19.50       | AV     |
| 7311            | 53.22          | 0.00              | 9.01              | H              | 62.23          | 73.98          | 11.75       | PK     |
| 7311            | 32.10          | 0.22              | 9.01              | H              | 41.33          | 53.98          | 12.65       | AV     |

Operation Mode: 802.11b  
 Transfer Rate: 1 Mbps  
 Operating Frequency 2462  
 Channel No. 11 Ch

| Frequency [MHz] | Reading dBuV | AN.+CL-AMP G [dB] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|--------------|-------------------|----------------|----------------|----------------|-------------|--------|
| 4924            | 43.62        | 2.43              | V              | 46.05          | 73.98          | 27.93       | PK     |
| 4924            | 31.29        | 2.43              | V              | 33.72          | 53.98          | 20.26       | AV     |
| 7386            | 43.89        | 9.44              | V              | 53.33          | 73.98          | 20.65       | PK     |
| 7386            | 33.21        | 9.44              | V              | 42.65          | 53.98          | 11.33       | AV     |
| 4924            | 43.58        | 2.43              | H              | 46.01          | 73.98          | 27.97       | PK     |
| 4924            | 31.18        | 2.43              | H              | 33.61          | 53.98          | 20.37       | AV     |
| 7386            | 43.69        | 9.44              | H              | 53.13          | 73.98          | 20.85       | PK     |
| 7386            | 33.14        | 9.44              | H              | 42.58          | 53.98          | 11.40       | AV     |

Operation Mode: 802.11g  
 Transfer Rate: 6 Mbps  
 Operating Frequency 2462  
 Channel No. 11 Ch

| Frequency [MHz] | Reading dBuV | Duty Cycle Factor | AN.+CL-AMP G [dB] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|--------------|-------------------|-------------------|----------------|----------------|----------------|-------------|--------|
| 4924            | 44.75        | 0.00              | 2.43              | V              | 47.18          | 73.98          | 26.80       | PK     |
| 4924            | 31.26        | 0.21              | 2.43              | V              | 33.90          | 53.98          | 20.08       | AV     |
| 7386            | 50.76        | 0.00              | 9.44              | V              | 60.20          | 73.98          | 13.78       | PK     |
| 7386            | 30.48        | 0.21              | 9.44              | V              | 40.13          | 53.98          | 13.85       | AV     |
| 4924            | 44.59        | 0.00              | 2.43              | H              | 47.02          | 73.98          | 26.96       | PK     |
| 4924            | 31.18        | 0.21              | 2.43              | H              | 33.82          | 53.98          | 20.16       | AV     |
| 7386            | 50.67        | 0.00              | 9.44              | H              | 60.11          | 73.98          | 13.87       | PK     |
| 7386            | 30.38        | 0.21              | 9.44              | H              | 40.03          | 53.98          | 13.95       | AV     |




Operation Mode: 802.11n (HT20)  
 Transfer MCS Index: 0  
 Operating Frequency: 2462  
 Channel No.: 11 Ch

| Frequency [MHz] | Reading dBuV | Duty Cycle Factor | AN.+CL-AMP G [dB] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|--------------|-------------------|-------------------|----------------|----------------|----------------|-------------|--------|
| 4924            | 43.86        | 0.00              | 2.43              | V              | 46.29          | 73.98          | 27.69       | PK     |
| 4924            | 31.58        | 0.22              | 2.43              | V              | 34.23          | 53.98          | 19.75       | AV     |
| 7386            | 50.16        | 0.00              | 9.44              | V              | 59.60          | 73.98          | 14.38       | PK     |
| 7386            | 30.39        | 0.22              | 9.44              | V              | 40.05          | 53.98          | 13.93       | AV     |
| 4924            | 43.77        | 0.00              | 2.43              | H              | 46.20          | 73.98          | 27.78       | PK     |
| 4924            | 31.76        | 0.22              | 2.43              | H              | 34.41          | 53.98          | 19.57       | AV     |
| 7386            | 50.04        | 0.00              | 9.44              | H              | 59.48          | 73.98          | 14.50       | PK     |
| 7386            | 30.26        | 0.22              | 9.44              | H              | 39.92          | 53.98          | 14.06       | AV     |


### Test Plots (Worst case : X-V)

Radiated Spurious Emissions plot – Average Reading (802.11b, Ch.1 3rd Harmonic)




Date: 8.AUG.2019 02:59:15

Radiated Spurious Emissions plot – Peak Reading (802.11b, Ch.1 3rd Harmonic)




Date: 8.AUG.2019 02:58:35

### Radiated Spurious Emissions plot – Average Reading (802.11g, Ch.1 3rd Harmonic)




Date: 8.AUG.2019 03:00:55

### Radiated Spurious Emissions plot – Peak Reading (802.11g, Ch.1 3rd Harmonic)




Date: 8.AUG.2019 03:01:30

Radiated Spurious Emissions plot – Average Reading (802.11n(20M), Ch.1 3rd Harmonic)



Date: 8.AUG.2019 03:03:41

Radiated Spurious Emissions plot – Peak Reading (802.11n(20M), Ch.1 3rd Harmonic)



Date: 8.AUG.2019 03:03:03

**Note:**

Plot of worst case are only reported.

### 9.7 RADIATED RESTRICTED BAND EDGES

|                     |                    |
|---------------------|--------------------|
| Operation Mode:     | 802.11b            |
| Transfer Rate:      | 1 Mbps             |
| Operating Frequency | 2412 MHz, 2462 MHz |
| Channel No.         | 01 Ch, 11 Ch       |

| Frequency [MHz] | Reading dBuV | ※ A.F.+CL [dB] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|--------------|----------------|----------------|----------------|----------------|-------------|--------|
| 2390.0          | 48.93        | 0.22           | H              | 49.15          | 73.98          | 24.83       | PK     |
| 2390.0          | 37.27        | 0.22           | H              | 37.49          | 53.98          | 16.49       | AV     |
| 2390.0          | 49.20        | 0.22           | V              | 49.42          | 73.98          | 24.56       | PK     |
| 2390.0          | 37.59        | 0.22           | V              | 37.81          | 53.98          | 16.17       | AV     |
| 2483.5          | 48.39        | 0.65           | H              | 49.04          | 73.98          | 24.94       | PK     |
| 2483.5          | 37.21        | 0.65           | H              | 37.86          | 53.98          | 16.12       | AV     |
| 2483.5          | 48.59        | 0.65           | V              | 49.24          | 73.98          | 24.74       | PK     |
| 2483.5          | 37.22        | 0.65           | V              | 37.87          | 53.98          | 16.11       | AV     |

|                     |                    |
|---------------------|--------------------|
| Operation Mode:     | 802.11g            |
| Transfer Rate:      | 6 Mbps             |
| Operating Frequency | 2412 MHz, 2462 MHz |
| Channel No.         | 01 Ch, 11 Ch       |


| Frequency [MHz] | Reading dBuV | Duty Cycle Factor | ※ A.F.+CL [dB] | ANT. POL [H/V] | Total [dBuV/m] | Limit [dBuV/m] | Margin [dB] | Detect |
|-----------------|--------------|-------------------|----------------|----------------|----------------|----------------|-------------|--------|
| 2390.0          | 56.44        | 0.00              | 0.22           | H              | 56.66          | 73.98          | 17.32       | PK     |
| 2390.0          | 43.04        | 0.21              | 0.22           | H              | 43.47          | 53.98          | 10.51       | AV     |
| 2390.0          | 56.56        | 0.00              | 0.22           | V              | 56.78          | 73.98          | 17.20       | PK     |
| 2390.0          | 43.34        | 0.21              | 0.22           | V              | 43.77          | 53.98          | 10.21       | AV     |
| 2483.5          | 52.18        | 0.00              | 0.65           | H              | 52.83          | 73.98          | 21.15       | PK     |
| 2483.5          | 40.11        | 0.21              | 0.65           | H              | 40.97          | 53.98          | 13.01       | AV     |
| 2483.5          | 52.47        | 0.00              | 0.65           | V              | 53.12          | 73.98          | 20.86       | PK     |
| 2483.5          | 40.24        | 0.21              | 0.65           | V              | 41.10          | 53.98          | 12.88       | AV     |

Operation Mode: 802.11n (HT20)  
 Transfer MCS Index: 0  
 Operating Frequency: 2412 MHz, 2462 MHz  
 Channel No.: 01 Ch, 11 Ch

| Frequency<br>[MHz] | Reading<br>dBuV | Duty<br>Cycle<br>Factor | ※ A.F.+CL<br>[dB] | ANT. POL<br>[H/V] | Total<br>[dBuV/m] | Limit<br>[dBuV/m] | Margin<br>[dB] | Detect |
|--------------------|-----------------|-------------------------|-------------------|-------------------|-------------------|-------------------|----------------|--------|
| 2390.0             | 57.96           | 0.00                    | 0.22              | H                 | 58.18             | 73.98             | 15.80          | PK     |
| 2390.0             | 43.21           | 0.22                    | 0.22              | H                 | 43.65             | 53.98             | 10.33          | AV     |
| 2390.0             | 58.81           | 0.00                    | 0.22              | V                 | 59.03             | 73.98             | 14.95          | PK     |
| 2390.0             | 43.68           | 0.22                    | 0.22              | V                 | 44.12             | 53.98             | 9.86           | AV     |
| 2483.5             | 53.14           | 0.00                    | 0.65              | H                 | 53.79             | 73.98             | 20.19          | PK     |
| 2483.5             | 41.08           | 0.22                    | 0.65              | H                 | 41.95             | 53.98             | 12.03          | AV     |
| 2483.5             | 53.68           | 0.00                    | 0.65              | V                 | 54.33             | 73.98             | 19.65          | PK     |
| 2483.5             | 41.21           | 0.22                    | 0.65              | V                 | 42.08             | 53.98             | 11.90          | AV     |


▣ Test Plots (Worst case : X-V)

Radiated Restricted Band Edges plot – Average Reading (802.11n(HT20) Ch.1)



Date: 8.AUG.2019 02:23:50

Radiated Restricted Band Edges plot – Peak Reading (802.11n(HT20) Ch.1)



Date: 8.AUG.2019 02:20:50

**Note:**

Plot of worst case are only reported.

## 10. LIST OF TEST EQUIPMENT

### Conducted Test

| Manufacturer    | Model / Equipment                            | Calibration Date | Calibration Interval | Serial No. |
|-----------------|--|------------------|----------------------|------------|
| Rohde & Schwarz | ENV216 / LISN                                | 12/12/2018       | Annual               | 102245     |
| Rohde & Schwarz | ESCI / Test Receiver                         | 06/18/2019       | Annual               | 100033     |
| ESPAC           | SU-642 /Temperature Chamber                  | 03/12/2019       | Annual               | 0093008124 |
| Agilent         | N9020A / Signal Analyzer                     | 05/23/2019       | Annual               | MY51110085 |
| Agilent         | N9030A / Signal Analyzer                     | 11/20/2018       | Annual               | MY49431210 |
| Agilent         | N1911A / Power Meter                         | 04/10/2019       | Annual               | MY45100523 |
| Agilent         | N1921A / Power Sensor                        | 04/10/2019       | Annual               | MY52260025 |
| Agilent         | 87300B / Directional Coupler                 | 11/20/2018       | Annual               | 3116A03621 |
| Hewlett Packard | 11667B / Power Splitter                      | 05/24/2019       | Annual               | 5001       |
| Hewlett Packard | E3632A / DC Power Supply                     | 06/18/2019       | Annual               | KR75303960 |
| Agilent         | 8493C / Attenuator(10 dB)                    | 07/02/2019       | Annual               | 07560      |
| Rohde & Schwarz | EMC32 / Software                             | N/A              | N/A                  | N/A        |
| HCT CO., LTD.   | FCC WLAN&BT&BLE Conducted Test Software v3.0 | N/A              | N/A                  | N/A        |
| Rohde & Schwarz | CBT / Bluetooth Tester                       | 05/16/2019       | Annual               | 100422     |

### Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.



**Radiated Test**

| Manufacturer           | Model / Equipment                                       | Calibration Date | Calibration Interval | Serial No.  |
|------------------------|---|------------------|----------------------|-------------|
| Innco system           | CO3000 / Controller(Antenna mast)                       | N/A              | N/A                  | CO3000-4p   |
| Innco system           | MA4640/800-XP-EP / Antenna Position Tower               | N/A              | N/A                  | N/A         |
| Emco                   | 2090 / Controller                                       | N/A              | N/A                  | 060520      |
| Ets                    | Turn Table  | N/A              | N/A                  | N/A         |
| Rohde & Schwarz        | Loop Antenna  | 08/23/2018       | Biennial             | 1513-175    |
| Schwarzbeck            | VULB 9160 / Hybrid Antenna                              | 08/09/2019       | Biennial             | 3368        |
| Schwarzbeck            | BBHA 9120D / Horn Antenna                               | 11/21/2017       | Biennial             | 9120D-1191  |
| Schwarzbeck            | BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)                | 12/04/2017       | Biennial             | BBHA9170541 |
| Rohde & Schwarz        | FSP(9 kHz ~ 30 GHz) / Spectrum Analyzer                 | 09/19/2018       | Annual               | 836650/016  |
| Rohde & Schwarz        | FSV40-N / Spectrum Analyzer                             | 09/19/2018       | Annual               | 101068-SZ   |
| Wainwright Instruments | WHKX10-2700-3000-18000-40SS / High Pass Filter          | 01/03/2019       | Annual               | 4           |
| Wainwright Instruments | WHKX8-6090-7000-18000-40SS / High Pass Filter           | 01/03/2019       | Annual               | 5           |
| Wainwright Instruments | WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter | 06/19/2019       | Annual               | 2           |
| Wainwright Instruments | WRCJV5100/5850-40/50-8EEK / Band Reject Filter          | 01/03/2019       | Annual               | 2           |
| Api tech.              | 18B-03 / Attenuator (3 dB)                              | 06/04/2019       | Annual               | 2           |
| WEINSCHTEL             | 56-10 / Attenuator(10 dB)                               | 10/10/2018       | Annual               | 72316       |
| CERNEX                 | CBLU1183540B-01/Broadband Bench Top LNA                 | 01/03/2019       | Annual               | 28549       |
| CERNEX                 | CBL06185030 / Broadband Low Noise Amplifier             | 01/03/2019       | Annual               | 24615       |
| CERNEX                 | CBL18265035 / Power Amplifier                           | 01/03/2019       | Annual               | 22966       |
| CERNEX                 | CBL26405040 / Power Amplifier                           | 06/18/2019       | Annual               | 25956       |
| TESCOM                 | TC-3000C / Bluetooth Tester                             | 03/26/2019       | Annual               | 3000C000276 |

**Note:**

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

### 11. ANNEX A\_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

| No. | Description         |
|-----|---------------------|
| 1   | HCT-RF-1908-FI027-P |