

### MPE Calculation : Bluetooth

RF function or Mode	Frequency range (MHz)	Max. Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm <sup>2</sup> )	Requirement (mW/cm <sup>2</sup> )
Bluetooth(1Mbps)	2402.00 ~ 2480.00	1.00	-0.05	0.95	1.245	0.0003	1.000
Bluetooth(2,3Mbps)	2402.00 ~ 2480.00	0.00	-0.05	-0.05	0.989	0.0002	1.000
	~						
	~						
	~						
	~						
	~						
	~						

Note: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 1.245 / (4 \times 20^2 \times \pi) \\
 &= 0.0003 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm<sup>2</sup>)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averageing time (minutes)
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19 / f	*180 / f <sup>2</sup>	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1,500			f / 1500	30
1,500 ~ 100,000			1.0	30

**Conclusion : The exposure condition of this device is compliant with FCC**

## MPE Calculation : LTE, CDMA

RF function or Mode	Frequency range (MHz)	Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm <sup>2</sup> )	Requirement (mW/cm <sup>2</sup> )
LTE(Band 13)	776.00 ~ 787.00	25.00	1.85	26.85	484.173	0.0964	0.517
LTE(Band 4)	1710.70 ~ 1755.00	25.00	2.02	27.02	503.501	0.1002	1.000
CDMA(Band 850)	824.70 ~ 848.31	26.00	2.80	28.80	758.578	0.1510	0.549
CDMA(Band 1900)	1851.25 ~ 1908.75	26.00	5.23	31.23	1327.395	0.2641	1.000
	~						
	~						
	~						
	~						

Note: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 484.173 / (4 \times 20^2 \times \pi) \\
 &= 0.0964 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm<sup>2</sup>)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna

### ▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averageing time (minutes)
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19 / f	*180 / f <sup>2</sup>	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1,500			f / 1500	30
1,500 ~ 100,000			1.0	30

**Conclusion : The exposure condition of this device is compliant with FCC**

# RF Exposure Compliance for simultaneous operations

▪ **Configurations for simultaneous operations**

- Configuration 1: BT + LTE, CDMA Module

▪ **Configurations for simultaneous operations(LTE, CDMA Module)**

- LTE Band 13 + CDMA 850(Cellular)
- LTE Band 4 + CDMA 850(Cellular)
- LTE Band 4 + CDMA 1900(PCS)
- LTE Band 13 + CDMA 1900(PCS)

Note: Above configuration was declared from applicant.

▪ **Configurations for simultaneous operator**

RF function or mode	BT	LTE		CDMA		-		Σ of MPE ratios
Band	2.4GHz	Band 13	Band 4	Cellular	PCS	-	-	
Power Density (mW/cm <sup>2</sup> )	0.0003	0.0964	0.1002	0.1510	0.2641			
Requirement (mW/cm <sup>2</sup> )	1.0000	0.5170	1.0000	0.5490	1.0000			
MPE ratio (Power Density/Requirement)	0.0003	0.1865	0.1002	0.2750	0.2641			
Configuration 1 (MPE ratio)	0.0003	0.1865		0.2750				<b>0.4618</b>
	0.0003		0.1002	0.2750				0.3755
	0.0003		0.1002		0.2641			0.3646
	0.0003	0.1865			0.2641			0.4509

Note: The maximum power density in each RF function was used for above table.

▪ Requirement = Σ of MPE ratios ≤ 1

**Conclusion : The exposure condition of this device is compliant with FCC rules.**