

# - RF Exposure

#### 1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissive Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm²]	Averaging Time [minute]		
Limits for General Population / Uncontrolled Exposure						
0.3 ~ 1.34	614	1.63	*(100)	30		
1.34 ~ 30	824/f	2.19/f	*(180/f <sup>2</sup> )	30		
30 ~ 300	27.5	0.073	0.2	30		
300 ~ 1 500	/	1	f/1 500	30		
1 500 ~ 15 000	/	1	1.0	30		

f=frequency in Mtz, \*= plane-wave equivalent power density

#### MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01  $S = PG/4\pi R^2$  ( $\Rightarrow R = \sqrt{PG/4\pi S}$ )

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]



# 2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

#### 3. Calculation Result of RF Exposure

Mode	Target power	Tune up tolerance	Max tune up power	Max tune up power	Ant Gain	Ant Gain	Power Density at 20 cm	Limit
	[dB <b>m</b> ]	[dB]	[dB <b>m</b> ]	[mW]	[dBi]	[mW]	[mW/cm²]	[mW/cm²]
Bluetooth_GFSK	-2.00	±1.00	-1.00	0.79	2.29	1.69	0.000 27	1.000 00
Total			-				0.000 27	1.000 00

# 4. Target power and tolerance, Max tuneup power

Mode	Target power [dBm]	Tolerance [dB]	Max tuneup power [dBm]	Average Power [dBm]
Bluetooth_GFSK Lowest	-2.00	±1.00	-1.00	-1.22
Bluetooth_GFSK Middle	-2.00	±1.00	-1.00	-1.30
Bluetooth_GFSK Highest	-2.00	±1.00	-1.00	-1.47
Bluetooth_π/4DQPSK Lowest	-3.50	±1.00	-2.50	-2.83
Bluetooth_π/4DQPSK Middle	-3.50	±1.00	-2.50	-2.95
Bluetooth_π/4DQPSK Highest	-3.50	±1.00	-2.50	-3.18
Bluetooth_8DPSK Lowest	-3.50	±1.00	-2.50	-2.82
Bluetooth_8DPSK Middle	-3.50	±1.00	-2.50	-2.96
Bluetooth_8DPSK Highest	-3.50	±1.00	-2.50	-2.69