

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2012-0383

2. Customer

- Name : HYUNDAI MOBIS CO., LTD.
- Address : 203, Teheran-ro Gangnam-gu, Seoul, South Korea, 135-977

3. Use of Report : FCC Original Grant

4. Product Name / Model Name : DISPLAY CAR SYSTEM / DA330DJAN
FCC ID : TQ8-DA330DJAN

5. FCC Regulation(s) : FCC Part 15.247

Test Method Used : KDB558074 D01v05r02, ANSI C63.10-2013

6. Date of Test : 2020.10.05 ~ 2020.11.23

7. Location of Test : Permanent Testing Lab On Site Testing

8. Testing Environment : See appended test report.

9. Test Result : Refer to the attached test result.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Affirmation	Tested by Name : JaeHyeok Bang 	Reviewed by Name : JaeJin Lee 
-------------	--	---

2020 . 12 . 08 .

DT&C Co., Ltd.

Unconnected with KS Q ISO / IEC 17025 and KOLAS accreditation

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description	Revised by	Reviewed by
DRTFCC2012-0383	Dec. 08, 2020	Initial issue	JaeHyeok Bang	JaeJin Lee

Table of Contents

1. EUT DESCRIPTION	4
2. INFORMATION ABOUT TESTING	5
2.1 Test mode.....	5
2.2 Auxiliary equipment	5
2.3 Tested environment	6
2.4 EMI suppression Device(s) / Modifications	6
2.5 Measurement Uncertainty.....	6
3. SUMMARY OF TESTS	7
4. TEST METHODOLOGY	8
4.1 EUT configuration	8
4.2 EUT exercise	8
4.3 General test procedures	8
4.4 Description of test modes	8
5. INSTRUMENT CALIBRATION	9
6. FACILITIES AND ACCREDITATIONS	9
6.1 Facilities	9
6.2 Equipment	9
7. ANTENNA REQUIREMENTS.....	9
8. TEST RESULT	10
8.1 6dB bandwidth	10
8.2 Maximum peak conducted output power.....	18
8.3 Maximum power spectral density	20
8.4 Out of band emissions at the band edge / conducted spurious emissions.....	27
8.5 Radiated spurious emissions.....	52
8.6 Power-line conducted emissions	58
9. LIST OF TEST EQUIPMENT.....	59
APPENDIX I	60
APPENDIX II	61
APPENDIX III	63

1. EUT DESCRIPTION

FCC Equipment Class	Digital Transmission System(DTS)
Product	DISPLAY CAR SYSTEM
Model Name	DA330DJAN
Add Model Name ^{Note1}	DA330DJKN, DA330DLKN, DA330DLAN
Add Model Name ^{Note1}	DA331DJAN, DA331DJKN, DA331DLKN, DA331DLAN
Hardware Version	V 1.0
Software Version	V 1.0
Power Supply	DC 14.4 V
Frequency Range	<ul style="list-style-type: none">▪ 802.11b/g/n(20 MHz) : 2 412 MHz ~ 2 462 MHz
Max. RF Output Power	2.4GHz Band <ul style="list-style-type: none">▪ 802.11b : 7.21 dBm▪ 802.11g : 14.37 dBm▪ 802.11n (HT20) : 13.85 dBm
Modulation Type	<ul style="list-style-type: none">▪ 802.11b: CCK, DSSS▪ 802.11g/n: OFDM
Antenna Specification	Antenna type: PCB Pattern Antenna Antenna gain: -0.01 dBi

Note 1: Difference between models

	Model Name	Difference
Base model	DA330DJAN	NA
Add model	DA331DJAN, DA331DJKN, DA331DLKN, DA331DLAN	This model contains module approved under Part 22/24/27.(FCC ID: YZP-VL3010)
Add models	DA330DJKN, DA330DLKN, DA330DLAN	Same as base model

2. INFORMATION ABOUT TESTING

2.1 Test mode

Test mode	Worst case data rate	Tested Frequency(MHz)		
		Lowest	Middle	Highest
TM 1	802.11b 1 Mbps	2 412	2 437	2 462
TM 2	802.11g 6 Mbps	2 412	2 437	2 462
TM 3	802.11n(HT20) MCS 0	2 412	2 437	2 462

Note 1: The worst case data rate is determined as above test mode according to the power measurements.

Note 2: The power measurement results for all modes and data rate were reported.

2.2 Auxiliary equipment

Equipment	Model No.	Serial No.	Manufacturer	Note
-	-	-	-	-
-	-	-	-	-

2.3 Tested environment

Temperature	: 20 °C ~ 25 °C
Relative humidity content	: 35 % ~ 45 %
Details of power supply	: DC 14.4 V

2.4 EMI suppression Device(s) / Modifications

EMI suppression device(s) added and/or modifications made during testing
→ None

2.5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C 63.4-2014 and ANSI C 63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Test items	Measurement uncertainty
Antenna-port conducted emission	0.9 dB (The confidence level is about 95 %, k = 2)
Radiated emission (1 GHz Below)	4.9 dB (The confidence level is about 95 %, k = 2)
Radiated emission (1 GHz ~ 18 GHz)	5.1 dB (The confidence level is about 95 %, k = 2)
Radiated emission (18 GHz Above)	5.3 dB (The confidence level is about 95 %, k = 2)

3. SUMMARY OF TESTS

FCC Part	Parameter	Limit	Test Condition	Status Note 1
15.247(a)	6 dB Bandwidth	> 500 kHz	Conducted	C
15.247(b)	Transmitter Output Power	< 1 Watt		C
15.247(d)	Out of Band Emissions / Band Edge	20 dBc in any 100 kHz BW		C
15.247(e)	Transmitter Power Spectral Density	< 8 dBm/3 kHz		C
15.247(d) 15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	FCC 15.209 limits (see section 8.5)	Radiated	C
15.207	AC Line Conducted Emissions	FCC 15.207 limits (see section 8.6)	AC Line Conducted	NA Note3
15.203	Antenna Requirements	FCC 15.203 (see section 7)	-	C

Note 1: C=Comply NC=Not Comply NT=Not Tested NA=Not Applicable

Note 2: For radiated emission tests below 30 MHz were performed on semi-anechoic chamber which is correlated with OATS.

Note 3: This device is installed in a car. Therefore the power source is a battery of car.

Note 4: The conducted test item were performed the base model.(MN: DA330DJAN)
The radiated test item were performed both "MN: DA330DJAN" and "MN: DA331DJAN".

4. TEST METHODOLOGY

The measurement procedures described in the ANSI C63.10-2013 and the guidance provided in KDB558074 D01v05r02 were used in measurement of the EUT.

The EUT was tested per the guidance of KDB558074 D01v05r02. And ANSI C63.10-2013 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing.

4.1 EUT configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT exercise

The EUT was operated in the test mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

4.3 General test procedures

Conducted Emissions

The power-line conducted emission test procedure is not described on the KDB558074 D01v05r02.

So this test was fulfilled with the requirements in Section 6.2 of ANSI C63.10-2013.

The EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and Average detector

Radiated Emissions

Basically the radiated tests were performed with KDB558074 D01v05r02. But some requirements and procedures like test site requirements, EUT setup and maximizing procedure were fulfilled with the requirements in Section 5 and 6 of the ANSI C63.10 as stated on section 12.1 of the KDB558074 D01v05r02.

The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

4.4 Description of test modes

The EUT has been tested with all modes of operating conditions to determine the worst case emission characteristics. A test program is used to control the EUT for staying in continuous transmitting mode.

5. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

6. FACILITIES AND ACCREDITATIONS

6.1 Facilities

DT&C Co., Ltd.

The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042.

The test site complies with the requirements of § 2.948 according to ANSI C63.4-2014.

- FCC & ISED MRA Designation No. : KR0034
- ISED#: 5740A

www.dtnc.net

Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

6.2 Equipment

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, loop, horn. Spectrum analyzers with pre-selectors and peak, quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

7. ANTENNA REQUIREMENTS

7.1 According to FCC 47 CFR §15.203

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The internal antenna is printed on the PCB.

Therefore this E.U.T Complies with the requirement of §15.203

8. TEST RESULT

8.1 6dB bandwidth

■ Test Requirements and limit, §15.247(a)

The bandwidth at 6 dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6 dB bandwidth is 500 kHz.

■ Test Configuration:

Refer to the APPENDIX I.

■ Test Procedure

- KDB558074 D01v05r02 - Section 8.2

- ANSI C63.10-2013 – Section 11.8.2

1. Set resolution bandwidth (RBW) = 100 kHz

2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.

(RBW : 100 kHz / VBW : 300 kHz)

3. Detector = Peak.

4. Trace mode = max hold.

5. Sweep = auto couple.

6. Allow the trace to stabilize.

7. Option 1 - Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Option 2 - The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq 3 \times$ RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.


■ Test Results: Comply

Test Mode	Frequency	Test Results[MHz]
TM 1	Lowest	7.10
	Middle	7.10
	Highest	7.12
TM 2	Lowest	16.32
	Middle	16.34
	Highest	15.93
TM 3	Lowest	17.20
	Middle	17.33
	Highest	17.21

□ RESULT PLOTS


6 dB Bandwidth

TM 1 & Lowest




6 dB Bandwidth

TM 1 & Middle




6 dB Bandwidth

TM 1 & Highest



6 dB Bandwidth

TM 2 & Lowest

**6 dB Bandwidth**

TM 2 & Middle




6 dB Bandwidth

TM 2 & Highest



6 dB Bandwidth

TM 3 & Lowest


**6 dB Bandwidth**

TM 3 & Middle



6 dB Bandwidth

TM 3 & Highest




8.2 Maximum peak conducted output power

■ Test Requirements and limit, §15.247(b)

The maximum permissible conducted output power is **1 Watt**.

■ Test Configuration



■ Test Procedure

1. PKPM1 Peak power meter method of KDB558074 D01v05r02

The maximum conducted output powers were measured using a broadband peak RF power meter which has greater video bandwidth than DUT's DTS bandwidth and utilize a fast-responding diode detector.

2. Method AVGPM-G (Measurement using a gated RF average power meter) of KDB558074 D01v05r02

The average conducted output powers were measured using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Test Results: Comply

Freq. (MHz)	Det.	Maximum Peak Conducted Output Power (dBm) for <u>802.11b</u>							
		Data Rate [Mbps]							
		1	2	5.5	11	-	-	-	-
2412	PK	7.21	7.15	7.11	7.01	-	-	-	-
	AV	4.11	4.08	4.05	4.01	-	-	-	-
2437	PK	6.59	6.52	6.47	6.42	-	-	-	-
	AV	4.35	4.32	4.30	4.27	-	-	-	-
2462	PK	6.29	6.25	6.17	6.12	-	-	-	-
	AV	4.41	4.38	4.35	4.34	-	-	-	-

Freq. (MHz)	Det.	Maximum Peak Conducted Output Power (dBm) for <u>802.11g</u>							
		Data Rate [Mbps]							
		6	9	12	18	24	36	48	54
2412	PK	14.37	14.35	14.31	14.28	14.21	14.15	14.11	14.09
	AV	4.66	4.63	4.59	4.55	4.52	4.48	4.42	4.39
2437	PK	14.17	14.11	14.06	14.02	14.00	13.96	13.92	13.91
	AV	4.41	4.38	4.33	4.31	4.28	4.25	4.20	4.17
2462	PK	13.82	13.81	13.77	13.72	13.65	13.63	13.58	13.56
	AV	3.92	3.89	3.85	3.81	3.77	3.72	3.71	3.68

Freq. (MHz)	Det.	Maximum Peak Conducted Output Power (dBm) for <u>802.11n(HT20)</u>							
		Data Rate [MCS]							
		0	1	2	3	4	5	6	7
2412	PK	13.85	13.81	13.80	13.72	13.70	13.66	13.62	13.58
	AV	4.11	4.08	4.06	4.05	4.01	3.98	3.92	3.91
2437	PK	13.56	13.51	13.44	13.41	13.33	13.31	13.25	13.22
	AV	3.69	3.67	3.65	3.61	3.56	3.55	3.52	3.50
2462	PK	13.67	13.62	13.60	13.57	13.50	13.44	13.41	13.33
	AV	3.44	3.41	3.35	3.33	3.30	3.28	3.24	3.20

8.3 Maximum power spectral density

■ Test requirements and limit, §15.247(e)

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

■ Test Configuration:

Refer to the APPENDIX I.

■ Test Procedure

- **KDB558074 D01v05r02 - Section 8.4**
- **ANSI C63.10-2013 – Section 11.10.2**

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to **1.5 times** the DTS bandwidth.
3. Set the RBW to : **3 kHz ≤ RBW ≤ 100 kHz**
4. Set the VBW **≥ 3 x RBW**
5. Detector = **Peak**
6. Sweep time = **Auto couple**
7. Trace mode = **Max hold.**
8. Allow trace to fully stabilize.
9. Use the **peak marker function** to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


■ Test Results: Comply

Test Mode	Frequency	RBW	PKPSD [dBm]
TM 1	Lowest	3 kHz	-15.80
	Middle	3 kHz	-16.04
	Highest	3 kHz	-16.72
TM 2	Lowest	3 kHz	-17.01
	Middle	3 kHz	-17.68
	Highest	3 kHz	-17.64
TM 3	Lowest	3 kHz	-17.48
	Middle	3 kHz	-17.58
	Highest	3 kHz	-18.30

RESULT PLOTS

Maximum PPSD

TM 1 & Lowest




Maximum PPSD

TM 1 & Middle




Maximum PPSD

TM 1 & Highest




Maximum PPSD

TM 2 & Lowest



Maximum PPSD

TM2 & Middle




Maximum PPSD

TM 2 & Highest




Maximum PPSD

TM 3 & Lowest



Maximum PPSD

TM 3 & Middle



Maximum PPSD

TM 3 & Highest



8.4 Out of band emissions at the band edge / conducted spurious emissions

■ Test requirements and limit, §15.247(d)

§15.247(d) specifies that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated **by at least 20 dB** relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in band average PSD level.

In either case, attenuation to levels below the general emission limits specified in §15.209(a) is not required.

■ Test Configuration:

Refer to the APPENDIX I.

■ Test Procedure

- KDB558074 D01v05r02 - Section 8.5
- ANSI C63.10-2013 – Section 11.11

Reference level measurement

1. Set instrument center frequency to DTS channel center frequency.
2. Set the span to ≥ 1.5 times the DTS bandwidth.
3. Set the RBW = 100 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = Peak.
6. Sweep time = Auto couple.
7. Trace mode = Max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum PSD level.

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured.
2. Set the RBW = 100 kHz. (Actual 1 MHz , See below note)
3. Set the VBW $\geq 3 \times$ RBW. (Actual 3 MHz, See below note)
4. Detector = Peak.
5. Ensure that the number of measurement points \geq Span / RBW.
6. Sweep time = Auto couple.
7. Trace mode = Max hold.
8. Allow the trace to stabilize. (this may take some time, depending on the extent of the span)
9. Use the peak marker function to determine the maximum amplitude level.

Note: The conducted spurious emission was tested with below settings.

Frequency range: 9 kHz ~ 30 MHz

RBW = 100 kHz, VBW = 300 kHz, Sweep time = Auto, Detector = Peak, Trace = Max hold, Sweep points: 40 001

Frequency range: 30 MHz ~ 10 GHz, 10 GHz ~ 25 GHz


RBW = 1 MHz, VBW = 3 MHz, Sweep time = Auto, Detector = Peak, Trace = Max hold, Sweep points: 40 001

LIMIT LINE = 20 dB below of the reference level of above measurement procedure Step 2. (RBW = 100 kHz, VBW = 300 kHz)


If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 kHz, VBW = 300 kHz, SPAN = 100 MHz and BINS = 2 001 to get accurate emission level within 100 kHz BW.

□ RESULT PLOTS



TM 1 & Lowest Reference



Low Band-edge





Conducted Spurious Emissions





Conducted Spurious Emissions



TM 1 & Middle
Reference

Conducted Spurious Emissions



Conducted Spurious Emissions





TM 1 & Highest Reference




High Band-edge



Conducted Spurious Emissions



Conducted Spurious Emissions



TM 2 & Lowest



Reference




Low Band-edge



Conducted Spurious Emissions



Conducted Spurious Emissions




TM 2 & Middle



Reference



Conducted Spurious Emissions



Conducted Spurious Emissions




TM 2 & Highest



Reference



High Band-edge




Conducted Spurious Emissions





Conducted Spurious Emissions




TM 3 & Lowest
Reference

Low Band-edge


Conducted Spurious Emissions



Conducted Spurious Emissions




TM 3 & Middle



Reference




Conducted Spurious Emissions





Conducted Spurious Emissions



TM 3 & Highest
Reference

High Band-edge


Conducted Spurious Emissions



Conducted Spurious Emissions



8.5 Radiated spurious emissions

Test Requirements and limit, §15.247(d), §15.205, §15.209

In any 100 kHz bandwidth outside the operating frequency band, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 KHz bandwidth within the band. In case the emission fall within the restricted band specified on 15.205(a) and (b), then the 15.209(a) limit in the table below has to be followed.

• FCC Part 15.209(a) and (b)

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 – 0.490	2 400 / F (kHz)	300
0.490 – 1.705	24 000 / F (kHz)	30
1.705 – 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 MHz - 72 MHz, 76 MHz - 88 MHz, 174 MHz - 216 MHz or 470 MHz - 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

• FCC Part 15.205 (a): Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.414 25 ~ 8.414 75	108 ~ 121.94	1 300 ~ 1 427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1 435 ~ 1 626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.173 5 ~ 2.190 5	12.519 75 ~ 12.520 25	149.9 ~ 150.05	1 645.5 ~ 1 646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.576 75 ~ 12.577 25	156.524 75 ~ 156.525 25	1 660 ~ 1 710	8.025 ~ 8.5	22.01 ~ 23.12
4.177 25 ~ 4.177 75	13.36 ~ 13.41	156.7 ~ 156.9	1 718.8 ~ 1 722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.207 25 ~ 4.207 75	16.42 ~ 16.423	162.0125 ~ 167.17	2 200 ~ 2 300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.694 75 ~ 16.695 25	167.72 ~ 173.2	2 310 ~ 2 390	10.6 ~ 12.7	36.43 ~ 36.5
6.267 75 ~ 6.268 25	16.804 25 ~ 16.804 75	240 ~ 285	2 483.5 ~ 2 500	13.25 ~ 13.4	Above 38.6
6.311 75 ~ 6.312 25	25.5 ~ 25.67	322 ~ 335.4	2 690 ~ 2 900		
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3 260 ~ 3 267		
8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3 332 ~ 3 339		
8.376 25 ~ 8.386 75	74.8 ~ 75.2	960 ~ 1 240	3 345.8 ~ 3 358		
			3 600 ~ 4 400		

- **FCC Part 15.205(b):** The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

■ Test Configuration

Refer to the APPENDIX I.

■ Test Procedure

1. The EUT is placed on a non-conductive table, emission measurements at below 1 GHz, the table height is 80 cm and above 1 GHz, the table height is 1.5 m.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 1 or 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

- KDB558074 D01v05r02 - Section 8.6

- ANSI C63.10-2013 – Section 11.12

Peak Measurement

RBW = As specified in below table, VBW \geq 3 x RBW, Sweep = Auto, Detector = Peak, Trace mode = Max Hold until the trace stabilizes.

Frequency	RBW
9 kHz – 150 kHz	200 Hz – 300 Hz
0.15 MHz – 30 MHz	9 kHz – 10 kHz
30 MHz – 1 000 MHz	100 kHz – 120 kHz
> 1 000 MHz	1 MHz

Average Measurement:

1. RBW = 1 MHz (unless otherwise specified).
 2. VBW \geq 3 x RBW.
 3. Detector = RMS (Number of points \geq 2 x Span / RBW)
 4. Averaging type = power. (i.e., RMS)
 5. Sweep time = auto.
 6. Perform a trace average of at least 100 traces.
7. A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

- 1) If power averaging (RMS) mode was used in step 4, then the applicable correction factor is $10 \log(1 / D)$, where D is the duty cycle.
- 2) If linear voltage averaging mode was used in step 4, then the applicable correction factor is $20 \log(1 / D)$, where D is the duty cycle.
- 3) If a specific emission is demonstrated to be continuous (\geq 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

Duty Cycle Correction factor

Test Mode	Date rate	T _{on} (ms)	T _{on+off} (ms)	D = T _{on} / (T _{on+off})	DCCF = 10 log(1 / D) (dB)
TM 1	1 Mbps	12.420	12.510	0.9928	N/A
TM 2	6 Mbps	2.064	2.165	0.9533	0.21
TM 3	MCS 0	1.920	2.021	0.9500	0.22

Note1: Where, T= Transmission duration / D = Duty cycle

Note2: Please refer to the appendix I for duty cycle plots.

■ Test Results: Comply

Test Notes.

1. The radiated emissions were investigated 9 kHz to 25 GHz. And no other spurious and harmonic emissions were found below listed frequencies.
2. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F+ DCCF + DCF / T.F = AF + CL + HL + AL – AG

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain, HL = High pass filter Loss, AL = Attenuator Loss, DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor

3. Information of Distance Correction Factor

For finding emissions, measurements may be performed at a distance closer than that specified in the regulations.

In this case, the distance correction factor is applied to the result.

- Calculation of distance correction factor

At frequencies below 30 MHz = $40 \log(\text{tested distance} / \text{specified distance})$

At frequencies at or above 30 MHz = $20 \log(\text{tested distance} / \text{specified distance})$

When distance factor is "N/A", the measurements were performed at the specified distance and distance factor is not applied.

Radiated Spurious Emissions data(9 kHz ~ 25 GHz) : TM 1 & MN: DA330DJAN

Tested Frequency	Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
Lowest	2 389.75	H	X	PK	49.85	8.46	N/A	N/A	58.31	74.00	15.69
	2 389.67	H	X	AV	38.65	8.46	N/A	N/A	47.11	54.00	6.89
	4 824.32	H	X	PK	48.95	1.78	N/A	N/A	50.73	74.00	23.27
	4 824.41	H	X	AV	39.01	1.78	N/A	N/A	40.79	54.00	13.21
	7 235.20	V	X	PK	46.16	8.31	N/A	N/A	54.47	74.00	19.53
	7 237.08	V	X	AV	36.52	8.32	N/A	N/A	44.84	54.00	9.16
Middle	4 873.84	H	X	PK	49.90	2.12	N/A	N/A	52.02	74.00	21.98
	4 873.97	H	X	AV	39.22	2.12	N/A	N/A	41.34	54.00	12.66
	7 310.11	V	X	PK	45.25	8.79	N/A	N/A	54.04	74.00	19.96
	7 309.80	V	X	AV	35.55	8.79	N/A	N/A	44.34	54.00	9.66
Highest	2 483.75	H	X	PK	48.39	9.09	N/A	N/A	57.48	74.00	16.52
	2 483.78	H	X	AV	38.84	9.09	N/A	N/A	47.93	54.00	6.07
	4 924.42	H	X	PK	49.63	2.45	N/A	N/A	52.08	74.00	21.92
	4 923.99	H	X	AV	39.22	2.45	N/A	N/A	41.67	54.00	12.33
	7 386.87	V	X	PK	44.90	8.53	N/A	N/A	53.43	74.00	20.57
	7 385.20	V	X	AV	35.42	8.54	N/A	N/A	43.96	54.00	10.04

Radiated Spurious Emissions data(9 kHz ~ 25 GHz) : TM 2 & MN: DA330DJAN

Tested Frequency (MHz)	Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
Lowest	2 389.18	H	X	PK	49.31	8.45	N/A	N/A	57.76	74.00	16.24
	2 389.25	H	X	AV	38.65	8.45	0.21	N/A	47.31	54.00	6.69
	4 824.18	H	X	PK	48.61	1.78	N/A	N/A	50.39	74.00	23.61
	4 824.16	H	X	AV	38.79	1.78	0.21	N/A	40.78	54.00	13.22
	7 236.77	V	X	PK	45.54	8.32	N/A	N/A	53.86	74.00	20.14
	7 236.67	V	X	AV	35.69	8.32	0.21	N/A	44.22	54.00	9.78
Middle	4 873.84	H	X	PK	49.77	2.12	N/A	N/A	51.89	74.00	22.11
	4 873.65	H	X	AV	38.85	2.12	0.21	N/A	41.18	54.00	12.82
	7 311.67	V	X	PK	45.93	8.80	N/A	N/A	54.73	74.00	19.27
	7 310.55	V	X	AV	35.21	8.79	0.21	N/A	44.21	54.00	9.79
Highest	2 484.75	H	X	PK	48.65	9.10	N/A	N/A	57.75	74.00	16.25
	2 484.81	H	X	AV	38.56	9.10	0.21	N/A	47.87	54.00	6.13
	4 923.67	H	X	PK	48.96	2.44	N/A	N/A	51.40	74.00	22.60
	4 924.44	H	X	AV	38.86	2.45	0.21	N/A	41.52	54.00	12.48
	7 384.72	V	X	PK	44.97	8.54	N/A	N/A	53.51	74.00	20.49
	7 383.37	V	X	AV	35.46	8.55	0.21	N/A	44.22	54.00	9.78

Radiated Spurious Emissions data(9 kHz ~ 25 GHz) : TM 3 & MN: DA330DJAN

Tested Frequency	Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
Lowest	2 389.54	H	X	PK	49.25	8.46	N/A	N/A	57.71	74.00	16.29
	2 389.50	H	X	AV	38.29	8.46	0.22	N/A	46.97	54.00	7.03
	4 823.85	H	X	PK	49.55	1.78	N/A	N/A	51.33	74.00	22.67
	4 824.53	H	X	AV	38.89	1.79	0.22	N/A	40.90	54.00	13.10
	7 236.11	V	X	PK	45.37	8.31	N/A	N/A	53.68	74.00	20.32
	7 236.34	V	X	AV	35.51	8.32	0.22	N/A	44.05	54.00	9.95
Middle	4 874.05	H	X	PK	49.96	2.12	N/A	N/A	52.08	74.00	21.92
	4 873.79	H	X	AV	38.73	2.12	0.22	N/A	41.07	54.00	12.93
	7 311.30	V	X	PK	45.35	8.80	N/A	N/A	54.15	74.00	19.85
	7 310.52	V	X	AV	35.11	8.79	0.22	N/A	44.12	54.00	9.88
Highest	2 483.86	H	X	PK	49.41	9.09	N/A	N/A	58.50	74.00	15.50
	2 483.85	H	X	AV	38.46	9.09	0.22	N/A	47.77	54.00	6.23
	4 923.74	H	X	PK	49.64	2.44	N/A	N/A	52.08	74.00	21.92
	4 924.45	H	X	AV	38.78	2.45	0.22	N/A	41.45	54.00	12.55
	7 386.36	V	X	PK	44.90	8.53	N/A	N/A	53.43	74.00	20.57
	7 386.59	V	X	AV	35.33	8.53	0.22	N/A	44.08	54.00	9.92

Radiated Spurious Emissions data(9 kHz ~ 25 GHz) : TM 1 & MN: DA331DJAN

Tested Frequency	Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
Highest	2 483.95	H	X	PK	49.10	9.09	N/A	N/A	58.19	74.00	15.81
	2 484.21	H	X	AV	38.70	9.09	N/A	N/A	47.79	54.00	6.21
	4 923.66	H	X	PK	49.82	2.44	N/A	N/A	52.26	74.00	21.74
	4 923.54	H	X	AV	38.92	2.44	N/A	N/A	41.36	54.00	12.64
	7 385.18	V	X	PK	45.15	8.54	N/A	N/A	53.69	74.00	20.31
	7 386.67	V	X	AV	35.44	8.53	N/A	N/A	43.97	54.00	10.03

8.6 Power-line conducted emissions

■ Test Requirements and limit, §15.207

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network(LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

■ Test Configuration

See test photographs for the actual connections between EUT and support equipment.

■ Test Procedure

Conducted emissions from the EUT were measured according to the ANSI C63.10-2013.

1. The test procedure is performed in a 6.5 m × 3.5 m × 3.5 m (L × W × H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) × 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

■ Test Results: NA

9. LIST OF TEST EQUIPMENT

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	19/12/16	20/12/16	MY50410357
Spectrum Analyzer	Agilent Technologies	N9020A	19/12/16	20/12/16	MY48011700
Spectrum Analyzer	Agilent Technologies	N9020A	20/06/24	21/06/24	US47360812
DC Power Supply	Agilent Technologies	66332A	20/06/24	21/06/24	MY43000211
Multimeter	FLUKE	17B	19/12/16	20/12/16	26030065WS
Signal Generator	Rohde Schwarz	SMBV100A	19/12/16	20/12/16	255571
Signal Generator	ANRITSU	MG3695C	19/12/16	20/12/16	173501
Thermohygrometer	BODYCOM	BJ5478	19/12/18	20/12/18	120612-1
Thermohygrometer	BODYCOM	BJ5478	19/12/18	20/12/18	120612-2
Thermohygrometer	BODYCOM	BJ5478	20/07/01	21/07/01	N/A
HYGROMETER	TESTO	608-H1	20/01/21	21/01/21	34862883
Loop Antenna	ETS-Lindgren	6502	19/09/18	21/09/18	00226186
BILOG ANTENNA	Schwarzbeck	VULB 9160	19/04/23	21/04/23	9160-3362
Horn Antenna	ETS-Lindgren	3117	20/10/23	21/10/23	00143278
Horn Antenna	A.H.Systems Inc.	SAS-574	20/06/24	21/06/24	155
PreAmplifier	tsj	MLA-0118-B01-40	19/12/16	20/12/16	1852267
PreAmplifier	tsj	MLA-1840-J02-45	20/06/24	21/06/24	16966-10728
PreAmplifier	H.P	8447D	19/12/16	20/12/16	2944A07774
High Pass Filter	Wainwright Instruments	WHKX12-935-1000-15000-40SS	20/06/24	21/06/24	8
High Pass Filter	Wainwright Instruments	WHKX10-2838-3300-18000-60SS	20/06/24	21/06/24	1
High Pass Filter	Wainwright Instruments	WHNX8.0/26.5-6SS	20/06/24	21/06/24	3
Attenuator	SMAJK	SMAJK-50-10	20/06/24	21/06/24	15081901
Attenuator	Hefei Shunze	SS5T2.92-10-40	20/06/24	21/06/24	16012202
Attenuator	SRTechnology	F01-B0606-01	20/06/24	21/06/24	13092403
Attenuator	Aeroflex/Weinschel	56-3	20/06/24	21/06/24	Y2370
Attenuator	SMAJK	SMAJK-2-3	20/06/24	21/06/24	2
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2488B MA2491A	20/01/02	21/01/02	0910025 0845333
Cable	Junkosha	MWX241	20/01/13	21/01/13	G-04
Cable	Junkosha	MWX241	20/01/13	21/01/13	G-07
Cable	DT&C	Cable	20/01/13	21/01/13	G-13
Cable	DT&C	Cable	20/01/13	21/01/13	G-14
Cable	HUBER+SUHNER	SUCOFLEX 104	20/01/13	21/01/13	G-15
Cable	Radiall	TESTPRO3	20/01/16	21/01/16	M-01
Cable	Junkosha	MWX315	20/01/16	21/01/16	M-05
Cable	Junkosha	MWX221	20/01/16	21/01/16	M-06
Cable	DT&C	Cable	20/01/13	21/01/13	RF-18
Test Software	tsj	Radiated Emission Measurement	NA	NA	Version 2.00.0177


Note 1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017

Note 2: The cable is not a regular calibration item, so it has been calibrated by DT & C itself.


APPENDIX I

Test set up diagrams

- Radiated Measurement



- Conducted Measurement



Path loss information

Frequency (GHz)	Path Loss (dB)	Frequency (GHz)	Path Loss (dB)
0.03	9.55	15	11.05
1	9.61	20	11.59
2.412 & 2.437 & 2.462	10.41	25	11.72
5	10.44	-	-
10	10.73	-	-

Note 1: The path loss from EUT to Spectrum analyzer was measured and used for test.
 Path loss (S/A's correction factor) = Cable A + Attenuator

APPENDIX II

Duty cycle plots

- **Test Procedure**


Duty Cycle was measured using **section 6.0 b) of KDB558074 D01v05r02** :

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value. Set VBW \geq RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)


Duty Cycle

TM 1 & Middle




Duty Cycle

TM 2 & Middle


Duty Cycle

TM 3 & Middle




APPENDIX III

Unwanted Emissions (Radiated) Test Plot _ MN: DA330DJAN

TM 1 & Lowest & X axis & Hor


Detector Mode : PK







TM 1 & Lowest & X axis & Hor



Detector Mode : AV






TM 1 & Highest & X axis & Hor
Detector Mode : PK

TM 1 & Highest & X axis & Hor
Detector Mode : AV


TM 2 & Lowest & X axis & Hor
Detector Mode : PK

TM 2 & Lowest & X axis & Hor
Detector Mode : AV


TM 2 & Highest & X axis & Hor
Detector Mode : PK

TM 2 & Highest & X axis & Hor
Detector Mode : AV



TM 3 & Lowest & X axis & Hor
Detector Mode : PK

TM 3 & Lowest & X axis & Hor
Detector Mode : AV


TM 3 & Highest & X axis & Hor
Detector Mode : PK

TM 3 & Highest & X axis & Hor
Detector Mode : AV


TM 1 & Lowest & X axis & Ver
Detector Mode : AV

TM 2 & Lowest & X axis & Ver
Detector Mode : AV


TM 3 & Middle & X axis & Ver


Detector Mode : AV



Unwanted Emissions (Radiated) Test Plot _ MN: DA331DJAN

TM 1 & Highest & X axis & Hor

Detector Mode : PK



TM 1 & Highest & X axis & Hor

Detector Mode : AV



TM 1 & Highest & X axis & Ver

Detector Mode : AV

