

Manual for vehicle manufacturer

Model name: FOB-4F36

OUTLINE

1. How to use FOB-4F36

- FOB-4F36 is a part of Remote Keyless System.
- This unit controls door lock/door unlock/trunk open/panic/remote engine start-stop/LAMP wirelessly.

2. Introduction of Transmitter (FOB-4F36)

- This unit has 6 buttons.
- This unit uses the battery
- Frequency is 433.92MHz

GENERAL DESCRIPTION

PRIMARY FUNCTION

- Remote door lock/door unlock/trunk open/panic/remote engine start-stop/LAMP
- Operating voltage: 3V DC
- Center freq.: 433.92MHz

MANUAL

1. LOCK Button

If the LOCK button is pressed, then TRANSMITTER sends the LOCK data.

2. UNLOCK Button

If the UNLOCK button is pressed, then TRANSMITTER sends the UNLOCK data.

3. TRUNK Button

If the TRUNK button is pressed, then TRANSMITTER sends the TRUNK data.

4. PANIC Button

If the PANIC button is pressed, then TRANSMITTER sends the PANIC data.

5. START-STOP Button

If the REMOTE ENGINE START-STOP button is pressed, then TRANSMITTER sends START-STOP data.

6. LAMP Button

If the LAMP Button is pressed, then TRANSMITTER sends the LAMP data.

FCC/ISED NOTICE

[FCC]

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

This transmitter must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC

[ISED]

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

1. This device may not cause interference.
2. This device must accept any interference, including interference that may cause undesired operation of the device.

L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

1. L'appareil ne doit pas produire de brouillage;
2. L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

This equipment complies with ISED radiation exposure limits set forth for an uncontrolled environment.

This transmitter must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the ISED

Cet appareil est conforme aux limites d'exposition aux rayonnements de l'ISDE pour un environnement non contrôlé.

L'émetteur ne doit pas être colocalisé ni fonctionner conjointement avec à autre antenne ou autre émetteur, à moins d'y être autorise par l'ISDE.