

HYUNDAI MOBIS CO.,LTD.

80-9, Mabook-Dong, Giheung-Gu Yongin-shi, Gyunggi-Do South Korea 446-912

DATE: September 7, 2012

FCC ID: TQ8-RKE-3F05

This device contains a transmitter that HYUNDAI MOBIS Co., LTD. confirms in compliance with the following Part 15 regulations:

15.231 (a)(1)

The following conditions shall be met to comply with the provisions for this periodic operation:

(1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

15.231 (b)

the field strength of emissions from Intentional radiators operated under this section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of fundamental (uV/m)	Field Strength of Spurious Emissions (uV/m)
40.66 ~ 40.70	22.50	225
70 ~ 130	1250	125
130 ~ 174	1250 to 3750 **	125 to 375 **
174 ~ 260	3750	375
260 ~ 470	3750 to 12500 **	375 to 1250 **
Above 470	12500	1250

15.231 (C)

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz.

Sign



Jong Tae Kim
HYUNDAI MOBIS CO.,LTD