



**Neutron Engineering Inc.**

# FCC & IC Radio Test Report

**FCC ID: TQYBS41IK5BTL00**

**IC: 6223A-41IK5BTL** (for Model 41IK5BTL)

**IC: 6223A-41IK5BTV** (for Model 41IK5BT2V2)

This report concerns (check one) :  Original Grant  Class II Change

**Issued Date** : Mar. 20, 2014

**Project No.** : 1402042

**Equipment** : Amphitheater

**Model Name** : 41IK5BTL; 41IK5BT2V2

**Applicant** : JAZZ HIPSTER CORPORATION

**Address** : 2F, 512 Yuan-San Road, Zhonghe  
District, New Taipei City, Taiwan

**Tested by:** Neutron Engineering Inc. EMC Laboratory

**Date of Receipt:** Feb. 10, 2014

**Date of Test:** Feb. 10, 2014 ~ Mar. 18, 2014

**Testing Engineer:** Gary Chou  
(Gary Chou)

**Technical Manager:** Jeff Yang  
(Jeff Yang)

**Authorized Signatory:** Andy Chiu  
(Andy Chiu)

**Neutron Engineering Inc.**  
B1, No. 37, Lane 365, YangGuang St.,  
NeiHu District 114, Taipei, Taiwan.

TEL: +886-2-2657-3299

FAX: +886-2-2657-3331





## Declaration

**Neutron** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

**Neutron's** reports apply only to the specific samples tested under conditions. It is manufacturer's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

**Neutron's** reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

**Neutron's** laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

## Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



## Table of Contents

REPORT ISSUED HISTORY	6
1 CERTIFICATION	7
2 . SUMMARY OF TEST RESULTS	8
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
3 GENERAL INFORMATION	10
3.1 GENERAL DESCRIPTION OF EUT	10
3.2 DESCRIPTION OF TEST MODES	12
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	13
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	14
3.5 DESCRIPTION OF SUPPORT UNITS	15
4 CONDUCTED EMISSION	16
4.1 LIMIT	16
4.2 MEASUREMENT INSTRUMENTS LIST	16
4.3 TEST PROCEDURES	17
4.4 TEST SETUP LAYOUT	17
4.5 DEVIATION FROM TEST STANDARD	17
4.6 EUT OPERATING CONDITIONS	18
4.7 TEST RESULTS	19
5 ANTENNA CONDUCTED SPURIOUS EMISSION	21
5.1 LIMIT	21
5.2 MEASUREMENT INSTRUMENTS LIST	21
5.3 TEST PROCEDURES	21
5.4 TEST SETUP LAYOUT	21
5.5 DEVIATION FROM TEST STANDARD	21
5.6 EUT OPERATING CONDITIONS	21
5.7 TEST RESULTS	22
6 HOPPING CHANNEL SEPARATION	30
6.1 LIMIT	30
6.2 MEASUREMENT INSTRUMENTS LIST	30
6.3 MEASURING INSTRUMENTS SETTING	30
6.4 TEST PROCEDURES	30
6.5 TEST SETUP LAYOUT	30
6.6 DEVIATION FROM TEST STANDARD	30
6.7 EUT OPERATING CONDITIONS	30
6.8 TEST RESULTS	31
7 MAXIMUM PEAK CONDUCTED OUTPUT POWER	39
7.1 LIMIT	39



## Table of Contents

7.2	MEASUREMENT INSTRUMENTS LIST	39
7.3	TEST PROCEDURES	39
7.4	TEST SETUP LAYOUT	39
7.5	DEVIATION FROM TEST STANDARD	39
7.6	EUT OPERATING CONDITIONS	39
7.7	TEST RESULTS	40
8	RADIATED SPURIOUS EMISSION (9 KHZ TO 1 GHZ)	44
8.1	LIMIT	44
8.2	MEASUREMENT INSTRUMENTS LIST	45
8.3	MEASURING INSTRUMENTS SETTING	45
8.4	TEST PROCEDURES	46
8.5	DEVIATION FROM TEST STANDARD	46
8.6	TEST SETUP LAYOUT	46
8.7	EUT OPERATING CONDITIONS	47
8.8	TEST RESULTS	48
9	RADIATED SPURIOUS EMISSION (ABOVE 1 GHZ)	50
9.1	LIMIT	50
9.2	MEASUREMENT INSTRUMENTS LIST	51
9.3	MEASURING INSTRUMENTS SETTING	51
9.4	TEST PROCEDURES	52
9.5	DEVIATION FROM TEST STANDARD	52
9.6	TEST SETUP LAYOUT	52
9.7	EUT OPERATING CONDITIONS	53
9.8	TEST RESULTS	54
9.9	TEST RESULTS (RESTRICTED BANDS)	78
10	NUMBER OF HOPPING FREQUENCY	86
10.1	LIMIT	86
10.2	MEASUREMENT INSTRUMENTS LIST	86
10.3	MEASURING INSTRUMENTS SETTING	86
10.4	TEST PROCEDURES	86
10.5	TEST SETUP LAYOUT	86
10.6	DEVIATION FROM TEST STANDARD	86
10.7	EUT OPERATING CONDITIONS	86
10.8	TEST RESULTS	87
11	AVERAGE TIME OF OCCUPANCY	89
11.1	LIMIT	89
11.2	MEASUREMENT INSTRUMENTS LIST	89
11.3	TEST PROCEDURES	89



## **Table of Contents**

11.4	TEST SETUP LAYOUT	89
11.5	DEVIATION FROM TEST STANDARD	89
11.6	EUT OPERATING CONDITIONS	90
11.7	TEST RESULTS	91
12	EUT TEST PHOTO	103



**REPORT ISSUED HISTORY**

Issue No.	Description	Issued Date
NEI-FCCP-1-1402042	Original Issue.	Mar. 20, 2014



## **1 CERTIFICATION**

Equipment : Amphitheater  
Brand Name : KICKER  
Model Name : 41IK5BTL; 41iK5BT2V2  
Applicant : JAZZ HIPSTER CORPORATION  
Date of Test : Feb. 10, 2014 ~ Mar. 18, 2014  
Standards : RSS-210, Issue 8, 2010  
                  FCC Part 15, Subpart C: 2012  
                  ANSI C63.4: 2009

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-1402042) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).



## 2. SUMMARY OF TEST RESULTS

RSS-210, Issue 8, 2010; FCC Part 15, Subpart C: 2012			
Standard Clause		Test Item	Result
RSS-210	FCC Part 15, Subpart C		
NOTE (2)	15.207	Conducted Emission	<b>PASS</b>
A8.5	15.247 (c)	Antenna conducted Spurious Emission	<b>PASS</b>
A8.1 (b)	15.247 (a)(1)	Hopping Channel Separation	<b>PASS</b>
A8.4 (2)	15.247 (b)	Maximum Peak Conducted Output Power	<b>PASS</b>
NOTE (3)	15.247 (c)	Radiated Spurious Emission	<b>PASS</b>
A8.1 (d)	15.247 (b)(1)	Number of Hopping Frequency	<b>PASS</b>
A8.1 (d)	15.247 (a)(1)	Average time of occupancy	<b>PASS</b>
NOTE (4)	15.205	Restricted Bands	<b>PASS</b>
NOTE (5)	15.203	Antenna Requirement	<b>PASS</b>

NOTE:

1. **N/A:** denotes test is not applicable in this Test Report
2. Reference standard is RSS-GEN 7.2.4
3. Reference standard is RSS-GEN 7.2.5
4. Reference standard is RSS-GEN 7.2.2
5. Reference standard is RSS-GEN 7.1.2



## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report:

### Conducted emission Test:

**C02:** (VCCI RN: C-3477; FCC RN: 614388; FCC DN: TW1054)

1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

### Radiated emission Test (Below 1 GHz):

**CB08:** (FCC RN: 614388; FCC DN: TW1054; IC Assigned Code: 4428C-1)

1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

### Radiated emission Test (Above 1 GHz):

**CB08:** (VCCI RN: G-91; FCC RN: 614388; FCC DN: TW1054; IC Assigned Code: 4428C-1)

1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

## 2.2 MEASUREMENT UNCERTAINTY

**The measurement uncertainty is not specified by FCC/Industry Canada rules and for reference only.**

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95%**.

The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

### A. Conducted emission test:

Test Site	Measurement Frequency Range	U , (dB)	NOTE
C02	150 kHz ~ 30 MHz	2.59	

### B. Radiated emission test:

Test Site	Item	Measurement Frequency Range	Uncertainty	NOTE
CB08	Radiated emission at 3m	Horizontal Polarization	30 - 200MHz	3.35 dB
			200 - 1000MHz	3.11 dB
			1 - 18GHz	3.97 dB
			18 - 40GHz	4.01 dB
	Radiated emission at 3m	Vertical Polarization	30 - 200MHz	3.22 dB
			200 - 1000MHz	3.24 dB
			1 - 18GHz	4.05 dB
			18 - 40GHz	4.04 dB

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our  $U_{lab}$  values in CISPR 16-4-2 terminology.

Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called  $U_{CISPR}$ , as follows:

Conducted Disturbance (mains port) – 150 kHz – 30 MHz : 3.6 dB

Radiated Disturbance (electric field strength on an open area test site or alternative test site) – 30 MHz – 1000 MHz : 5.2 dB

It can be seen that our  $U_{lab}$  values are smaller than  $U_{CISPR}$ .



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Equipment	Amphitheater																										
Brand Name	KICKER																										
Model Name	41IK5BTL; 41iK5BT2V2																										
OEM Brand/Model Name	N/A																										
Model Difference	<p>All models are technically identical to each other, only differ in: 1. Model Name; 2. IC ID; 3. Apple 8 pin Lighting.</p> <table border="1"><tr><td>Model Name</td><td>IC ID</td><td>Apple 8 pin Lighting</td></tr><tr><td>41IK5BTL</td><td>6223A-41IK5BTL</td><td>YES</td></tr><tr><td>41iK5BT2V2</td><td>6223A-41IK5BTV</td><td>NO</td></tr></table> <p>41IK5BTL was found to be the worst case and used for final testing and collecting test data included in this report.</p>			Model Name	IC ID	Apple 8 pin Lighting	41IK5BTL	6223A-41IK5BTL	YES	41iK5BT2V2	6223A-41IK5BTV	NO															
Model Name	IC ID	Apple 8 pin Lighting																									
41IK5BTL	6223A-41IK5BTL	YES																									
41iK5BT2V2	6223A-41IK5BTV	NO																									
Product Description	<table border="1"><tr><td>Operation Frequency</td><td colspan="2">2402 MHz ~ 2480 MHz</td></tr><tr><td>Modulation Type</td><td colspan="2">FHSS(GFSK, π/4-DQPSK, 8-DPSK)</td></tr><tr><td>Bit Rate of Transmitter</td><td colspan="2">1/2/3 Mbps</td></tr><tr><td>Number Of Channel</td><td colspan="2">Please refer to the Note 2.</td></tr><tr><td>Antenna Designation</td><td colspan="2">Please refer to the Note 3.</td></tr><tr><td>Antenna Gain(Peak)</td><td colspan="2">Please refer to the Note 3.</td></tr><tr><td>Maximum Peak Conducted</td><td colspan="2">1 Mbps: -2.61 dBm (0.0005 W)</td></tr><tr><td>Output Power:</td><td colspan="2">3 Mbps: -9.90 dBm (0.0001 W)</td></tr></table> <p>More details of EUT technical specification please refer to the User's Manual.</p>			Operation Frequency	2402 MHz ~ 2480 MHz		Modulation Type	FHSS(GFSK, π/4-DQPSK, 8-DPSK)		Bit Rate of Transmitter	1/2/3 Mbps		Number Of Channel	Please refer to the Note 2.		Antenna Designation	Please refer to the Note 3.		Antenna Gain(Peak)	Please refer to the Note 3.		Maximum Peak Conducted	1 Mbps: -2.61 dBm (0.0005 W)		Output Power:	3 Mbps: -9.90 dBm (0.0001 W)	
Operation Frequency	2402 MHz ~ 2480 MHz																										
Modulation Type	FHSS(GFSK, π/4-DQPSK, 8-DPSK)																										
Bit Rate of Transmitter	1/2/3 Mbps																										
Number Of Channel	Please refer to the Note 2.																										
Antenna Designation	Please refer to the Note 3.																										
Antenna Gain(Peak)	Please refer to the Note 3.																										
Maximum Peak Conducted	1 Mbps: -2.61 dBm (0.0005 W)																										
Output Power:	3 Mbps: -9.90 dBm (0.0001 W)																										
Power Source	DC Voltage supplied from External Power Supply.																										
Power Rating	I/P: AC 100-240V 50/60Hz 1.5A / O/P: DC 24V 2900mA 69.6W																										
Connecting I/O Port(s)	Please refer to the User's Manual																										
Products Covered	1 * SWITCHING MODE POWER SUPPLY: KICKER, GPE060D-240290D 1 * Remote Control																										
EUT Modification(s)	N/A																										



# Neutron Engineering Inc.

## NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Printed	N/A	0.18



### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test Items	Mode	Data Rate	Tested Channel/Mode
Conducted Emission	GFSK	1 Mbps	2441 MHz
Antenna conducted Spurious Emission	GFSK	1 Mbps	2402 MHz, 2441 MHz, 2480 MHz
	8DPSK	3 Mbps	
Hopping Channel Separation	GFSK	1 Mbps	2402 MHz, 2441 MHz, 2480 MHz
	8DPSK	3 Mbps	
Maximum Peak Conducted Output Power	GFSK	1 Mbps	2402 MHz, 2441 MHz, 2480 MHz
	8DPSK	3 Mbps	
Radiated Spurious Emission (30 MHz to 1 GHz)	GFSK	1 Mbps	2441 MHz
Radiated Spurious Emission (above 1 GHz)	GFSK	1 Mbps	2402 MHz, 2441 MHz, 2480 MHz
	8DPSK	3 Mbps	
Number of Hopping Frequency	GFSK	1 Mbps	2402 MHz ~ 2480 MHz
	8DPSK	3 Mbps	
Average time of occupancy	GFSK	1 Mbps	2402 MHz, 2441 MHz, 2480 MHz
	8DPSK	3 Mbps	
Restricted Bands	GFSK	1 Mbps	2402 MHz, 2480 MHz
	8DPSK	3 Mbps	
Antenna Requirement	GFSK	---	---

NOTE: The measurements are performed at the highest, middle, lowest available channels.



### **3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING**


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Data Rate	1 Mbps		
Test software Version	Bluetest 3		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameter	60	60	60

Data Rate	3 Mbps		
Test software Version	Bluetest 3		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameter	120	120	120



### **3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED**



C-1 DATA Cable  
C-2 VGA Cable  
C-3 USB Cable  
C-4 USB Cable  
C-5 DATA Cable  
C-6 USB Cable



### **3.5 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID/IC ID	Series No.	Note
E-1	Amphitheater	KICKER	41IK5BTL	TQYBS41IK5BTL00 6223A-41IK5BTL	N/A	EUT
E-2	PC	HP	HP Compaq dx7400	DOC	SGH7480DKZ	
E-3	Fixture	N/A	N/A	N/A	N/A	
E-4	USB K/B	DELL	L50U	DOC	N/A	
E-5	USB Mouse	DELL	MS111-L	DOC	CN-09RRC7-44751-1 7J-OH1F	
E-6	24" LCD Monitor	DELL	U2410f	DOC	CN-OJ257M-72872-0 9J-067L	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.8M	
C-2	YES	YES	1.8M	
C-3	YES	NO	1.8M	
C-4	YES	NO	1.5M	
C-5	YES	NO	1.5M	
C-6	YES	NO	1M	

NOTE: The support equipment was authorized by Declaration of Conformity (DOC).



## 4 CONDUCTED EMISSION

### 4.1 LIMIT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 - 5.0	73.00	60.00	56.00	46.00
5.0 - 30.0	73.00	60.00	60.00	50.00

NOTE:

1. The tighter limit applies at the band edges.
2. The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.
3. The test result calculated as following:

Measurement Value = Reading Level + Correct Factor

Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)

Margin Level = Measurement Value – Limit Value

### 4.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	Schwarzbeck	NSLK 8127	8127685	Jun. 3, 2014
2	Test Cable	TIMES	CFD300-NL	130	Jun. 13, 2014
3	EMI Test Receiver	Agilent	N9038A	MY51210215	Feb. 23, 2015
4	Measurement Software	EZ	EZ_EMCA (Version NB-02A)	N/A	N/A

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.




## 4.3 TEST PROCEDURES

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### NOTE:

- a. Reading in which marked as Peak, QP or AVG means measurements by using are Quasi-Peak or Average Mode with Detector BW=9 kHz (6 dB Bandwidth).
- b. All readings are Peak Mode value unless otherwise stated QP or AVG in column of Note. If the Peak or QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only Peak or QP Mode was measured, but AVG Mode didn't perform.

## 4.4 TEST SETUP LAYOUT



## 4.5 DEVIATION FROM TEST STANDARD

No deviation




#### **4.6 EUT OPERATING CONDITIONS**

The EUT was programmed to be in continuously transmitting mode.



## 4.7 TEST RESULTS

EUT	Amphitheater	Model Name	41IK5BTL
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	0.1521	44.32	8.65	52.97	65.88	-12.91	peak	
2		0.2200	37.60	9.18	46.78	62.82	-16.04	peak	
3		0.4776	31.67	8.96	40.63	56.38	-15.75	peak	
4		1.0670	28.31	8.96	37.27	56.00	-18.73	peak	
5		1.4540	27.74	9.10	36.84	56.00	-19.16	peak	
6		3.6680	23.05	9.57	32.62	56.00	-23.38	peak	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

### Phase: Neutral



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		0.1528	44.17	8.66	52.83	65.85	-13.02	peak	
2		0.1864	40.08	9.12	49.20	64.20	-15.00	peak	
3	*	0.4867	34.78	8.96	43.74	56.22	-12.48	peak	
4		1.1300	27.76	8.98	36.74	56.00	-19.26	peak	
5		1.4270	27.67	9.09	36.76	56.00	-19.24	peak	
6		11.7500	19.17	9.98	29.15	60.00	-30.85	peak	



## **5 ANTENNA CONDUCTED SPURIOUS EMISSION**

### **5.1 LIMIT**

Test Item	Frequency Range (MHz)	Limit
Antenna conducted Spurious Emission	30-25000	20 dB less than the peak value of fundamental frequency

### **5.2 MEASUREMENT INSTRUMENTS LIST**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

### **5.3 TEST PROCEDURES**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

### **5.4 TEST SETUP LAYOUT**



### **5.5 DEVIATION FROM TEST STANDARD**

No deviation

### **5.6 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 4.6 Unless otherwise a special operating condition is specified in the follows during the testing.




## 5.7 TEST RESULTS

EUT	Amphitheater	Model Name	41IK5BTL
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps		


Channel of Worst Data			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2399.80	-53.59	2483.80	-48.92
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.			



**Bluetooth/1 Mbps/The max. radio frequency power in any 100kHz bandwidth outside the frequency band**




**Bluetooth/1 Mbps/The max. radio frequency power in any 100 kHz bandwidth within the frequency band**






**Bluetooth/1 Mbps/2402 MHz/10 Harmonic of the frequency**




**Bluetooth/1 Mbps/2441 MHz/10 Harmonic of the frequency**





**Bluetooth/1 Mbps/2480 MHz/10 Harmonic of the frequency**






EUT	Amphitheater	Model Name	41IK5BTL
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps		


Channel of Worst Data			
The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.	
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)
2399.60	-58.42	2490.20	-58.21
Result			
In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.			



**Bluetooth/3 Mbps/The max. radio frequency power in any 100kHz bandwidth outside the frequency band**




**Bluetooth/3 Mbps/The max. radio frequency power in any 100 kHz bandwidth within the frequency band**






**Bluetooth/3 Mbps/2402 MHz/10 Harmonic of the frequency**




**Bluetooth/3 Mbps/2441 MHz/10 Harmonic of the frequency**





**Bluetooth/3 Mbps/2480 MHz/10 Harmonic of the frequency**





## **6 HOPPING CHANNEL SEPARATION**

### **6.1 LIMIT**

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

### **6.2 MEASUREMENT INSTRUMENTS LIST**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.


### **6.3 MEASURING INSTRUMENTS SETTING**

EMI Test Receiver	Parameter Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 300 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### **6.4 TEST PROCEDURES**

- a. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- b. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- c. The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised for channel separation measurement.

### **6.5 TEST SETUP LAYOUT**



### **6.6 DEVIATION FROM TEST STANDARD**

No deviation

### **6.7 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.



## 6.8 TEST RESULTS


EUT	Amphitheater	Model Name	41IK5BTL
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz, 2441 MHz, 2480 MHz		

Frequency	Channel Separation (MHz)	20 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Two-thirds of the 20 dB Bandwidth	Result
2402 MHz	1.002	0.938	0.852	0.625	PASS
2441 MHz	1.002	0.930	0.860	0.620	PASS
2480 MHz	1.008	0.930	0.872	0.620	PASS


NOTE: Ch. Separation Limits: >25 KHz or >2/3 of 20dB bandwidth



Bluetooth/1 Mbps/2402 MHz/Channel Separation




Bluetooth/1 Mbps/2402 MHz/20dB Bandwidth






Bluetooth/1 Mbps/2441 MHz/Channel Separation




Bluetooth/1 Mbps/2441 MHz/20dB Bandwidth






Bluetooth/1 Mbps/2480 MHz/Channel Separation



Bluetooth/1 Mbps/2480 MHz/20dB Bandwidth






EUT	Amphitheater	Model Name	41IK5BTL
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz, 2441 MHz, 2480 MHz		

Frequency	Channel Separation (MHz)	20 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Two-thirds of the 20 dB Bandwidth	Result
2402 MHz	1.008	1.261	1.168	0.841	PASS
2441 MHz	1.008	1.253	1.172	0.836	PASS
2480 MHz	1.002	1.285	1.168	0.857	PASS


NOTE: Ch. Separation Limits: >25 KHz or >2/3 of 20dB bandwidth



Bluetooth/3 Mbps/2402 MHz/Channel Separation




Bluetooth/3 Mbps/2402 MHz/20dB Bandwidth






Bluetooth/3 Mbps/2441 MHz/Channel Separation




Bluetooth/3 Mbps/2441 MHz/20dB Bandwidth






Bluetooth/3 Mbps/2480 MHz/Channel Separation



Bluetooth/3 Mbps/2480 MHz/20dB Bandwidth





## **7 MAXIMUM PEAK CONDUCTED OUTPUT POWER**

### **7.1 LIMIT**

Test Item	Frequency Range (MHz)	Limit
Maximum Peak Conducted Output Power	2400-2483.5	1 watt or 30 dBm

### **7.2 MEASUREMENT INSTRUMENTS LIST**


Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

### **7.3 TEST PROCEDURES**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 3 MHz, VBW= 3 MHz, Sweep time = Auto.

### **7.4 TEST SETUP LAYOUT**



### **7.5 DEVIATION FROM TEST STANDARD**

No deviation

### **7.6 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.




## 7.7 TEST RESULTS

EUT	Amphitheater	Model Name	41IK5BTL
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz, 2441 MHz, 2480 MHz		


Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2402 MHz	-2.61	0.0005	30	1	PASS
2441 MHz	-2.66	0.0005	30	1	PASS
2480 MHz	-3.11	0.0005	30	1	PASS

### Bluetooth/1 Mbps/2402 MHz/Peak Output Power






## Bluetooth/1 Mbps/2441 MHz/Peak Output Power



## Bluetooth/1 Mbps/2480 MHz/Peak Output Power






EUT	Amphitheater	Model Name	41IK5BTL
Temperature	26°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz, 2441 MHz, 2480 MHz		

Frequency	Peak Output Power		Limit		Result
	(dBm)	(W)	(dBm)	(W)	
2402 MHz	-9.90	0.0001	30	1	PASS
2441 MHz	-9.91	0.0001	30	1	PASS
2480 MHz	-10.49	0.0001	30	1	PASS

## Bluetooth/3 Mbps/2402 MHz/Peak Output Power






**Bluetooth/3 Mbps/2441 MHz/Peak Output Power**



**Bluetooth/3 Mbps/2480 MHz/Peak Output Power**





## **8 RADIATED SPURIOUS EMISSION (9 KHZ TO 1 GHZ)**

### **8.1 LIMIT**

20 dB in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency Range: 9 kHz to 1 GHz		
FREQUENCY (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Frequency Range: above 1 GHz				
FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
above 1 GHz	80	60	74	54

**NOTE:**

(1) The limit for radiated test was performed according to FCC PART 15B.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

(4) The test result calculated as following:

Measurement Value = Reading Level + Correct Factor

Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain(if use)

Margin Level = Measurement Value – Limit Value



## 8.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Apr. 15, 2014
3	Microwave Pre_amplifier	Agilent	8449B	3008A01714	Apr. 16, 2014
4	Microflex Cable	Harbour industries	27478LL142	1m	May. 13, 2014
5	Microflex Cable	EMC	S104-SMA	8m	May. 13, 2014
6	Microflex Cable	Harbour industries	27478LL142	3m	May. 13, 2014
7	Test Cable	LMR	LMR-400	12m	May. 14, 2014
8	Test Cable	LMR	LMR-400	3m	May. 14, 2014
9	Pre-Amplifier	Anritsu	MH648A	M92649	Jun. 18, 2014
10	Log-Bicon Antenna	Schwarzbeck	VULB9168-352	9168-352	Jun. 11, 2014

Remark: "N/A" denotes No Model Name, No Serial No. or No Calibration specified.

## 8.3 MEASURING INSTRUMENTS SETTING

EMI Test Receiver	Parameter Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



## 8.4 TEST PROCEDURES

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1 GHz. For frequencies above 1 GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m Semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. The testing follows the guidelines in ANSI C63.4 and FCC Public Notice DA 00-705 Measurement Guidelines. In case the emission is fail due to the used RBW/VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.


### NOTE:

- a. Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode with Detector BW=120 kHz; SPA setting in RBW=100 kHz, VBW =100 kHz, Swp. Time = 0.3 sec./ MHz.
- b. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.

## 8.5 DEVIATION FROM TEST STANDARD

No deviation

## 8.6 TEST SETUP LAYOUT





## **8.7 EUT OPERATING CONDITIONS**


The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.



## 8.8 TEST RESULTS

EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

### Polarization: Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		233.7000	54.51	-15.99	38.52	46.00	-7.48	peak	
2		367.0750	54.05	-12.20	41.85	46.00	-4.15	peak	
3		500.4500	48.56	-9.48	39.08	46.00	-6.92	peak	
4	*	733.2500	48.11	-5.73	42.38	46.00	-3.62	peak	
5		869.0500	43.12	-3.90	39.22	46.00	-6.78	peak	
6		932.1000	42.61	-2.85	39.76	46.00	-6.24	peak	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

**Polarization: Horizontal**



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	165.8000	54.83	-14.45	40.38	43.50	-3.12	peak	
2		265.2250	57.09	-14.50	42.59	46.00	-3.41	peak	
3		367.0750	54.57	-12.20	42.37	46.00	-3.63	peak	
4		667.7750	46.71	-6.74	39.97	46.00	-6.03	peak	
5		733.2500	47.68	-5.73	41.95	46.00	-4.05	peak	
6		801.1500	45.48	-4.82	40.66	46.00	-5.34	peak	



## **9 RADIATED SPURIOUS EMISSION (ABOVE 1 GHZ)**

### **9.1 LIMIT**

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency Range: 9 kHz to 1 GHz		
FREQUENCY (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Frequency Range: above 1 GHz				
FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
above 1 GHz	80	60	74	54

**NOTE:**

(1) The limit for radiated test was performed according to FCC PART 15B.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

(4) The test result calculated as following:

Measurement Value = Reading Level + Correct Factor

Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain(if use)

Margin Level = Measurement Value – Limit Value



## 9.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Apr. 15, 2014
3	Microwave Pre_amplifier	Agilent	8449B	3008A01714	Apr. 16, 2014
4	Microflex Cable	Harbour industries	27478LL142	1m	May. 13, 2014
5	Microflex Cable	EMC	S104-SMA	8m	May. 13, 2014
6	Microflex Cable	Harbour industries	27478LL142	3m	May. 13, 2014
7	Test Cable	LMR	LMR-400	12m	May. 14, 2014
8	Test Cable	LMR	LMR-400	3m	May. 14, 2014
9	Pre-Amplifier	Anritsu	MH648A	M92649	Jun. 18, 2014
10	Log-Bicon Antenna	Schwarzbeck	VULB9168-352	9168-352	Jun. 11, 2014

Remark: "N/A" denotes No Model Name, No Serial No. or No Calibration specified.

## 9.3 MEASURING INSTRUMENTS SETTING

Spectrum Analyzer	Parameter Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average



## 9.4 TEST PROCEDURES

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1 GHz. For frequencies above 1 GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m Semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. The testing follows the guidelines in ANSI C63.4 and FCC Public Notice DA 00-705 Measurement Guidelines. In case the emission is fail due to the used RBW/VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.


### NOTE:

- a. Reading in which marked as Peak means measurements by using are Peak Mode with instrument setting in RBW= 1 MHz, VBW= 1 MHz, Swp. Time = Auto.  
Reading in which marked as AV means measurements by using are Average Mode with instrument setting in RBW= 1 MHz, VBW= 10 Hz, Swp. Time = Auto.
- b. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform.

## 9.5 DEVIATION FROM TEST STANDARD

No deviation

## 9.6 TEST SETUP LAYOUT





## **9.7 EUT OPERATING CONDITIONS**


The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.



## 9.8 TEST RESULTS

EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		

### Polarization: Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2390.000	23.54	31.81	55.35	74.00	-18.65	peak	
2		2390.000	11.68	31.81	43.49	54.00	-10.51	Avg	
3	X	2402.000	63.12	31.86	94.98	74.00	20.98	peak	
4	*	2402.000	52.71	31.86	84.57	54.00	30.57	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		

**Polarization: Vertical**




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.075	55.89	6.19	62.08	74.00	-11.92	peak	
2	*	4804.075	42.22	6.19	48.41	54.00	-5.59	AVG	
3		7206.575	44.40	12.38	56.78	74.00	-17.22	peak	
4		7206.575	31.47	12.38	43.85	54.00	-10.15	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		

**Polarization: Horizontal**




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2390.000	23.79	31.81	55.60	74.00	-18.40	peak	
2		2390.000	11.65	31.81	43.46	54.00	-10.54	Avg	
3	X	2402.000	63.70	31.86	95.56	74.00	21.56	peak	
4	*	2402.000	53.17	31.86	85.03	54.00	31.03	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		

**Polarization: Horizontal**




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.060	55.19	6.19	61.38	74.00	-12.62	peak	
2	*	4804.060	41.29	6.19	47.48	54.00	-6.52	Avg	
3		7205.938	44.14	12.38	56.52	74.00	-17.48	peak	
4		7205.938	31.52	12.38	43.90	54.00	-10.10	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

**Polarization: Vertical**




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dB <sub>UV</sub>	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB		
1	X	2441.000	61.54	32.02	93.56	74.00	19.56	peak	
2	*	2441.000	51.38	32.02	83.40	54.00	29.40	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

### Polarization: Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4882.100	56.53	6.29	62.82	74.00	-11.18	peak	
2		4882.100	38.21	6.29	44.50	54.00	-9.50	Avg	
3		7323.230	45.05	12.81	57.86	74.00	-16.14	peak	
4	*	7323.230	32.03	12.81	44.84	54.00	-9.16	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

**Polarization: Horizontal**




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2441.000	62.30	32.02	94.32	74.00	20.32	peak	
2	*	2441.000	52.06	32.02	84.08	54.00	30.08	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		

### Polarization: Horizontal




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4882.095	55.38	6.29	61.67	74.00	-12.33	peak	
2		4882.095	37.79	6.29	44.08	54.00	-9.92	Avg	
3		7322.960	45.46	12.81	58.27	74.00	-15.73	peak	
4	*	7322.960	32.08	12.81	44.89	54.00	-9.11	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		

### Polarization: Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2480.000	63.14	32.18	95.32	74.00	21.32	peak	
2	*	2480.000	52.73	32.18	84.91	54.00	30.91	Avg	
3		2483.500	24.98	32.19	57.17	74.00	-16.83	peak	
4		2483.500	13.60	32.19	45.79	54.00	-8.21	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		

### Polarization: Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4960.055	55.68	6.39	62.07	74.00	-11.93	peak	
2	*	4960.055	40.27	6.39	46.66	54.00	-7.34	Avg	
3		7440.150	45.41	13.25	58.66	74.00	-15.34	peak	
4		7440.150	32.41	13.25	45.66	54.00	-8.34	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		

### Polarization: Horizontal




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2480.000	59.64	32.18	91.82	74.00	17.82	peak	
2	*	2480.000	49.85	32.18	82.03	54.00	28.03	Avg	
3		2483.500	24.30	32.19	56.49	74.00	-17.51	peak	
4		2483.500	12.62	32.19	44.81	54.00	-9.19	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		

## Polarization: Horizontal




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4960.090	57.93	6.39	64.32	74.00	-9.68	peak	
2	*	4960.090	41.91	6.39	48.30	54.00	-5.70	Avg	
3		7440.150	32.41	13.25	45.66	54.00	-8.34	Avg	
4		7440.885	45.03	13.25	58.28	74.00	-15.72	peak	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		

### Polarization: Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dB <sub>UV</sub>	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB		
1		2390.000	23.74	31.81	55.55	74.00	-18.45	peak	
2		2390.000	11.69	31.81	43.50	54.00	-10.50	AVG	
3	X	2402.000	57.98	31.86	89.84	74.00	15.84	peak	
4	*	2402.000	48.59	31.86	80.45	54.00	26.45	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		

### Polarization: Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.085	51.64	6.19	57.83	74.00	-16.17	peak	
2	*	4804.085	38.50	6.19	44.69	54.00	-9.31	AVG	
3		7206.300	44.30	12.38	56.68	74.00	-17.32	peak	
4		7206.300	31.25	12.38	43.63	54.00	-10.37	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		

### Polarization: Horizontal




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dB <sub>UV</sub>	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB		
1		2390.000	23.57	31.81	55.38	74.00	-18.62	peak	
2		2390.000	11.74	31.81	43.55	54.00	-10.45	Avg	
3	X	2402.000	58.40	31.86	90.26	74.00	16.26	peak	
4	*	2402.000	48.93	31.86	80.79	54.00	26.79	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		

## Polarization: Horizontal




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.045	51.99	6.19	58.18	74.00	-15.82	peak	
2	*	4804.045	38.15	6.19	44.34	54.00	-9.66	Avg	
3		7206.075	44.46	12.38	56.84	74.00	-17.16	peak	
4		7206.075	31.28	12.38	43.66	54.00	-10.34	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2441 MHz		

### Polarization: Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dB <sub>UV</sub>	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB		
1	X	2441.000	59.18	32.02	91.20	74.00	17.20	peak	
2	*	2441.000	49.54	32.02	81.56	54.00	27.56	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2441 MHz		

### Polarization: Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4882.070	52.59	6.29	58.88	74.00	-15.12	peak	
2	*	4882.070	39.57	6.29	45.86	54.00	-8.14	Avg	
3		7323.005	45.15	12.81	57.96	74.00	-16.04	peak	
4		7323.005	32.10	12.81	44.91	54.00	-9.09	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2441 MHz		

**Polarization: Horizontal**




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dB <sub>UV</sub>	dB	dB <sub>UV</sub> /m	dB			
1	X	2441.000	58.22	32.02	90.24	74.00	16.24	peak	
2	*	2441.000	48.76	32.02	80.78	54.00	26.78	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2441 MHz		

**Polarization: Horizontal**




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4882.045	52.64	6.29	58.93	74.00	-15.07	peak	
2		4882.045	37.67	6.29	43.96	54.00	-10.04	AVG	
3		7323.455	45.15	12.81	57.96	74.00	-16.04	peak	
4	*	7323.455	32.17	12.81	44.98	54.00	-9.02	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		

**Polarization: Vertical**




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2480.000	58.24	32.18	90.42	74.00	16.42	peak	
2	*	2480.000	48.78	32.18	80.96	54.00	26.96	Avg	
3		2483.500	24.16	32.19	56.35	74.00	-17.65	peak	
4		2483.500	12.84	32.19	45.03	54.00	-8.97	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		

### Polarization: Vertical




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4960.075	51.53	6.39	57.92	74.00	-16.08	peak	
2	*	4960.075	38.89	6.39	45.28	54.00	-8.72	Avg	
3		7440.125	45.35	13.25	58.60	74.00	-15.40	peak	
4		7440.125	32.00	13.25	45.25	54.00	-8.75	Avg	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		

### Polarization: Horizontal




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2480.000	54.93	32.18	87.11	74.00	13.11	peak	
2	*	2480.000	46.01	32.18	78.19	54.00	24.19	AVG	
3		2483.500	24.40	32.19	56.59	74.00	-17.41	peak	
4		2483.500	12.28	32.19	44.47	54.00	-9.53	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		

**Polarization: Horizontal**




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4960.070	52.19	6.39	58.58	74.00	-15.42	peak	
2	*	4960.070	39.67	6.39	46.06	54.00	-7.94	Avg	
3		7439.960	45.06	13.25	58.31	74.00	-15.69	peak	
4		7439.960	32.03	13.25	45.28	54.00	-8.72	Avg	



## 9.9 TEST RESULTS (RESTRICTED BANDS)

EUT	Amphitheater	Model Name	41IK5BTL
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

### Polarization: Vertical




No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB		
1	2390.000	23.54	31.81	55.35	74.00	-18.65	peak	
2 *	2390.000	11.68	31.81	43.49	54.00	-10.51	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

**Polarization: Horizontal**




No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Level	Factor	ment				
1	2390.000	23.79	31.81	55.60	74.00	-18.40	peak	
2 *	2390.000	11.65	31.81	43.46	54.00	-10.54	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

### Polarization: Vertical




No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB		
1	2483.500	24.98	32.19	57.17	74.00	-16.83	peak	
2 *	2483.500	13.60	32.19	45.79	54.00	-8.21	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

**Polarization: Horizontal**




No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dB <sub>uV</sub>	dB	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>	dB		
1	2483.500	24.30	32.19	56.49	74.00	-17.51	peak	
2 *	2483.500	12.62	32.19	44.81	54.00	-9.19	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

**Polarization: Vertical**




No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Level	Factor	ment				
1	2390.000	23.74	31.81	55.55	74.00	-18.45	peak	
2 *	2390.000	11.69	31.81	43.50	54.00	-10.50	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		
NOTE	The transmitter was setup to transmit at the lowest channel and the field strength was measured at 2310-2390 MHz.		

**Polarization: Horizontal**




No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB		
1	2390.000	23.57	31.81	55.38	74.00	-18.62	peak	
2 *	2390.000	11.74	31.81	43.55	54.00	-10.45	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

**Polarization: Vertical**




No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB		
1	2483.500	24.16	32.19	56.35	74.00	-17.65	peak	
2 *	2483.500	12.84	32.19	45.03	54.00	-8.97	AVG	



EUT	Amphitheater	Model Name	41IK5BTL
Temperature	24°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		
NOTE	The transmitter was setup to transmit at the highest channel and the field strength was measured at 2483.5-2500 MHz.		

### Polarization: Horizontal



No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Level	Factor	ment				
1	2483.500	24.40	32.19	56.59	74.00	-17.41	peak	
2 *	2483.500	12.28	32.19	44.47	54.00	-9.53	AVG	



## **10 NUMBER OF HOPPING FREQUENCY**

### **10.1 LIMIT**

Test Item	Frequency Range (MHz)	Limit
Number of Hopping Channel	2400-2483.5	shall use at least 15 channels

### **10.2 MEASUREMENT INSTRUMENTS LIST**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014

NOTE: **N/A:** denotes No Model Name, No Serial No. or No Calibration specified.

### **10.3 MEASURING INSTRUMENTS SETTING**

Spectrum Analyzer	Parameter Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### **10.4 TEST PROCEDURES**

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting: RBW= 100 kHz, VBW=100 kHz, Sweep time = Auto.

### **10.5 TEST SETUP LAYOUT**



### **10.6 DEVIATION FROM TEST STANDARD**

No deviation

### **10.7 EUT OPERATING CONDITIONS**


The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.



## 10.8 TEST RESULTS

EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps		


Number of Hopping Channel	Limit	Result
79	15	Pass





EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	62%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps		

Number of Hopping Channel	Limit	Result
79	15	Pass





## 11 AVERAGE TIME OF OCCUPANCY

### 11.1 LIMIT

Test Item	Frequency Range (MHz)	Limit
Average time of occupancy	2400-2483.5	shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 11.2 MEASUREMENT INSTRUMENTS LIST


Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-30	100854	Sep. 08, 2014

NOTE: **N/A**: denotes No Model Name, No Serial No. or No Calibration specified.

### 11.3 TEST PROCEDURES

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 100 kHz and VBW to 100 kHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. DH5 Packet permit maximum  $1600 / 79 / 6 = 3.37$  hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times  $3.37 \times 31.6 = 106.6$  within 31.6 seconds.
- j. DH3 Packet permit maximum  $1600 / 79 / 4 = 5.06$  hops per second in each channel (3 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times  $5.06 \times 31.6 = 160$  within 31.6 seconds.
- k. DH1 Packet permit maximum  $1600 / 79 / 2 = 10.12$  hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times  $10.12 \times 31.6 = 320$  within 31.6 seconds.

### 11.4 TEST SETUP LAYOUT



### 11.5 DEVIATION FROM TEST STANDARD

No deviation



## **11.6 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 5.6 Unless otherwise a special operating condition is specified in the follows during the testing.




## 11.7 TEST RESULTS

EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2402 MHz		


Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2402 MHz	3.0411	0.3244	0.4	PASS
DH3	2402 MHz	1.0020	0.1603	0.4	PASS
DH1	2402 MHz	0.5207	0.1666	0.4	PASS

### Bluetooth/1 Mbps/2402 MHz/DH1






Bluetooth/1 Mbps/2402 MHz/DH3



Bluetooth/1 Mbps/2402 MHz/DH5






EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2441 MHz		


Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2441 MHz	3.0454	0.3248	0.4	PASS
DH3	2441 MHz	0.9622	0.1540	0.4	PASS
DH1	2441 MHz	0.4802	0.1537	0.4	PASS

## Bluetooth/1 Mbps/2441 MHz/DH1






Bluetooth/1 Mbps/2441 MHz/DH3



Bluetooth/1 Mbps/2441 MHz/DH5






EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/1 Mbps/2480 MHz		


Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2480 MHz	3.0444	0.3247	0.4	PASS
DH3	2480 MHz	0.9611	0.1538	0.4	PASS
DH1	2480 MHz	0.5206	0.1666	0.4	PASS

## Bluetooth/1 Mbps/2480 MHz/DH1






**Bluetooth/1 Mbps/2480 MHz/DH3**



**Bluetooth/1 Mbps/2480 MHz/DH5**






EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2402 MHz		


Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2402 MHz	3.0843	0.3290	0.4	PASS
DH3	2402 MHz	1.8022	0.2884	0.4	PASS
DH1	2402 MHz	0.5200	0.1664	0.4	PASS

#### Bluetooth/3 Mbps/2402 MHz/DH1






Bluetooth/3 Mbps/2402 MHz/DH3



Bluetooth/3 Mbps/2402 MHz/DH5






EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2441 MHz		


Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2441 MHz	3.0459	0.3249	0.4	PASS
DH3	2441 MHz	1.8031	0.2885	0.4	PASS
DH1	2441 MHz	0.5208	0.1667	0.4	PASS

#### Bluetooth/3 Mbps/2441 MHz/DH1






Bluetooth/3 Mbps/2441 MHz/DH3



Bluetooth/3 Mbps/2441 MHz/DH5






EUT	Amphitheater	Model Name	41IK5BTL
Temperature	25°C	Relative Humidity	46%
Test Voltage	AC 120V/60Hz		
Test Mode	Bluetooth/3 Mbps/2480 MHz		


Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limit (s)	Result
DH5	2480 MHz	3.0442	0.3247	0.4	PASS
DH3	2480 MHz	1.7624	0.2820	0.4	PASS
DH1	2480 MHz	0.5603	0.1793	0.4	PASS

## Bluetooth/3 Mbps/2480 MHz/DH1






Bluetooth/3 Mbps/2480 MHz/DH3



Bluetooth/3 Mbps/2480 MHz/DH5





## 12 EUT TEST PHOTO

### Conducted emission test photos





**Radiated spurious emission test photos**

