

# RF Exposure Evaluation Report

FCC ID : TTUBEOPLAYEXC  
Equipment : Charging Case  
Brand Name : Bang & Olufsen  
Model Name : EX Charging case  
Applicant : Bang & Olufsen A/S  
Bang og Olufsen Allé 1, 7600 Struer, Denmark  
Manufacturer : Bang & Olufsen A/S  
Bang og Olufsen Allé 1, 7600 Struer, Denmark  
Standard : 47 CFR Part 2.1093

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part 2.1093 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No.TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.



Approved by: Cona Huang / Deputy Manager



**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan





## 1. General Information

### 1.1 Description of Device Under Test (DUT)

Product Feature & Specification	
DUT Type	Charging Case
Brand Name	Bang & Olufsen
Model Name	EX Charging case
FCC ID	TTUBEOPLAYEXC
Wireless Technology and Frequency Range	Bluetooth: 2400 MHz ~ 2483.5 MHz
Mode	Bluetooth LE
Antenna Type	Bluetooth: Printed antenna
DUT Stage	Identical Prototype

**Remark:** The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 2. Maximum RF output power among production units

Mode	Maximum Output Power (dBm)
Bluetooth LE	0



### 3. RF Exposure Evaluation

Bluetooth Max Power (dBm)	mW	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
0	1	5	2.48	0.31

**Note:**

1. Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

**Conclusion:** Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.31 which is ≤ 3, SAR testing is not required.