

RF Exposure Evaluation Report

Applicant's company	Bang & Olufsen a/s
Applicant Address	Peter Bangs Vej 15, DK-7600 Struer, Denmark
FCC ID	TTUBEOPLAYH8I
Manufacturer's company	Bang & Olufsen a/s
Manufacturer Address	Peter Bangs Vej 15, DK-7600 Struer, Denmark

Product Name	Bluetooth Headphone
Brand Name	Bang & Olufsen
Model Name	Beoplay H8i
Ref. Standard(s)	47 CFR FCC Part 2 Subpart J, section 2.1093
Received Date	Sep. 14, 2017
Final Test Date	Sep. 28, 2017
Submission Type	Original Equipment

Reviewed by:


Kevin Liang / Assistant Manager
SPORTON INTERNATIONAL INC.



Table of Contents

1. GENERAL DESCRIPTION	4
1.1. EUT General Information	4
1.2. Testing Location Information.....	4
2. RF EXPOSURE EVALUATION	5
2.1. Applicable Standard	5
2.2. SAR evaluation.....	5

PHOTOGRAPHS OF EUT V01



History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA792502	Rev. 01	Initial issue of report	Nov. 13, 2017

1. GENERAL DESCRIPTION

1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: DSSS (GFSK)

1.2. Testing Location Information

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

2. RF EXPOSURE EVALUATION

2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2. SAR evaluation

- Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$$

$$[\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

- ♦ $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- ♦ Power and distance are rounded to the nearest mW and mm before calculation
- ♦ The result is rounded to one decimal place for comparison

Tune-up Average Power		Test Distance (mm)	Frequency (GHz)	Exclusion Thresholds
(dBm)	(mW)			
5.99	3.97	5	2.44	1.2

- Per FCC KDB 447498 D01 v06 exclusion thresholds is $1.2 < 3$, RF exposure evaluation is not required.