

**Test Report**

**for**

**Widex A/S**

**on**

**D-9**

**Document No. TRA 006043-01-W-US1**

**TRaC Wireless Test Report** : TRA 006043-01-W-US1

**Applicant** : Widex A/S

**Apparatus** : D-9

**Specification(s)** : CFR 47, Part 15, October 2010

**Purpose of Test** : Certification

**FCCID** : TTY-D9

**IC ID** : 5676B-D9

**Authorised by**

:



Radio Product Manager

**Issue Date**

: 25<sup>th</sup> November 2011

**Authorised Copy Number**

: PDF

**Contents**

Section 1: Introduction	4
1.1 General	4
1.2 Tests Requested By	5
1.3 Manufacturer	5
1.4 Apparatus Assessed	5
1.5 Test Result Summary	6
1.6 Notes relating to the assessment	7
1.7 Deviations from Test Standards	7
Section 2: Measurement Uncertainty	8
2.1 Measurement Uncertainty Values	8
Section 3: Modifications	9
3.1 Modifications Performed During Assessment	9
Appendix A: Formal Emission Test Results	10
A1 Transmitter Intentional Emission Radiated	11
A2 Radiated Electric Field Emissions	12
A3 Unintentional Radiated Emissions	14
Appendix B: Supporting Graphical Data	16
Appendix C: Additional Test and Sample Details	21
Appendix D: Additional Information	27
Appendix E: Calculation of the duty cycle correction factor	28
Appendix F: Photographs and Figures	29
Appendix G: MPE Calculation	31
Appendix H: Cross Reference FCC Part 15c to IC RSS 210	32

## Section 1: Introduction

### 1.1 General

This report contains an assessment of an apparatus against Electromagnetic Compatibility Standards based upon tests carried out on samples submitted to the Laboratory.

Test performed at:	TRaC Global Unit E South Orbital Trading Park Hedon Road Hull HU9 1NJ. United Kingdom	<input checked="" type="checkbox"/>
	Telephone: +44 (0) 1482 801801 Fax: +44 (0) 1482 801806	
	TRaC Global Unit 1 Pendle Place Pimbo Industrial Estate Skelmersdale WN8 6BF United Kingdom	<input checked="" type="checkbox"/>
	Telephone: +44 (0) 1695 556666 Fax: +44 (0) 1695 577077	
	Email: <a href="mailto:test@tracglobal.com">test@tracglobal.com</a> Web site: <a href="http://www.tracglobal.com">http://www.tracglobal.com</a>	

Tests performed by: K J Anderson, S J Hodgkinson

Report author: Sandeep Bharat

**This report must not be reproduced except in full without prior written permission from TRaC Global.**

## **1.2 Tests Requested By**

This testing in this report was requested by:

Widex A/S  
Nymoellevej 6  
DK-3540 Lynge  
Denmark

## **1.3 Manufacturer**

Widex A/S  
Nymoellevej 6  
DK-3540 Lynge  
Denmark

## **1.4 Apparatus Assessed**

The following apparatus was assessed between 07-07-2011 & 12-07-2011:

D-9

The above equipment is a hearing aid containing radio circuitry operating at 10.6 MHz

### 1.5 Test Result Summary

Full details of test results are contained within Appendix A. The following table summarises the results of the assessment.

The statements relating to compliance with the standards below apply ONLY as qualified in the notes and deviations stated in sections 1.6 to 1.7 of this test report.

Full details of test results are contained within Appendix A. The following table summarises the results of the assessment.

Test Type	Regulation	Measurement standard	Result
Spurious Emissions Radiated <1000MHz	Title 47 of the CFR: Part 15 Subpart (c) 15.209	ANSI C63.10	Pass
Spurious Emissions Radiated >1000MHz	Title 47 of the CFR: Part 15 Subpart (c)	ANSI C63.10	N/A
AC Power conducted emissions	Title 47 of the CFR: Part 15 Subpart (c) 15.207	ANSI C63.10	N/A
Intentional Emission Frequency	Title 47 of the CFR: Part 15 Subpart (c) 15.209	ANSI C63.10	Pass
Intentional Emission Field Strength:	Title 47 of the CFR: Part 15 Subpart (c) 15. 209	ANSI C63.10	Pass
Intentional Emission Band Occupancy	Title 47 of the CFR: Part 15 Subpart (c) 15.215	ANSI C63.10	Pass
Intentional Emission ERP (mW)	Title 47 of the CFR: Part 15 Subpart (c)	ANSI C63.10	N/A
Unintentional Radiated Spurious Emissions	Title 47 of the CFR: Part 15 Subpart (b) 15.109	ANSI C63.10	Pass
Antenna Arrangements Integral:	Title 47 of the CFR: Part 15 Subpart (c) 15.203	-	Pass
Antenna Arrangements External Connector	Title 47 of the CFR: Part 15 Subpart (c) 15.204	-	-
Restricted Bands	Title 47 of the CFR: Part 15 Subpart (c) 15.205	-	-
Maximum Frequency Of Search	Title 47 of the CFR: Part 15 Subpart (c) 15.33	-	-
Extrapolation Factor	Title 47 of the CFR: Part 15 Subpart (c) 15.31(f)	-	-

Abbreviations used in the above table:

CFR : Code of Federal Regulations  
REFE : Radiated Electric Field Emissions

ANSI : American National Standards Institution  
PLCE : Power Line Conducted Emissions

## **1.6 Notes relating to the assessment**

With regard to this assessment, the following points should be noted:

The results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

The apparatus was set up and exercised using the configurations, modes of operation and arrangements defined in this report only.

Particular operating modes, apparatus monitoring methods and performance criteria required by the standards tested to have been performed except where identified in Section 1.7 of this test report (Deviations from Test Standards).

For emissions testing, throughout this test report, "Pass" indicates that the results for the sample as tested were below the specified limit (refer also to Section 2, Measurement Uncertainty).

Where relevant, the apparatus was only assessed using the monitoring methods and susceptibility criteria defined in this report.

All testing with the exception of testing at the Open Area Test Site was performed under the following environmental conditions:

Temperature	: 17 to 23 °C
Humidity	: 45 to 75 %
Barometric Pressure	: 86 to 106 kPa

All dates used in this report are in the format dd/mm/yy.

This assessment has been performed in accordance with the requirements of ISO/IEC 17025.

## **1.7 Deviations from Test Standards**

There were no deviations from the standards tested to.

**Section 2:****Measurement Uncertainty****2.1 Measurement Uncertainty Values**

For test data recorded in accordance with note (iii) of Section 2.1 the following measurement uncertainty was calculated:

Radiated Electric Field Emissions

Quantity Range	Quantity	Expanded Uncertainty
9kHz to 150 kHz	Amplitude dB( $\mu$ V/m)	$\pm 1.6$ dB
150 kHz to 30 MHz	Amplitude dB( $\mu$ V/m)	$\pm 2.1$ dB
30MHz to 300MHz Horizontal	Amplitude dB( $\mu$ V/m)	$\pm 5.1$ dB
30MHz to 300MHz Vertical	Amplitude dB( $\mu$ V/m)	$\pm 5.2$ dB
300MHz to 1GHz Horizontal	Amplitude dB( $\mu$ V/m)	$\pm 5.4$ dB
300MHz to 1GHz Vertical	Amplitude dB( $\mu$ V/m)	$\pm 5.2$ dB
1GHz to 18GHz Horizontal	Amplitude dB( $\mu$ V/m)	$\pm 4.4$ dB
1GHz to 18GHz Vertical	Amplitude dB( $\mu$ V/m)	$\pm 4.4$ dB
18GHz to 26.5GHz Horizontal	Amplitude dB( $\mu$ V/m)	$\pm 4.2$ dB
18GHz to 26.5GHz Vertical	Amplitude dB( $\mu$ V/m)	$\pm 4.2$ dB
26.5GHz to 40GHz Horizontal	Amplitude dB( $\mu$ V/m)	$\pm 4.3$ dB
26.5GHz to 40GHz Vertical	Amplitude dB( $\mu$ V/m)	$\pm 4.3$ dB



### **Section 3:**

### **Modifications**

#### **3.1 Modifications Performed During Assessment**

No modifications were performed during the assessment

**Appendix A:****Formal Emission Test Results**

Abbreviations used in the tables in this appendix:

Spec	: Specification	ALSR	: Absorber Lined Screened Room
Mod	: Modification	OATS	: Open Area Test Site
		ATS	: Alternative Test Site
EUT	: Equipment Under Test		
SE	: Support Equipment	Ref	: Reference
		Freq	: Frequency
L	: Live Power Line		
N	: Neutral Power Line	MD	: Measurement Distance
E	: Earth Power Line	SD	: Spec Distance
Pk	: Peak Detector	Pol	: Polarisation
QP	: Quasi-Peak Detector	H	: Horizontal Polarisation
Av	: Average Detector	V	: Vertical Polarisation
CDN	: Coupling & decoupling network		

**A1 Transmitter Intentional Emission Radiated**

Test Details	
Regulation	Title 47 of the CFR: Part15 Subpart (c) 15.209(b)(1)
Measurement standard	ANSI C63.10:2009
EUT sample number	S05
Modification state	0
SE in test environment	None
SE isolated from EUT	None
EUT set up	Refer to Appendix C
Photographs (Appendix F)	Photograph 1

Frequency (MHz)	Measurement Distance (m)	Measurement Rx Reading (dBμV/m)	Extrapolation Factor (dB)	Field Strength (μV/m)
10.816	1	33.3	59.1	0.05
Limit value @ frequency		30 μV/m		
Band occupancy @ -20 dBc		f <sub>lower</sub> (MHz)		f <sub>higher</sub> (MHz)
		10.340038462		10.987473462
		BW = 647.435 kHz		

- Notes:**
- 1 Results quoted are extrapolated as indicated
  - 2 Receiver detector @ fc = Quasi Peak 10 kHz
  - 3 When battery powered the EUT was powered with new batteries
  - 4 Extrapolation 1 - 30 Meters 59.1 dB as per 15.31(f)
  - 5 Due to the low level of the signal, measurements at distances greater than 1 m could not be made

- Test Method:**
- 1 As per Radio – Noise Emissions, ANSI C63.10
  - 2 Measuring distance = 1m
  - 3 EUT 0.8 m above ground plane
  - 4 Emissions maximized by rotation of EUT, on an automatic turntable
  - 5 Raising and lowering the receiver antenna between 1m & 4m
  - 6 Horizontal and vertical polarizations, of the receive antenna
  - 7 EUT orientation in three orthogonal planes
  - 8 Maximum results recorded

**A2 Radiated Electric Field Emissions**

Preliminary scans were performed using a peak detector with the RBW = 100 kHz. The radiated electric field emission test applies to all spurious emissions and harmonics emissions. The maximum permitted field strength is listed in Section 15.209. The EUT was set to transmit as required.

The following test site was used for final measurements as specified by the standard tested to:

3m open area test site :

☐

3m alternative test site :

☒

The effect of the EUT set-up on the measurements is summarised in note (c) below.

Test Details	
Regulation	Title 47 of the CFR, Part 15 Subpart (c) Clause 15.209
Measurement standard	ANSI C63.10:2009
Frequency range	9kHz – 1000MHz
EUT sample number	S05
Modification state	0
SE in test environment	None
SE isolated from EUT	None
EUT set up	Refer to Appendix C
Photographs (Appendix F)	Photographs 1 and 2

The worst case radiated emission measurements for spurious emissions and harmonics that fall within the restricted bands are listed below:

Ref No.	Frequency (MHz)	Measured at Rx (dBµV)	Cable Loss (dB)	Antenna Factor (dB/m)	Pre-Amp Gain (dB)	Field Strength (dBµV/m)	Extrapolation Factor (dB)	Field Strength (µV/m)	Limit (µV/m)
No Significant Emissions Within 20 dB of the limit									

**Notes:**

- 1 Any testing performed below 30 MHz was performed using a magnetic loop antenna in accordance with ANSI C63.10: section 4.5, Table 1. For emissions below 30MHz the cable losses are assumed to be negligible.
- 2 In accordance with 15.35(b), above 1 GHz, emissions measured using a peak detector shall not exceed a level 20 dB above the average limit.
- 3 Testing was performed with the EUT orientated in three orthogonal planes and the maximum emissions level recorded. In addition, the EUT antenna was varied within its range of motion in order to maximise emissions.
- 4 For Frequencies below 1 GHz, RBW= 120 kHz, testing was performed with CISPR16 compliant test receiver with QP detector. Above 1 GHz tests were performed using a spectrum analyser using the following settings:

Peak                      RBW=VBW= 1MHz  
Average      RBW=VBW= 1MHz

The upper and lower frequency of the measurement range was decided according to 47 CFR Part 15:2011 Clause 15.33(a) and 15.33(a)(1).

Radiated emission limits 47 CFR Part 15: Clause 15.209 for all emissions:

Frequency of emission (MHz)	Field strength $\mu\text{V/m}$	Measurement Distance m	Field strength $\text{dB}\mu\text{V/m}$
0.009-0.490	2400/F(kHz)	300	67.6/F (kHz)
0.490-1.705	24000/F(kHz)	30	87.6/F (kHz)
1.705-30	30	30	29.5
30-88	100	3	40.0
88-216	150	3	43.5
216-960	200	3	46.0
Above 960	500	3	54.0

- (a) Where results have been measured at one distance, and a signal level displayed at another, the results have been extrapolated using the following formula:

$$\text{Extrapolation (dB)} = 20 \log_{10} \left( \frac{\text{measurement distance}}{\text{specification distance}} \right)$$

- (b) The levels may have been rounded for display purposes.
- (c) The following table summarises the effect of the EUT operating mode, internal configuration and arrangement of cables / samples on the measured emission levels:

	See (i)	See (ii)	See (iii)	See (iv)
Effect of EUT operating mode on emission levels		✓		
Effect of EUT internal configuration on emission levels		✓		
Effect of Position of EUT cables & samples on emission levels	✓			
(i) Parameter defined by standard and / or single possible, refer to Appendix D (ii) Parameter defined by client and / or single possible, refer to Appendix D (iii) Parameter had a negligible effect on emission levels, refer to Appendix D (iv) Worst case determined by initial measurement, refer to Appendix D				

**A3 Unintentional Radiated Emissions**

Preliminary scans were performed using a peak detector with the RBW = 100 kHz. The radiated electric field emission test applies to all spurious emissions on directly related to the transmitter. The maximum permitted field strength is listed in Section 15.109. The EUT was set to operate in transmit standby / receive mode.

The following test site was used for final measurements as specified by the standard tested to:

3m open area test site :

☐

3m alternative test site :

☒

The effect of the EUT set-up on the measurements is summarised in note (c) below.

Test Details	
Regulation	Title 47 of the CFR, Part 15 Subpart (c) Clause 15.109
Measurement standard	ANSI C63.10:2009
Frequency range	9kHz – 1000MHz
EUT sample number	S03
Modification state	0
SE in test environment	None
SE isolated from EUT	None
EUT set up	Refer to Appendix C
Photographs (Appendix F)	Photographs 1 and 2

The worst case radiated emission measurements for spurious emissions are listed below:

Ref No.	Frequency (MHz)	Measured at Rx (dBμV)	Cable Loss (dB)	Antenna Factor (dB/m)	Pre-Amp Gain (dB)	Field Strength (dBμV/m)	Extrapolation Factor (dB)	Field Strength (μV/m)	Limit (μV/m)
No Significant Emissions Within 20 dB of the limit									

**Notes:**

- 1 Any testing performed below 30 MHz was performed using a magnetic loop antenna in accordance with ANSI C63.10: section 4.5, Table 1. For emissions below 30MHz the cable losses are assumed to be negligible.
- 2 In accordance with 15.35(b), above 1 GHz, emissions measured using a peak detector shall not exceed a level 20 dB above the average limit.
- 3 Testing was performed with the EUT orientated in three orthogonal planes and the maximum emissions level recorded. In addition, the EUT antenna was varied within its range of motion in order to maximise emissions.
- 4 For Frequencies below 1 GHz, RBW = 120 kHz, testing was performed with CISPR16 compliant test receiver with QP detector. Above 1 GHz tests were performed using a spectrum analyser using the following settings:

Peak                      RBW=VBW= 1MHz  
Average      RBW=VBW= 1MHz

The upper and lower frequency of the measurement range was decided according to 47 CFR Part 15:2011 Clause 15.33(a) and 15.33(a)(1).

Radiated emission limits 47 CFR Part 15: Clause 15.109 for all emissions:

Frequency of emission (MHz)	Field strength $\mu\text{V/m}$	Measurement Distance m	Field strength $\text{dB}\mu\text{V/m}$
30-88	100	3	40.0
88-216	150	3	43.5
216-960	200	3	46.0
Above 960	500	3	54.0

- (a) Where results have been measured at one distance, and a signal level displayed at another, the results have been extrapolated using the following formula:

$$\text{Extrapolation (dB)} = 20 \log_{10} \left( \frac{\text{measurement distance}}{\text{specification distance}} \right)$$

- (b) The levels may have been rounded for display purposes.
- (c) The following table summarises the effect of the EUT operating mode, internal configuration and arrangement of cables / samples on the measured emission levels :

	See (i)	See (ii)	See (iii)	See (iv)
Effect of EUT operating mode on emission levels		✓		
Effect of EUT internal configuration on emission levels		✓		
Effect of Position of EUT cables & samples on emission levels	✓			
(i) Parameter defined by standard and / or single possible, refer to Appendix D (ii) Parameter defined by client and / or single possible, refer to Appendix D (iii) Parameter had a negligible effect on emission levels, refer to Appendix D (iv) Worst case determined by initial measurement, refer to Appendix D				

**Appendix B:**

**Supporting Graphical Data**


This appendix contains graphical data obtained during testing.


Notes:

- (a) The radiated electric field emissions and conducted emissions graphical data in this appendix is preview data. For details of formal results, refer to Appendix A and Appendix B.
- (b) The time and date on the plots do not necessarily equate to the time of the test.
- (c) Where relevant, on power line conducted emission plots, the limit displayed is the average limit, which is stricter than the quasi peak limit.
- (d) Appendix C details the numbering system used to identify the sample and its modification state.
- (e) The plots presented in this appendix may not be a complete record of the measurements performed, but are a representative sample, relative to the final assessment.






**Radiated Electric Field Emissions (Transmit Mode)**


**Radiated Magnetic Field Emissions (Receive Mode)**

9 kHz to 150 kHz




150 kHz to 30 MHz

## Radiated Electric Field Emissions (Receive Mode)



30 MHz to 200 MHz



200 MHz to 1 GHz

**Appendix C:****Additional Test and Sample Details**

This appendix contains details of:

1. The samples submitted for testing.
2. Details of EUT operating mode(s)
3. Details of EUT configuration(s) (see below).
4. EUT arrangement (see below).

Throughout testing, the following numbering system is used to identify the sample and it's modification state:

**Sample No:** Sxx Mod w

where:

xx	= sample number	eg. S01
w	= modification number	eg. Mod 2

The following terminology is used throughout the test report:

**Support Equipment (SE)** is any additional equipment required to exercise the EUT in the applicable operating mode. Where relevant SE is divided into two categories:

SE in test environment: The SE is positioned in the test environment and is not isolated from the EUT (e.g. on the table top during REFE testing).

SE isolated from the EUT: The SE is isolated via filtering from the EUT. (e.g. equipment placed externally to the ALSR during REFE testing).

**EUT configuration** refers to the internal set-up of the EUT. It may include for example:

- Positioning of cards in a chassis.
- Setting of any internal switches.
- Circuit board jumper settings.
- Alternative internal power supplies.

Where no change in EUT configuration is **possible**, the configuration is described as "single possible configuration".

**EUT arrangement** refers to the termination of EUT ports / connection of support equipment, and where relevant, the relative positioning of samples (EUT and SE) in the test environment.

For further details of the test procedures and general test set ups used during testing please refer to the related document "EMC Test Methods - An Overview", which can be supplied by TRaC Telecoms & Radio upon request.

**C1      Test samples**

The following samples of the apparatus were submitted by the client for testing:

<b>Sample No</b>	<b>Description</b>
S03	Hearing Aid (Normal sample)
S05	Hearing Aid (Constant transmit sample)

**C2 EUT operating mode during testing**

During testing, the EUT was exercised as described in the following tables:

Test	Description of Operating Mode: Transmit
REFE: Radiated E-Field (Transmitter carrier output levels dBuV/m)	The EUT was transmitting continuously on maximum power using FSK (center frequency 10.6MHz / Deviation $\pm 200$ kHz) modulation and powered by a new battery.
REFE: Radiated Spurious emissions E-Field at frequencies below 30MHz (dBuV/m) (15.209)	
Radiated Spurious emissions (E-Field) at frequencies $\geq 30$ MHz (15.209)	
20dB Bandwidth of Emissions	

Test	Description of Operating Mode: Receive mode
REFE: 15.109 Radiated Spurious emissions E-field below 30MHz (Receive)	The EUT was placed in receive mode (non-transmitting) Mode during the test. Powered by a new battery.
REFE: 15.109 Radiated Spurious emissions (E-Field) frequencies $\geq 30$ MHz (Receive)	

### **C3 EUT Configuration Information**

The EUT was submitted for testing in one single possible configuration



**C4 List of EUT Ports**

The tables below describe the termination of EUT ports:

Sample : S05 & S03

Tests : Radiated E-Field, Radiated H-Field (Carrier power), 20dB Bandwidth of Emissions,  
REFE

Port	Description of Cable Attached	Cable length	Equipment Connected
DC power port	None	N/A	PR48 Zinc-Air 1.25Vdc Battery
Antenna port	None	N/A	Integral

**C5 Details of Equipment Used**

For Radiated Electric Field Emissions 9 kHz to 30 MHz

RFG No	Type	Description	Manufacturer	Date Calibrated
274	ATS	Ferrite Lined Chamber	TRaC	10/06/10
023	HFH-Z2	Mag Loop Antenna 9kHz-30MHz	R & S	26/05/09
214	ESAI	Spec Analyser/Test Rxer (LF/HF)	R & S	22/03/10
246	N-type	RF coaxial cable (Lab 10)	TRaC	22/09/09
270	N-type	RF coaxial cable (Lab 10)	TRaC	22/09/09

For Radiated Electric Field Emissions 30MHz to 1GHz

RFG No	Type	Description	Manufacturer	Date Calibrated.
274	ATS	Ferrite Lined Chamber	TRaC	10/06/10
231	CBL6111	Blue Bilog Antenna (0.03 - 1GHz)	Chase	12/08/08
214	ESAI	Spec Analyser/Test Rxer (LF/HF)	R & S	22/03/10
246	N-type	RF coaxial cable (Lab 10)	TRaC	22/09/09
270	N-type	RF coaxial cable (Lab 10)	TRaC	22/09/09

For 20dB Bandwidth measurement

RFG No	Type	Description	Manufacturer	Date Calibrated
REF847	ESU	EMI Test Receiver (Spectrum analyser)	R&S	11/06/10

**Appendix D:**

**Additional Information**

This appendix contains no additional information

**Appendix E: Calculation of the duty cycle correction factor**

No average detector measurements were made during testing; therefore this calculation is not required.


## **Appendix F:**

## **Photographs and Figures**

The following photographs were taken of the test samples:

1. Radiated electric field emissions arrangement: H-field
2. Radiated electric field emissions arrangement: E-field

**Photograph 1**



**Photograph 2**



**Appendix G:****MPE Calculation**

OET Bulletin No. 65, Supplement C 01-01

47 CFR §§1.1307 and 2.1091

2.1091 Radio frequency radiation exposure evaluation: mobile devices.

For purposes of these requirements mobile devices are defined by the FCC as transmitters designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimetres is normally maintained between radiating structures and the body of the user or nearby persons. These devices are normally evaluated for exposure potential with relation to the MPE limits. As the 20cm separation specified under FCC rules may not be achievable under normal operation of the EUT, an RF exposure calculation is needed to show the minimum distance required to be less than 1mW/cm<sup>2</sup> power density limit, as required under FCC rules.

**Prediction of MPE limit at a given distance**

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{EIRP}{4 \pi R^2} \text{ re - arranged} \quad R = \sqrt{\frac{EIRP}{S 4 \pi}}$$

where:

S = power density

R = distance to the centre of radiation of the antenna

EIRP = EUT Maximum power

Note:

The EIRP value was determined using the peak H Field measurement

Result:

Prediction Frequency (MHz)	Maximum EIRP (mW)	Power density limit (S) (mW/cm <sup>2</sup> )	Distance (R) cm required to be less than 1.6 mW/cm <sup>2</sup>
10.6	4.8x10 <sup>-8</sup>	1.6	4.9x10 <sup>-5</sup>

**Appendix H:****Cross Reference FCC Part 15c to IC RSS 210**


The testing of the C4-9 was carried out to FCC 47CFR Part 15c and the results for this testing can be found in Appendix A of this report.

All measurements were carried out in accordance with ANSI C63.4, 'Methods of Measurements of RF Emissions from low voltage Electrical and Electronic Equipment in the Range 9 kHz to 1 GHz.

The table below shows the applicable RSS-210 parts and the corresponding FCC 47CFR Part 15 rules:

RSS-210	FCC 47CFR Part 15
2.6	Part 15.109
2.6	Part 15.209

In addition below is a plot of the 99% emissions bandwidth, as stipulated in Section 4.4.1 of RSS-Gen.



Date: 11.JUL.2011 15:55:32





**HULL**

Unit E, South Orbital Trading Park, Hedon Road, Hull, HU9 1NJ, UK.

**T** +44 (0)1482 801801 **F** +44 (0)1482 801806 **E** test@tracglobal.com

[www.tracglobal.com](http://www.tracglobal.com)