

RF EXPOSURE REPORT

REPORT NO.: SA960510A02A

MODEL NO.: BHS-303

ACCORDING: FCC Guidelines for Human Exposure

IEEE C95.1

APPLICANT: IQUALTD.

ADDRESS: Kimmeltie 3 02110 Espoo FINLAND

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Linko Hsiang

244, Taipei Hsien, Taiwan, R.O.C.

Report No: SA960510A02A

Reference No.: 960510A02, 960510A03



Conclusion

No Evaluation Required if power is below this threshold:

| F(GHz) | | mW | |
|--------|-------|-------|--|
| Low | 2.402 | 24.58 | |
| High | 2.480 | 24.50 | |

Maximum measured transmitter power:

| Pout (dBm | Pout (mW) | |
|-----------------|-----------|-------|
| Conducted Power | 3.99 | 2.506 |
| EIRP Power | 0.99 | 1.256 |

*Note: The antenna is PIFA antenna with -3dBi gain

Threshold for no SAR evaluation is 24.58mW Transmitter power is 2.506mW

PIFA

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

2

Report No: SA960510A02A

Reference No.: 960510A02, 960510A03